



Standard Specification for Commercial Food Waste Pulper and Waterpress Assembly¹

This standard is issued under the fixed designation F 1150; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This specification covers commercial pulping and waterpress assemblies intended for grinding of food scraps, paper, cardboard, and disposable plastic food-service ware.

1.2 The values as stated in inch-pound units are to be regarded as the standard. The values in parentheses are given for information only.

1.3 The following safety hazards caveat pertains only to the test method portion, Section 13, of this specification:

1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 ASTM Standards:

- A 6 Specification for General Requirements for Rolled Steel Plates, Shapes, Sheet Piling, and Bars for Structural Use²
- A 29 Specification for General Requirements for Steel Bars, Carbon and Alloy, Hot-Wrought and Cold-Finished³
- A 120 Specification for Pipe, Steel, Black and Hot-Dipped, Zinc-Coated (Galvanized), Welded and Seamless, for Ordinary Uses⁴
- A 126 Specification for Gray Iron Castings for Valves, Flanges, and Pipe Fittings⁵
- A 167 Specification for Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet, and Strip⁶
- A 269 Specification for Seamless and Welded Austenitic Stainless Steel Tubing for General Service⁷
- A 276 Specification for Stainless Steel and Heat-Resisting Steel Bars and Shapes³
- A 436 Specification for Austenitic Gray Iron Castings⁵
- A 505 Specification for General Requirements for Steel and Strip, Alloy, Hot-Rolled and Cold-Rolled⁶

- A 513 Specification for Electric-Resistance-Welded Carbon and Alloy Steel Mechanical Tubing⁷
 - A 519 Specification for Seamless Carbon and Alloy Steel Mechanical Tubing⁷
 - A 532 Specification for Abrasion-Resistant Cast Iron⁵
 - A 554 Specification for Welded Stainless Steel Mechanical Tubing⁷
 - A 582 Specification for Free Machining Stainless and Heat-Resisting Steel Bars; Hot-Rolled or Cold-Finished³
 - A 681 Specification for Alloy Tool Steels³
 - B 43 Specification for Seamless Red Brass Pipe, Standard Sizes⁸
 - B 75 Specification for Seamless Copper Tube⁸
 - D 2000 Classification System for Rubber Products in Automotive Applications⁹
 - D 2287 Specification for NonRigid Vinyl Chloride Polymer and Copolymer Molding and Extrusion Compounds¹⁰
 - D 3915 Specification for Poly(Vinyl Chloride) (PVC) and Related Plastic Pipe and Fitting Compounds¹¹
 - D 3951 Practice for Commercial Packaging¹²
 - E 674 Specification for Industrial Perforated Plate and Screens (Round Opening Series)¹³
 - F 104 Classification System for NonMetallic Gasket Materials¹⁴
 - F 437 Specification for Threaded Chlorinated Poly(Vinyl Chloride) (CPVC) Plastic Pipe Fittings, Schedule 80¹⁵
 - F 439 Specifications for Socket-Type Chlorinated Poly(Vinyl Chloride) (CPVC) Plastic Pipe Fittings (Schedule 80)¹⁵
 - F 441 Specification for Chlorinated Poly(Vinyl Chloride) (CPVC) Plastic Pipe, Schedules 40 and 80¹⁵
 - F 442 Specification for Chlorinated Poly(Vinyl Chloride) (CPVC) Plastic Pipe, (SDR-PR)¹⁵
 - F 443 Specification for Bell-End Chlorinated Poly(Vinyl Chloride) (CPVC) Pipe, Schedule 40¹⁵
- 2.2 *Underwriters Laboratory Standards:*¹⁶
- UL 430 Waste Disposers

¹ This specification is under the jurisdiction of ASTM Committee F-26 on Food Service Equipment and is the direct responsibility of Subcommittee F26.04 on Mechanical Preparation Equipment.

Current edition approved July 25, 1988. Published September 1988.

² *Annual Book of ASTM Standards*, Vol 01.04.

³ *Annual Book of ASTM Standards*, Vol 01.05.

⁴ Discontinued. See *Annual Book of ASTM Standards*, Vol 01.01.

⁵ *Annual Book of ASTM Standards*, Vol 01.02.

⁶ *Annual Book of ASTM Standards*, Vol 01.03.

⁷ *Annual Book of ASTM Standards*, Vol 01.01.

⁸ *Annual Book of ASTM Standards*, Vol 02.01.

⁹ *Annual Book of ASTM Standards*, Vol 09.01.

¹⁰ *Annual Book of ASTM Standards*, Vol 08.02.

¹¹ *Annual Book of ASTM Standards*, Vol 08.04.

¹² *Annual Book of ASTM Standards*, Vol 15.09.

¹³ *Annual Book of ASTM Standards*, Vol 14.02.

¹⁴ *Annual Book of ASTM Standards*, Vol 09.02.

¹⁵ *Annual Book of ASTM Standards*, Vol 08.04.

¹⁶ Available from Underwriters Laboratories, Inc., 333 Pfingsten Road, Northbrook, IL 60062.

UL 508 Electrical Industrial Control Equipment
 2.3 National Fire Protection Agency Standard:¹⁷
 NFPA No. 70 National Electric Code

2.4 Other Publication:

ASSE Standard No. 1012 Backflow Preventers with Intermediate Atmospheric Vent¹⁸

3. Terminology

3.1 *General*—Commercial pulpers with waterpresses are intended for grinding food waste, food service paper and cardboard products, food service plastic products, documents including computer printouts, general office and retail store paper, and cardboard waste. Materials are ground in a water-filled tank (pulper) to produce a slurry which is then passed to the waterpress to be de-watered. Pulpers are not intended to be used for grinding glass, china, metal, wood, clam, or oyster shells. Any small pieces of metal inadvertently placed in the pulper, such as cardboard box staples, aluminum refreshment cans, or tin food cans, shall be removable from the outside of the pulper tank.

3.2 *Definitions of Terms Specific to This Standard:*

3.2.1 *pulper*—the pulper tank has a motor driven grinding disk to grind and cut waste material, and mixes this material with water to produce a slurry that is pumped to the waterpress through a sizing screen. Pulpers may consist of the following principle parts: tank, motor, grinding disk, particle sizing ring, trash box, legs, feed chute, stationary, and rotating cutters.

3.3 *waterpress*—the waterpress de-waters the slurry generated in the pulper by use of a tapered compression cone and perforated screen, then discharges the pulp down a chute to a waste container. Water removed during this process is pumped to the pulper tank in order to conserve fresh water use. Waterpresses may consist of the following parts: shell, helical transport screw, perforated screen, gearbox, motor, compression cone, discharge housing, chute, and pump.

4. Classification

4.1 *General*—Pulper and waterpress assemblies shall be of the following type, size, and options as specified.

4.2 *Type, Size, and Options* (See Table 1):

4.2.1 *Type A*—Free-standing pulper and waterpress assembly with tray assembly and flanged feet.

4.2.2 *Type B*—Undercounter pulper for 34-in. (86-cm) high counter and waterpress with feed hood and bullet feet.

4.3 All equipment of the same model designation and options on the same purchase order shall have component interchangeability for serviceability.

5. Ordering Information

5.1 Purchasers should select the preferred options permitted in this specification and include the following information in procurement documents:

5.1.1 Title, number, and date of this standard.

¹⁷ Available from the National Fire Protection Agency, Batterymarch Park, Quincy, MA 02269.

¹⁸ Available from American Society of Sanitary Engineering, P.O. Box 9712, Bay Village, OH 44140.

TABLE 1 Type, Size, and Options

Options	Type Pulper with Waterpress	A		B	
	Size Pulper Diameter Inches—Maximum	24	30	24	30
	Pulper Motor HP	5	7.5	5	7.5
	Waterpress Motor HP	2	3	2	3
1	Automatic Shutdown Timer	3	3	3	3
2	18 In. Higher than Standard Waterpress	3	3	3	3
3	Tray Flush (Recirculated Water)	3	3	3	3
4	Trough Flush (Recirculated)	2	2	3	3
5	Single Feed Through Connection	2	2	3	3
6	Double Feed Through Connection	2	2	3	3
7	Feed Hood with Tray	4	4	3	3

- (1) Pulper cover plate supplied in lieu of feed hood.
- (2) Pulper and waterpress type not compatible with optional feature.
- (3) Indicates available option for given type pulper with waterpress.
- (4) Standard for Type A.

- 5.1.2 Classification of size and type (see Section 4).
- 5.1.3 Electrical power supply voltage range (see 9.1).
- 5.1.4 Electrical controls when specified to be remote from the unit (see 9.3).
- 5.1.5 Optional automatic shutdown timer when specified (see Section 4).
- 5.1.6 Spare and maintenance parts required.
- 5.1.7 Optional tray flush uses recycled water from the waterpress when specified (see Section 4).
- 5.1.8 Optional waterpress for high profile pulp discharge 18 in. above standard height optional when specified (see Section 4).
- 5.1.9 Optional trough flush when specified (see Section 4).
- 5.1.10 Optional single feed trough connections on when specified (see Section 4).
- 5.1.11 Optional double feed trough connections when specified (see Section 4).
- 5.1.12 Optional feed hood with tray for Type B (see Section 4).
- 5.1.13 Designate special features required for installation, such as location of controls, location of feed-hood and trough openings, waterpress discharge location, and location for cold water and drain connections.

6. Materials

6.1 Unless otherwise specified, pulpers and waterpresses shall be fabricated of materials specified in documents referenced in Section 2. Materials used shall be free from defects which would adversely affect the performance or maintainability of individual components or the overall assembly. Unit shall be manufactured for cleanability.

6.1.1 *Corrosion-Resistant Steel*—Shall conform to the requirements of any 300 series steel specified in Specification A 167, Specification A 554, Specification A 276, and Specification A 582.

6.1.2 *Corrosion-Resisting Material*—Corrosion-resisting material is other than corrosion resistant steel that is equivalent in the pulper and waterpress application.

6.1.3 *Abrasion-Resistant Cast Iron*—Shall conform to the requirements specified in Specification A 532.

6.1.4 *Austenitic Gray Iron*—Shall conform to the requirements specified in Specification A 436.