

Edition 1.0 2016-07

INTERNATIONAL STANDARD

NORME **INTERNATIONALE**

Fibre optic interconnecting devices and passive components - Performance standard -

Part 052-6: Single-mode fibre non-connectorized fixed attenuator – Category O in outside plant environment

IEC 61753-052-6:2016

https://standards.iteh.ai/catalog/standards/sist/9e760593-0506-4a4b-ba00-Dispositifs d'interconnexion et composants passifs fibroniques – Norme de performance -

Partie 052-6: Affaiblisseur fixe non connectorisé à fibres unimodales - Catégorie O pour des installations dans un environnement extérieur





THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2016 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office 3, rue de Varembé CH-1211 Geneva 20 Switzerland

Tel.: +41 22 919 02 11 info@iec.ch www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad SLAHUALU

IEC publications search - webstore.iec.ch/advsearchform

variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing 21/000 terms and definitions in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

The advanced search enables to find IEC publications by a)-0.67-000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Catalogue IEC - webstore.iec.ch/catalogue

Application autonome pour consulter tous les renseignements bibliographiques sur les Normes internationales, Spécifications techniques, Rapports techniques et autres documents de l'IEC. Disponible pour PC, Mac OS, tablettes Android et iPad.

Recherche de publications IEC webstore.iec.ch/advsearchform

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études,...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire en ligne de termes électroniques et électriques. Il contient 21 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans 16 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Glossaire IEC - std.iec.ch/glossary

67 000 entrées terminologiques électrotechniques, en anglais et en français, extraites des articles Termes et Définitions des publications IEC parues depuis 2002. Plus certaines entrées antérieures extraites des publications des CE 37, 77, 86 et CISPR de l'IEC.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: sales@iec.ch.



Edition 1.0 2016-07

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Fibre optic interconnecting devices and passive components – Performance standard – (standards.iteh.ai) Part 052-6: Single-mode fibre non-connectorized fixed attenuator – Category O in outside plant environment IEC 61753-052-6:2016

https://standards.iteh.ai/catalog/standards/sist/9e760593-0506-4a4b-ba00-

Dispositifs d'interconnexion et composants passifs fibroniques – Norme de performance –

Partie 052-6: Affaiblisseur fixe non connectorisé à fibres unimodales – Catégorie O pour des installations dans un environnement extérieur

INTERNATIONAL ELECTROTECHNICAL COMMISSION

COMMISSION ELECTROTECHNIQUE INTERNATIONALE

ICS 33.180.20

ISBN 978-2-8322-5270-3

Warning! Make sure that you obtained this publication from an authorized distributor. Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

 Registered trademark of the International Electrotechnical Commission Marque déposée de la Commission Electrotechnique Internationale

CONTENTS

FOREWORD	3
1 Scope	5
2 Normative references	5
3 Test	6
4 Test report	6
5 Performance requirements	6
5.1 Sample size, sequencing and grouping	6
5.2 Dimensions	6
5.3 Test details and requirements	6
Annex A (normative) Test sequencing for single-mode non-connectorized fixed attenuators, category O	12
Bibliography	
Table 1 – Test details and requirements	7
Table A.1 – Test sequence for single-mode non-connectorized fixed attenuators,	

iTeh STANDARD PREVIEW (standards.iteh.ai)

category O12

<u>IEC 61753-052-6:2016</u> https://standards.iteh.ai/catalog/standards/sist/9e760593-0506-4a4b-ba00-457f328910a7/iec-61753-052-6-2016 INTERNATIONAL ELECTROTECHNICAL COMMISSION

FIBRE OPTIC INTERCONNECTING DEVICES AND PASSIVE COMPONENTS – PERFORMANCE STANDARD –

Part 052-6: Single-mode fibre non-connectorized fixed attenuator – Category O in outside plant environment

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, TEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61753-052-6 had been prepared by subcommittee 86B: Fibre optic interconnecting devices and passive components of IEC technical committee 86: Fibre optics.

This bilingual version (2018-01) corresponds to the monolingual English version, published in 2016-07.

The text of this standard is based on the following documents:

FDIS	Report on voting
86B/3995/FDIS	86B/4010/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

The French version of this standard has not been voted upon.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 61753 series, published under the general title Fibre optic interconnecting devices and passive components – Performance standard, can be found on the IEC website.

Future standards in this series will carry the new general title as cited above. Titles of existing standards in this series will be updated at the time of the next edition.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn, .

iTeh STANDARD PREVIEW

(standards.iteh.ai)

- replaced by a revised edition, or
- amended.

IEC 61753-052-6:2016 https://standards.iteh.ai/catalog/standards/sist/9e760593-0506-4a4b-ba00-457f328910a7/jec-61753-052-6-2016

FIBRE OPTIC INTERCONNECTING DEVICES AND PASSIVE COMPONENTS -PERFORMANCE STANDARD -

Part 052-6: Single-mode fibre non-connectorized fixed attenuator -Category O in outside plant environment

1 Scope

This part of IEC 61753 contains the minimum initial test and measurement requirements and severities which a fibre optic attenuator satisfies in order to be categorised as meeting the requirements of single-mode fibre non-connectorized fixed attenuator devices used in outside plant environments. IEC 60869-1 contains the generic specification of the optical attenuator.

Optical performances specified in this document relate only to non-connectorized optical attenuators.

Normative references 2

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61753-052-6:2016

IEC 60793-2-50, Optical fibres – Part 2-50, Product specifications – Sectional specification for class B single-mode fibres

IEC 60794-2-50, Optical fibre cables - Part 2.50: Indoor cables - Family specification for simplex and duplex cables for use in terminated cable assemblies

IEC 61300-2-1, Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-1: Tests – Vibration (sinusoidal)

IEC 61300-2-4, Fibre optic interconnecting devices and passive components - Basic test and measurement procedures – Part 2-4: Tests – Fibre/cable retention

IEC 61300-2-5, Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-5:Tests – Torsion

IEC 61300-2-9, Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-9: Tests – Shock

IEC 61300-2-14, Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-14: Tests – High optical power

IEC 61300-2-19, Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-19: Tests – Damp heat (steady state)

IEC 61300-2-22, Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-22: Tests – Change of temperature

IEC 61300-2-42, Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-42: Tests – Static side load for strain relief

IEC 61300-2-44, Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-44: Tests – Flexing of the strain relief of fibre optic devices

IEC 61300-2-48, Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-48: Tests – Temperature-humidity cycling

IEC 61300-3-2, Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-2: Examination and measurements – Polarization dependent loss in a single-mode fibre optic device

IEC 61300-3-3, Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-3: Examinations and measurements – Active monitoring of changes in attenuation and return loss

IEC 61300-3-7, Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-7: Examinations and measurements – Wavelength dependence of attenuation and return loss of single mode components

3 Test

All test methods are in accordance with the IEC 61300 series. Tests validate performance over

All test methods are in accordance with the IEC 61300 series. Tests validate performance over the required operating wavelength and power range. The samples shall be terminated onto single-mode fibres as per IEC 60793-2-50, type B1.1 or B1.3 or B6 in either coated fibres (primary and secondary) or reinforced cable format as per IEC 60794-2-50.

<u>IEC 61753-052-6:2016</u> https://standards.iteh.ai/catalog/standards/sist/9e760593-0506-4a4b-ba00-457f328910a7/iec-61753-052-6-2016

4 Test report

Fully documented test reports and supporting evidence shall be prepared and shall be available for inspection as evidence that the tests have been carried out and complied with.

5 Performance requirements

5.1 Sample size, sequencing and grouping

The sample size to be used for the tests shall be as defined in Annex A.

5.2 Dimensions

Dimensions shall comply with those given in appropriate manufacturer's drawings.

5.3 Test details and requirements

Table 1 defines the performance requirements and test details for single-mode non-connectorized fixed attenuators, category O.

No. 1

2

3

4

test, the return loss shall

meet the requirements of

During the test, insertion

 $\leq \pm$ 0,5 dB for attenuator

 $\leq \pm$ 10% for attenuators

During the test, the maximum allowed change in

insertion loss is:

loss and return loss shall be

test No. 2.

monitored.

 \leq 5 dB.

> 5 dB.

Tests	Requirements	Details		
Attenuation	Operating wavelength	Method:	Method B2.1	
IEC 61300-3-7	range: 1 260 nm to 1 360 nm and/or 1 460 nm to 1 625 nm	Launch patchcord length:	≥ 2 m. Only the fundamental mode shall propagate at the attenuator interface and at the detector.	
	For nominal values \leq 5 dB, the tolerance shall be $\leq \pm 0.5$ dB around the nominal insertion loss value.	Launch conditions:	The wavelength of the source shall be longer than cut-off wavelength of the fibre.	
	For nominal values > 5 dB, the tolerance shall be $\leq \pm 10$ % around the	Optical source wavelength:	Tunable narrowband non polarized source. 1 260 nm to 1 360 nm and 1 460 nm to 1 660 nm	
	nominal insertion loss value.	Source power stability:	Within \pm 0,05 dB over the measuring period or at least 1 h	
		Total uncertainty:	$\leq \pm 0,1 \text{ dB}$	
Return loss	≥ 50 dB	Method:	measurement method 1 OCWR	
IEC 61300-3-7		Optical source wavelength:	1 310 nm \pm 10 nm, 1 550 nm \pm 10 nm and 1 625 nm \pm 10 nm	
			Test every sample with the three wavelengths.	
	iTeh STAND	Other requirements:	This test shall be performed twice, reversing the sample. Both measurements shall be within the specified limits.	
Delevizetiev				
Polarization dependent loss IEC 61300-3-2	\leq 0,3 dB at 1 550 nm The samples shall be terminated onto single-mode	Method: Optical source wavelength:	1 310 nm \pm 10 nm, 1 550 nm \pm 10 nm and/or 1 625 nm \pm 10 nm	
h	fibres as per IEC 60793-2-50 ttps://standards.itch.ai/catalog/stan	5 3 officertainty: ndards/sist/9e760593	≤ ± 0,05 dB over the dynamic range to be measured00-	
High optical	Before, during and after the	Method: 052-6-201	6	
power	test, the insertion loss shall meet the requirements of	Test temperature:	25 °C ± 2 °C	
IEC 61300-2-14	test No.1 Before, during and after the	Optical source wavelength:	1 550 nm ± 10 nm	
	test the return loss shall	— • • • •		

Test duration:

Power:

1 h

of 100 mW.

For nominal insertion loss \leq 5 dB:

For nominal insertion loss > 5 dB:

100 mW continuous power increments

10 mW continuous power increments

The above increments are applied up

to the maximum allowed power input

Table 1 – Test details and requirements

- 7 -

- 8 -

No.	Tests	Requirements		Details
5	Damp heat (steady state) IEC 61300-2-19	Before and after the test, the insertion loss requirements of test No. 1 shall be met.	Temperature:	+ 75 °C ± 2 °C
		Before and after the test,	Relative humidity:	> 90 % RH ± 2 % RH
		the return loss requirement of test No. 2 shall be met.	Duration:	168 h
		During the test, the change in Insertion Loss shall be measured by test method IEC 61300-3-3	Optical source wavelength:	1 310 nm \pm 10 nm, 1 550 nm \pm 10 nm and/or 1 625 nm \pm 10 nm
				Before and after the test the samples will be measured with three wavelengths. During the test the samples will be measured with one wavelength.
			Maximum sampling interval during the test:	1 h
			Specimen optically functioning:	Yes
6	Vibration	Before, during and after the test, the insertion loss shall		
	IEC 61300-2-1	meet the requirements of	Frequency range:	10 Hz to 55 Hz
	test No. 1. Before and after the test, the return loss shall meet the requirements of test No. 2.	Constant vibration amplitude:	1,52 mm	
		Duration per axis: Number of axes:	2 h 3 orthogonal	
		During test, the change in a insertion loss shall be $\leq \pm 0.5$ dB.	Sweep rate: Optical source wavelength:	1 octave/min 1 310 nm ± 10 nm, 1 550 nm ± 10 nm and/or 1 625 nm ± 10 nm
	https://standards.iteh.ai/catalog/sta	<u>53-052-6:2016</u> ndards/sist/9e760593- ec-61753-052-6-201	Before and after the test the samples will be measured with three wavelengths. During the test the samples will be measured with one wavelength.	
			Specimen optically functioning:	Yes
7	Shock IEC 61300-2-9	Before and after the test, the insertion loss shall meet the requirements of test No. 1.	Acceleration force:	5 000 m/s²
		Before and after the test the	Number of axes:	3 axes, 2 directions
		return loss shall meet the requirements of test No. 2.	Number of cycles:	2 shocks per direction, 12 shocks total
			Duration per axis:	Nominal 1 ms duration, half sine pulse
			Measurements required:	Before, after each axis, and after the test
			Specimen optically functioning:	Νο
			Optical source Wavelength	1 310 nm \pm 10 nm, 1 550 nm \pm 10 nm and/or 1 625 nm \pm 10 nm

No.	Tests	Requirements		Details
8	Change of	Before, during and after the	Method:	Test Nb
	temperature IEC 61300-2- 22	test, the insertion loss requirements of test No. 1 shall be met.		During the test the change in insertion loss shall be measured by test method IEC 61300-3-3.
		Before and after the test, the return loss requirement of test No. 2 shall be met.	High temperature:	+75 °C ± 2 °C
			Low temperature:	-40 °C ± 2 °C
			Number of cycles:	10
			Rate of	1 °C/min
			temperature change:	Dwell at + 23 °C allowed between temperature extreme.
			Duration at extreme temperatures:	1 h
			Optical source wavelength:	1 310 nm \pm 10 nm, 1 550 nm \pm 10 nm and/or 1 625 nm \pm 10 nm
				Before and after the test the samples will be measured with three wavelengths. During the test the samples will be measured with one wavelength.
			Maximum	15 min
		iTeh STAND	sampling interval during the test: Specimen	Yes
		(standa)	optically eh ai	
9	Temperature- humidity cycling h IEC 61300-2-	Before, during and after the test, the insertion lose shall 7 the requirements of star test No. 1. 457f328910a7/i	Method: 53-052-6:2016 ndards/sist/9e760593- ec-61753-052-6-201	Method A During the test, the change in insertion loss shall be measured by test method IEC 61300-3-3.
	48	Before and after the test, the return loss shall meet the requirements of test No. 2.	Temperature range:	(-40 \pm 2) °C to (+85 \pm 2) °C for primary, secondary coated fibre, and reinforced cables, but limited to: (-40 \pm 2) °C to (+ 75 \pm 2) °C for LSZH cables
			Relative humidity:	85 % RH \pm 5 % RH at the maximum temperature
			Duration:	1 h minimum duration at extremes
			Rate of temperature change:	1 °C /min rate of change
			Number of cycles:	42
			Optical source wavelength:	1 310 nm \pm 10 nm, 1 550 nm \pm 10 nm and/or 1 625 nm \pm 10 nm
				Before and after the test the samples will be measured with three wavelengths. During the test the samples will be measured with one wavelength.
			Specimen optically functioning:	Yes

No.	Tests	Requirements	Details	
10	Optical fibre cable flexing IEC 61300-2- 44	Before and after the test, the insertion loss shall meet the requirements of test No. 1. Before and after the test,	Method: Magnitude of the load:	5 N for reinforced cable 2 N for primary and secondary coated fibres
		the return loss shall meet the requirements of test No. 2.	Angle of deflection per cycle:	± 90°
			Number of cycles:	30
			Specimen optically functioning:	Νο
			Method of mounting:	The sample shall be rigidly mounted such that the load is only applied to the fibre/cable.
11	Torsion/twist	,	Method:	IEC 61300-2-5
	IEC 61300-2-5		Magnitude of the load:	5,0 N at 0,1 N/s for reinforced cables 2,0 N at 0,1 N/s for primary and secondary coated fibres
			Rate of load application:	0,1 N/s
	No. 2.	No. 2.	Number of cycles:	10 cycles, \pm 180° angular movement
		iTeh STAND	Specimen optically functioning:	N°IEW
12	Static side load ^a IEC 61300-2- 42 h	Before and after the test, 2 the insertion loss shall meet the requirements of test No. 1. IEC 617 Before and after the test stat the return loss shall meet 7/1		5 N for 5 s for reinforced cable 2,3 N for 5 s for primary and secondary coated fibres 0506-4a4b-ba00-
		the requirements of test No. 2.	Load application point:	0,3 m from the end of the device and two mutually perpendicular directions as permitted by the product design
			Specimen optically functioning:	Νο