

SLOVENSKI STANDARD SIST EN 10020:2000

01-november-2000

Nadomešča:

SIST EN 10020:1988/AC1:1989:2007

SIST EN 10020:1995

SIST EN 10020:1995/AC1:1996

Definicija in razvrščanje jekel

Definition and classification of grades of steel

Begriffsbestimmung für die Einteilung der Stähle (standards.iteh.ai)

Définition et classification des nuances d'acier 020:2000

https://standards.iteh.ai/catalog/standards/sist/c621d12a-de22-4485-a77a-

531d505bcbb0/sist-en-10020-2000

Ta slovenski standard je istoveten z: EN 10020:2000

ICS:

01.040.77 Metalurgija (Slovarji) Metallurgy (Vocabularies)

77.080.20 Jekla Steels

SIST EN 10020:2000 en

SIST EN 10020:2000

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 10020:2000

https://standards.iteh.ai/catalog/standards/sist/c621d12a-de22-4485-a77a-531d505bcbb0/sist-en-10020-2000

EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

EN 10020

March 2000

ICS 01.040.77; 77.080.20

Supersedes EN 10020:1988

English version

Definition and classification of grades of steel

Définition et classification des nuances d'acier

Begriffsbestimmung für die Einteilung der Stähle

This European Standard was approved by CEN on 18 February 2000.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.

(standards.iteh.ai)

<u>SIST EN 10020:2000</u> https://standards.iteh.ai/catalog/standards/sist/c621d12a-de22-4485-a77a-531d505bcbb0/sist-en-10020-2000



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Central Secretariat: rue de Stassart, 36 B-1050 Brussels

Contents

Foreword3						
1	Scope	4				
2	Term and definition					
3	Classification by chemical composition					
	Applicable alloy contents	4 4				
3.2	Applicable alloy contents Definition of classes	5				
3.2.1	Non alloy steels	5				
3.2.2	Stainless steels	5				
	Other alloy steels					
4	Classification of main quality classes	6				
4.1	Non alloy steelsNon alloy quality steels	6				
4.1.1	Non alloy quality steels	6				
4.1.2	Non alloy special steels	6				
4.2	Stainless steels	7				
4.3	Other alloy steels	7				
4.3.1	Alloy quality steels	7				
4.3.2	Alloy quality steels	8				
	11eh STANDARD PREVIEW					

(standards.iteh.ai)

SIST EN 10020:2000

https://standards.iteh.ai/catalog/standards/sist/c621d12a-de22-4485-a77a-531d505bcbb0/sist-en-10020-2000

Foreword

This European Standard has been prepared by Technical Committee ECISS/TC 6 "Steels - Definition and classification", the secretariat of which is held by AFNOR.

This European Standard replaces EN 10020:1988.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by September 2000, and conflicting national standards shall be withdrawn at the latest by September 2000.

At the Co-ordination Committee (COCOR) meeting of May 31/June 1, 1995, ECISS decided to revise EN 10020:1988.

That standard used EURONORM 20:1974 as the basis for work, revising it to align EN 10020 as far as possible at that time :

- with the Harmonised System nomenclature of the World Customs Organisation (WCO);
- with ISO 4948-1 and ISO 4948-2 :

taking into account experience gained from using the EURONORM together with new developments in the steel industry.

This European standard is more closely aligned with the Harmonised System in that the same limit values have been adopted for alloy relements, stogether with deletion of the aprevious "70 % rule" for specified combinations of elements. 531d505bcbb0/sist-en-10020-2000

One main quality class in EN 10020:1988, base steels, has been deleted and merged with non alloy quality steels.

Further developments in the iron and steel industry and progress in European standardisation have also been taken into account.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and the United Kingdom.

Page 4 EN 10020:2000

1 Scope

This European Standard defines the term "steel" (see clause 2) and classifies steel grades into:

- non alloy, stainless steel and other alloy steels by chemical composition (see clause 3);
- main quality classes (see clause 4) defined by main property or application characteristics for non alloy, stainless and other alloy steels.

2 Term and definition

For the purposes of this standard, the following term and definition apply:

2.1

steel

material which contains by mass more iron than any other single element, having a carbon content generally less than 2% and containing other elements. A limited number of chromium steels may contain more than 2% of carbon, but 2% is the usual dividing line between steel and cast iron.

3 Classification by chemical composition

3.1 Applicable alloy contents STANDARD PREVIEW

For European standards the classification given in the product standard or specification applies regardless of the steel which is actually produced, provided that the chemical composition complies with the requirements of the standard concerned.

SIST EN 10020:2000

- 3.1.1 Classification is based on the ladle analysis specified in the product standard or specification and is determined by the minimum value specified for each element. 10020-2000
- **3.1.2** Where for elements other than manganese a maximum value only is specified in the product standard or specification for the ladle analysis, a value of 70 % of this maximum value shall be taken for classification as set out in tables 1 and 2. For manganese see note a of table 1.
- **3.1.3** Where a product standard or specification is based on product analysis an equivalent ladle analysis is calculated using the permitted deviations from ladle analysis specified in the product standard or specification or corresponding European Standard or EURONORM.
- **3.1.4** In the absence of a product standard or specification or a precisely specified chemical composition, classification is based on the actual ladle analysis reported by the manufacturer.
- **3.1.5** The results of product analysis may deviate from those of the ladle analysis to an extent permitted by the appropriate product standard or specification (such deviations do not affect the classification of the steel as non alloy or alloy).

If the product analysis indicates a value, which would place the steel in a class other than intended, then its inclusion in the class originally intended shall be separately and reliably substantiated.

- **3.1.6** Composite or coated products are classified according to the specified chemical composition of the product, which has been coated or clad.
- **3.1.7** For each alloy element, the specified, calculated or actual ladle analysis value is expressed to the same number of decimal places as the corresponding limit value shown in table 1. For example in this European Standard a specified range of 0,3 % to 0,5 % corresponds to a range of 0,30 % to 0,50 %. Similarly a specified content of 2 % is taken to mean a content of 2,00 %.

3.2 Definition of classes

3.2.1 Non alloy steels

Non alloy steels are steel grades in which none of the limit values in table 1 is reached by the contents as defined in 3.1.

3.2.2 Stainless steels

Stainless steels are steels with at least 10,5 % of chromium and max.1,2% of carbon .

3.2.3 Other alloy steels

Other alloy steels are steel grades not complying with the definition of stainless steels in which at least one of the limit values in table 1 is reached by the contents as defined in 3.1.

Table 1 - Boundary between non alloy and alloy steels (ladle analysis)

Specified element	Limit value					
	% by mass					
Al Aluminium	0,30					
B Boron	0,0008					
Bi Bismuth iTeh STANDARD PREV	0,10					
Co Cobalt (standards.iteh.ai)	0,30					
Cr Chromium	0,30					
Cu Copper SIST EN 10020:2000 https://standards.iteh.ai/catalog/standards/sist/c621d12a-d	-22-4485-27 0,4 0					
La Lanthanides (each) 531d505bcbb0/sist-en-10020-2000	0,10					
Mn Manganese	1,65 ^{a)}					
Mo Molybdenum	0,08					
Nb Niobium	0,06					
Ni Nickel	0,30					
Pb Lead	0,40					
Se Selenium	0,10					
Si Silicon	0,60					
Te Tellurium	0,10					
Ti Titanium	0,05					
V Vanadium	0,10					
W Tungsten	0,30					
Zr Zirconium	0,05					
Others (except carbon, phosphorus, sulphur, nitrogen) (each) a) Where manganese is specified only as a maximum the limit value is 1,80 % and the 70 % rule						
(see 3.1.2) does not apply.						

Page 6 EN 10020:2000

4 Classification of main quality classes

4.1 Non alloy steels

4.1.1 Non alloy quality steels

4.1.1.1 General description

Non alloy quality steels are steel grades which, in general, have specified property requirements such as, for example, toughness, grain size control and/or formability.

4.1.1.2 Definition

Non alloy quality steels are non alloy steels other than those defined in 4.1.2.2 as non alloy special steels.

Non alloy electrical steels are defined as: non alloy quality steels with specified requirements for maximum values of specific total loss or minimum values of magnetic induction, polarisation or permeability

4.1.2 Non alloy special steels

4.1.2.1 General description

Non alloy special steels have a higher degree of cleanness than quality steels particularly in respect of non-metallic inclusions. In most cases they are intended for quenching and tempering or surface hardening and are characterized by consistent response to such treatment. Precise control of chemical composition and special care in manufacture and process control ensure improved properties to meet exacting requirements. These properties which are generally in combination and within closely controlled limits include high or closely controlled strength or hardenability values sometimes associated with suitability for cold forming, welding or toughness.

SIST EN 10020:2000

4.1.2.2 Definition

https://standards.iteh.ai/catalog/standards/sist/c621d12a-de22-4485-a77a-531d505bcbb0/sist-en-10020-2000

Non alloy special steels are steel grades, which comply with one or more of the following requirements:

- specified minimum impact strength in the quenched and tempered condition;
- specified hardness penetration depth or surface hardness in the quenched, quenched and tempered or surface hardened condition;
- particularly low contents of non-metallic inclusions are specified;

NOTE This class includes grades where the product standard or specification specifies such limitations of inclusions subject to agreement at the time of ordering. However, specified through thickness reduction of area properties do not change the classification of the original steel.

- specified maximum phosphorus and sulphur content:
 - for ladle analysis $\leq 0.020 \%$:
 - for product analysis \leq 0,025 %.

(e.g. rod for high strength springs, electrodes, tyre cord wire);

specified minimum impact strength on Charpy-V-notch test pieces at - 50 °C greater than 27 J for test pieces taken in the longitudinal direction or greater than 16 J for test pieces taken in the transverse direction ;

¹⁾ If no impact value is specified at - 50 °C the value specified between - 50 °C and - 60 °C shall be used.

 steels t	for	nuclear	reactors	having	the	following	specified	elements	simultaneously	restricted	on	product
analysis	s to	:		, -		•	•				• • •	p. 0 a a o

- copper \leq 0,10 %, cobalt \leq 0,05 %, vanadium \leq 0,05 %;
- specified electrical conductivity > 9 S⁻m/mm²;
- precipitation hardening steels with minimum specified carbon contents of 0,25 % or more in the ladle analysis and a ferritic/pearlitic microstructure, containing one or more micro alloy elements such as niobium or vanadium with contents less than the limit values for alloy steels. Precipitation hardening is generally achieved by controlled cooling from the hot forming temperature;
- prestressing steels.

4.2 Stainless steels

Stainless steels are defined by chemical composition in 3.2.2. They are subdivided further according to the following criteria :

- by nickel content into:
 - nickel less than 2,5 %;
 - nickel 2,5 % or more.
- by main property into :

iTeh STANDARD PREVIEW

corrosion resisting;

(standards.iteh.ai)

— heat resisting ;

SIST EN 10020:2000

creep resisting.

https://standards.iteh.ai/catalog/standards/sist/c621d12a-de22-4485-a77a-531d505bcbb0/sist-en-10020-2000

4.3 Other alloy steels

4.3.1 Alloy quality steels

4.3.1.1 General description

Alloy quality steels are steel grades for which requirements exist with regard to, for example, toughness, grain size control and/or formability.

Alloy quality steels are not generally intended for quenching and tempering or for surface hardening.

4.3.1.2 Definition

Alloy quality steels are given in 4.3.1.2.1 to 4.3.1.2.5.

- **4.3.1.2.1** Weldable fine grained structural steels, including steels for pressure vessels and tubes, other than those defined in 4.3.1.2.3 which meet all the following conditions:
- specified minimum yield strength < 380 N/mm² for thickness ≤ 16 mm;
- alloy contents as defined by 3.1 are less than the limit values given in table 2;
- specified minimum impact strength on Charpy-V-notch test pieces at 50 °C ≤ 27 J for test pieces taken in the longitudinal direction or ≤ 16 J for test pieces taken in the transverse direction .

¹⁾ If no impact value is specified at – 50°C the value specified between – 50°C and –60°C shall be used.