



SLOVENSKI STANDARD

SIST EN 300 392-2 V2.5.2:2006

01-april-2006

Prizemni snopovni radio (TETRA) – Govor in podatki (V+D) – 2. del: Radijski vmesnik (AI)

Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 2: Air Interface (AI)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 392-2 V2.5.2:2006](https://standards.iteh.ai/catalog/standards/sist/4cdf3e3e-7143-4b03-8f4e-12c182d95700/sist-en-300-392-2-v2-5-2-2006)

Ta slovenski standard je istoveten z: **EN 300 392-2 Version 2.5.2**

ICS:

33.070.10	Prizemni snopovni radio (TETRA)	Terrestrial Trunked Radio (TETRA)
-----------	---------------------------------	-----------------------------------

SIST EN 300 392-2 V2.5.2:2006 **en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 392-2 V2.5.2:2006

<https://standards.iteh.ai/catalog/standards/sist/4cd3eccc-7143-4b03-8f4e-12c182f937b0/sist-en-300-392-2-v2-5-2-2006>

ETSI EN 300 392-2 V2.5.2 (2005-11)

European Standard (Telecommunications series)

Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 2: Air Interface (AI)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 392-2 V2.5.2:2006](https://standards.iteh.ai/catalog/standards/sist/4cd3eccc-7143-4b03-8f4e-12c182f937b0/sist-en-300-392-2-v2-5-2-2006)

<https://standards.iteh.ai/catalog/standards/sist/4cd3eccc-7143-4b03-8f4e-12c182f937b0/sist-en-300-392-2-v2-5-2-2006>



Reference

REN/TETRA-03129

Keywords

radio, TETRA, V+D**ETSI**

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 392-2 V2.5.2:2006<https://standards.iteh.ai/catalog/standards/sist/4cd3e3ce-7143-4b03-8f4e-12c182f9377d/etsi-en-300-392-2-v2-5-2-2006>**Important notice**

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2005.
All rights reserved.

DECT™, **PLUGTESTS™** and **UMTS™** are Trade Marks of ETSI registered for the benefit of its Members.
TIPHON™ and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members.
3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Contents

Intellectual Property Rights	31
Foreword.....	31
1 Scope	33
2 References	34
3 Definitions and abbreviations.....	36
3.1 Definitions	36
3.2 Abbreviations	41
4 Radio aspects.....	45
4.1 Introduction	45
4.2 Set of logical channels.....	45
4.3 Reference configuration	45
4.4 Error control schemes.....	45
4.5 Multiple access and time slot structure.....	46
4.5.1 Hyperframes, multiframe and frames.....	46
4.5.2 Time slots and bursts	46
4.5.3 Mapping of logical channels onto physical channels.....	47
4.6 Coding, interleaving and scrambling.....	47
4.7 Modulation	47
4.8 Transmission and reception.....	47
4.9 Other radio-related functions.....	47
4.10 Performance	48
4.11 TETRA modes of operation	48
4.11.1 Transmission modes	48
4.11.1.1 D-CT mode	48
4.11.1.2 D-CTT mode.....	48
4.11.1.3 D-MCCTT mode.....	48
4.11.1.4 U-MST mode	48
4.11.2 Control modes.....	49
4.11.2.1 NCM	49
4.11.2.2 MC mode	49
5 Modulation	50
5.1 Introduction	50
5.2 Modulation type	50
5.3 Modulation rate	50
5.4 Modulation symbol definition.....	50
5.5 Modulated signal definition.....	51
5.6 Modulation filter definition.....	52
5.7 Modulation block diagram	52
6 Radio transmission and reception.....	53
6.1 Introduction	53
6.2 Frequency bands and channel arrangement.....	53
6.3 Reference test planes	53
6.4 Transmitter characteristics.....	54
6.4.1 Output power	54
6.4.1.1 Base Station (BS).....	55
6.4.1.2 Mobile Station (MS)	55
6.4.2 Unwanted conducted emissions.....	55
6.4.2.1 Definitions.....	55
6.4.2.2 Unwanted emissions close to the carrier	56
6.4.2.2.1 Emission during the useful part of the burst	56
6.4.2.2.2 Emission during the switching transients	57
6.4.2.3 Unwanted emissions far from the carrier	57
6.4.2.4 Unwanted emissions during the CLCH and BLCH	58

6.4.2.5	Unwanted emissions in the non-transmit state	58
6.4.3	Unwanted radiated emissions	58
6.4.4	RF tolerance.....	58
6.4.5	RF Output power time mask	58
6.4.5.1	BS.....	59
6.4.5.2	MS.....	59
6.4.6	Transmitter intermodulation attenuation.....	59
6.4.6.1	Definition	59
6.4.6.2	BS.....	60
6.4.6.3	MS.....	60
6.4.7	Intra-BS intermodulation requirements	60
6.5	Receiver characteristics	60
6.5.1	Blocking characteristics	60
6.5.1.1	Definition	60
6.5.1.2	Specification.....	61
6.5.2	Spurious response rejection	61
6.5.2.1	Definition	61
6.5.2.2	Specification.....	61
6.5.3	Intermodulation response rejection.....	62
6.5.3.1	Definition	62
6.5.3.2	Specification.....	62
6.5.4	Unwanted conducted emissions	62
6.5.4.1	Definition	62
6.5.4.2	Specification.....	62
6.5.5	Unwanted radiated emissions	62
6.6	Transmitter/receiver performance	62
6.6.1	Modulation accuracy.....	63
6.6.1.1	Ideal case.....	63
6.6.1.2	Vector error magnitude requirement at symbol time	63
6.6.2	Receiver performance	64
6.6.2.1	Nominal error rates	64
6.6.2.2	Dynamic reference sensitivity performance	65
6.6.2.2.1	BS receiver performance	65
6.6.2.2.2	MS receiver performance	65
6.6.2.3	Receiver performance at reference interference ratios	66
6.6.2.3.1	BS receiver performance	66
6.6.2.3.2	MS receiver performance	67
6.6.2.4	Static reference sensitivity performance	67
6.6.2.4.1	BS receiver performance	67
6.6.2.4.2	MS receiver performance	68
6.6.2.5	MS receiver performance for synchronization burst acquisition.....	68
6.6.3	Propagation conditions	68
6.6.3.1	Propagation conditions - introduction	68
6.6.3.2	Tap-gain process types	69
6.6.3.3	Propagation models	69
7	Radio sub-system synchronization	71
7.1	Introduction	71
7.2	General description of synchronization system.....	71
7.3	Timebase counters	71
7.3.1	Timing counters	71
7.3.2	Values of the counters.....	71
7.4	Timing of transmitted signals.....	72
7.5	BS requirements for synchronization	72
7.6	MS requirements for synchronization	72
8	Channel coding and scrambling	73
8.1	Introduction	73
8.2	General	73
8.2.1	Interfaces in the error control structure.....	73
8.2.2	Notation	74
8.2.3	Definition of error control codes.....	75

8.2.3.1	16-state Rate-Compatible Punctured Convolutional (RCPC) codes	75
8.2.3.1.1	Encoding by the 16-state mother code of rate 1/4	75
8.2.3.1.2	Puncturing of the mother code.....	75
8.2.3.1.3	Puncturing scheme of the RCPC code of rate 2/3.....	76
8.2.3.1.4	Puncturing scheme of the RCPC code of rate 1/3.....	76
8.2.3.1.5	Puncturing scheme of the RCPC code of rate 292/432.....	76
8.2.3.1.6	Puncturing scheme of the RCPC code of rate 148/432.....	76
8.2.3.2	Shortened (30,14) Reed-Muller (RM) code	76
8.2.3.3	$(K_I + 16, K_I)$ block code	77
8.2.4	Definition of interleaving schemes	77
8.2.4.1	Block interleaving	77
8.2.4.2	Interleaving over N blocks	77
8.2.5	Definition of scrambling	78
8.2.5.1	Scrambling method	78
8.2.5.2	Scrambling sequence.....	78
8.3	Error control schemes.....	79
8.3.1	Access Assignment Channel (AACH).....	80
8.3.2	Broadcast Synchronization Channel (BSCH)	80
8.3.3	Traffic channels in circuit switched mode	81
8.3.3.1	Traffic CHannel, net rate = 4,8 kbit/s (TCH/4,8).....	81
8.3.3.2	Traffic CHannel, net rate = 2,4 kbit/s (TCH/2,4).....	82
8.3.3.3	Traffic CHannel, net rate = 7,2 kbit/s (TCH/7,2).....	82
8.3.3.4	Speech Traffic Channel, full slot (TCH/S).....	83
8.3.3.5	Speech Traffic Channel, half slot (TCH/S)	83
8.3.4	Signalling channels for signalling and packet mode data	83
8.3.4.1	Signalling CHannel for mapping onto Half-bursts on the Downlink (SCH/HD), Broadcast Network CHannel (BNCH), and STealing CHannel (STCH)	83
8.3.4.2	Signalling CHannel for mapping onto Half-bursts on the Uplink (SCH/HU).....	84
8.3.4.3	Signalling CHannel for mapping onto Full bursts (SCH/F).....	84
9	Channel multiplexing for V+D.....	85
9.1	Introduction	85
9.2	Logical channels	85
9.2.1	Logical channels hierarchy	85
9.2.2	Traffic channels	85
9.2.3	Control CHannels (CCH).....	85
9.2.3.1	General	85
9.2.3.2	BCCH.....	86
9.2.3.3	LCH.....	86
9.2.3.4	SCH.....	86
9.2.3.5	AACH	86
9.2.3.6	STCH	86
9.3	The physical resource	87
9.3.1	General.....	87
9.3.2	RF channels	87
9.3.3	Timeslots	88
9.3.4	TDMA frame	88
9.3.5	Timeslot numbering	88
9.3.6	Subslot	88
9.3.7	Multiframe	88
9.3.8	Hyperframe	88
9.3.9	Frame alignment	88
9.4	Physical channels	88
9.4.1	General.....	88
9.4.2	Types of physical channels	89
9.4.2.1	CP channel	89
9.4.2.2	TP channel.....	89
9.4.2.3	UP channel	89
9.4.3	Bursts	89
9.4.3.1	General	89
9.4.3.2	Modulation symbol numbering	89
9.4.3.3	Modulation bit numbering.....	90

9.4.3.4	Burst timing.....	90
9.4.4	Type of bursts	90
9.4.4.1	General.....	90
9.4.4.2	Modulation bits allocation.....	92
9.4.4.2.1	Control uplink Burst (CB).....	92
9.4.4.2.2	Linearization uplink Burst (LB).....	92
9.4.4.2.3	Linearization downlink burst.....	92
9.4.4.2.4	Normal Uplink Burst (NUB).....	93
9.4.4.2.5	Normal continuous downlink burst.....	93
9.4.4.2.6	Synchronization continuous downlink burst.....	93
9.4.4.2.7	Normal discontinuous downlink burst.....	94
9.4.4.2.8	Synchronization discontinuous downlink burst.....	94
9.4.4.3	Burst fields.....	94
9.4.4.3.1	Frequency correction field.....	94
9.4.4.3.2	Normal training sequence.....	95
9.4.4.3.3	Extended training sequence.....	95
9.4.4.3.4	Synchronization training sequence.....	95
9.4.4.3.5	Tail bits.....	95
9.4.4.3.6	Phase adjustment bits.....	96
9.4.5	Transmission modes.....	96
9.4.5.1	BS continuous transmission.....	96
9.4.5.2	BS timesharing transmission.....	97
9.4.5.3	MS multiple slot transmission.....	97
9.5	Mapping of logical channels into physical channels.....	98
9.5.1	General mapping of logical channels.....	98
9.5.2	Mapping of BCCH and CLCH.....	99
9.5.3	Mapping of SCH.....	100
9.5.4	Mapping of TCH and STCH.....	100
9.5.5	Mapping of AACB.....	100
9.6	Monitoring pattern for transmitting MSs.....	100
9.7	BS timesharing transmission.....	101
9.7.1	Carrier sharing.....	101
9.7.2	MCCH sharing.....	101
9.8	Modes of control.....	101
9.8.1	NCM.....	101
9.8.2	MCM.....	102
10	Radio subsystem link control.....	103
10.1	Introduction.....	103
10.2	RF power control.....	103
10.3	Radio link measurements.....	103
10.3.1	Received signal strength.....	103
10.3.1.1	Signal strength measurement.....	103
10.3.1.2	Sample duration for signal strength measurement.....	103
10.3.2	Signal quality.....	103
10.3.3	Round-trip MS-BS path delay.....	103
11	Call Control (CC) service description.....	104
11.1	Introduction.....	104
11.2	Services offered.....	104
11.3	CC service.....	105
11.3.1	CC primitives exchanged through the TNCC-SAP.....	105
11.3.2	Service primitives at the TNCC-SAP.....	105
11.3.3	Primitive description.....	106
11.3.3.1	TNCC-ALERT primitive.....	106
11.3.3.2	TNCC-COMPLETE primitive.....	107
11.3.3.3	TNCC-DTMF primitive.....	107
11.3.3.4	TNCC-MODIFY primitive.....	108
11.3.3.5	TNCC-NOTIFY primitive.....	108
11.3.3.6	TNCC-PROCEED primitive.....	109
11.3.3.7	TNCC-RELEASE primitive.....	109
11.3.3.8	TNCC-SETUP primitive.....	109

11.3.3.9	TNCC-TX primitive.....	111
11.3.4	Parameter description	111
11.4	States for CC SAP	119
12	Supplementary Service (SS) service description.....	119
12.1	Introduction	119
12.2	Services offered.....	120
12.3	SS service	120
12.3.1	Primitives exchanged through TNSS-SAP	120
12.3.2	Parameter description	120
13	Short Data Service (SDS) service description.....	121
13.1	Introduction	121
13.2	Services offered.....	121
13.3	SDS	121
13.3.1	SDS primitives exchanged through the TNSDS-SAP	121
13.3.2	Service primitives at the TNSDS-SAP	122
13.3.2.1	TNSDS-STATUS primitive	122
13.3.2.2	TNSDS-REPORT primitive.....	123
13.3.2.3	TNSDS-UNITDATA primitive.....	123
13.3.2.4	TNSDS-CANCEL primitive	124
13.3.3	Parameter description	124
13.3.4	State description.....	127
13.3.4.1	NULL state.....	127
13.3.4.2	SHORT DATA INITIATED state	127
13.3.5	Service state diagram for the TNSDS-SAP	127
14	CMCE protocol	128
14.1	Introduction	128
14.2	Overview of CMCE.....	128
14.2.1	Communication routes of the CMCE model.....	129
14.2.2	Protocol structure and protocol stack.....	129
14.2.3	Addressing rules	131
14.2.4	CC, SS and SDS sub-entities.....	131
14.2.4.1	CC sub-entity	131
14.2.4.2	SS sub-entity	132
14.2.4.3	SDS sub-entity	132
14.2.5	PC sub-entity	132
14.2.6	Internal routes	133
14.2.7	Intra-CMCE primitive summary	135
14.2.7.1	Down link CC PDU parameters.....	135
14.2.7.2	Uplink CC PDU parameters.....	135
14.2.7.3	Downlink SS PDU parameters.....	136
14.2.7.4	Uplink SS PDU parameters.....	136
14.2.7.5	Down link SDS PDU parameters.....	136
14.2.7.6	Uplink SDS PDU parameters.....	136
14.2.7.7	CMCE management primitives.....	136
14.2.7.7.0	ACTIVITY request.....	136
14.2.7.7.1	BREAK indication.....	136
14.2.7.7.1a	BUSY indication	136
14.2.7.7.2	CANCEL request.....	137
14.2.7.7.3	CLOSE indication	137
14.2.7.7.4	CONFIGURE indication	137
14.2.7.7.5	CONFIGURE request.....	137
14.2.7.7.6	IDENTITIES request.....	137
14.2.7.7.6a	IDLE indication	137
14.2.7.7.6b	INFO indication.....	138
14.2.7.7.7	OPEN indication.....	138
14.2.7.7.8	REOPEN indication.....	138
14.2.7.7.9	REPORT indication.....	138
14.2.7.7.10	RESUME indication	138
14.3	Overview of services required by the CMCE.....	139
14.4	CMCE protocol states	139

14.4.1	States for PC	139
14.4.1.1	CLOSED	139
14.4.1.2	OPEN	139
14.4.2	States for CC	140
14.4.2.1	IDLE	142
14.4.2.2	MO-CALL-SETUP	142
14.4.2.3	MT-CALL-SETUP	142
14.4.2.4	CALL ACTIVE	143
14.4.2.5	CALL DISCONNECT	143
14.4.2.6	WAIT	143
14.4.3	States for SS	143
14.4.4	States for SDS	144
14.5	Procedures	144
14.5.1	Individual CC procedures	145
14.5.1.1	Call set-up procedures	145
14.5.1.1.1	Incoming call	146
14.5.1.1.2	Outgoing call	148
14.5.1.1.3	Colliding calls	149
14.5.1.1.4	Unsuccessful call set-up	149
14.5.1.1.5	Call rejection	150
14.5.1.2	Call maintenance procedures	150
14.5.1.2.1	Transmission control procedures	151
14.5.1.2.2	Call status information procedures	155
14.5.1.2.3	Call modification procedures	156
14.5.1.2.4	Call restoration procedures	157
14.5.1.2.5	DTMF procedures	159
14.5.1.2.6	Calls to and from external subscribers	160
14.5.1.3	Call disconnection procedures	161
14.5.1.3.1	User initiated disconnection	161
14.5.1.3.2	Network initiated disconnection	162
14.5.1.3.3	Reception of disconnection request	162
14.5.1.3.4	Expiry of timers	162
14.5.1.3.5	Colliding disconnection	163
14.5.1.4	U-Plane switching	163
14.5.1.4.1	End of call set-up phase	164
14.5.1.4.2	During call maintenance phase	164
14.5.1.4.3	Call disconnection phase	165
14.5.2	Group CC procedures	165
14.5.2.1	Call set-up procedures	165
14.5.2.1.1	Incoming call	166
14.5.2.1.2	Outgoing call	167
14.5.2.1.3	Colliding calls	168
14.5.2.1.4	Unsuccessful call set-up	168
14.5.2.1.5	Call rejection	168
14.5.2.2	Call maintenance procedures	169
14.5.2.2.1	Transmission control procedures	169
14.5.2.2.2	Call status information procedures	173
14.5.2.2.3	Call modification procedures	174
14.5.2.2.4	Call restoration procedures	175
14.5.2.2.5	DTMF procedures	177
14.5.2.2.6	Temporary address handling procedures	177
14.5.2.2.7	Calls to and from external subscribers	178
14.5.2.3	Call disconnection procedures	178
14.5.2.3.1	User initiated disconnection	179
14.5.2.3.2	Network initiated disconnection	180
14.5.2.3.3	Reception of disconnection request	180
14.5.2.3.4	Colliding disconnection	180
14.5.2.3.5	Expiry of timers	180
14.5.2.4	U-Plane switching	181
14.5.2.4.1	End of call set-up phase	181
14.5.2.4.2	During call maintenance phase	182
14.5.2.4.3	Call disconnection phase	183

14.5.2.5	Void.....	183
14.5.2.6	Acknowledged group call procedures	183
14.5.2.7	Call ownership	183
14.5.3	Traffic channel assignment procedures.....	184
14.5.3.1	SwMI related procedures	184
14.5.3.2	MS related procedures.....	185
14.5.3.2.1	General procedures	185
14.5.3.2.2	Procedures for acceptance of individually-addressed channel allocation.....	186
14.5.3.2.3	Procedures for acceptance of group-addressed channel allocation.....	186
14.5.4	SS procedures	188
14.5.5	SDS procedures	188
14.5.5.1	Incoming short data message	188
14.5.5.2	Outgoing short data messages	188
14.5.6	PC procedures.....	189
14.5.6.1	Access to the communication resources.....	189
14.5.6.2	Access priority handling	189
14.5.6.2.1	Cancel.....	190
14.5.6.3	CMCE PDU exchange	190
14.5.6.3.1	Choice of layer 2 service	190
14.5.6.4	Control information exchange.....	190
14.5.6.5	PC protocol error conditions	191
14.5.6.5.1	PDU type error	191
14.5.6.5.2	Invalid call identifier	191
14.5.6.5.3	MS busy.....	191
14.5.7	Subscriber class	191
14.5.8	Activity handling	191
14.6	Protocol timers	192
14.7	PDU descriptions.....	193
14.7.1	PDU description tables - downlink	194
14.7.1.1	D-ALERT.....	194
14.7.1.2	D-CALL PROCEEDING.....	194
14.7.1.3	D-CALL RESTORE	195
14.7.1.4	D-CONNECT.....	195
14.7.1.5	D-CONNECT ACKNOWLEDGE.....	196
14.7.1.6	D-DISCONNECT	196
14.7.1.7	D-FACILITY	196
14.7.1.8	D-INFO	197
14.7.1.9	D-RELEASE.....	197
14.7.1.10	D-SDS-DATA.....	198
14.7.1.11	D-STATUS	198
14.7.1.12	D-SETUP	199
14.7.1.13	D-TX CEASED.....	199
14.7.1.14	D-TX CONTINUE.....	200
14.7.1.15	D-TX GRANTED	200
14.7.1.16	D-TX INTERRUPT	201
14.7.1.17	D-TX WAIT.....	201
14.7.2	PDU description tables - uplink.....	202
14.7.2.1	U-ALERT.....	202
14.7.2.2	U-CALL RESTORE	202
14.7.2.3	U-CONNECT.....	203
14.7.2.4	U-DISCONNECT	203
14.7.2.5	U-FACILITY	203
14.7.2.6	U-INFO	204
14.7.2.7	U-STATUS	204
14.7.2.8	U-SDS-DATA.....	204
14.7.2.9	U-RELEASE.....	205
14.7.2.10	U-SETUP	206
14.7.2.11	U-TX CEASED.....	206
14.7.2.12	U-TX DEMAND.....	207
14.7.3	PDU description tables - downlink and uplink	207
14.7.3.1	General rules for function not supported.....	207
14.7.3.2	CMCE FUNCTION NOT SUPPORTED	207

14.8	Information elements coding.....	208
14.8.1	Area Selection.....	208
14.8.2	Basic service information	209
14.8.3	Call identifier.....	209
14.8.3a	Call identifier present.....	209
14.8.4	Call ownership.....	209
14.8.5	Called party type identifier	210
14.8.6	Called party SNA.....	210
14.8.7	Called party extension	210
14.8.8	Called party SSI.....	210
14.8.9	Calling party type identifier.....	211
14.8.10	Calling party extension	211
14.8.11	Calling party SSI.....	211
14.8.12	Call priority.....	211
14.8.13	Call status	212
14.8.14	Call queued	212
14.8.15	Continue.....	212
14.8.16	Call time-out	213
14.8.17	Call time-out, set-up phase	213
14.8.17a	Circuit mode type	214
14.8.17b	CLIR control.....	214
14.8.17c	Communication type.....	214
14.8.18	Disconnect cause	215
14.8.18a	DM-MS address.....	215
14.8.19	DTMF	215
14.8.19a	DTMF digit.....	216
14.8.19b	DTMF type	216
14.8.20	External subscriber number	217
14.8.21	Encryption control	217
14.8.21a	Encryption flag	217
14.8.22	Facility	218
14.8.23	Hook method selection	218
14.8.24	Length indicator	218
14.8.25	New call identifier	218
14.8.26	Modify	218
14.8.27	Notification indicator.....	219
14.8.27a	Other party type identifier.....	219
14.8.27b	Other party SNA	219
14.8.27c	Other party extension.....	219
14.8.27d	Other party SSI	219
14.8.28	PDU type	220
14.8.29	Poll request	220
14.8.30	Poll response.....	220
14.8.31	Poll response addresses.....	221
14.8.32	Poll response number.....	221
14.8.33	Poll response percentage.....	221
14.8.34	Pre-coded status	222
14.8.35	Proprietary	222
14.8.36	Request to transmit/send data	222
14.8.37	Reset call time-out timer (T310).....	222
14.8.38	Short data type identifier.....	223
14.8.39	Simplex/duplex selection.....	223
14.8.39a	Slots per frame	223
14.8.40	Speech service	223
14.8.41	Temporary address.....	223
14.8.42	Transmission grant.....	224
14.8.43	Transmission request permission.....	224
14.8.44	Transmitting party type identifier	224
14.8.45	Transmitting party extension	224
14.8.46	Transmitting party SSI.....	225
14.8.47	TX demand priority	225
14.8.48	Type 3 element identifier.....	225

14.8.49	User defined data-1	225
14.8.50	User defined data-2	226
14.8.51	User defined data-3	226
14.8.52	User defined data-4	226
15	Mobility Management (MM) service description	227
15.1	Introduction	227
15.2	Services offered	227
15.3	Primitive description	228
15.3.1	Service state model for the MS	228
15.3.2	Service primitives at the TNMM-SAP, MS/LS side	228
15.3.3	Primitive description	229
15.3.3.1	TNMM-ATTACH DETACH GROUP IDENTITY primitive	229
15.3.3.2	TNMM-DEREGISTRATION primitive	229
15.3.3.3	TNMM-DISABLING primitive	229
15.3.3.4	TNMM-ENABLING primitive	229
15.3.3.5	TNMM-ENERGY SAVING primitive	230
15.3.3.6	TNMM-REPORT primitive	230
15.3.3.7	TNMM-REGISTRATION primitive	230
15.3.3.8	TNMM-SERVICE primitive	231
15.3.3.9	TNMM-STATUS primitive	231
15.3.4	Parameters description	232
15.3.5	State description for the MS	236
15.3.5.1	Not updated	236
15.3.5.2	Wait updating	236
15.3.5.3	Updated	236
15.3.5.4	Temporary disabled	236
15.3.5.5	Permanently disabled	236
15.3.6	Service state diagram for the TNMM-SAP	237
16	MM protocol	241
16.1	Introduction	241
16.2	MM procedures	241
16.2.1	General	241
16.2.2	Services provided by the protocol	242
16.2.3	Underlying services assumed by the protocol	242
16.2.4	Services assumed from the local environment	242
16.3	Protocol functions	242
16.3.1	Activation and control of underlying MLE Service	244
16.3.1.1	Activation procedure	244
16.3.1.2	Deactivation procedure	245
16.3.1.3	Maintenance procedures	245
16.3.1.3.1	Report and cancel handling	245
16.3.1.3.2	Stealing permission and stealing repeats flag handling	245
16.3.1.3.3	Busy handling	246
16.3.1.3.4	Activity handling	246
16.4	Registration procedure	246
16.4.1	MLE initiated registration procedure	246
16.4.1.1	Normal registration	247
16.4.1.2	Forward registration	252
16.4.2	User application initiated registration procedure	254
16.4.3	Infrastructure initiated registration procedure	258
16.4.4	Colliding registrations	260
16.4.5	Expiry of timer T351	260
16.4.6	Expiry of LA timers	260
16.4.7	Lifetime of ASSI/(V)ASSI	261
16.4.7.1	ASSI/(V)ASSI validity at migration	261
16.4.7.2	ASSI/(V)ASSI validity by MS initiative	261
16.4.7.3	ASSI/(V)ASSI validity at registration rejection	261
16.4.8	Temporary registration	261
16.4.9	Subscriber class procedures	262
16.4.10	Frequency band capability procedures	262

16.4.11	Air to ground reporting procedure	263
16.5	Enable and disable procedures	263
16.6	De-registration procedure	264
16.6.1	Trunking mode de-registration	264
16.6.2	Direct mode related de-registration	264
16.7	Energy economy	265
16.7.1	Energy economy mode procedure	265
16.7.2	Procedures for requesting Direct Mode dual watch operation	266
16.7.2.1	Introduction	266
16.7.2.2	MS requesting to start, modify or resume dual watch mode	267
16.7.2.3	MS terminating dual watch mode	268
16.7.2.4	SwMI modifying or terminating dual watch mode	269
16.7.2.5	Changing between modes	269
16.7.2.6	General dual watch procedures	270
16.7.2.7	Idle dual watch without informing SwMI	270
16.7.3	Expiry of timer T352	271
16.8	Attachment/detachment of group identities and group reporting procedures	271
16.8.1	Infrastructure initiated attachment/detachment of group identities procedure	272
16.8.2	MS initiated attachment/detachment of group identities procedure	273
16.8.3	SwMI initiated group report procedure	274
16.8.4	MS initiated group report procedure	275
16.8.5	Expiry of timer T353	276
16.8.6	Colliding requests for group attachment/detachment and group reporting	276
16.8.7	Group Identity Address Type (GIAT) usage in group identity downlink/uplink	276
16.8.8	PDU or function not supported	277
16.9	MM PDU structures and contents	278
16.9.1	MM PDU general description	278
16.9.2	MM PDU description tables - downlink	278
16.9.2.1	D-ATTACH/DETACH GROUP IDENTITY	278
16.9.2.2	D-ATTACH/DETACH GROUP IDENTITY ACKNOWLEDGEMENT	279
16.9.2.3	Void	279
16.9.2.4	Void	279
16.9.2.5	D-MM STATUS generic structure	279
16.9.2.5.1	D-MM STATUS generic structure	279
16.9.2.5.2	D-CHANGE OF ENERGY SAVING MODE REQUEST	280
16.9.2.5.3	D-CHANGE OF ENERGY SAVING MODE RESPONSE	280
16.9.2.5.4	D-DUAL WATCH MODE RESPONSE	280
16.9.2.5.5	D-TERMINATING DUAL WATCH MODE RESPONSE	281
16.9.2.5.6	D-CHANGE OF DUAL WATCH MODE REQUEST	282
16.9.2.5.7	Direct mode gateway related D-MM STATUS	282
16.9.2.5.8	D-MS FREQUENCY BANDS REQUEST	282
16.9.2.5.9	DISTANCE REPORTING REQUEST	283
16.9.2.6	Void	283
16.9.2.7	D-LOCATION UPDATE ACCEPT	283
16.9.2.8	D-LOCATION UPDATE COMMAND	284
16.9.2.9	D-LOCATION UPDATE REJECT	284
16.9.2.10	D-LOCATION UPDATE PROCEEDING	285
16.9.3	MM PDU descriptions - uplink	285
16.9.3.1	U-ATTACH/DETACH GROUP IDENTITY	285
16.9.3.2	U-ATTACH/DETACH GROUP IDENTITY ACKNOWLEDGEMENT	286
16.9.3.3	U-ITSI DETACH	286
16.9.3.4	U-LOCATION UPDATE DEMAND	287
16.9.3.5	U-MM STATUS	287
16.9.3.5.1	U-MM STATUS generic construction	287
16.9.3.5.2	U-CHANGE OF ENERGY SAVING MODE REQUEST	288
16.9.3.5.3	U-CHANGE OF ENERGY SAVING MODE RESPONSE	288
16.9.3.5.4	U-DUAL WATCH MODE REQUEST	289
16.9.3.5.5	U-TERMINATING DUAL WATCH MODE REQUEST	289
16.9.3.5.6	U-CHANGE OF DUAL WATCH MODE RESPONSE	290
16.9.3.5.7	U-START OF DIRECT MODE OPERATION	290
16.9.3.5.8	Direct mode gateway related U-MM STATUS	291
16.9.3.5.9	U-MS FREQUENCY BANDS INFORMATION	291

16.9.4	PDU description tables - downlink and uplink	292
16.9.4.1	MM FUNCTION NOT SUPPORTED	292
16.10	MM information elements coding	292
16.10.1	Address extension	292
16.10.2	Cipher control	292
16.10.3	Cipher parameters	293
16.10.4	Void	293
16.10.5	Class of MS	293
16.10.6	Class of usage	294
16.10.7	Disabling type	294
16.10.7a	Default group attachment lifetime	294
16.10.7b	Distance reporting timer	295
16.10.7c	Distance reporting validity	295
16.10.8	Distribution on 18th frame	295
16.10.8a	DMO carrier	296
16.10.8b	Dual watch mode	296
16.10.9	Energy saving mode	297
16.10.10	Energy saving information	297
16.10.11	Frame Number	297
16.10.11a	Frequency band definition	298
16.10.12	Group identity accept/reject	298
16.10.13	Group identity acknowledgement request	298
16.10.14	Group identity acknowledgement type	298
16.10.15	Group identity address type	299
16.10.16	Group identity attachment lifetime	299
16.10.17	Group identity attach/detach mode	299
16.10.18	Group identity attach/detach type identifier	299
16.10.19	Group identity attachment	300
16.10.20	Group identity detachment (downlink)	300
16.10.21	Group identity detachment uplink	300
16.10.22	Group identity downlink	301
16.10.23	Group identity location accept	301
16.10.24	Group identity location demand	301
16.10.25	Void	301
16.10.26	Group identity report	302
16.10.27	Group identity uplink	302
16.10.27a	Group report response	302
16.10.28	Group Short Subscriber Identity (GSSI)	302
16.10.29	KSG number	303
16.10.30	LA	303
16.10.31	LACC	303
16.10.32	LANC	303
16.10.33	LA timer	303
16.10.34	LA information	304
16.10.34a	Length of the copied PDU	304
16.10.35	Location update type	304
16.10.35a	Location update accept type	305
16.10.36	Mobile Country Code (MCC)	305
16.10.37	Mobile Network Code (MNC)	305
16.10.37a	Mode change information	305
16.10.37b	MS operating with type 2 repeater	306
16.10.38	Multiframe Number (MN)	306
16.10.38a	Not-supported PDU type	306
16.10.38b	Number of frequency band definitions	306
16.10.39	PDU type	307
16.10.40	New registered area	307
16.10.41	Proprietary	307
16.10.41a	Reason for dual watch change by SwMI	308
16.10.42	Reject cause	308
16.10.43	Request to append LA	309
16.10.43a	Re-send interval	309
16.10.43b	Result of dual watch request	309