

INTERNATIONAL STANDARD



**Process management for avionics – Atmospheric radiation effects –
Part 5: Assessment of thermal neutron fluxes and single event effects in
avionics systems**

IEC 62396-5:2014

<https://standards.iteh.ai/catalog/standards/sist/0faf35fa-162b-4050-bf77-f92e00e315d4/iec-62396-5-2014>



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2014 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in 14 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Glossary - std.iec.ch/glossary

More than 55 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

INTERNATIONAL STANDARD PREVIEW
(standards.iec.ch)
IEC 62396-2:2014
https://standards.iec.ch/catalog/standards/csc/62396-2-2014



IEC 62396-5

Edition 1.0 2014-08

INTERNATIONAL STANDARD



**Process management for avionics – Atmospheric radiation effects –
Part 5: Assessment of thermal neutron fluxes and single event effects in
avionics systems**

IEC 62396-5:2014

<https://standards.iteh.ai/catalog/standards/sist/0faf35fa-162b-4050-bf77-f92e00e315d4/iec-62396-5-2014>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE

S

ICS 03.100.50; 31.020; 49.060

ISBN 978-2-8322-1821-1

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	3
1 Scope.....	5
2 Normative references.....	5
3 Terms and definitions	5
4 Overview of thermal neutron single event rate calculation.....	5
5 Thermal neutron flux inside an airliner.....	7
5.1 Definition of thermal neutron	7
5.2 Overview.....	7
5.3 Background on aircraft measurements	7
5.4 Calculational approach.....	8
5.5 Processing of in-flight neutron flux data	9
6 Thermal neutron SEU cross-sections	13
6.1 Overview of the issue	13
6.2 Mechanism involved.....	13
6.3 Thermal neutron SEU cross-sections and Ratio-2	15
7 Recommendation for devices in avionics at the present time.....	17
7.1 General.....	17
7.2 Ratio-1.....	17
7.3 Ratio-2.....	18
7.4 Thermal neutron upset rate.....	18
8 Determining thermal neutron SEE rates for use in equipment assessments.....	18
8.1 Demonstration of thermal neutron immunity to SEE.....	18
8.1.1 Thermal neutron test.....	18
8.1.2 Absence of boron 10 (B10).....	18
8.2 Determination of thermal neutron SEE where there is no evidence of thermal neutron immunity	19
8.2.1 Results from thermal neutron testing	19
8.2.2 Conservative estimation	19
8.2.3 High voltage devices.....	19
9 Single event burn out in high voltage devices due to thermal neutrons.....	19
Bibliography	20
Figure 1 – Atmospheric neutron spectra measured in four aircraft.....	10
Figure 2 – Neutron cross-sections for boron-10 including total cross-section (red), total elastic cross-section (green) and (n,α) nuclear capture cross-section (blue).....	15
Table 1 – Tabulation of the various atmospheric neutron measurements used.....	9
Table 2 – Comparison of thermal and high energy neutron fluxes and their ratios.....	11
Table 3 – Calculated neutron fluxes in the Boeing 747 structure	12
Table 4 – SRAM SEU cross-sections induced by thermal and high energy neutrons	16

iTech STANDARD PREVIEW
(standards.iteh.ai)

IEC 62396-5:2014
<https://standards.iteh.ai/catalog/standards/sist/01af35fa-1626-4050-b177-192c00c315d4/iec-62396-5-2014>

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**PROCESS MANAGEMENT FOR AVIONICS –
ATMOSPHERIC RADIATION EFFECTS –****Part 5: Assessment of thermal neutron
fluxes and single event effects in avionics systems**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62396-5 has been prepared by IEC technical committee 107: Process management for avionics.

This first edition cancels and replaces the first edition of IEC/TS 62396-5 published in 2008. This edition constitutes a technical revision.

This edition includes the following technical changes with respect to the previous technical specification:

- a) Change to title.
- b) Updated references and bibliography.
- c) Subclause 6.2 expanded to consider smaller geometry devices.

- d) Table 4 neutron cross-sections expanded to add more recent data and the ratio between thermal and high energy neutron cross-section amended to 2,42 from 2,77.
- e) Addition of reference section on thermal neutron high voltage burn out.
- f) New clause on determination of thermal neutron SEE rates for use in equipment assessments.
- g) Document aligned as an IEC standard.

The text of this international standard is based on the following documents:

FDIS	Report on voting
107/237/FDIS	107/242/RVD

Full information on the voting for the approval of this international standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all the parts in the IEC 62396 series, published under the general title *Process management for avionics – Atmospheric radiation effects*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or [IEC 62396-5:2014](#)
- amended. <https://standards.iteh.ai/catalog/standards/sist/0faf35fa-162b-4050-bf77-f92e00e315d4/iec-62396-5-2014>

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

PROCESS MANAGEMENT FOR AVIONICS – ATMOSPHERIC RADIATION EFFECTS –

Part 5: Assessment of thermal neutron fluxes and single event effects in avionics systems

1 Scope

The purpose of this part of IEC 62396 is to provide a more precise definition of the threat that thermal neutrons pose to avionics as a second mechanism for inducing single event upset (SEU) in microelectronics. There are two main points that will be addressed in this part of IEC 62396:

- a) a detailed evaluation of the existing literature on measurements of the thermal flux inside of airliners, and
- b) an enhanced compilation of the thermal neutron SEU cross-section in currently available SRAM devices (more than 20 different devices).

The net result of the reviews of these two different sets of data will be two ratios that are considered to be very important for leading to the ultimate objective of how large a threat is the SEU rate from thermal neutrons compared to the SEU threat from the high energy neutrons ($E > 10$ MeV). The threat from the high energy neutrons has been dealt with extensively in the literature and has been addressed by two standards (IEC 62396-1 in avionics and JESD89A [1]¹ in microelectronics on the ground). Neutrons with $E > 1$ MeV are considered for parts with geometries below 150 nm.

NOTE Reference is made to IEC 62396-1:2012, 5.3.2, for smaller geometry parts below 150 nm which provides the neutron flux for energies above 1 MeV.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 62396-1:2012, *Process management for avionics – Atmospheric radiation effects – Part 1: Accommodation of atmospheric radiation effects via single event effects within avionics electronic equipment*

IEC 62396-4, *Process management for avionics – Atmospheric radiation effects – Part 4: Design of high voltage aircraft electronics managing potential single event effects*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 62396-1 apply.

4 Overview of thermal neutron single event rate calculation

The two ratios that this part of IEC 62396 considers to be important are:

¹ Numbers in square brackets refer to the Bibliography.

- a) the ratio of the thermal neutron flux inside an airliner relative to the flux of high energy (> 10 MeV) neutrons inside the airliner, and
- b) the ratio of the SEU cross-section due to thermal neutrons relative to that due to high energy neutrons.

These ratios are considered to be important because with them, once the SEU rates are defined from the high energy neutrons for an avionics box, a topic which has been dealt with extensively, such as in IEC 62396-1 and [1], then the additional SEU rate due to thermal neutrons can be obtained with these ratios. Thus, given the SEU rate from high energy neutrons, multiplying this by the two ratios gives the SEU rate from the thermal neutrons. The total SEU rate will be the combination of the SEU rates from both the high energy and thermal neutrons.

The process for calculating the SEU rate from the thermal neutrons is shown in the following set of equations, (1) to (5).

$$\text{SEU rate (Hi E}^2, \text{upset/dev}\cdot\text{h)} = \Phi_{\text{Hi}} (\text{neutron flux} = 6\,000 \text{ n/cm}^2\text{h}) \times \sigma(\text{Hi E, SEU X-Sctn. cm}^2\text{/dev)} \quad (1)$$

$$\text{SEU rate (thermal neutron, upset/dev}\cdot\text{h)} = \text{SEU rate (Hi E)} \times \frac{\Phi_{\text{therm}} (\text{neutron flux})}{\Phi_{\text{Hi}} (\text{neutron flux})} \times \frac{\sigma(\text{therm SEU X - Sctn.})}{\sigma(\text{Hi E SEU X - Sctn.})} \quad (2)$$

iTeh STANDARD PREVIEW

$$\text{Ratio-1} = \frac{\Phi_{\text{thermal}} (\text{neutron flux})}{\Phi_{\text{Hi}} (\text{neutron flux})} \quad (3)$$

$$\text{Ratio-2} = \frac{\sigma(\text{therm SEU X - Sctn.})}{\sigma(\text{Hi E SEU X - Sctn.})} \quad (4)$$

$$\text{SEU rate (thermal neutron, upset/dev}\cdot\text{h)} = \text{SEU rate (Hi E neutron upset/dev}\cdot\text{h)} \times \text{Ratio-1} \times \text{Ratio-2} \quad (5)$$

The objective of this part of IEC 62396 is to provide the values of Ratio-1, the ratio of the thermal to high energy neutron flux within an airplane, and of Ratio-2, the ratio of the SEU cross-section due to thermal neutrons relative to that due to high energy neutrons. The Ratio-1 should be relatively similar in various types of commercial airliners, but it could vary significantly in other types of aircraft, such as military fighters. However, in the larger type of military aircraft, such as AWACS (Advanced Warning and Command System, E-3, which is based on either a Boeing 707-320-B or 767) and JSTARS (Joint Surveillance Target Attack Radar System, E-8C, which is based on Boeing 707-300 airframe), the ratio should be very similar to that in airliners.

With regard to the ratio of the thermal neutron SEU cross-sections, until recently, not very many such SEU cross-sections were reported in the literature. There were a few, and these were cited in [1]. Due to the data that has recently become available, the number of devices in which the thermal neutron SEU cross-section has been measured has increased significantly. This additional data allows us to have good confidence on the values that have been measured and the resulting average value of the ratio.

² Hi E = High Energy.

5 Thermal neutron flux inside an airliner

5.1 Definition of thermal neutron

Thermal neutrons are so called because although most atmospheric neutrons are produced at high energies following cosmic ray interactions, after a sufficient number of in-elastic collisions with the surrounding medium, the neutron velocity is reduced such that it has approximately the same average kinetic energy as the molecules of the surrounding medium. This energy depends on the temperature of the medium, so it is called thermal energy. The thermal neutrons are therefore in thermal equilibrium with the molecules (or atoms) of the medium in which they are present.

In a medium that has only a small probability of absorbing, rather than scattering, neutrons, the kinetic energies of the thermal neutrons is distributed statistically according to the Maxwell-Boltzmann law. Therefore, based on this Maxwell-Boltzmann distribution, the neutron kinetic energy that corresponds to the most probable velocity is kT , where T is the absolute temperature of the medium and k a constant. For a temperature of 20 °C, room temperature, this is 0,025 eV. This is based on a highly idealized model of elastic collisions between two kinds of particles, nuclei and neutrons, within a gaseous medium, and so there are departures from it in the real world.

Therefore, even though a neutron energy of around 0,025 eV is usually taken to be the definition of thermal neutrons, for purposes of this part of IEC 62396, neutrons with energies < 1 eV will be considered as thermal neutrons. Additional details on this are found in 6.2.

5.2 Overview

In a modern airliner, we know that the thermal neutron flux inside the aircraft should be higher than the thermal neutrons outside of the airplane because of the presence of all of the hydrogenous materials within it (fuel, plastic structures, baggage, people, etc.). The hydrogenous materials "slow down" the high energy neutrons through nuclear collisions, primarily with the hydrogen atoms. After a large number of such interactions, the high energy neutrons (energy > 10 MeV) have had their energy reduced by about seven orders of magnitude. For practical purposes, neutrons with $E < 1$ eV are considered as thermal neutrons. However, the more accurate definition of thermal neutrons is neutrons with energies close to 0,025 eV (equivalent to those at room temperature, hence the term "thermal"). The thermal neutron flux in the atmosphere is relatively low due to absorption by atmospheric molecular nitrogen. By contrast, both calculation and measurement show that the high energy neutron flux inside an aircraft structure is very similar to that in the atmosphere. The presence of the airplane structure and its contents produce far more thermal neutrons inside the aircraft than that are present in the atmosphere just outside the airplane.

5.3 Background on aircraft measurements

The thermal neutron flux inside an airliner is a rather elusive quantity that has not been measured very often despite the fact that hundreds and in fact thousands of ionizing radiation measurements have been and are currently being made inside of aircraft. Firstly, most of the thousands of measurements are of the dose equivalent that passengers and crew accumulate during flight. Although it varies depending on the location of the flight path, in general, the dose equivalent is approximately (50 to 60) % from the high energy neutrons, about (25 to 35) % from electrons and the remainder from other charged particles, mainly protons (10 to 20) %, gamma rays (< 10 %) and muons (< 10 %) [2]. Most of these kinds of instruments measure the combined dose rate from all of the charged particles present in the atmosphere.

Thus, to measure only the neutrons in the atmosphere required a detector system that was sensitive only to neutrons. The early systems that were flown in the 1960s consisted of detectors that were optimized to measure mainly neutrons in the energy range of (1 to 10) MeV. This information was used to develop the simplified Boeing model [3] based on the variation of the (1 to 10) MeV neutron flux with altitude and latitude. The key parameter is not latitude, however, but rigidity. Geomagnetic cut-off rigidity is a measure of the momentum a

charged particle requires in order to penetrate the Earth's magnetic field at a given location. The vertical rigidity cut-off varies mainly with latitude, but there is also a variation due to longitude. Similarly, NASA-LaRC developed a more elaborate model [4] that was also based on the (1 to 10) MeV measurements.

Since that time, there have been more recent flight measurements made with neutron-specific instruments that respond to the entire neutron spectrum. These have been primarily a series of Bonner spheres, a set of instruments with a detector that measures thermal neutrons surrounded by varying thicknesses of moderating material. The moderating material, generally polyethylene, is used to "slow down" the high energy neutrons which constitute most of the neutrons, through nuclear interactions with the hydrogen within it. The larger the sphere of surrounding polyethylene, the more thermal neutrons are produced and the larger the signal by the detector. Careful calibrations are needed of the set of Bonner sphere detectors before a collection of in-flight measurements can be transformed into neutron fluxes within specific energy ranges. This is a painstaking process and therefore is undertaken by a limited number of research groups.

Two such sets of measurements have been made, one by a NASA-Ames group [5], and the other by a Japanese group [6], and these are used in this evaluation. In addition, the most highly regarded set of such measurements [7] were made by P. Goldhagen of the Environmental Measurements Laboratory (formerly part of DOE, now a part of the Homeland Security Administration). Unfortunately, Goldhagen's measurements were made in an ER-2 aircraft.

The ER-2 is drastically different from a modern airliner. Exacerbating the situation even more, the detector that Goldhagen relied upon for the thermal neutron measurement was located in the very tip of the nose of the ER-2 [8]. For all practical purposes, this detector was located in a part of the airplane that is almost indistinguishable from the atmosphere outside of the airplane. Thus, the thermal neutron flux measured by Goldhagen in the ER-2 is too low compared to what is expected within a large airliner. In this case, the main interest lies in Ratio-1, i.e., the ratio between the thermal neutron flux and the high energy ($E > 10$ MeV) neutron flux.

A more recent paper by a group at EADS [9] that used a simpler detector system, again Bonner spheres, but specifically designed to be used in an airliner was examined. Unfortunately, the high energy neutron fluxes from this paper are considered to be far too low to be realistic. Thus, it is believed that the data collected by this detector system and contained in [9] cannot be considered to be accurate enough and consistent enough to be used for our purposes of obtaining a reliable and representative value for Ratio-1.

5.4 Calculational approach

There is one paper in the literature [10] that represents a very significant step forward. It is based on applying an elaborate calculational method to a geometry consisting of a large airliner (a Boeing 747) and the atmosphere around it. The gross take-off weight of a large Boeing 747 is close to 450 000 kg (1 million lbs) and the overall internal volume is approximately 850 m³ (30 000 ft³) (based on the cargo capacity of cargo versions of the Boeing 747). The actual size is therefore enormous (length of aircraft is ~76 m (~250 ft) and wingspan of ~69 m (~225 ft) compared to most structures or vehicles that are modelled for purposes of radiation transport calculations. Out of necessity, the calculation had to simplify the true geometry by orders of magnitude in order to be able to develop the model and carry out the calculations in a relatively short time. As a result, the full aircraft is described as being comprised of approximately 30 smaller volumes, into which the different proportions of the full 1 million lbs are distributed, using gross approximations for the various materials (fuel, baggage, aluminium structure, interior, etc.).

Thus, it is unclear how accurate the results of these calculations are, especially for the thermal neutrons. For the high energy neutrons, it is clear that for most locations the neutron flux should be very similar inside the airplane as it is outside the airplane, and that is true in the results of [10], so this serves as a consistency check. However, for the thermal neutrons,

there are no consistency checks. The thermal neutron fluxes are much higher everywhere inside the aircraft compared to outside within the atmosphere, so there is no idea of how accurate a result [10] represents. It may be correct, but it also may be that especially for locations where the electronics are located, a much smaller model, greatly reduced in overall size, but much more detailed in terms of the internal structures and the mass distribution that is used, would be needed to calculate the thermal neutron flux accurately.

Therefore, the results from [10] will be used, but they will also be compared to the measurements from [5] and [6], to obtain Ratio-1. The results from [10] will represent the upper bound and the results from the in-flight measurements will represent a lower bound.

5.5 Processing of in-flight neutron flux data

For the comparison of in-flight measurements data is taken from four groups, [5], [6], [7] and [9], and in addition the calculations from two other groups, [10] and Armstrong [11] are used. First, the measured spectra from the four aircraft measurements are shown in Figure 1, along with the calculated spectrum from [11]. A tabulation of the main features concerning where the measurements were taken and which aircraft were used is given in Table 1.

Table 1 – Tabulation of the various atmospheric neutron measurements used

Researcher	Organization	Detector	Aircraft	Year	Altitude ft (km)	Ref.
Goldhagen	EML	Bonner sphere	ER-2	1997	40 000 (12,2 km)	[7]
Hubert	EADS	7-detect spectrometer	A300	2004	34 800 (10,6 km)	[9]
Hewitt	NASA-Ames	Bonner sphere	C-141	1974	40 600 (12,4 km)	[5]
Nakamura	Tohoku U.	Bonner sphere	DC-8	1985	37 000 (11,3 km)	[6]
Armstrong	ORNL	Calculation	Atmosphere	1973	39 000 (11,9 km)	[11]