

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Fibre optic interconnecting devices and passive components – Performance standard –

Part 052-3: Single-mode fibre non-connectorized fixed attenuator – Category U in uncontrolled environment

[IEC 61753-052-3:2016](#)

<https://standards.iteh.ai/catalog/standards/sist/27adbe13-e4e9-4751-94c7->

Dispositifs d'interconnexion et composants passifs fibroniques – Norme de performance –

Partie 052-3: Affaiblisseur fixe non connectorisé à fibres unimodales – Catégorie U dans un environnement non contrôlé



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2016 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms, containing 21 000 terms and definitions in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Catalogue IEC - webstore.iec.ch/catalogue

Application autonome pour consulter tous les renseignements bibliographiques sur les Normes internationales, Spécifications techniques, Rapports techniques et autres documents de l'IEC. Disponible pour PC, Mac OS, tablettes Android et iPad.

Recherche de publications IEC - webstore.iec.ch/advsearchform

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études,...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire en ligne de termes électroniques et électriques. Il contient 21 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans 16 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Glossaire IEC - std.iec.ch/glossary

67 000 entrées terminologiques électrotechniques, en anglais et en français, extraites des articles Termes et Définitions des publications IEC parues depuis 2002. Plus certaines entrées antérieures extraites des publications des CE 37, 77, 86 et CISPR de l'IEC.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: sales@iec.ch.

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Fibre optic interconnecting devices and passive components – Performance standard –

Part 052-3: Single-mode fibre non-connectorized fixed attenuator – Category U in uncontrolled environment

[IEC 61753-052-3:2016](#)

<https://standards.iteh.ai/catalog/standards/sist/27adbe13-e4e9-4751-94c7->

Dispositifs d'interconnexion et composants passifs fibroniques – Norme de performance –

Partie 052-3: Affaiblisseur fixe non connectorisé à fibres unimodales – Catégorie U dans un environnement non contrôlé

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 33.180.20

ISBN 978-2-8322-5269-7

Warning! Make sure that you obtained this publication from an authorized distributor.

Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

CONTENTS

FOREWORD.....	3
1 Scope.....	5
2 Normative references.....	5
3 Test.....	6
4 Test report.....	6
5 Performance requirements.....	6
5.1 Sample size, sequencing and grouping.....	6
5.2 Dimensions.....	6
5.3 Test details and requirements.....	7
Annexe A (normative) Test sequencing for single-mode non-connectorized fixed attenuators, category U.....	12
Bibliography.....	13
Table 1 – Test details and requirements.....	7
Table A.1 – Test sequence for single-mode non-connectorized fixed attenuators, category U.....	12

iTeh STANDARD PREVIEW **(standards.iteh.ai)**

[IEC 61753-052-3:2016](https://standards.iteh.ai/catalog/standards/sist/27adbe13-e4e9-4751-94c7-a3d713c3a470/iec-61753-052-3-2016)

<https://standards.iteh.ai/catalog/standards/sist/27adbe13-e4e9-4751-94c7-a3d713c3a470/iec-61753-052-3-2016>

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**FIBRE OPTIC INTERCONNECTING DEVICES
AND PASSIVE COMPONENTS –
PERFORMANCE STANDARD –****Part 052-3: Single-mode fibre non-connectorized fixed attenuator –
Category U in uncontrolled environment**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61753-052-3 has been prepared by subcommittee SC86B: Fibre optic interconnecting devices and passive components, of IEC technical committee 86: Fibre optics.

This bilingual version (2018-01) corresponds to the monolingual English version, published in 2016-07.

This second edition cancels and replaces the first edition published in 2001. This edition constitutes a technical revision.

This edition includes the following significant technical change with respect to the previous edition:

- reconsideration of performance requirements.

The text of this standard is based on the following documents:

FDIS	Report on voting
86B/3994/FDIS	86B/4009/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

The French version of this standard has not been voted upon.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 61753 series, published under the general title *Fibre optic interconnecting devices and passive components – Performance standard*, can be found on the IEC website.

Future standards in this series will carry the new general title as cited above. Titles of existing standards in this series will be updated at the time of the next edition.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
 - withdrawn,
 - replaced by a revised edition, or
 - amended.
- iTeh STANDARD PREVIEW**
(standards.iteh.ai)
- <https://standards.iteh.ai/catalog/standards/sist/27adbe13-e4e9-4751-94c7-a3d713c3a470/iec-61753-052-3-2016>

FIBRE OPTIC INTERCONNECTING DEVICES AND PASSIVE COMPONENTS – PERFORMANCE STANDARD –

Part 052-3: Single-mode fibre non-connectorized fixed attenuator – Category U in uncontrolled environment

1 Scope

This part of IEC 61753 contains the minimum initial test and measurement requirements and severities which a fibre optic attenuator satisfies in order to be categorised as meeting the requirements of single-mode fibre non-connectorized fixed attenuator devices used in uncontrolled environments. IEC 60869-1 contains the generic specification of the optical attenuator.

Optical performances specified in this document relate only to non-connectorized configurations optical attenuators.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60793-2-50, *Optical fibres – Part 2.50: Product specifications – Sectional specifications for class B single mode fibres*

IEC 60794-2-50, *Optical fibre cables – Part 2.50: Indoor cables – Family specification for simplex and duplex cables for use in terminated cable assemblies*

IEC 61300-2-1, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-1: Tests – Vibration (sinusoidal)*

IEC 61300-2-4, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-4: Tests – Fibre/cable retention*

IEC 61300-2-5, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-5: Tests – Torsion*

IEC 61300-2-9, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-9: Tests – Shock*

IEC 61300-2-14, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-14: Tests – High optical power*

IEC 61300-2-17, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-17: Tests – Cold*

IEC 61300-2-18, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-18: Tests – Dry heat – High temperature endurance*

IEC 61300-2-22, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-22: Tests – Change of temperature*

IEC 61300-2-26, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-26: Tests – Salt mist*

IEC 61300-2-27, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-27: Tests – Dust – Laminar flow*

IEC 61300-2-42, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-42: Tests – Static side load for strain relief*

IEC 61300-2-44, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-44: Tests – Flexing of the strain relief of fibre optic devices*

IEC 61300-2-46, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-46: Tests – Damp heat, cyclic*

IEC 61300-3-2, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-2: Examination and measurements – Polarization dependent loss in a single-mode fibre optic device*

IEC 61300-3-3, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-3: Examinations and measurements – Active monitoring of changes in attenuation and return loss*

IEC 61300-3-7, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-7: Examinations and measurements – Wavelength dependence of attenuation and return loss of single mode components*

IEC 61300-3-28, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-28: Examinations and measurements – Transient loss*

3 Test

All test methods are in accordance with the IEC 61300 series. Tests validate performance over the required operating wavelength and power range. The samples shall be terminated onto single-mode fibres as per IEC 60793-2-50, type B1.1 or B1.3 or B6 in either coated fibres (primary and secondary) or reinforced cable format as per IEC 60794-2-50.

4 Test report

Fully documented test reports and supporting evidence shall be prepared and shall be available for inspection as evidence that the tests have been carried out and complied with.

5 Performance requirements

5.1 Sample size, sequencing and grouping

The sample size to be used for the tests shall be as defined in Annex A.

5.2 Dimensions

Dimensions shall comply with those given in appropriate manufacturer's drawings.

5.3 Test details and requirements

Table 1 defines the performance requirements and test details for single-mode non-connectorized fixed attenuators, category U.

Table 1 – Test details and requirements

No.	Tests	Requirements	Details	
1	Attenuation IEC 61300-3-7	Operating wavelength range: 1 260 nm to 1 360 nm and/or 1 460 nm to 1 625 nm. For nominal values ≤ 5 dB, the tolerance shall be $\leq \pm 0,5$ dB around the nominal insertion loss value. For nominal values > 5 dB, the tolerance shall be $\leq \pm 10$ % around the nominal insertion loss value.	Method: Launch patchcord length: Launch conditions: Optical source wavelength: Source power stability: Total uncertainty:	Method B2.1 ≥ 2 m. Only the fundamental mode shall propagate at the limiter interface and at the detector. The wavelength of the source shall be longer than cut-off wavelength of the fibre. Tunable narrowband non polarized source. 1 260 nm to 1 360 nm and 1 460 to 1 660 nm. Within $\pm 0,05$ dB over the measuring period or at least 1 h. $\leq \pm 0,1$ dB
2	Return loss IEC 61300-3-7	≥ 50 dB Grade U	Method: Optical source wavelength: Other requirements: Total uncertainty:	Measurement method 1 OCWR 1 310 nm ± 10 nm, 1 550 nm ± 10 nm and/or 1 625 nm ± 10 nm Test every sample with the three wavelengths. This test shall be performed twice, reversing the sample. Both measurements shall be within the specified limits. $\leq \pm 1$ dB
3	Polarization dependent loss IEC 61300-3-2	$\leq 0,3$ dB at 1 550 nm The samples shall be terminated onto single-mode fibres as per IEC 60793-2-50,	Optical source Wavelength: Total uncertainty:	1 310 nm ± 10 nm, 1 550 nm ± 10 nm and/or 1 625 nm ± 10 nm $\leq \pm 0,05$ dB over the dynamic range to be measured
4	High optical power IEC 61300-2-14	Before, during and after the test, the insertion loss shall meet the requirements of test No. 1. Before, during and after the test, the return loss shall meet the requirements of test No. 2. During the test, the change in insertion loss and return loss shall be measured by test method IEC 61300-3-3	Test temperature: Optical source wavelength: Test duration: Power increments:	60 °C ± 2 °C 1 310 nm ± 10 nm, 1 550 nm ± 10 nm and/or 1 625 nm ± 10 nm 1 h at each power level For nominal insertion loss ≤ 5 dB: start at 0 dBm and go up to maximum allowed power input in 100 mW increments of CW source input For nominal insertion loss > 5 dB: 10 mW continuous power increments The above increments are applied up to the maximum allowed power input of 100 mW

No.	Tests	Requirements	Details	
5	Vibration (sinusoidal) IEC 61300-2-1	<p>Before and after the test, the insertion loss shall meet the requirements of test No. 1.</p> <p>Before and after the test, the return loss shall meet the requirements of test No. 2.</p> <p>During the test, the change in insertion loss shall be $\leq \pm 0,5$ dB.</p>	<p>Method:</p> <p>Frequency range:</p> <p>Constant vibration amplitude:</p> <p>Number of cycles:</p> <p>Number of axes:</p> <p>Sweep rate:</p> <p>Optical source wavelength:</p> <p>Specimen optically functioning:</p>	<p>During the test, the change in insertion loss shall be measured by transient loss test method IEC 61300-3-28.</p> <p>10 Hz to 55 Hz</p> <p>0,75 mm</p> <p>15</p> <p>3 orthogonal</p> <p>1 octave/min</p> <p>1 310 nm \pm 10 nm, 1 550 nm \pm 10 nm and/or 1 625 nm \pm 10 nm</p> <p>Yes</p>
6	Cold IEC 61300-2-17	<p>During the test, the maximum allowed change in insertion loss is:</p> <p>$\leq \pm 0,5$ dB for attenuator ≤ 5 dB.</p> <p>$\leq \pm 10$ % for attenuators > 5 dB.</p> <p>Before and after the test, the insertion loss requirements of test No. 1 shall be met.</p> <p>Before and after the test, the return loss requirement of test No. 2 shall be met.</p>	<p>Method:</p> <p>Temperature:</p> <p>Duration of the exposure:</p> <p>Optical source wavelength:</p> <p>Maximum sampling interval during the test:</p> <p>Specimen optically functioning:</p>	<p>During the test, the change in insertion loss shall be measured by test method IEC 61300-3-3.</p> <p>-25 °C ± 2 °C</p> <p>96 h</p> <p>1 310 nm \pm 10 nm, 1 550 nm \pm 10 nm and/or 1 625 nm \pm 10 nm</p> <p>Before and after the test, the samples will be measured with three wavelengths. During the test, the samples will be measured with one wavelength.</p> <p>1 h</p> <p>Yes</p>
7	Dry heat – High temperature endurance IEC 61300-2-18	<p>During the test, the maximum allowed change in insertion loss is:</p> <p>$\leq \pm 0,5$ dB for attenuator ≤ 5 dB</p> <p>$\leq \pm 10\%$ for attenuators > 5 dB</p> <p>Before and after the test, the insertion loss requirements of test No. 1 shall be met</p> <p>Before and after the test, the return loss requirement of test No. 2 shall be met</p>	<p>Method:</p> <p>Temperature:</p> <p>Duration of the exposure:</p> <p>Optical source wavelength:</p> <p>Maximum sampling interval during the test:</p> <p>Specimen optically functioning:</p>	<p>During the test, the change in insertion loss shall be measured by test method IEC 61300-3-3.</p> <p>$+ 70$ °C ± 2 °C</p> <p>96 h</p> <p>1 310 nm \pm 10 nm, 1 550 nm \pm 10 nm and/or 1 625 nm \pm 10 nm</p> <p>Before and after the test, the samples will be measured with three wavelengths. During the test, the samples will be measured with one wavelength.</p> <p>1 h</p> <p>Yes</p>

No.	Tests	Requirements	Details	
8	Damp heat (cyclic) IEC 61300-2-46	<p>Before, during and after the test the insertion loss requirements of test No. 1 shall be met</p> <p>Before and after the test the return loss requirement of test No. 2 shall be met</p> <p>During the test the change in Insertion Loss shall be measured by test method IEC 61300-3-3</p>	<p>Method:</p> <p>High temperature:</p> <p>Low temperature:</p> <p>Humidity:</p> <p>Number of cycles:</p> <p>Duration of each cycle:</p> <p>Optical source wavelength:</p> <p>Maximum sampling interval during the test:</p> <p>Specimen optically functioning:</p>	<p>During the test the change in insertion loss shall be measured by test method IEC 61300-3-3.</p> <p>+ 70 °C ± 2 °C</p> <p>+ 25 °C ± 2 °C</p> <p>> 95 % RH ± 2 % RH</p> <p>4</p> <p>24 h</p> <p>1 310 nm ± 10 nm, 1 550 nm ± 10 nm and/or 1 625 nm ± 10 nm</p> <p>Before and after the test, the samples will be measured with three wavelengths. During the test, the samples will be measured with one wavelength.</p> <p>1 h</p> <p>Yes</p>
9	Change of temperature IEC 61300-2-22	<p>Before, during and after the test, the insertion loss requirements of test No 1 shall be met.</p> <p>Before and after the test, the return loss requirement of test No 2 shall be met.</p>	<p>Method:</p> <p>High temperature:</p> <p>Low temperature:</p> <p>Number of cycles:</p> <p>Rate of temperature change:</p> <p>Duration at extreme temperatures:</p> <p>Optical source wavelength:</p> <p>Maximum sampling interval during the test:</p> <p>Specimen optically functioning:</p>	<p>Test Nb</p> <p>During the test, the change in insertion loss shall be measured by test method IEC 61300-3-3.</p> <p>+ 70 °C ± 2 °C</p> <p>– 25 °C ± 2 °C</p> <p>12</p> <p>1 °C/min</p> <p>1 h</p> <p>1 310 nm ± 10 nm, 1 550 nm ± 10 nm and/or 1 625 nm ± 10 nm</p> <p>Before and after the test, the samples will be measured with three wavelengths. During the test, the samples will be measured with one wavelength.</p> <p>15 min</p> <p>Yes</p>

No.	Tests	Requirements	Details	
10	Dust IEC 61300-2-27	<p>Before and after the test, the insertion loss shall meet the requirements of test No. 1.</p> <p>Before and after the test, the return loss shall meet the requirements of test No. 2.</p> <p>Before and after the test. Specimen tested in mated position.</p> <p>No significant difference either in the visual aspect or in the strength coupling mechanism shall be noticed</p>	<p>Temperature:</p> <p>Relative humidity:</p> <p>Dust type:</p> <p>Dust particle diameter:</p> <p>Dust concentration:</p> <p>Test duration:</p> <p>Particle size</p> <p>Specimen optically functioning:</p>	<p>+ 35 °C ± 2 °C</p> <p>+ 60 % RH ± 2 % RH</p> <p>Talc</p> <p>< 150 µm</p> <p>10,6 g/m³ ± 7,1 g/m³</p> <p>10 min</p> <p>d < 150 µm</p> <p>No</p>
11	Salt mist IEC 61300-2-26	<p>Before and after the test, the insertion loss shall meet the requirements of test No. 1.</p> <p>Before and after the test, the return loss shall meet the requirements of test No. 2.</p> <p>Before and after the test. Specimen tested in mated position.</p>	<p>Temperature:</p> <p>Salt solution (NaCl) concentration:</p> <p>pH:</p> <p>Test duration:</p> <p>Specimen optically functioning:</p>	<p>+ 35 °C ± 2 °C</p> <p>5 % ± 1 %</p> <p>Between 6,5 and 7,2</p> <p>96 h</p> <p>No</p>
12	Shock IEC 61300-2-9	<p>Before and after the test, the insertion loss shall meet the requirements of test No. 1.</p> <p>Before and after the test, the return loss shall meet the requirements of test No. 2.</p>	<p>Acceleration force:</p> <p>Time:</p> <p>No. of shocks:</p> <p>Specimen optically functioning:</p> <p>Optical source wavelength:</p>	<p>5 000 m/s²</p> <p>1ms duration, half sine pulse</p> <p>3 axes in 2 directions, 2 shocks per axis, 12 shocks total</p> <p>No</p> <p>1 310 nm ± 10 nm, 1 550 nm ± 10 nm and/or 1 625 nm ± 10 nm</p>
13	Optical fibre cable flexing IEC 61300-2-44	<p>Before and after the test, the insertion loss shall meet the requirements of test No. 1.</p> <p>Before and after the test, the return loss shall meet the requirements of test No. 2.</p>	<p>Magnitude of the load:</p> <p>Angle of deflection per cycle:</p> <p>Number of cycles:</p> <p>Specimen optically functioning:</p> <p>Method of mounting:</p>	<p>5 000 m/s² for reinforced cable</p> <p>± 90°</p> <p>30</p> <p>No</p> <p>The sample shall be rigidly mounted such that the load is only applied to the fibre/cable.</p>