IEC 61978-1

Edition 3.0 2014-05

INTERNATIONAL STANDARD

Fibre optic interconnecting devices and passive components – Fibre optic passive chromatic dispersion compensators – Part 1: Generic specification

IEC 61978-1:2014-05(en)

IEC Central Office
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC
The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications
The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue
The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub
The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,…). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished
Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org
The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in 14 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary
More than 55 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc
If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

IEC 61978-1

Edition 3.0 2014-05

INTERNATIONAL STANDARD

colour inside

Fibre optic interconnecting devices and passive components – Fibre optic passive chromatic dispersion compensators – Part 1: Generic specification

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PRICE CODE U

ICS 33.180.01

ISBN 978-2-8322-1583-8

CONTENTS

INTERNATIONAL ELECTROTECHNICAL COMMISSION

FIBRE OPTIC INTERCONNECTING DEVICES AND PASSIVE COMPONENTS – FIBRE OPTIC PASSIVE CHROMATIC DISPERSION COMPENSATORS –

Part 1: Generic specification

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61978-1 has been prepared by subcommittee 86B: Fibre optic interconnecting devices and passive components, of IEC technical committee 86: Fibre optics.

This third edition cancels and replaces the second edition, published in 2009, and constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

a) introduction of new terms and definitions;
b) revision of classifications;
c) addition of Annex E.

The text of this standard is based on the following documents:

CDV	Report on voting
86B/3639/CDV	86B/3710/RVC

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 61978 series, published under the general title *Fibre optic interconnecting devices and passive components – Fibre optic passive chromatic dispersion compensators,* can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The "colour inside" logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this publication using a colour printer.

FIBRE OPTIC INTERCONNECTING DEVICES AND PASSIVE COMPONENTS – FIBRE OPTIC PASSIVE CHROMATIC DISPERSION COMPENSATORS –

Part 1: Generic specification

1 Scope

This part of IEC 61978 applies to fibre optic passive chromatic dispersion compensators, all exhibiting the following features:

– they are optically passive;
– they have an optical input and an optical output for transmitting optical power;
– the ports are optical fibres or optical fibre connectors;
– they are wavelength sensitive;
– they may be polarization sensitive.

This standard establishes uniform requirements for the passive chromatic dispersion compensator.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60027 (all parts), *Letter symbols to be used in electrical technology*

IEC 60050-731, *International Electrotechnical Vocabulary – Chapter 731: Optical fibre communication*

IEC 60617 (all parts), *Graphical symbols for diagrams*

IEC 60695-11-5, *Fire hazard testing – Part 11-5: Test flames – Needle-flame test method – Apparatus, confirmatory test arrangement and guidance*

IEC 60793-2-50:2012, *Optical fibres – Part 2-50: Product specifications – Sectional specification for class B single-mode fibres*

IEC 60825 (all parts), *Safety of laser products*

IEC 61300 (all parts), *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures*

IEC 61300-3-38, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-38: Examinations and measurements – Group delay, chromatic dispersion and phase ripple*

IEC TR 61930, *Fibre optic graphical symbology*

IEC Guide 102, *Electronic components – Specification structures for quality assessment (Qualification approval and capability approval)*

ISO 129-1, *Technical drawings – Indication of dimensions and tolerances – Part 1: General principles*

ISO 286-1, *Geometrical product specifications (GPS) – ISO coding system for tolerances of linear sizes – Part 1: Bases of tolerances and fits*

ISO 1101, *Geometrical Product Specifications (GPS) – Geometrical tolerancing – Tolerances of form, orientation, location and run-out*

ISO 8601, *Data elements and interchange formats – Information interchange – Representation of dates and times*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60050-731, as well as the following definitions apply.

3.1 Basic terms

3.1.1
port
optical fibre or optical fibre connector attached to a passive component for the entry and/or exit of optical power (input and/or output port)

3.2 Component terms

3.2.1
passive chromatic dispersion compensator
PCDC
two-port in-line passive device used to perform chromatic dispersion compensation

Note 1 to entry: PCDCs are commonly used to compensate the chromatic dispersion of an optical path by adding the opposite sign chromatic dispersion.

Note 2 to entry: The typical optical paths comprise single-mode fibre, dispersion shifted fibre and/or non-zero dispersion shifted fibre. PCDCs have either negative or positive chromatic dispersion values depending on the chromatic dispersion sign of the optical path.

3.2.2
dispersion compensating fibre
DCF
speciality fibre to compensate for the chromatic dispersion of an optical path

3.2.3
passive DCF based dispersion compensator
PCDC which constitutes DCF; realised by having chromatic dispersion characteristics of opposite sign to that of the optical path which are controlled the refractive index profile of the fibre

3.2.4
fibre Bragg grating
FBG
fibre type optical device which has modulated refractive index profile in the core

3.2.5
passive FBG based dispersion compensator
PCDC which constitutes a FBG; PCDC is realised by a chirped FBG which has gradually changing refractive index along the fibre axis

3.2.6
virtually imaged phased array
VIPA
optical device having a glass plate with a highly reflective mirror

Note 1 to entry: A VIPA has the same functions as a grating.

3.2.7
passive VIPA based dispersion compensator
PCDC which consisting of a VIPA, focusing lens and 3-dimensional mirror

Note 1 to entry: PCDC produces both positive and negative chromatic dispersion by the movement of the 3-dimensional mirror to compensate for the chromatic dispersion of an optical path.

3.2.8
etalon
optical cavity which consists of a pair of parallel reflective mirrors

3.2.9
Gires-Tournois etalon
GT etalon
etalon having a highly reflective mirror and a half mirror

Note 1 to entry: The GT etalon is sometimes called a GT interferometer.

3.2.10
passive GT etalon based dispersion compensator
PCDC which comprises a GT etalon

3.3 Performance parameter

3.3.1
chromatic dispersion compensation
process by which a specific amount of chromatic dispersion is removed in order to mitigate the system impairment caused by unwanted dispersion

3.3.2
group delay
time by which a pulse is delayed by an optical device

Note 1 to entry: The group delay generally varies with the operating wavelength.

3.3.3
chromatic dispersion
derivative of group delay with respect to wavelength or frequency

Note 1 to entry: A typical unit is ps/nm or ps/GHz. The chromatic dispersion generally varies with the operating wavelength.

Note 2 to entry: The units of ps/GHz are not commonly used; however, it is suitable for the evaluation of transmission system influence.

3.3.4
dispersion slope
derivative of chromatic dispersion with respect to wavelength or frequency

Note 1 to entry: A typical unit is ps/nm2 or ps/GHz2.The unit of ps/GHz2 is not commonly used; however, it is suitable for the evaluation of transmission system influence.

Note 2 to entry: The dispersion slope generally varies with the operating wavelength

3.3.5
operating wavelength
nominal wavelength λ at which a passive device operates with the specified performance

Note 1 to entry: Operating wavelength includes the wavelength to be nominally transmitted, attenuated and isolated.

3.3.6
operating wavelength range
specified range of wavelengths including all operating wavelengths

Note 1 to entry: Operating wavelength range shall include all passbands when two or more the passbands are exist.

3.3.7
figure of merit
FoM
ratio of the dispersion to the insertion loss of a PCDC at a particular operating wavelength

3.3.8
passband
wavelength range within which a passive optical component is required to operate with optical attenuation less than or equal to a specified optical attenuation value

Note 1 to entry: There may be one or more passbands for a PCDC.

3.3.9
passband ripple
maximum peak-to-peak variation of insertion loss in the passband

Note 1 to entry: The passband ripple of a PCDC is defined as the maximum passband ripple for all passbands.

3.3.10
group delay ripple
GDR
maximum peak-to-peak variation of the group delay approximated by a desired function of wavelength (or frequency), typically a linear fit, within a channel wavelength (or frequency) range

3.3.11
phase ripple
maximum peak-to-peak variation in measured phase spectrum when compared to a quadratic fit within a channel wavelength (or frequency) range

Note 1 to entry: Phase ripple (unit: radian) is calculated as the product of a peak-to-peak group delay ripple (unit: s) and a period of group delay ripple (unit: Hz). Refer to IEC 61300-3-38.

3.3.12
insertion loss
reduction in optical power between an input and output port of a passive component expressed in decibels. It is defined as follows:

$$a = -10\log\frac{P_a}{P_0}$$

where

P_0 is the optical power launched into the input port;