

INTERNATIONAL STANDARD

ISO
3626

Second edition
1996-10-15

Photography — Processing chemicals — Specifications for potassium thiocyanate

iTeh STANDARD PREVIEW

*Photographie — Produits chimiques de traitement — Spécifications
relatives au thiocyanate de potassium*

ISO 3626:1996

<https://standards.iteh.ai/catalog/standards/sist/d3aa8dce-e930-4556-a228-debfe0fcac11/iso-3626-1996>



Reference number
ISO 3626:1996(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 3626 was prepared by Technical Committee ISO/TC 42, *Photography*.

This second edition cancels and replaces the first edition (ISO 3626:1976), which has been technically revised.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 3626
<https://standards.iteh.ai/catalog/standards/sist/d3aa8dce-e930-4556-a228-debfe0fcac11/iso-3626-1996>

© ISO 1996

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case Postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

Introduction

0.1 This International Standard is one of a series that establishes criteria of purity for chemicals used in processing photographic materials. General test methods and procedures cited in this International Standard are compiled in parts 1, 5 and 6 of ISO 10349.

This International Standard is intended for use by individuals with a working knowledge of analytical techniques, which may not always be the case. Some of the procedures utilize caustic, toxic or otherwise hazardous chemicals. Safe laboratory practice for the handling of chemicals requires the use of safety glasses or goggles, rubber gloves and other protective apparel such as face masks or aprons where appropriate. Normal precautions required in the performance of any chemical procedure are to be exercised at all times but care has been taken to provide warnings for hazardous materials. Hazard warnings designated by a letter enclosed in angle brackets “ $\langle \rangle$ ” are used as a reminder in those steps detailing handling operations and are defined in ISO 10349-1. More detailed information regarding hazards, handling and use of these chemicals may be available from the manufacturer.

ISO 3626:1996

<https://standards.iteh.ai/catalog/standards/sist/ba612600-4500-4500-4500-4500/iso-3626-1996>
0.2 This International Standard provides chemical and physical requirements for the suitability of a photographic-grade chemical. The tests correlate with undesirable photographic effects. Purity requirements are set as low as possible consistent with these photographic effects. These criteria are considered the minimum requirements necessary to assure sufficient purity for use in photographic processing solutions, except that if the purity of a commonly available grade of chemical exceeds photographic processing requirements and if there is no economic penalty in its use, the purity requirements have been set to take advantage of the availability of the higher-quality material. Every effort has been made to keep the number of requirements to a minimum. Inert impurities are limited to amounts which will not unduly reduce the assay. All tests are performed on samples “as received” to reflect the condition of materials furnished for use. Although the ultimate criterion for suitability of such a chemical is its successful performance in an appropriate use test, the shorter, more economical test methods described in this International Standard are generally adequate.

Assay procedures have been included in all cases where a satisfactory method is available. An effective assay requirement serves not only as a safeguard of chemical purity but also as a valuable complement to the identity test. Identity tests have been included whenever a possibility exists that another chemical or mixture of chemicals could pass the other tests.

All requirements listed in clause 4 are mandatory. The physical appearance of the material and any footnotes are for general information only and are not part of the requirements.

0.3 Efforts have been made to employ tests which are capable of being run in any normally equipped laboratory and, wherever possible, to avoid tests which require highly specialized equipment or techniques. Instrumental methods have been specified only as alternative methods or alone in those cases where no other satisfactory method is available.

Over the past few years, great improvements have been made in instrumentation for various analyses. Where such techniques have equivalent or greater precision, they may be used in place of the tests described in this International Standard. Correlation of such alternative procedures with the given method is the responsibility of the user. In case of disagreement in results, the method called for in the specification shall prevail. Where a requirement states "to pass test", however, alternative methods shall not be used.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO 3626:1996](https://standards.iteh.ai/catalog/standards/sist/d3aa8dce-e930-4556-a228-debfe0fcac11/iso-3626-1996)

<https://standards.iteh.ai/catalog/standards/sist/d3aa8dce-e930-4556-a228-debfe0fcac11/iso-3626-1996>

Photography — Processing chemicals — Specifications for potassium thiocyanate

1 Scope

This International Standard establishes criteria for the purity of photographic-grade potassium thiocyanate and specifies the test methods to be used to determine the purity.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 10349-1:1992, *Photography — Photographic-grade chemicals — Test methods — Part 1: General.*

ISO 10349-5:1992, *Photography — Photographic-grade chemicals — Test methods — Part 5: Determination of heavy metals and iron content.*

ISO 10349-6:1992, *Photography — Photographic-grade chemicals — Test methods — Part 6: Determination of halide content.*

3 General

3.1 Physical properties

Potassium thiocyanate (KCNS) exists as colourless, deliquescent crystals. It has a relative molecular mass of 97,18.

3.2 Hazardous properties

Potassium thiocyanate presents no special hazardous problems under normal handling.

3.3 Storage

Store in a cool dry place. Care shall be taken to avoid conditions of high heat and/or humidity which can cause decomposition and emission of toxic fumes.

4 Requirements

A summary of the requirements is shown in table 1.

5 Reagents and materials, including glassware

All reagents, materials and glassware shall conform to the requirements specified in ISO 10349-1 unless otherwise noted. The hazard warning symbols used as a reminder in those steps detailing handling operations are defined in ISO 10349-1. These symbols are used to provide information to the user and are not meant to provide conformance with hazardous labelling requirements, as these vary from country to country.

6 Sampling

See ISO 10349-1.

7 Test procedures

7.1 Assay

iTeh STANDARD PREVIEW
(standards.iteh.ai)

7.1.1 Specification

Content of KCNS shall be 98,0 % (*m/m*) min.

[ISO 3626:1996](https://standards.iteh.ai/catalog/standards/sist/d3aa8dce-e930-4556-a228-debfe0fcac11/iso-3626-1996)

<https://standards.iteh.ai/catalog/standards/sist/d3aa8dce-e930-4556-a228-debfe0fcac11/iso-3626-1996>

Table 1 — Summary of requirements

Test	Limit	Subclause	International Standard in which test method is given
Assay	98,0 % (<i>m/m</i>) min.	7.1	ISO 3626
Heavy metals content (as Pb)	0,002 % (<i>m/m</i>) max.	7.2	ISO 10349-5
Iron content	0,000 2 % (<i>m/m</i>) max.	7.3	ISO 10349-5
Halide content (as Cl ⁻)	0,05 % (<i>m/m</i>) max.	7.4	ISO 10349-6
pH value	5,3 to 8,7	7.5	ISO 3626
Sulfur compounds		7.6	ISO 3626
a) For developer solution, use amount precipitated by ammoniacal silver nitrate	0,001 % (<i>m/m</i>) max.	7.6.1	ISO 3626
b) For fixer solution, use iodine consumption	To pass test	7.6.2	ISO 3626
Sulfate content (as SO ₄ ²⁻)	0,06 % (<i>m/m</i>) max.	7.7	ISO 3626
Copper content	0,000 1 % (<i>m/m</i>) max.	7.8	ISO 3626
Appearance of aqueous solution	Clear and free from insoluble matter except for a slight flocculence	7.9	ISO 3626
Appearance of ethanolic solution	Clear and free from insoluble matter except for a slight flocculence	7.10	ISO 3626
NOTE — <i>m/m</i> = mass/mass			

7.1.2 Reagents

7.1.2.1 Nitric acid (HNO₃), (1 + 9) solution ¹⁾.

7.1.2.2 Ammonium iron(III) sulfate [(NH₄)Fe(SO₄)₂], 50 g/l solution.

7.1.2.3 Silver nitrate (AgNO₃), standard volumetric solution of 0,100 mol/l (17,0 g/l) ²⁾ ³⁾.

7.1.2.4 Ammonium thiocyanate (NH₄SCN), standard volumetric solution of 0,100 mol/l (7,61 g/l) ²⁾.

7.1.3 Apparatus

7.1.3.1 Burette, of 50 ml capacity.

7.1.3.2 Pipette, of 50 ml capacity.

7.1.4 Procedure

Weigh, to the nearest 0,001 g, a test portion of about 0,3 g and dissolve it in 50 ml of water. Add 5 ml of the nitric acid (7.1.2.1), followed by 50,00 ml of the silver nitrate (7.1.2.3) using the pipette (7.1.3.2). Shake well, add 2 ml of the ammonium iron(III) sulfate (7.1.2.2) and titrate the excess of silver nitrate with the ammonium thiocyanate (7.1.2.4) to a permanent red endpoint.

iTech STANDARD PREVIEW
(standards.iteh.ai)

7.1.5 Expression of results

The assay, expressed as a percentage by mass of KCNS, is given by

$$9,718(50 \cdot c_1 - V \cdot c_2) / m$$

<https://standards.iteh.ai/catalog/standards/sist/d3aa8dce-e930-4556-a228-debfe0fcac11/iso-3626-1996>

where

- c_1 is the actual concentration, in moles per litre, of the silver nitrate (7.1.2.3);
- c_2 is the actual concentration, in moles per litre, of the ammonium thiocyanate (7.1.2.4);
- V is the volume, in millilitres, of the ammonium thiocyanate (7.1.2.4) used for the titration;
- m is the mass, in grams, of the test portion;
- 50 is the volume, in millilitres, of silver nitrate added (7.1.4);
- 9,718 is the conversion factor obtained from the mass of potassium thiocyanate equivalent to 1 mole of silver nitrate (i.e. 97,18) × the conversion factor for millilitres to litres (i.e. 0,001) × 100 (for percentage).

7.2 Heavy metals content

7.2.1 Specification

Maximum content of heavy metals shall be 0,002 % (*m/m*).

1) This solution may be prepared from concentrated nitric acid, 69 % (*m/m*) (approx.) (DANGER: (C)(B)(O)). (Hazard warning codes are defined in ISO 10349-1.)

2) Commercially available analysed reagent solutions are recommended. Procedures for the preparation of these materials are available in any quantitative analysis text.

3) This solution may be prepared from solid silver nitrate (DANGER: (C)).

7.2.2 Procedure

NOTE — The standard for the iron test (7.3) is prepared in the same way as the heavy metals standard.

Determine the percentage of heavy metals in accordance with ISO 10349-5. Use a test portion of 1,90 g to 2,10 g, prepared in accordance with ISO 10349-5:1992, 7.2. Use 4 ml of the heavy metals standard prepared in accordance with ISO 10349-5:1992, 8.1.1.

7.3 Iron content

7.3.1 Specification

Maximum content of iron shall be 0,000 2 % (*m/m*).

7.3.2 Procedure

Determine the percentage of iron in accordance with ISO 10349-5. Use a test portion of 9,90 g to 10,10 g, prepared in accordance with ISO 10349-5:1992, 7.2. Use 2 ml of the iron standard prepared in accordance with ISO 10349-5:1992, 8.1.1.

7.4 Halide content (as Cl⁻)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

7.4.1 Specification

Maximum content of halide shall be 0,05 % (*m/m*) [0,1 % (*m/m*) as KCl].

[ISO 3626:1996](#)

<https://standards.iteh.ai/catalog/standards/sist/d3aa8dce-e930-4556-a228-debf0fcac11/iso-3626-1996>

7.4.2 Reagents

7.4.2.1 Sodium hydroxide, solid (DANGER: <<C>>).

7.4.2.2 Hydrogen peroxide (H₂O₂), 67 g/l (approx.) solution.

Dilute 1 volume of 30 % hydrogen peroxide (DANGER: <<C>>(O)) with 4 volumes of water.

7.4.3 Procedure

Weigh, to the nearest 0,1 g, a test portion of about 1 g and dissolve it in 30 ml of the hydrogen peroxide (7.4.2.2). Add 1 g of sodium hydroxide (7.4.2.1) (DANGER: <<C>>) and swirl until the vigorous reaction ceases. Add another 30 ml of hydrogen peroxide (7.4.2.2) and boil for 2 min. Cool and dilute to 100 ml with water. Use a 10 ml aliquot of this test solution. Continue the procedure in accordance with ISO 10349-6:1992, clause 4, using 5 ml of the halide standard solution A.

7.5 pH value

7.5.1 Specification

The pH of the solution shall be between 5,3 and 8,7.

7.5.2 Apparatus

7.5.2.1 Electronic pH-meter, equipped with a glass electrode and standard reference electrode.

7.5.3 Procedure

Weigh, to the nearest 0,1 g, a test portion of about 5 g and dissolve it in about 80 ml of boiled water. Dilute to 100 ml. Measure the pH of the solution at 20 °C, using the pH-meter (7.5.2.1) in accordance with the manufacturer's instructions.

7.6 Sulfur compounds

For use in non-developer solutions (e.g. fixers), the less-sensitive iodine consumption test is adequate, whereas for use in developers the more-sensitive ammoniacal silver nitrate test is required.

7.6.1 Amount precipitated by ammoniacal silver nitrate⁴⁾

7.6.1.1 Specification

Maximum content of sulfur shall be 0,001 % (m/m).

7.6.1.2 Reagents

7.6.1.2.1 Sulfide standard solution (1 ml = 0,010 mg S²⁻).

Dissolve 1,5 g of sodium sulfide nonahydrate (Na₂S·9H₂O) (DANGER: <S>) in 100 ml of water in a 200 ml volumetric flask. Dilute to volume with water and mix well. Pipette 1 ml of this solution into a 100 ml volumetric flask, dilute to volume with water and mix well. Label this solution "sulfide standard".

7.6.1.2.2 Ammonium hydroxide (NH₄OH), ρ ≈ 0,91 g/ml (DANGER: <C>).

7.6.1.2.3 Silver nitrate (AgNO₃), 100 g/l solution³⁾

7.6.1.2.4 Silver nitrate, standard volumetric solution of 0,001 mol/l (0,170 g/l)^{2) 3)}.

7.6.1.3 Apparatus

7.6.1.3.1 Two matched Nessler colour-comparison cylinders, of 50 ml capacity.

7.6.1.4 Procedure

Weigh, to the nearest 0,01 g, a test portion of about 1 g and dissolve it in 25 ml of water. Add this solution to a mixture of 20 ml of ammonium hydroxide (7.6.1.2.2) (DANGER: <C>) and 2 ml of the silver nitrate (7.6.1.2.3).

Also prepare a control by adding 1 ml of sulfide standard (7.6.1.2.1) to a mixture of 20 ml of water, 20 ml of ammonium hydroxide (7.6.1.2.2) and 3 ml of 0,001 mol/l silver nitrate (7.6.1.2.4). Heat both solutions in a boiling water bath for 15 min. Cool, transfer to the Nessler colour-comparison cylinders (7.6.1.3.1) and dilute to 50 ml.

Compare the colours produced in the two Nessler colour-comparison cylinders. Any colour produced in the sample shall not exceed that produced in the sulfide standard control.

CAUTION — Dispose of all test solutions and rinse all used apparatus immediately. Explosive compounds may be formed on standing.

4) The test method given here for sulfur compounds is not the same as the ammoniacal silver nitrate test given in ISO 10349-9:1992, *Photography — Photographic-grade chemicals — Test methods — Part 9: Reaction to ammoniacal silver nitrate*.