INTERNATIONAL STANDARD



First edition 1994-12-15

Road vehicles — Sheath-type glow-plugs with conical seating and their cylinder head housing —

iTeh Spart 2DARD PREVIEW (M12ndal, 25.glow-plugs

ISO 6550-2:1994

https://standards.iv/enicales/fouriers^{ls/sist}Bougies³de⁸préchauffage à fourreau et à siège confique, et leuri logément dans la culasse —

Partie 2: Bougies $M12 \times 1,25$



Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting VIEW a vote.

International Standard ISO 6550-2 was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 1, *Ignition equipment*.

This first edition of ISO 6550-2ptogether with ISO 6550-1 acancel and 8e3-b8cc-4599-9c83place ISO 6550:1989, which has been split into three parts part 32covering M10 glow-plugs.

ISO 6550 consists of the following parts, under the general title *Road vehicles* — Sheath-type glow-plugs with conical seating and their cylinder head housing:

- Part 1: M14 x 1,25 glow-plugs
- Part 2: M12 x 1,25 glow-plugs
- Part 3: M10 glow-plugs

© ISO 1994

Printed in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization

Case Postale 56 • CH-1211 Genève 20 • Switzerland

Road vehicles — Sheath-type glow-plugs with conical seating and their cylinder head housing —

Part 2:

 $M12 \times 1,25$ glow-plugs

1 Scope

3 Dimensions and tolerances

This part of ISO 6550 specifies the main characteristics of M12 \times 1,25 sheath-type glow-plugs with RD Plugs conical seating and their cylinder head housing, for use with diesel (compression-ignition) engines. **Carcs** I given in figure 1.

2 Normative references

ISO 6550-2:19312 Cylinder head housing

https://standards.iteh.ai/catalog/standards/sist/42aba803-b8ee-4599-9c83-

The following standards contain provisions 4 which, is through reference in this text, constitute provisions of this part of ISO 6550. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this part of ISO 6550 are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 2705:1991, Road vehicles — M12 x 1,25 sparkplugs with flat seating and their cylinder head housing.

ISO 8092-1:—¹⁾, Road vehicles — Connections for on-board electric harnesses — Part 1: Single-pole connector tabs — Dimensions and specific requirements.

The following standards contain provisions 4 which / iso-655 the dimensions and tolerances of the cylinder head housing for sheath-type glow-plugs are given in figure 2.

3.3 Dimension limits of thread

The threads of M12 \times 1,25 glow-plugs and the corresponding tapped holes in the cylinder head shall conform to the threads specified for M12 \times 1,25 spark-plugs in ISO 2705.


4 Installation tightening torque

The installation torque values shall be as given in table 1. The values apply to new sheath-type glow-plugs without lubricant on the threads. If threads are lubricated, the torque value shall be reduced by approximately one-third to avoid overstressing.

¹⁾ To be published. (Revision of ISO 8092-1:1989)

Tightening torque				
Cast iron and aluminium cylinder heads	M5 terminal thread ¹⁾			
15 to 25	4			
NOTE — Engine manufacturers may specify different torques for the first glow-plug installation.				
1) Differing specifications apply to the admissible tighten- ing torque according to the nut used.				

Table 1 — Installation tightening torque Values in newton metres




 For flat tab terminations of sizes 6,3 and 9,5, the 7 mm min. and 25 mm max. dimensions shall change to 12 mm min. and 30 mm max. respectively. Tab dimensions of these 6,3 mm and 9,5 mm sizes are given in ISO 8092-1.
 The length of 25 mm is preferred.

Glow-plug type	L ₁ +1 0	L ₂ ± 1	<i>D</i> ₁ 0 -0,3	D ₂ 0 -0.2
M12 A1	6 26	6,1		
M12 A2		26	5,1	—
M12 A3			5,1	4,1
M12 B	3	20	6,1	

Figure 1 — M12 \times 1,25 sheath-type glow-plug with conical seating

Dimensions in millimetres

Dimensions in millimetres



 The determination of the exact dimension above the minimum is left to the manufacturer. The clearance between the sheath heating element and the cylinder head shall be kept to a minimum.

Glow-plug type	L ₃	L ₄ max.
M12 A	5 ⁰ ₋₁	23
M12 B	2 ⁰ _{-0,3}	17

Figure 2 — Cylinder head housing for glow-plug

iTeh STANDARD PREVIEW This page intentionally left blank (standards.iteh.ai)

<u>ISO 6550-2:1994</u> https://standards.iteh.ai/catalog/standards/sist/42aba803-b8ee-4599-9c83-3c5724c525dd/iso-6550-2-1994

iTeh STANDARD PREVIEW This page intentionally left blank (standards.iteh.ai)

<u>ISO 6550-2:1994</u> https://standards.iteh.ai/catalog/standards/sist/42aba803-b8ee-4599-9c83-3c5724c525dd/iso-6550-2-1994

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 6550-2:1994</u> https://standards.iteh.ai/catalog/standards/sist/42aba803-b8ee-4599-9c83-3c5724c525dd/iso-6550-2-1994

ICS 43.060.50

Descriptors: road vehicles, motor vehicles, internal combustion engines, diesel engines, ignition systems (engines), preheating plugs, housings, dimensions, dimensional tolerances.

Price based on 3 pages

Ξ