

SLOVENSKI STANDARD

SIST EN 301 178:2000

01-januar-2000

9`Y_Hfca U[bYhbUnXfi ý`lj cghifØ A7Ł]b`nUXYj Yj `nj Yn]`n'fUX]`g_`a `gdY_Hfca `fØFAŁ!
HM b] bY_UFU_HYf]gh]_Y]b`a Yf]bY'a YlcXY`nUdfYbcgbY'fUX]chY'YZcbg_Y'bUdfUj Y
J<: `nUdca cfg_c`a cV]bc`g`i ýVcž_]XYi `Yt`bUdUgi `J<: `fbUa c`nUi dcfUVc
]nj Yb`; A8 GGŁ

ElectroMagnetic Compatibility and Radio Spectrum Matters (ERM); Technical characteristics and methods of measurement for portable Very High Frequency (VHF) radiotelephone equipment for the maritime mobile service operating in the VHF bands (for non-GMDSS applications only)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 301 178:2000
<https://standards.iteh.ai/catalog/standards/sist/1ab6a2ce-fc5e-44f6-a355-fbf76bd22eba/sist-en-301-178-2000>

Ta slovenski standard je istoveten z: **EN 301 178 Version 1.1.1**

ICS:

33.060.99	Druga oprema za radijske komunikacije	Other equipment for radiocommunications
33.100.01	Elektromagnetna združljivost na splošno	Electromagnetic compatibility in general
47.020.70	Navigacijska in krmilna oprema	Navigation and control equipment

SIST EN 301 178:2000

en

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

SIST EN 301 178:2000

<https://standards.iteh.ai/catalog/standards/sist/1ab6a2ce-fc5e-44f6-a355-fbf76bd22eba/sist-en-301-178-2000>

EN 301 178 V1.1.1 (1999-05)

European Standard (Telecommunications series)

**Electromagnetic compatibility
and Radio spectrum Matters (ERM);
Technical characteristics and methods of measurement for
portable Very High Frequency (VHF) radiotelephone equipment
for the maritime mobile service operating in the VHF bands
(for non-GMDSS applications only)**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 301 178:2000

<https://standards.iteh.ai/catalog/standards/sist/1ab6a2ce-fc5e-44f6-a355-fbf76bd22eba/sist-en-301-178-2000>



Reference

DEN/ERM-RP01-012 (awo00ico.PDF)

Keywords

maritime, radio

ETSI

Postal address

F-06921 Sophia Antipolis Cedex - FRANCE

iTeh STANDARD PREVIEW

Office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 NAF 742 C

Association à but non lucratif enregistrée à la
Sous-Prefecture de Grasse (06) N° 7803/88<https://standards.etsi.org/standards/sist-en-301-178-2000>

Internetsecretariat@etsi.frIndividual copies of this ETSI deliverable
can be downloaded from<http://www.etsi.org>If you find errors in the present document, send your
comment to: editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1999.
All rights reserved.

ETSI

Contents

Intellectual Property Rights	7
Foreword	7
1 Scope.....	8
2 References	8
3 Definitions, symbols and abbreviations.....	9
3.1 Definitions	9
3.2 Symbols	9
3.3 Abbreviations.....	9
4 General and operational requirements.....	9
4.1 Construction.....	9
4.2 Controls and indicators	10
4.3 Microphone and loudspeaker.....	11
4.4 Safety precautions.....	11
4.5 Labelling	11
5 Technical requirements.....	11
5.1 Switching time	11
5.2 Class of emission and modulation characteristics	11
6 General conditions of measurement	12
6.1 Arrangements for RF connections to the equipment	12
6.1.1 RF connections to integral antenna equipment.....	12
6.1.2 RF connection to equipment with a detachable antenna.....	12
6.2 Arrangements for test signals applied to the receiver input	12
6.3 Squelch	12
6.4 Normal test modulation.....	12
6.5 Artificial antenna	12
6.6 Arrangements for test signals applied to the transmitter input	12
6.7 Test channels	12
6.8 Measurement uncertainty and interpretation of the measured results	13
6.8.1 Measurement uncertainty	13
6.8.2 Interpretation of the measurement results.....	13
6.9 Test conditions, power sources and ambient temperatures	13
6.9.1 Normal and extreme test conditions	13
6.9.2 Test power source	14
6.10 Normal test conditions	14
6.10.1 Normal temperature and humidity.....	14
6.10.2 Normal power sources.....	14
6.10.2.1 Battery power source.....	14
6.10.2.2 Other power sources	14
6.11 Extreme test conditions.....	14
6.11.1 Extreme temperatures.....	14
6.11.2 Extreme values of test power sources.....	15
6.11.2.1 Battery power source	15
6.11.2.2 Other power sources	15
6.12 Procedure for tests at extreme temperatures	15
7 Environmental tests	15
7.1 Procedure	15
7.2 Performance check	15
7.3 Drop test	15
7.3.1 Definition	15
7.3.2 Method of measurement.....	16
7.3.3 Requirement	16
7.4 Temperature tests	16

7.4.1	Definition	16
7.4.2	Dry heat.....	16
7.4.2.1	Definition.....	16
7.4.2.2	Method of measurement	16
7.4.2.3	Requirement	16
7.4.3	Damp heat	16
7.4.3.1	Definition.....	16
7.4.3.2	Method of measurement	17
7.4.3.3	Requirement	17
7.4.4	Low temperature cycle	17
7.4.4.1	Definition.....	17
7.4.4.2	Method of measurement	17
7.4.4.3	Requirement	17
8	Transmitter.....	17
8.1	Frequency error.....	17
8.1.1	Definition	17
8.1.2	Method of measurement.....	18
8.1.3	Limits	18
8.2	Carrier power	18
8.2.1	Definitions.....	18
8.2.2	Method of measurement.....	18
8.2.3	Limits, Normal and extreme test conditions.....	18
8.3	Frequency deviation.....	18
8.3.1	Definition	18
8.3.2	Maximum permissible frequency deviation.....	18
8.3.2.1	Method of measurement	18
8.3.2.2	Limits.....	19
8.3.3	Reduction of frequency deviation at modulation frequencies above 3 kHz	19
8.3.3.1	Method of measurement	19
8.3.3.2	Limits.....	19
8.4	Sensitivity of the modulator, including microphone.....	19
8.4.1	Definition	19
8.4.2	Method of measurement	20
8.4.3	Limits	20
8.5	Audio frequency response.....	20
8.5.1	Definition	20
8.5.2	Method of measurement.....	20
8.5.3	Limit.....	20
8.6	Audio frequency harmonic distortion of the emission	21
8.6.1	Definition	21
8.6.2	Method of measurement.....	21
8.6.2.1	Normal test conditions.....	21
8.6.2.2	Extreme test conditions.....	22
8.6.3	Limits	22
8.7	Adjacent channel power.....	22
8.7.1	Definition	22
8.7.2	Method of measurement.....	22
8.7.3	Limits	22
8.8	Conducted spurious emissions conveyed to the antenna.....	23
8.8.1	Definition	23
8.8.2	Method of measurement.....	23
8.8.3	Limit.....	23
8.9	Cabinet radiation and conducted spurious emissions other than those conveyed to the antenna	23
8.9.1	Definitions.....	23
8.9.2	Method of measurement.....	23
8.9.3	Limits	24
8.10	Residual modulation of the transmitter	24
8.10.1	Definition	24
8.10.2	Method of measurement.....	25
8.10.3	Limit.....	25

8.11	Transient frequency behaviour of the transmitter	25
8.11.1	Definitions.....	25
8.11.2	Method of measurement.....	26
8.11.3	Limits	27
9	Receiver	29
9.1	Harmonic distortion and rated audio frequency output power.....	29
9.1.1	Definition	29
9.1.2	Methods of measurement	29
9.1.3	Limits	29
9.2	Audio frequency response.....	29
9.2.1	Definition	29
9.2.2	Method of measurement.....	29
9.2.3	Limits	30
9.3	Maximum usable sensitivity.....	31
9.3.1	Definition	31
9.3.2	Method of measurement.....	31
9.3.3	Limits	31
9.4	Co-channel rejection	31
9.4.1	Definition	31
9.4.2	Method of measurement.....	31
9.4.3	Limit.....	32
9.5	Adjacent channel selectivity	32
9.5.1	Definition	32
9.5.2	Method of measurement.....	32
9.5.3	Limits	32
9.6	Spurious response rejection	32
9.6.1	Definition	32
9.6.2	Method of measurement.....	32
9.6.3	Limit.....	33
9.7	Intermodulation response.....	33
9.7.1	Definition	33
9.7.2	Method of measurement.....	33
9.7.3	Limit.....	33
9.8	Blocking or desensitization.....	33
9.8.1	Definition	33
9.8.2	Method of measurement.....	34
9.8.3	Limit.....	34
9.9	Conducted spurious emissions	34
9.9.1	Definition	34
9.9.2	Method of measurement.....	34
9.9.3	Limit.....	34
9.10	Radiated spurious emissions	34
9.10.1	Definition	34
9.10.2	Method of measurements	35
9.10.3	Limit.....	35
9.11	Receiver noise and hum level	36
9.11.1	Definition	36
9.11.2	Method of measurement.....	36
9.11.3	Limit.....	36
9.12	Squelch operation	36
9.12.1	Definition	36
9.12.2	Method of measurement.....	36
9.12.3	Limits	37
9.13	Squelch hysteresis	37
9.13.1	Definition	37
9.13.2	Method of measurement.....	37
9.13.3	Limit.....	37

Annex A (normative):	Measuring receiver for adjacent channel power measurement	38
A.1	Power measuring receiver specification	38
A.1.1	IF filter.....	38
A.1.2	Attenuation indicator	39
A.1.3	Rms value indicator	39
A.1.4	Oscillator and amplifier	39
Annex B (normative):	Radiated measurements	40
B.1	Test sites and general arrangements for measurements involving the use of radiated fields.....	40
B.1.1	Outdoor test site.....	40
B.1.2	Test antenna	40
B.1.3	Substitution antenna.....	41
B.1.4	Optional additional indoor site	41
B.2	Guidance on the use of radiation test sites	42
B.2.1	Measuring distance	42
B.2.2	Test antenna	42
B.2.3	Substitution antenna.....	42
B.2.4	Artificial antenna	43
B.2.5	Auxiliary cables	43
B.2.6	Acoustic measuring arrangement	43
B.3	Further optional alternative indoor test site using an anechoic chamber	43
B.3.1	Example of the construction of a shielded anechoic chamber.....	44
B.3.2	Influence of parasitic reflections in anechoic chambers.....	44
B.3.3	Calibration of the shielded anechoic chamber	45
History.....		47

**ITHE STANDARD PREVIEW
(standards.iteh.ai)**

SIST EN 301 178:2000

https://standards.iteh.ai/catalog/standards/sist/1ab6a2ce-fc5e-44f6-a355-
fbf76bd22eba/sist-en-301-178-2000

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available **free of charge** from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

National transposition dates	
Date of adoption of this EN:	30 April 1999
Date of latest announcement of this EN (doa):	31 July 1999
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 January 2000
Date of withdrawal of any conflicting National Standard (dow):	31 January 2000

SIST EN 301 178:2000
<https://standards.iteh.ai/catalog/standards/sist/1ab6a2ce-fc5e-44f6-a355-fbf76bd22eba/sist-en-301-178-2000>

1 Scope

The present document states the minimum technical characteristics and methods of measurement required for portable Very High Frequency (VHF) radiotelephones not providing maritime distress and safety communications functions (i.e. not forming part of the Global Maritime Distress and Safety System (GMDSS)) operating in the bands between 156 MHz and 174 MHz allocated to the maritime mobile services by the Radio Regulations, Appendix 18 [1].

The present document also specifies technical characteristics, methods of measurement and required test results.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.
- A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.

- [1] Radio Regulations, Appendix 18 (1990); "Table of Transmitting Frequencies in the Band 156-174 MHz for Stations in the Maritime Mobile Service".
(standards.itec.ai)
- [2] ITU-T Recommendation E.161 (1993); "Arrangement of digits, letters and symbols on telephones and other devices that can be used for gaining access to a telephone network".
SIST EN 301 178:2000
- [3] ITU-R Recommendation M.493-9 (1997); "Digital selective-calling system for use in the maritime mobile service".
<https://standards.itec.ai/catalog/standards/sist-en-301-178-2000> *fbf76bd22eba/sist-en-301-178-2000*
- [4] ITU-R Recommendation M.541-8 (1997); "Operational procedures for the use of digital selective-calling equipment in the maritime mobile service".
- [5] ETS 300 225; "Radio Equipment and Systems (RES); Technical characteristics and methods of measurement for survival craft portable VHF radiotelephone apparatus".
- [6] ITU-T Recommendation P.53 (1994); "Psophometer for use on telephone-type circuits".
- [7] ITU-R Recommendation SM 332-4; "Selectivity of receivers".
- [8] ETR 028; "Radio Equipment and Systems (RES); Uncertainties in the measurement of mobile radio equipment characteristics".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the following definitions apply:

integral antenna: antenna that is permanently fixed to the equipment and not detachable by the user.

detachable antenna: antenna fixed to the equipment by means of an antenna connector and detachable by the user.

G3E: phase-modulation (frequency modulation with a pre-emphasis of 6 dB/octave) for speech.

modulation index: ratio between the frequency deviation and the modulation frequency.

performance check: check of:

- the transmitter carrier power and frequency; and
- receiver sensitivity.

3.2 Symbols

For the purposes of the present document, the following symbols apply:

dBA
emf

Relative to 2×10^{-5} Pa
Electromotive force

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:
https://standards.iteh.ai/catalog/standards/sist_en_301-178-000-fbf76bd22eba/sist-en-301-178-2000

DSC
EUT
GMDSS
rms
SINAD
VHF

Digital Selective Calling
Equipment Under Test
Global Maritime Distress and Safety System
root mean square
(Signal + Noise + Distortion)/(Noise + Distortion)
Very High Frequency

4 General and operational requirements

4.1 Construction

The manufacturer shall declare that compliance to the requirements of clause 4 is achieved and shall provide relevant documentation.

The mechanical and electrical construction and finish of the equipment shall conform in all respects to good engineering practice, and the equipment shall be suitable for use on board ships.

All controls shall be of sufficient size to enable the usual control functions to be easily performed and the number of controls should be the minimum necessary for simple and satisfactory operation.

All parts of the equipment to be checked during inspection or maintenance operations shall be readily accessible. The components shall be readily identifiable.

Technical documentation shall be supplied with the equipment.

The VHF maritime mobile service uses both single-frequency and two-frequency channels. For two-frequency channels there shall be a separation of 4,6 MHz between the transmitting frequency and the receiving frequency (see Radio Regulations Appendix 18 [1]).

The equipment, which can consist of more than one unit, shall be capable of operating on single frequency and two-frequency channels with manual control (simplex).

The equipment shall be of a colour which distinguishes it from the portable VHF equipment specified in ETS 300 225 [5].

The equipment shall be able to operate on all channels defined in Radio Regulations, Appendix 18 [1].

Operation on channels 75 and 76 shall be restricted to a maximum transmitted power of 1W.

Additional VHF channels outside those defined by Radio Regulations, Appendix 18 [1] may also be provided, but means shall be provided to block any channel, including Appendix 18 channels.

It shall not be possible for the user to unblock or block any channels.

Scan or multiple watch may be provided but means shall be provided to block or unblock these functions.

If the equipment is fitted with an auxiliary antenna connector, simultaneous connection of both the auxiliary antenna and the normal antenna shall be prevented.

The equipment shall be so designed that use of channel 70 for purposes other than Digital Selective Calling (DSC) is prevented (see ITU-R Recommendation M.493-9 [3] and ITU-R Recommendation M.541-8 [4]).

It shall not be possible to transmit while any frequency synthesizer used within the transmitter is out of lock.

THE STANDARD PREVIEW
(standards.iteh.ai)

4.2 Controls and indicators

https://standards.iteh.ai/catalog/standards/sist/1ab6a2ce-fc5e-44f6-a355-1570022ca03a_2007-05-01

The equipment shall have a channel selector and shall indicate the designator, as shown in Radio Regulations, Appendix 18 [1], of the channel at which the equipment is set. The channel designator shall be legible irrespective of the external lighting conditions.

Where an input panel on the equipment for entering the digits 0 to 9 is provided, this shall conform to ITU-T Recommendation E.161 [2].

The equipment shall have the following additional controls and indicators:

- on/off switch for the equipment with a visual indication that the equipment is in operation;
- a manual, non-locking push to talk switch to operate the transmitter;
- a switch for reducing transmitter output power to no more than 1 W where the RF output power is more than 1 watt;
- an audio frequency power volume control;
- a squelch control;
- a visual indication that the transmitter is activated.

The equipment shall also meet the following requirements:

- the user shall not have access to any control which, if wrongly set, might impair the technical characteristics of the equipment.

4.3 Microphone and loudspeaker

The equipment shall be fitted with an integral microphone and an integral loudspeaker.

During transmission the receiver output shall be muted.

4.4 Safety precautions

Measures shall be taken to protect the equipment against the effects of overcurrent or overvoltage.

Measures shall be taken to prevent damage to the equipment that might arise from an accidental reversal of polarity of the electrical power source.

No damage to the equipment shall occur when the antenna terminals are placed on open circuit or short circuit while transmitting for a period of at least 5 minutes in each case.

In order to provide protection against damage due to the build up of static voltages at the antenna terminals, there shall be a dc path from the antenna terminals to chassis not exceeding 100 kΩ.

The information in any volatile memory device shall be protected from interruptions in the power supply of up to 60 s duration.

4.5 Labelling

All controls, instruments, indicators and terminals shall be clearly labelled.

iTeh STANDARD PREVIEW

Details of any external power supply from which the equipment is intended to operate shall be clearly indicated on the equipment.
(standards.iteh.ai)

The equipment shall be clearly and indelibly marked on the exterior with the identification of the manufacturer, type designation of the equipment, the serial number of the unit and the text: "Not intended for distress and safety purposes".

<https://standards.iteh.ai/catalog/standards/sist/1ab6a2ce-fc5e-44f6-a355->

The compass safe distance shall be stated on the equipment.

5 Technical requirements

5.1 Switching time

The channel switching arrangement shall be such that the time necessary to change over from using one of the channels to using any other channel does not exceed 5 s.

The time necessary to change over from transmission to reception or vice versa, shall not exceed 0,3 s.

5.2 Class of emission and modulation characteristics

The equipment shall use phase modulation, G3E (frequency modulation with a pre-emphasis of 6 dB/octave) for speech.

The equipment shall be designed to operate satisfactorily with a channel separation of 25 kHz.

The frequency deviation corresponding to 100 % modulation shall be ± 5 kHz as nearly as practicable.