







THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2014 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office 3, rue de Varembé CH-1211 Geneva 20	Tel.: +41 22 919 02 11 Fax: +41 22 919 03 00 info@iec.ch	
Switzerland	www.iec.ch	

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications, Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in 14 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

More than 55,000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

2349:201

https://standards.iteh.av



Edition 2.0 2014-02



CONTENTS

FO	REWORD	4
1	Scope and object	6
2	Normative references	6
3	Terms and definitions	6
4	Testing conditions	7
5	5 Guidance for dimensional characteristics measurement of polarization-maintaining optical fibres	
	5.1 Object	7
	5.2 Overview of method	7
	5.3 Reference test method	8
6	Guidance for cut-off wavelength measurement of polarization-maintaining optical	o
	libles	0
	6.1 Object	ð
7	6.2 Overview of method	0
'	fibres	8
	7.1 Object	8
	7.2 Overview of method	8
8	Guidance for beat length measurement of polarization-maintaining optical fibres	9
	8.1 Object	9
	8.2 Overview of methods	9
	8.3 Reference test method	9
	8.4 Specimen	9
	8.5 ds in Beat length measuring method	.4.9.92014
	8.5.1 Method A: Phase beat length measurement method	9
	8.5.2 Method B: Group beat length measurement method	12
	0.0 Results	12
	8.6.2 Information available upon request	12
9	Guidance for polarization crosstalk measurement of polarization-maintaining	
	optical fibres	13
	9.1 Object	13
	9.2 Polarization crosstalk measuring method	13
	9.2.1 General	13
	9.2.2 Method A: Power ratio method	13
_	9.2.3 Method B: In-line polarimetric method	15
Anr	nex A (informative) Cut-off wavelength of PM fibre and SM fibre – Profiles and bend dependence of cut-off wavelength	17
Anr	nex B (informative) Difference of beat length by measurement method	19
	B.1 Modal birefringence and beat length	19
	B.2 Beat length defined by Method B	19
Anr	nex C (informative) Electromagnet for Faraday rotation	22
Bib	liography	23

https://standards.iteh.a

Figure 1 – Apparatus of beat length measurement – Method A	10
Figure 2 – Example of measurement profile by electro magnet	11
Figure 3 – Example of test apparatus for polarization crosstalk measurement (power ratio method)	14
Figure 4a – Front view of data arc and fitted circle	16
Figure 4b – 90° – Rotated cutaway view defining the geometrical relationships	16
Figure 4 – Poincaré sphere representations for Method B	16
Figure A. 1 – Cut-off wavelength profiles of PM fibre and SM fibre	17
Figure A. 2 – Cut-off wavelength profile of PM fibre with extra bending	17
Figure C. 1 – A schematic of the electromagnet	22

iteh.ai)

68-91ab-4ec9-91e4-16dbf9aa2858/iec-tr-62349-2014

eview

INTERNATIONAL ELECTROTECHNICAL COMMISSION

GUIDANCE OF MEASUREMENT METHODS AND TEST PROCEDURES – BASIC TESTS FOR POLARIZATION-MAINTAINING OPTICAL FIBRES

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, [Fechnical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.

7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or

- other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
 - 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
 - 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a technical report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

IEC/TR 62349, which is a technical report, has been prepared by subcommittee 86A: Fibres and cables, of IEC technical committee 86: Fibre optics.

This second edition cancels and replaces the first edition published in 2005. It constitutes a technical revision.

In this edition, guidance of measurement methods and test procedures for dimensional characteristics, cut-off wavelength, mode field diameter and beat length of polarization-maintaining optical fibres have been added. Thus, the title of the technical report is changed to "Guidance of measurement methods and test procedures – Basic tests for polarization-maintaining optical fibres" from "Guidance for polarization crosstalk measurement of optical fibre".

The text of this technical report is based on the following documents:

Enquiry draft	Report on voting
86A/1488/DTR	86A/1507/RVC

Full information on the voting for the approval of this technical report can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The "colour inside" logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print-this publication using a colour printer.

3-91ab-4ec9-91e4-16dbf9aa2858/iec-tr-62349-2014

GUIDANCE OF MEASUREMENT METHODS AND TEST PROCEDURES – BASIC TESTS FOR POLARIZATION-MAINTAINING OPTICAL FIBRES

1 Scope and object

This technical report applies to polarization-maintaining (PM) optical fibres.

The object of this report is to define test procedures to be used in establishing uniform requirements for the geometrical and transmission properties of PM fibres.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60068-1, Environmental testing – Part 1: General and guidance

IEC 60793-1-20:2001, Optical fibres – Part 1-20: Measurement methods and test procedures – Fibre geometry

IEC 60793-1-44, Optical fibres – Part 1-44: Measurement methods and test procedures – Cutoff wavelength

IEC 60793-1-45:2001, Optical fibres – Part 1-45: Measurement methods and test procedures – Mode field diameter

IEC 60793-1-48, Optical fibres – Part 1-48: Measurement methods and test procedures – Polarization mode dispersion

3 Terms and definitions

For the purposes of this document, the following ters and definitions apply.

NOTE IEC 60793-1-1[1]¹ provides general definitions for testing.

3.1

polarization-maintaining optical fibre

PM fibre

optical fibre capable of transmitting, under external perturbations such as bending or lateral pressure, both independently of or either of the polarization modes HE_{11}^{X} and HE_{11}^{Y} whose directions of electric field vector intersect orthogonally with each other and which have different propagation constants

¹ Numbers in square brackets refer to the bibliography.

3.2

phase beat length

one cycle of the periodical coupled polarization state by the phase difference of two linearpolarization modes intersecting orthogonally in the PM fibre

Note 1 to entry: Small beat length results in high polarization maintaining capability

3.3

group beat length

one cycle of the periodical coupled polarization state by the group delay difference of two linear-polarization modes intersecting orthogonally in the PM fibre

Note 1 to entry: Small beat length results in high polarization maintaining capability.

3.4

polarization crosstalk

strength of coupling of the two polarization modes intersecting orthogonally with each other within a polarization-maintaining optical fibre, representing the ratio in optical strength exiting the fibre of one polarization mode launched at the input end to the optical power of the other polarization mode exiting the fibre when only the former polarization mode is excited (see also 9.2.2.4.2)

4 Testing conditions

Unless otherwise specified, the test is conducted under the standard conditions specified in IEC 60068-1. However, when it is difficult to make measurements in the standard conditions, the test can be conducted in conditions other than the standard conditions provided that no doubts will arise about judgments.

5 Guidance for dimensional characteristics measurement of polarizationmaintaining optical fibres

htp 5.1 Object

Clause 5 describes measurement methods and test procedures for the dimensional characteristics of uncoated PM optical fibres.

5.2 Overview of method

This technical report gives measurement methods for dimensional characteristics of PM fibre which are given in terms of the following parameters:

- cladding diameter;
- cladding non-circularity;
- core concentricity error.

Two methods are described for measuring dimensional characteristics of PM fibre:

- Method A: Refracted near-field;
- Method B: Grey-scale technique of near-field light distribution.

Information pertaining to each individual method is given in Annexes A and C of IEC 60793-1-20:2001. Only notes for PM fibre are described below.

For a general optical fibre, a circle-fitting is used to determine the core centre. However, as for the PM fibre, in particular the elliptical core PM fibre, the core centre cannot be determined if an ellipse-fitting is not used, because the fibre has an oval core.

5.3 Reference test method

Method B is the reference test method (RTM), which is the one used to settle disputes.

6 Guidance for cut-off wavelength measurement of polarization-maintaining optical fibres

6.1 Object

Clause 6 describes a measurement method and a test procedure for the cut-off wavelength, $\lambda_{\rm c}$ of PM fibres.

6.2 Overview of method

The measurement method in this technical report describes procedures for determining the cut-off wavelength of a sample fibre in a short length, uncabled and primary coated condition (λ_c) .

Information pertaining to each individual method is given in IEC 60793-1-44. Only notes for PM fibre are described below.

As shown in Annex A, the cut-off wavelength of the PM fibre is measured paying attention to excite a LP_{11} mode sufficiently and not to impose an extra, small bending more carefully than the cut-off wavelength measurement of a single-mode (SM) optical fibre.

The recommended deployment configuration of the sample fibre is as defined for the fibre cutoff wavelength in IEC 60793-1-44.

7 Guidance for mode field diameter measurement of polarization-maintaining optical fibres

7.1 Object

Clause 7 describes measurement methods and test procedures for the mode field diameter (MFD) of PM fibres.

7.2 Overview of method

Three methods are described for measuring the MFD of the PM fibre:

- Method A: direct far-field scan;
- Method B: variable aperture in the far field;
- Method C: near-field scan.

Information pertaining to each individual method is given in Annexes A, B and C of IEC 60793-1-45:2001. Only notes for PM fibre are described below.

The MFD of the PM fibre is non-axisymmetric in principle. The MFD is measured in the same directions by rotating the fibre around the axis properly. The azimuthal dependence of the MFD of a stress induced PM fibre and an elliptical sheath PM fibre are relatively small. On the other hand, the azimuthal dependence of the MFD of an elliptical core PM fibre is relatively large. The MFD of a stress induced fibre and an elliptical sheath PM fibre may be measured without rotating the fibre complying with the demand of a required accuracy of the customer depending on the measurement method.