

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Fibre optic interconnecting devices and passive components – Performance standard –

Part 042-2: Plug-pigtail-style and plug-receptacle-style OTDR reflecting devices for category C – Controlled environments

[IEC 61753-042-2:2014](#)

<https://standards.iteh.ai/catalog/standards/sist/50979b47-ad4c-48da-aba1->

Dispositifs d'interconnexion et composants passifs à fibres optiques – Norme de performance –

Partie 042-2: Dispositifs de réflexion pour OTDR de modèle à fiche-fibre amorce et modèle à fiche-embase pour catégorie C – Environnements contrôlés



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2014 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in 14 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

More than 55 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Catalogue IEC - webstore.iec.ch/catalogue

Application autonome pour consulter tous les renseignements bibliographiques sur les Normes internationales, Spécifications techniques, Rapports techniques et autres documents de l'IEC. Disponible pour PC, Mac OS, tablettes Android et iPad.

Recherche de publications IEC - www.iec.ch/searchpub

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études,...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire en ligne de termes électroniques et électriques. Il contient plus de 30 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans 14 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Glossaire IEC - std.iec.ch/glossary

Plus de 55 000 entrées terminologiques électrotechniques, en anglais et en français, extraites des articles Termes et Définitions des publications IEC parues depuis 2002. Plus certaines entrées antérieures extraites des publications des CE 37, 77, 86 et CISPR de l'IEC.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: csc@iec.ch.



INTERNATIONAL STANDARD

NORME INTERNATIONALE

**Fibre optic interconnecting devices and passive components – Performance standard –
Part 042-2: Plug-pigtail-style and plug-receptacle-style OTDR reflecting devices for category C – Controlled environments**

<https://standards.iteh.ai/catalog/standards/sist/50979b47-ad4c-48da-aba1-5111b3c09125/iec-61753-042-2>

**Dispositifs d'interconnexion et composants passifs à fibres optiques – Norme de performance –
Partie 042-2: Dispositifs de réflexion pour OTDR de modèle à fiche-fibre amorce et modèle à fiche-embase pour catégorie C – Environnements contrôlés**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

PRICE CODE
CODE PRIX



ICS 33.180.20

ISBN 978-2-8322-1788-7

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

CONTENTS

FOREWORD.....	3
1 Scope.....	5
2 Normative references.....	5
3 Terms, definitions and abbreviations	6
3.1 Terms and definitions	6
3.2 Abbreviations	6
4 Test	7
5 Test report.....	7
6 Reference components	7
7 Performance requirements.....	7
7.1 Dimensions	7
7.2 Sample size	7
7.3 Test details and requirements.....	7
Annex A (normative) Sample size.....	14
Annex B (informative) General information of OTDR reflecting devices	15
Bibliography	16
Figure B.1 – Examples of structure of OTDR reflecting device	15
Figure B.2 – Picture of OTDR reflecting device.....	15
Table 1 – Test details and requirements for plug-pigtail style (1 of 4)	7
Table 2 – Test details and requirements for plug-receptacle style (1 of 3)	11
Table A.1 – Number of plug-pigtail style samples for each test.....	14
Table A.2 – Number of plug-receptacle style samples for each test.....	14

ITeCh STANDARD PREVIEW
(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/50979b47-ad4c-48da-aba1-031b73aab654/iec-61753-042-2-2014>

INTERNATIONAL ELECTROTECHNICAL COMMISSION

—————

**FIBRE OPTIC INTERCONNECTING DEVICES AND
PASSIVE COMPONENTS – PERFORMANCE STANDARD –**

**Part 042-2: Plug-pigtail-style and plug-receptacle-style
OTDR reflecting devices for category C –
Controlled environments**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user. standards.iteh.ai
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter. <http://standards.iteh.ai/>
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61753-042-2 has been prepared by subcommittee 86B: Fibre optic interconnecting devices and passive components of IEC technical committee 86: Fibre optics.

The text of this standard is based on the following documents:

CDV	Report on voting
86B/3709/CDV	86B/3785/RVC

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of IEC 61753 series, under the general title *Fibre optic interconnecting devices and passive components performance standards*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

iTeh STANDARD PREVIEW **(standards.iteh.ai)**

[IEC 61753-042-2:2014](#)

<https://standards.iteh.ai/catalog/standards/sist/50979b47-ad4c-48da-aba1-031b73aab654/iec-61753-042-2-2014>

FIBRE OPTIC INTERCONNECTING DEVICES AND PASSIVE COMPONENTS – PERFORMANCE STANDARD –

Part 042-2: Plug-pigtail-style and plug-receptacle-style OTDR reflecting devices for category C – Controlled environments

1 Scope

This part of IEC 61753 contains the minimum initial performance, test and measurement requirements and severities which plug-pigtail style and plug-receptacle style OTDR reflecting devices need to satisfy in order to be categorized as meeting the requirements of category C- Controlled environments, as defined in Annex A of IEC 61753-1:2007 [1]¹. They are for out-of-band OTDR testing of an optical fibre system.

Annex B of this standard provides information concerning this device.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

<https://standards.iteh.ai/catalog/standards/sist/50979b47-ad4c-48da-aba1-071b73c1b554/iec-61753-042-2-2014>
IEC 60793-2-50, *Optical fibres – Part 2-50: Product specifications – Sectional specification for class B single-mode fibres*

IEC 61300 (all parts), *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures*

IEC 61300-1, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 1: General and guidance*

IEC 61300-2-1, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-1: Tests – Vibration (sinusoidal)*

IEC 61300-2-4, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-4: Tests–Fibre/cable retention*

IEC 61300-2-9, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-9: Tests –Shock*

IEC 61300-2-14, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-14: Tests – High optical power*

IEC 61300-2-17, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-17: Tests – Cold*

¹ Numbers in square brackets refer to the Bibliography.

IEC 61300-2-18, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-18: Tests – Dry heat – High temperature endurance*

IEC 61300-2-19, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-19: Tests – Damp heat (steady state)*

IEC 61300-2-22, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-22: Tests – Change of temperature*

IEC 61300-2-42, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-42: Tests – Static side load for connectors*

IEC 61300-2-44, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-44: Tests – Flexing of the strain relief of fibre optic devices*

IEC 61300-3-2, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-2: Examination and measurements – Polarization dependent loss in a single-mode fibre optic device*

IEC 61300-3-7, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-7: Examinations and measurements – Wavelength dependence of attenuation and return loss of single mode components*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

3 Terms, definitions and abbreviations

For the purposes of this document, the following terms and definitions apply.

3.1 Terms and definitions

3.1.1

OTDR reflecting device

optical filter having two ports that light from the signal wavelength ranges transmits from the first port to the second port and OTDR light from the OTDR wavelength range launched into one port is (partly) reflected back to that launch port

Note 1 to entry: It is used for out of band testing of optical fibre systems.

3.2 Abbreviations

FBG	Fibre Bragg grating
PDL	Polarisation dependent loss
ONU	Optical network unit
OTDR	Optical time-domain reflectometer
TFF	Thin-film filtre

4 Test

Unless otherwise specified, all test methods are in accordance with the IEC 61300 series. Each test defines the number of samples to be evaluated. The samples used for each test are intended to be previously unstressed new samples but may also be selected from previously used samples if desired. The plug-pigtail style samples shall be terminated onto single-mode fibres as per IEC 60793-2-50 category B1.1, B1.3 or B6 in either coated fibres (primary and secondary) or reinforced cable format. For plug-receptacle style samples fibres as per IEC 60793-2-50 category B1.1, B1.3 or B6 shall be used. All measurements shall be carried out at standard atmosphere condition defined in IEC 61300-1, unless otherwise stated.

All tests shall be carried out over the operating wavelength range: the signal wavelength ranges of 1 260 nm to 1 360 nm, 1 480 nm to 1 500 nm and 1 550 nm to 1 560 nm, and the OTDR wavelength of 1 620 nm to 1 630 nm or 1 645 nm to 1 655 nm, unless otherwise specified.

NOTE 1 310 nm, 1 490 nm and 1 550 nm are the nominal or centre wavelengths, stated for the ranges 1 260 nm to 1 360 nm, 1 480 nm to 1 500 nm and 1 550 nm to 1 560 nm as defined in ITU-T Recommendations G.983.3 [2], G.984.2 [3] and IEEE standard 802.3ah-2004 [4].

5 Test report

Fully documented test reports and supporting evidences shall be prepared and be available for inspections as evidence that the tests have been carried out and complied with.

iTeh STANDARD PREVIEW

6 Reference components (standards.iteh.ai)

The test for these components does not require the use of reference components.

<https://standards.iteh.ai/catalog/standards/sist/50979b47-ad4c-48da-aba1-031b73aab654/iec-61753-042-2-2014>

7 Performance requirements

7.1 Dimensions

Dimensions shall comply with either an appropriate IEC interface standard or with those given in appropriate manufacturers drawings, where the IEC interface standard does not exist or cannot be used.

7.2 Sample size

Sample sizes for the test are defined in Annex A.

7.3 Test details and requirements

Test details and requirements are shown in Table 1 for plug-pigtail style and Table 2 for plug-receptacle style.

Table 1 – Test details and requirements for plug-pigtail style (1 of 4)

No	Tests	Requirements	Details	
1	Attenuation (Insertion loss) IEC 61300-3-7	<p>≤1,0 dB (Class A)</p> <p>≤1,5 dB (Class B)</p> <p>Insertion loss shall include connector loss.</p> <p>Insertion loss shall be met over the passband</p>	<p>Launch fibre length:</p> <p>Polarization state of light source:</p> <p>Measurement uncertainty:</p>	<p>≥2,0 m</p> <p>Unpolarized</p> <p>±0,1 dB</p>

Table 1 (2 of 4)

No	Tests	Requirements	Details	
2	Wavelength Isolation IEC 61300-3-7	<p>≥20 dB (Class A) ≥40 dB (Class B)</p> <p>Wavelength isolation between passband wavelength range and reflection-band wavelength range</p>	<p>Launch fibre length:</p> <p>Polarization state of light source:</p> <p>Measurement uncertainty:</p>	<p>≥2,0 m</p> <p>Unpolarized</p> <p>±1 dB</p>
3	Return loss IEC 61300-3-7	<p>Grade S1: ≥22 dB for signal wavelength range(s) for both input and output ports and ≤12 dB for OTDR wavelength range for input port only.</p> <p>Grade S2: ≥22 dB for operating signal range(s) for both input and output ports and ≤1,5 dB for OTDR wavelength range for input port only.</p> <p>Grade T1: ≥35 dB for signal wavelength range(s) for both input and output ports and ≤5 dB for OTDR wavelength range for input port only.</p> <p>Grade T2: ≥35 dB for signal wavelength range(s) for both input and output ports and ≤1,0 dB for OTDR wavelength range for input port only</p>	<p>Polarization state of light source:</p> <p>Measurement uncertainty:</p> <p>Measurement uncertainty:</p>	<p>≥2,0 m</p> <p>Unpolarized</p> <p>±0,05 dB for RL <1,0 dB ±0,2 dB for RL <1,5 dB ±0,5 dB for RL <5 dB ±1 dB for RL ≥5 dB</p>
4	Polarisation dependent loss (PDL) IEC 61300-3-2	<p>≤0,5 dB</p> <p>Polarisation dependent loss shall be met over the passband wavelength range</p>	<p>Launch fibre length:</p> <p>Measurement uncertainty:</p>	<p>≥2,0 m</p> <p>±0,05 dB</p>
5	High optical power IEC 61300-2-14	<p>Before and after the test, the limits of insertion loss, isolation and return loss of test No. 1, 2 and 3 shall be met.</p> <p>During the test, the insertion loss change is monitored. During and after the test, the insertion loss change shall be within ±0,3 dB of the initial value.</p> <p>During the test, the wavelength isolation change is monitored. The sum of the initial value and the change of the isolation shall be within the value defined at test No. 2.</p> <p>During the test, the return loss change is monitored. The sum of the initial value and the change of the return loss shall be within the value defined at test No. 3</p>	<p>Optical power:</p> <p>Wavelength:</p> <p>Duration of the optical power exposure:</p> <p>Temperature:</p> <p>Relative humidity:</p> <p>Measurement uncertainty:</p>	<p>300 mW</p> <p>1 550 nm 1 650 nm</p> <p>30 min for each wavelength</p> <p>60 °C ± 2° C</p> <p>(93⁺²₋₃) % RH</p> <p>±0,1 dB for insertion loss measurement) ±0,05 dB for RL <1,0 dB ±0,2 dB for RL <1,5 dB ±0,5 dB for RL <5 dB ±1 dB for RL ≥5 dB</p>

Table 1 (3 of 4)

No	Tests	Requirements	Details	
6	Cold IEC 61300-2-17	Before and after the test, the limits of insertion loss, isolation and return loss of test No.1, 2 and 3 shall be met. The insertion loss change after the test shall be within $\pm 0,3$ dB of the initial value	Temperature: Duration of exposure:	$-10^{\circ}\text{C} \pm 2^{\circ}\text{C}$ 96 h
7	High temperature endurance IEC 61300-2-18	Before and after the test, the limits of insertion loss, isolation and return loss of test no.1, 2 and 3 shall be met. The insertion loss change after the test shall be within $\pm 0,3$ dB of the initial value	Temperature: Duration of exposure:	$+60^{\circ}\text{C} \pm 2^{\circ}\text{C}$ 96 h
8	Damp heat (steady state) IEC 61300-2-19	Before and after the test, the limits of insertion loss, isolation and return loss of test No.1, 2 and 3 shall be met. During and after the test, the insertion loss change is monitored. The insertion loss change shall be within $\pm 0,3$ dB of the initial value. During the test, the isolation change is monitored. The sum of the initial value and the change of the Isolation shall be within the value defined at test no.2	Temperature: Relative humidity: Duration of exposure:	$+40^{\circ}\text{C} \pm 2^{\circ}\text{C}$ $(93^{+2}_{-3})\% \text{ RH}$ 96 h
9	Change of temperature IEC 61300-2-22	Before and after the test, the limits of insertion loss, isolation and return loss of test No.1, 2 and 3 shall be met. During and after the test, the insertion loss change is monitored. The insertion loss change shall be within $\pm 0,3$ dB of the initial value. During the test, the isolation change is monitored. The sum of the initial value and the change of the Isolation shall be within the value defined at test No.2	High temperature: Low temperature: Number of cycles: Duration at extreme temperature: Rate of change:	$+60^{\circ}\text{C} \pm 2^{\circ}\text{C}$ $-10^{\circ}\text{C} \pm 2^{\circ}\text{C}$ 5 cycles 60 min $1^{\circ}\text{C}/\text{min}$
10	Vibration IEC 61300-2-1	Before and after the test, the limits of insertion loss, isolation and return loss of test No.1, 2 and 3 shall be met. The insertion loss change after the test shall be within $\pm 0,3$ dB of the initial value	Frequency range: Number of axes: Number of sweeps: Sweep rate: Amplitude:	10 Hz – 55 Hz 3 orthogonal axes 15 /axis 1 octave./min 0,75 mm
11	Optical fibre cable flexing IEC 61300-2-44	Before and after the test, the limits of insertion loss, isolation and return loss of test no.1, 2 and 3 shall be met. The insertion loss change after the test shall be within $\pm 0,3$ dB of the initial value	Tensile force: Number of cycles:	2 N for reinforced cable 30 cycles, $\pm 90^{\circ}$

Table 1 (4 of 4)

No	Tests	Requirements	Details	
12	Fibre/cable retention IEC 61300-2-4	Before and after the test, the limits of insertion loss, isolation and return loss of test No.1, 2 and 3 shall be met. The insertion loss change after the test shall be within $\pm 0,3$ dB of the initial value	Magnitude and rate of application: Duration of the test: Point of application of tensile load: Method of mounting:	(10 ± 1) N at 5 N/s for reinforced cables $(5,0 \pm 0,5)$ N at 0,5 N/s for secondary coated fibres $(2,0 \pm 0,2)$ N at 0,5 N/s for primary coated fibres 120 s duration at 10 N 60 s duration at 2 N or 5 N 0,3 m from the exit point of the fibre/cable from the specimen. The sample shall be rigidly mounted such that the load is only applied to the fibre/cable retention mechanism
13	Static side load IEC 61300-2-42	Before and after the test, the limits of insertion loss, isolation and return loss of test No.1, 2 and 3 shall be met. The insertion loss change after the test shall be within $\pm 0,3$ dB of the initial value	Magnitude and duration of the tensile load: Direction of application:	1 N for 1 h for reinforced cable 0,2 N for 5 min for secondary coated fibres Two mutually perpendicular directions
14	Shock IEC 61300-2-9	Before and after the test, the limits of insertion loss, isolation and return loss of test No.1, 2 and 3 shall be met. The insertion loss change after the test shall be within $\pm 0,3$ dB of the initial value	Acceleration: Duration: Number of axis: Number of shocks:	Components: $5\ 000\ \text{m/s}^2$ 1 ms, half sine pulse 3 axes in 2 directions 2 shocks per axis, 12 shock in total

Table 2 – Test details and requirements for plug-receptacle style (1 of 3)

No	Tests	Requirements	Details	
1	Attenuation (Insertion loss) IEC 61300-3-7	<p>≤1,0 dB (Class A)</p> <p>≤1,5 dB (Class B)</p> <p>Insertion loss shall include connector loss.</p> <p>Insertion loss shall be met over the passband wavelength range</p>	<p>Launch fibre length:</p> <p>Polarization state of light source:</p> <p>Measurement uncertainty:</p>	<p>≥2,0 m</p> <p>Unpolarized</p> <p>±0,1 dB</p>
2	Wavelength isolation IEC 61300-3-7	<p>≥20 dB (Class A)</p> <p>≥40 dB (Class B)</p> <p>Wavelength isolation between passband wavelength range and reflection-band wavelength range</p>	<p>Launch fibre length:</p> <p>Polarization state of light source:</p> <p>Measurement uncertainty:</p>	<p>≥2,0 m</p> <p>Unpolarized</p> <p>±1 dB</p>
3	Return loss IEC 61300-3-7	<p>Grade S1: ≥22 dB for signal wavelength range(s) for both input and output ports and ≤12 dB for OTDR wavelength range for input port only.</p> <p>Grade S2: ≥22 dB for operating signal range(s) for both input and output ports and ≤1,5 dB for OTDR wavelength range for input port only.</p> <p>Grade T1: ≥35 dB for signal wavelength range(s) for both input and output ports and ≤5 dB for OTDR wavelength range for input port only.</p> <p>Grade T2: ≥35 dB for signal wavelength range(s) for both input and output ports and ≤1,0 dB for OTDR wavelength range for input port only</p>	<p>Launch fibre length:</p> <p>Polarization state of light source:</p> <p>Measurement uncertainty:</p>	<p>≥2,0 m</p> <p>Unpolarized</p> <p>±0,05 dB for RL < 1,0 dB</p> <p>±0,2 dB for RL < 1,5 dB</p> <p>±0,5 dB for RL < 5 dB</p> <p>±1 dB for RL ≥ 5 dB</p>
4	Polarization dependent loss (PDL) IEC 61300-3-2	<p>≤0,5 dB</p> <p>Polarisation dependent loss shall be met over the passband wavelength range</p>	<p>Launch fibre length:</p> <p>Measurement uncertainty:</p>	<p>≥2,0 m</p> <p>±0,05 dB</p>