

Edition 3.0 2015-03

INTERNATIONAL STANDARD





THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2015 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office Tel.: +41 22 919 02 11 3, rue de Varembé Fax: +41 22 919 03 00

CH-1211 Geneva 20 info@iec.ch Switzerland www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in 15 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary -std.iec.ch/glossary

More than 60 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

06:2015

nttps://standards.iteh.\//iki\//standard\/iec\17956a2-bcc0-47c0-b959-3e5a59413b85/iec-62106-201



Edition 3.0 2015-03

INTERNATIONAL STANDARD

Specification of the radio data system (RDS) for VHF/FM sound broadcasting in the frequency range from 87,5 MHz to 108,0 MHz



INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 33.160.40 ISBN 978-2-8322-2544-8

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

F	OREWO	RD	9
IN	ITRODU	CTION	11
1	Scop	e	12
2	Norm	ative references	12
3	Abbr	eviations	12
4	Modu	llation characteristics of the data channel (physical layer)	13
	4.1	General	
	4.2	Subcarrier frequency	
	4.3	Subcarrier phase.	15
	4.4	Subcarrier level	15
	4.5	Method of modulation	
	4.6	Clock-frequency and data-rate	15
	4.7	Differential coding	16
	4.8	Data-channel spectrum shaping.	16
5	Base	band coding (data-link layer)	
	5.1	Baseband coding structure	19
	5.2	Order of bit transmission	20
	5.3	Error protection	21
	5.4	Synchronisation of blocks and groups	21
6	Mess	age format (session and presentation layers)	22
	6.1	Addressing	22
	6.1.1	Design principles	22
	6.1.2	Principal features	22
	6.1.3		
	6.1.4	is iteh Nizita Noistar Vard Viec XII /Yaha /Lhocil-4 icil-hyay-keaaay4 Ikhxa/iec-h/	25
	6.1.5	Coding of the group types.	27
	6.2	Coding of information	
	6.2.1		
	6.2.2	. \ \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	
	6.23		
	6.2.4	, ,	
	6.2.5	,	
	6.2.6		
	6.2.7	8 8 7	
_	6.2.8		
7		ription of features	
	7.1	Alternative frequencies list (AF)	
	7.2	Clock Time and date (CT)	
	7.3	Decoder Identification (DI) and dynamic PTY Indicator (PTYI)	
	7.4	Extended Country Code (ECC)	
	7.5	Enhanced Other Networks information (EON)	
	7.6	Emergency Warning System (EWS)	
	7.7	In House application (IH)	
	7.8	Music Speech switch (MS)	
	7.9 7.10	Open Data Applications (ODA)	58 58
	7 111	PLOGRAMMA INDUITIONING IPI)	n×

	Programme Item Number (PIN)	
7.12	Programme Service name (PS)	59
7.13	Programme Type (PTY)	59
7.14	Programme Type Name (PTYN)	59
7.15	Radio Paging (RP)	59
7.16	RadioText (RT)	59
7.17	Enhanced RadioText (eRT)	59
7.18	RadioText Plus (RT+)	60
7.19	Traffic Announcement identification (TA)	60
7.20	Transparent Data Channels (TDC)	60
7.21	Traffic Message Channel (TMC)	60
7.22	Traffic Programme identification (TP)	60
8 Mark		60
	normative) Offset words to be used for group and block synchronisation	,62
	informative) Theory and implementation of the modified shortened cyclic	
		63
	General	
B.2	Encoding procedure	
B.2.1	Theory	63
B.2.2		65
	Decoding procedure	65
B.3.1		
B.3.2	ihttng.//stanco.do.itah ail	67
_	informative) Implementation of group and block synchronisation using the	
modified s	shortened cyclic code	69
C.1	Theory	69
C.1.1		
ps://sta C .1.2		
	Shift register arrangement for deriving group and block synchronisation	
0.2	information	69
Annex D (normative) Programme identification codes and extended country codes	72
D.1	General	
_	Pl structure	
	Extended country codes	
	Country codes: 'Nibble 1'	
	Programme in terms of area coverage (codes for fixed location transmitters	
2.0	only): 'Nibble 2'	76
D.6	Programme reference number: 'Nibbles 3 and 4'	76
D.7	PI codes for low-power short range transmitting devices	77
	normative) Basic and extended RDS character sets	
Annex F (normative) Programme type codes	98
•	informative) Conversion between time and date conventions	
Annex H (informative) ARI (Autofahrer-Rundfunk-Information) system –	
	uation	
Annex J (ı	normative) Language identification	104
Annex K (informative) RDS logo	106
Annex L (i	informative) Open data registration	107
•	(normative) Coding of Radio Paging (RP)	110

M.1	General	110
M.2	Basic paging protocol	110
M.2.	1 Coding characteristics for paging	110
M.2.	2 Transmitter network group designation	111
M.2.	3 Locking to a channel	113
M.2.	4 Loss of synchronization	113
M.2.	5 Group type 7A message format	113
M.3	Enhanced paging	119
M.3.		
M.3.		
M.3.		126
M.3.	4 Battery saving mode	126
M.3.		\
M.3.		138
M.4	Examples of the traffic handling capacity of the specified radio paging	139
Annov N	system	
	pean Broadcasting Area	142
N.1	African Broadcasting Area	142
N.2	Allocations of symbols for countries in ITN Region 2	
N.3	Allocations of symbols for countries in ITU Region 3	146
	(normative) Coding of RadioText Plus information (RT+)	
P.1		
P.2	General Definitions	148
P.3	RT+ tag	
P.4	RT+ information elements and data model	
P.4.		
P.4.2	/ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	
P.4.3	us.item.a\\a\\c\a\stan\anus\ite\-\\anus\ite\-\\anus\ite\-\\and\anus\ite\-\\anu\anu\anu\ite\-\\anu\anu\anu\anu\anu\anu\anu\anu\anu\an	
P.4.4		
P.5	Coding RT+in QDA groups	
P.5.		
P.54	\wedge \setminus \setminus \setminus	
P.5.3		
P.5.4		
P.6	Broadcasting conventions	159
P.7	Receiving conventions	159
P.8	Marking	160
Annex Q	(normative) Coding of enhanced RadioText (eRT)	161
Q.1	General	161
Q.2	Coding eRT in ODA groups	161
Q.2.	1 General	161
Q.2.	eRT identification (Group type 3A)	161
Q.2.	3 Coding of the eRT text string	162
Q.3	Broadcasting conventions	164
Q.4	Receiving conventions	165
Q.5	Marking	165
Annex R	(informative) RBDS in the USA	166
Annex S	(normative) List of RDS specific abbreviations	167

Bibliography	168
Figure 1 – Block diagram of radio-data equipment at the transmitter	14
Figure 2 – Block diagram of a typical radio-data receiver/decoder	15
Figure 3 – Amplitude response of the specified transmitter or receiver data-shaping filter 17	
Figure 4 – Amplitude response of the combined transmitter and receiver data-shapir filters	
Figure 5 – Spectrum of biphase coded radio-data signals	18
Figure 6 – Time-function of a single biphase symbol	19
Figure 7 – 57 kHz radio-data signals	19
Figure 8 – Structure of the baseband coding	
	20
Figure 10 – ODA version A groups	26
Figure 11 – ODA version B groups	27
Figure 12 – Basic tuning and switching information – Type 8A group	27
Figure 13 – Basic tuning and switching information – Type 0B group	27
Figure 14 – Programme item number and slow labelling codes – Type 1A group	
Figure 15 – Programme Item Number - Type 1B group	30
Figure 16 – RadioText – Type 2A group	30
Figure 17 – RadioText – Type 2B group	31
Figure 18 – Application identification for open data – Type 3A group	
Figure 19 – Open data – Type 38 group	33
Figure 20 - Clock-time and date transmission - Type 4A group	
Figure 21 – Open data – Type 4B group	
Figure 22 – Transparent data channels – Type 5A group	35
Figure 23 – Transparent data channels – Type 5B group	
Figure 24 – In-house applications – Type 6A and 6B group	
Figure 25 Radio paging – Type 7A group	
Figure 26 – Type 78 group	37
Figure 27 – Traffic message channel – Type 8A group	
Figure 28 – Open data – Type 8B group	
Figure 29 – Allocation of EWS message bits – Type 9A group	38
Figure 30 – Open data – Type 9B group	
Figure 31 – Programme type name PTYN – Type 10A group	39
Figure 32 – Open data – Type 10B group	39
Figure 33 – Open data – Type 11A and 11B groups	
Figure 34 – Open data – Type 12A and 12B groups	
Figure 35 – Enhanced paging information – Type 13A group	
Figure 36 – Open data – Type 13B group	
Figure 37 – Enhanced other networks information – Type 14A groups	
Figure 38 – Enhanced Other Networks information – Type 14B groups	
Figure 39 – Open data – Type 15A group	
Figure 40 – Fast basic tuning and switching information – Type 15B group	

Figure 41 – Structure of Block 3 of Type 1A groups	52
Figure 42 – Structure of variant 12 of block 3 of type 14A groups (linkage information) – National link	53
Figure 43 – Structure of variant 12 of block 3 of type 14A groups (linkage information) – International link	53
Figure 44 – Structure of Variant 7 of Block 3 of type 1A groups for Identification of a programme carrying EWS information	56
Figure B.1 – Generator matrix of the basic shortened cyclic code in binary notation	64
Figure B.2 – Shift-register implementation of the encoder	65
Figure B.3 – Parity-check matrix of the basic shortened cyclic code	
Figure B.4 – Shift-register implementation of the decoder	67
Figure C.1 – Group and block synchronisation detection circuit	
Figure D.1 – PI structure	
Figure D.2 – Structure of Variant 0 of Block 3 of type 1A groups (ECC)	73
Figure D.3 – European Broadcasting Area – Correspondence between geographical locations and the symbols used	74
Figure G.1 – Conversion routes between Modified Julian Date (MJD) and Coordinated Universal Time (UTC)	101
Figure J.1 – Language identification code allocation	104
Figure M.1 – Group type 7A message format for radio paging	113
Figure M.2 – Group type 7A paging without an additional message	114
Figure M.3 – Group type 7A paging with an additional 10 digit message	115
Figure M.4 – Group type 7A paging with an additional 18 digit message	115
Figure M.5 – Group type 7A paging with an additional alphanumeric message	116
Figure M.6 – Group type 74 paging with an additional international 15 digit message	
Figure M.7 – Functions message in international paging	118
Figure M.8 – Variant 0 of 1A group with PIN	120
Figure M.9 – Variant 2 of 1A group with PIN	121
Figure M.10 - Variants of 1A group without PIN	122
Figure M.11 – Group type 13A	
Figure M.12 – Group type A paging with tone-only message	130
Figure M.13 – First 7A group of a variable-length message	131
Figure M.14 – Group type 7A national paging with additional alphanumeric message	132
Figure M.15 – Group type 7A national paging with additional variable-length numeric message	134
Figure M.16 – Group type 7A national paging with additional variable-length functions message	135
Figure M.17 – The two first 7A groups of an international alphanumeric message	136
Figure M.18 – The two first 7A groups of an international variable-length numeric message	137
Figure M.19 – The two first 7A groups of an international variable-length functions message	137
Figure M.20 – Traffic handling capacity, busy hour, call rate = 0,10 calls/pager/hour	140
Figure M.21 – Traffic handling capacity, busy hour, call rate = 0,067 calls/pager/hour	141
Figure M.22 – Traffic handling capacity, busy hour, call rate = 0,05 calls/pager/hour	141

Figure P.1 – RT+ information of the category 'Item' (see Table P.2) will be attached to the programme elements Item 1 and Item 2	153
Figure P.2 – RT+ information of the category 'Item' will be attached to the programme elements Item 1 and Item 2, but not to the programme element News	153
Figure P.3 – RT+ information of the category 'Item' will be attached only to the programme element Item 1, but not to the programme element Talk	
Figure P.4 – Bit allocation for group 3A (message bits and AID)	
Figure P.5 – Coding of the message bits of the application group	
Figure Q.1 – Bit allocation for group 3A (message bits and AID)	
Figure Q.2 – Coding of the message bits of the application group	163
3. 1. d. 3. 1. d. 1.	
Table 1 – Encoding rules	16
Table 2 – Decoding rules	16
Table 3 – Group types	23
Table 4 – Main feature repetition rates	24
Table 5 – Group repetition rates	25
Table 6 – ODA group availability signalled in type 3A groups	26
Table 7 – STY codes	41
Table 8 – Codes for TP and TA	45
Table 9 – Bit d ₀ to d ₃ meanings	45
Table 10 – VHF code table	46
Table 11 – Special meanings code table	46
Table 12 – Code tables according to ITU regions; LE/MF code table – For ITU regions 1 and 3 (9 kHz spacing)	46
Table 13 – Code tables according to ITU regions; MF code table – For ITU region 2 (10 kHz spacing)	47
Table A.1 – Offset word codes	62
Table B.1 – Offset word syndromes using matrix of Figure B.3	67
Table C.1 – Offset word syndromes for group and block synchronisation	71
Table D.1 - Pl code structure	72
Table D.2 - European Broadcasting Area - Symbols used for ECC and PI country codes	75
Table D.3 – Area coverage codes	76
Table D.4 – Programme reference number codes	76
Table D.5 – PI codes for short range transmitting devices	77
Table E.1 – Basic RDS character set	
Table E.2 – Non-transmitted UCS-2 equivalents (1 of 7)	79
Table E.3 – Extended RDS character set, for eRT only (1 of 13)	85
Table F.1 – Programme type codes and corresponding terms for display	98
Table G.1 – Symbols used	101
Table J.1 – Language identification codes	104
Table M.1 – Pager group codes	111
Table M.2 – Codes for additional message content	114
Table M.3 – Paging segment address codes for 10 and 18 digit messages	115
Table M.A. Paging segment address codes for alphanumeric messages	116

Table M.5 – Paging segment address codes for international 15 digit messages	117
Table M.6 – Paging segment address codes for functions message	118
Table M.7 – Sub-usage codes	122
Table M.8 – Group designation codes	126
Table M.9 – Cycle selection codes	127
Table M.10 – Message sorting codes	128
Table M.11 – Codes for message types	130
Table M.12 – Description of the control byte	131
Table M.13 – Use of paging call repetition flag	132
Table M.14 – Paging segment address codes for alphanumeric message	133
Table M.15 – Paging segment address codes for variable length numeric message:	134
Table M.16 – Paging segment address codes for national paging with variable length functions message	135
Table M.17 – Address notification (50 bit)	138
Table M.18 – Address notification (25 bit)	139
Table M.19 – Z3 parity relationship	139
Table P.1 – RT+ information elements	148
Table P.2 - Code list and 'RT+ class' description of 'RT/eRT content types (1 of 3)	157
Table Q.1 – eRT information elements	161

(https://scanolydy.iteh.ai)

5 206:2015

https://standards.iteh.&/zatzi/v/stanlard&iec/V7956a2-bcc0-47c0-b959-3e5a59413b85/iec-62106-2015

INTERNATIONAL ELECTROTECHNICAL COMMISSION

SPECIFICATION OF THE RADIO DATA SYSTEM (RDS) FOR VHF/FM SOUND BROADCASTING IN THE FREQUENCY RANGE FROM 87,5 MHz TO 108,0 MHz

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62106 has been prepared by technical area 1: Terminals for audio, video and data services and contents, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

This third edition cancels and replaces the second edition, published in 2009 and constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- for the RDS feature EON and the use of group types 14A and 14B some additional explanations were added;
- in Annex E, containing the character code tables to be used in RDS, the explanation for Table E.1 and Table E.2 was extended;
- several small typing errors were corrected;
- to Enhanced RadioText in Annex Q an additional explanation was added.

The text of this standard is based on the following documents:

CDV	Report on voting
100/2122A/CDV	100/2418/RVC

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.1

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later plate.

(https://standards.iteh.ai)
Decument Preview

https://standards.iteh.ai/arcylice (1/956a2-bce0-47c0-b959-3e5a59413b85/iec-62106-2013

¹ For technical reasons equations and some figures had to be left unchanged and are not in accordance with the ISO/IEC Directives, Part 2:2011.

INTRODUCTION

IEC 62106:2000 (first edition) and IEC 62106:2009 (second edition) have the same main text and annex structure. However, the main text of this edition is slightly restructured to more closely conform to ISO/IEC Directives, Part 2:2011. Nevertheless, cross-referencing between this edition and the previous editions remains possible. To find the corresponding subclause quickly between this edition and the first edition, it is basically sufficient to subtract 3 clauses. Example: see 3.1.5.1 in the first edition, published in 2000 becomes, see 6.1.5.1.



SPECIFICATION OF THE RADIO DATA SYSTEM (RDS) FOR VHF/FM SOUND BROADCASTING IN THE FREQUENCY RANGE FROM 87,5 MHz TO 108,0 MHz

1 Scope

This International Standard describes the Radio Data System, RDS, intended for application to VHF/FM sound broadcasts in the range 87,5 MHz to 108,0 MHz which may carry either stereophonic (pilot-tone system) or monophonic programmes (as stated in ITU-R Recommendation BS 450-3 and ITU-R Recommendation BS.643-3). The main objectives of RDS are to enable improved functionality for FM receivers and to make them more user-friendly by using features such as Programme Identification, Programme Service name display and, where applicable, automatic tuning for portable and can radios in particular. The relevant basic tuning and switching information therefore has to be implemented by the type 0 group (see 6.1.5.1), and it is not optional unlike many of the other possible features in RDS.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 10646:2014, Information technology - Universal Coded Character Set (UCS)

ISO 14819 (all parts), Intelligent transport systems – Traffic and travel information messages via traffic message coding

ITU-R Recommendation BS 450-3, Transmission standards for FM sound broadcasting at VHF

ITU-R Recommendation BS.643-3, Radio data system for automatic tuning and other applications in FM radio receivers for use with pilot-tone system

ITU-T Recommendation E.212, For the three digit Mobile Country Codes used in Annex M of this RDS specification refer to Complement to ITU-T Rec. E.212 (05/2004) published by ITU Geneva as Annex to ITU Operational Bulletin 897, dated 2007-12-01

US NRSC-4-B, National Radio Systems Committee – NRSC-4-A: United States RBDS standard

ETSI EN 301 700, Digital Audio Broadcasting (DAB); VHF/FM broadcasting: cross referencing to simulcast DAB services by RDS-ODA 147

3 Abbreviations

For the purposes of this document, the following abbreviations apply.

3.1

AM

<broadcasting> amplitude modulation