



Edition 2.0 2015-01 REDLINE VERSION

INTERNATIONAL STANDARD



Explosive atmospheres – Part 10-2: Classification of areas – Explosive dust atmospheres

Document Preview

IEC 60079-10-2:2015





THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2015 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office 3, rue de Varembé CH-1211 Geneva 20 Switzerland Tel.: +41 22 919 02 11 info@iec.ch www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing 21 000 terms and definitions in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

<u>IEC 60079-10-2:2015</u>





Edition 2.0 2015-01 REDLINE VERSION

INTERNATIONAL STANDARD



Explosive atmospheres – Standards Part 10-2: Classification of areas – Explosive dust atmospheres

Document Preview

IEC 60079-10-2:201

https://standards.iteh.ai/catalog/standards/iec/60636f20-3db4-481c-ae1c-636cd2f74b6b/iec-60079-10-2-2015

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 29.260.20

ISBN 978-2-8322-2213-3

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

	FC	DREWC	PD	4
	IN	TRODU	JCTION	2
	1	Scop	ю	8
	2	Norn	native references	8
	3	Term	is and definitions	
	4	Area	classification	12
	•	л 1	General	12
		4.2	Area classification procedure for explosive dust atmospheres	13
1		4.3	Competence of personnel	10
	5	Sour	ces of release	
	•	5 1	General	14
		5.2	Dust containment	15
		5.3	Identification and grading of sources of release	
	6	Zone	S	
		6.1	General	
1		6.2	Zones	15
		6.3	Extent of zones	16
		6.3.1	General	
		6.3.2	Zone 20	
		6.3.3	Zone 21	
		6.3.4	Zone 22	17
	7	Dust	layers	18
	8	Docu	Imentation	18
		8.1	<u>IEC 60079-10-2:2015</u> General	
		8.2	Drawings, data sheets and tables	
		8.2.1	Content of documents	19
		8.2.2	Preferred Symbol key for area classification zones	20
	Ar	inex A	(informative) Area classification-application examples	21
1		A.1	Examples of zones	21
		A.1.′	General	21
		A.1.2	2 Zone 20	21
		A.1.3	3 Zone 21	21
		A.1.4	Zone 22	21
		A.2	Bag emptying station within a building and without exhaust ventilation	22
		A.3	Bag emptying station with exhaust ventilation	23
		A.4	Cyclone and filter with clean outlet outside building	24
		A.4 A.5	Cyclone and filter with clean outlet outside building Drum tipper within a building without exhaust ventilation	24 25
	Ar	A.4 A.5 Inex B	Cyclone and filter with clean outlet outside building Drum tipper within a building without exhaust ventilation (informative) Risk of fire from hot surface ignition of dust layer	24 25
	<mark>Ar</mark> Ar	A.4 A.5 I <mark>INEX B</mark>	Cyclone and filter with clean outlet outside building Drum tipper within a building without exhaust ventilation (informative) Risk of fire from hot surface ignition of dust layer (informative) Housekeeping	24 25
	<mark>Ar</mark> Ar	A.4 A.5 Inex B Inex B B.1	Cyclone and filter with clean outlet outside building Drum tipper within a building without exhaust ventilation (informative) Risk of fire from hot surface ignition of dust layer (informative) Housekeeping Introductory remarks	24 25 28 28
	<mark>Ar</mark> Ar	A.4 A.5 Inex B Inex B B.1 B.2	Cyclone and filter with clean outlet outside building Drum tipper within a building without exhaust ventilation (informative) Risk of fire from hot surface ignition of dust layer (informative) Housekeeping Introductory remarks Levels of housekeeping	
	Ar Ar Ar	A.4 A.5 Inex B Inex B B.1 B.2 Inex D Compa	Cyclone and filter with clean outlet outside building Drum tipper within a building without exhaust ventilation	24 25 28 28 28 28

IEC 60079-10-2:2015 RLV © IEC 2015 - 3 -

C.1	General	30	
C.2	Ventilation	35	
C.3	Explosive limits	35	
C.4	Chemical reactions	35	
C.5	Minimum ignition parameters	35	
C.6	Final classification	35	
Bibliography			

Figure 1 – Identification of zones on drawings	.20
Figure A.1 – Bag emptying station within a building and without exhaust ventilation	.23
Figure A.2 – Bag emptying station with exhaust ventilation	.24
Figure A.3 – Cyclone and filter with clean outlet outside building	.25
Figure A.4 – Drum tipper within a building without exhaust ventilation	.26

Table 1 – Designation of zones depending on presence of dust 17						
Table D.1 Traditional relationship of EPLs to zones (no additional risk assessment)						
Table D.2 Description of risk of ignition protection provided						

iTeh Standards (https://standards.iteh.ai) Document Preview

IEC 60079-10-2:2015

INTERNATIONAL ELECTROTECHNICAL COMMISSION

EXPLOSIVE ATMOSPHERES –

Part 10-2: Classification of areas – Explosive dust atmospheres

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.

6) All users should ensure that they have the latest edition of this publication.

- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This redline version of the official IEC Standard allows the user to identify the changes made to the previous edition. A vertical bar appears in the margin wherever a change has been made. Additions are in green text, deletions are in strikethrough red text.

International Standard IEC 60079-10-2 has been prepared by subcommittee 31J: Classification of hazardous areas and istallation requirements, of IEC technical committee 31: Equipment for explosive atmospheres.

This second edition of IEC 60079-10-2 cancels and replaces the first edition of IEC 60079-10-2 published in 2009. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

		Туре			
Explanation of the significance of the changes	Clause	Minor and editorial changes	Extension	Major technical changes	
Definition of "atmospheric conditions" deleted	3	Х			
Definition of "combustible dust" aligned with other documents per recommendations of WG 28	3.4	х			
Editorial change to definition of "explosive dust atmosphere" to delete mention of flyings, since the definition of dust according to 60079-10-2 includes flyings.	3.5	х			
Definition of "combustible flyings" aligned with other documents per recommendations of WG 28	3.8	х			
Definition of "continuous formation of a dust cloud" added	3.14	Х			
Definition of "catastrophic failure" added	3.20	x			
Definition of "ignition temperature of a dust layer" aligned with other documents per recommendations of WG 28 and to change reference from 61241-2-1 to 80079-20-2	3.22	elx.ai			
Definitions of "zone 20, zone 21 and zone 22" added.	3.25.1	ew			
the document.	3.25.2	Х			
IEC 60070-10	3.25.3				
Dust cloud density and concentration added as factors to consider for a release	4-48 4.1 -ae1	c-636cd2f	4b6lXiec-6	0079-10-2	-201
Wording changed to require EPL to be noted on area classification drawing	4.1		х		
Notes 1 and 3 changed to normative text	4.1		Х		
Reference to published sources for dust characteristics deleted	4.2	х			
Reference to 80079-20-2 added	4.2 a)		Х		
Section on competence of personnel added	4.3		Х		
Note on verification dossier deleted	5.2	Х			
Example added for continuous grade of release, zone information moved to Clause 6	5.3	х			
Paragraph added about dust layers being raised into a cloud	7		х		
EPLs added to list for documentation, note added warning of variability in published dust data	8.1		х		
Symbol keys are identified as preferred	8.2	Х			
Note added to zone 21 and zone 22 clause about distance around source of release	Annex A	х			
Zone 22 paragraph added to this example, and figure modified to show Zone 22 location	A.2	Х			
Annex B on hot surfaces deleted	Annex B in previous edition	х			

				Туре		
Explanation of the significance of the changes		Clause	Minor and editorial changes	Extension	Major technical changes	
Annex D on explanation of EPLs deleted		Annex D in previous edition	х			
Annex on hybrid mixtures added		Annex C	Х			
Explanation of the types	ofs	ignificant cha	inges:			
 Minor and editorial changes: These are changes which modify requirements in an edit 	nor and editorial changes: nor and editorial changes: are changes which modify requirements in an editorial or a minor technical way. They include changes of				changes of	
the wording to clarify technical requirements without any requirement.	tecr	inical change	, or a reduction	on in the level	of existing	
2. Extension:	-	Addition of t	echnical option	ons		
These are changes which add new or modify existing technical requirements, in a way that new options are given, but without increasing the requirements that are fully compliant with the previous standard. Therefore, these will not have to be considered for existing area classifications in conformity with the preceding edition.						
3. Major technical changes: – Addition of technical requirements – Increase of technical requirements						
These are changes to technical requirements (addition, increase of the level or removal) made in a way that an existing area classification in conformity with the preceding edition will not always be able to fulfil the requirements given in the later edition. These changes have to be considered for existing area classifications in conformity with the preceding edition.						

The text of this standard is based on the following documents:

FDISEC 60079	Report on voting	
31J/244/FDIS	31J/248/RVD 3600	f74b6b/iec-60079-10-2-2015

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 60079 series, under the general title *Explosive atmospheres*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The "colour inside" logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this publication using a colour printer.

IEC 60079-10-2:2015 RLV © IEC 2015 - 7 -

INTRODUCTION

Dusts, as defined in this standard, are hazardous because when they are dispersed in air by any means they may form potentially explosive atmospheres. Furthermore, layers of dust may ignite and act as ignition sources for an explosive atmosphere.

This part of IEC 60079 gives guidance on the identification and classification of areas where such hazards from dust can arise. It sets out the essential criteria against which the ignition hazards can be assessed and gives guidance on the design and control parameters which can be used in order to reduce such a hazard. General and special criteria are given, with examples, for the procedure used to identify and classify areas process of identification and classification of hazardous areas.

This standard contains an informative Annex A giving practical examples for classifying areas.

iTeh Standards (https://standards.iteh.ai) Document Preview

IEC 60079-10-2:2015

EXPLOSIVE ATMOSPHERES –

Part 10-2: Classification of areas – Combustible Explosive dust atmospheres

1 Scope

This part of IEC 60079 is concerned with the identification and classification of areas where explosive dust atmospheres and combustible dust layers are present, in order to permit the proper assessment of ignition sources in such areas.

In this standard, explosive dust atmospheres and combustible dust layers are treated separately. In Clause 4, area classification for explosive dusts clouds is described, with dust layers acting as one of the possible sources of release. In Clause 7, the hazard of other general considerations for dust layers ignition are described.

The examples in this standard are based on a system of effective housekeeping being implemented in the plant to prevent dust layers from accumulating. Where effective housekeeping is not present, the area classification includes the possible formation of explosive dust clouds from dust layers.

The principles of this standard can also be followed when combustible fibres or flyings-may might cause a hazard.

This standard is intended to be applied where there can be a risk due to the presence of explosive dust atmospheres or combustible dust layers under normal atmospheric conditions (see Note 1).

IEC 60079-10-2:2015

NOTE 1 Atmospheric conditions include variations in pressure and temperature above and below reference levels 2015 of 101,3 kPa (1 013 mbar) and 20 °C (293 K), provided that the variations have a negligible effect on the explosive properties of the combustible materials.

It does not apply to

- underground mining areas,
- areas where a risk can arise due to the presence of hybrid mixtures,
- dusts of explosives that do not require atmospheric oxygen for combustion, or to such as pyrophoric substances, propellants, pyrotechnics, munitions, peroxides, oxidizers, waterreactive elements or compounds, or other similar materials,
- catastrophic failures which are beyond the concept of abnormality dealt with in this standard (see Note 1),
- any risk arising from an emission of flammable or toxic gas from the dust.

This standard does not apply to where a hazard might arise due to the presence of flammable gas or vapour, but the principles may be used in the assessment of a hybrid mixture (see also IEC 60079-10-1).

NOTE 2 Additional guidance on hybrid mixtures is provided in Annex C.

This standard does not take into account the effects of consequential damage following a fire or an explosion.

NOTE 1 Catastrophic failure in this context is applied, for example, to the rupture of a storage silo or a pneumatic conveyor.

IEC 60079-10-2:2015 RLV © IEC 2015 - 9 -

NOTE 2 In any process plant, irrespective of size, there can be numerous sources of ignition apart from those associated with equipment. Appropriate precautions will be necessary to ensure safety in this context, but these are outside the scope of this standard.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60079-0, Explosive atmospheres – Part 0: Equipment – General requirements

IEC 60079-10-1, *Explosive atmospheres – Part 10-1: Classification of areas – Explosive gas atmospheres*

ISO/IEC 80079-20-2, *Explosive Atmospheres – Part 20-2: Material Characteristics – Combustible dusts test methods*¹

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60079-0 and the following apply.

NOTE Additional definitions applicable to explosive atmospheres can be found in IEC 60050-426.

(IIII) (IIII) (IIII) (IIII)

3.1 area

three-dimensional region or space

<u>3.2</u>

EC 60079-10-2:2015

tps:/**atmospheric_conditions**andards/iec/60636f20-3db4-481c-ae1c-636cd2f74b6b/iec-60079-10-2-2015 (surrounding_conditions)

conditions that include variations in pressure and temperature above and below reference levels of 101,3 kPa (1 013 mbar) and 20 °C (293 K), provided that the variations have a negligible effect on the explosive properties of the combustible dust

3.2

hybrid mixture

mixture of a flammable-substances in different physical states, gas or vapour with air a dust

NOTE An example of a hybrid mixture is a mixture of methane, coal dust and air.

3.3

dust

generic term including both combustible dust and combustible flyings

3.4

combustible dust

finely divided solid particles, 500 μ m or less in nominal size, which may be suspended in air, may settle out of the atmosphere under their own weight, can burn or glow in air, and may form an explosive mixture with air at atmospheric pressure and normal temperatures

Note 1 to entry: This-definition may also includes dust and grit as defined in ISO 4225.

¹ To be published.

Note 2 to entry: The term solid particles is intended to address particles in the solid phase and not the gaseous or liquid phase, but does not preclude a hollow particle.

Note 3 to entry: Materials passing a U.S. No. 40 Standard sieve as defined in ASTM E 11–04 are considered to meet the 500 μ m criterion.

Note 4 to entry: Combustible dust test methods can be found in ISO/IEC 80079-20-2.

3.5

explosive dust atmosphere

mixture with air, under atmospheric conditions, of flammable substances in the form of dust, or flyings in which, after ignition, permits self-sustaining-flame propagation

3.6

conductive dust

combustible dust with electrical resistivity equal to or less than $10^3 \Omega m$

Note 1 to entry: Conductive dust is classified as Group IIIC.

3.7

non-conductive dust

combustible dust with electrical resistivity greater than $10^3 \Omega m$

Note 1 to entry: Non-conductive dust is classified as Group IIIB.

3.8

combustible flyings

solid particles including fibers, greater than 500 μ m in nominal size, which may be suspended in air, may settle out of the atmosphere under their own weight, can burn or glow in air, and may form an explosive mixture with air at atmospheric pressure and normal temperatures

Note 1 to entry: Examples of fibres and flyings include rayon, cotton (including cotton linters and cotton waste) sisal, jute, hemp, cocoa fiber, okum and baled waste kapok.

Note 2 to entry: Combustible flyings are classified as Group IIIA.

https://gigndards.iteh.ai/catalog/standards/iec/60636f20-3db4-481c-ae1c-636cd2f74b6b/iec-60079-10-2-2015

hazardous area (dust)

area in which combustible dust, in the form of a cloud is present, or may be expected to be present, in quantities such as to require special precautions for the construction, installation and use of equipment

Note 1 to entry: Hazardous areas are divided into zones based upon the frequency and duration of the occurrence of explosive dust atmospheres (see 6.2 and 6.3).

Note 2 to entry: The potential of creating an explosive dust cloud from a dust layer also needs to be considered.

3.10

non-hazardous area (dust)

area in which combustible dust in the form of a cloud is not expected to be present in quantities such as to require special precautions for the construction, installation and use of equipment

3.11

dust containment

process equipment housing which is intended to handle, process, transport or store materials inside of it, while <u>preventing</u> minimizing the risk of the release of <u>combustible</u> dust to the surrounding atmosphere

3.12

source of dust release

point or location from which-combustible dust-can may be released into the atmosphere

IEC 60079-10-2:2015 RLV © IEC 2015 - 11 -

Note 1 to entry: The source of dust release can be from a dust containment or from a dust layer.

3.13

continuous grade of release

release which is continuous or is expected to occur frequently or for long periods

3.14

continuous formation of a dust cloud

locations in which a dust cloud may exist continuously, or may be expected to continue for long periods or for short periods which occur frequently

3.15

primary grade of release

release which can be expected to occur periodically or occasionally during normal operation

3.16

secondary grade of release

release which is not expected to occur in normal operation and, if it does occur, is likely to do so only infrequently and for short periods

3.17

extent of zone

distance in any direction from the edge of a source of release to the point where the hazard associated with the release is considered to exist no longer

3.18

normal operation

operation of equipment conforming electrically and mechanically with its design specification and used within the limits specified by the manufacturer

Note 1 to entry: Minor releases of dust which may form a cloud or layer (e.g. releases from filters) can be part of normal operation. EC 60079-10-2:2015

https:/3.19dards.iteh.ai/catalog/standards/iec/60636f20-3db4-481c-ae1c-636cd2f74b6b/iec-60079-10-2-2015 abnormal operation

process-linked malfunctions that occur infrequently

3.20

catastrophic failure

occurrence which exceeds the design parameters of the process plant and control system resulting in major release of flammable material

Note 1 to entry: Catastrophic failure in this context is applied, for example, to the rupture of a storage silo or a pneumatic conveyor.

3.21

equipment (for explosive atmospheres)

general term including apparatus, fittings, devices, components, and the like used as a part of, or in connection with, an electrical installation in an explosive atmosphere

3.22

ignition temperature of a dust layer

lowest temperature of a hot surface at which ignition occurs in a dust layer of specified thickness on the hot surface

Note 1 to entry: The ignition temperature of a dust layer may be determined by the test method given in IEC 61241-2-1 ISO/IEC 80079-20-2.

3.23

ignition temperature of a dust cloud

lowest temperature of the hot inner wall of a furnace at which ignition occurs in a dust cloud in air contained therein

Note 1 to entry: The ignition temperature of a dust cloud may be determined by the test method given in IEC 61241-2-1 ISO/IEC 80079-20-2.

3.24

verification dossier

set of documents showing the compliance of electrical equipment and installations

Note 1 to entry: Requirements for a 'verification dossier' are given in IEC 60079-14.

3.25

zones

3.25.1

Zone 20

a place in which an explosive dust atmosphere, in the form of a cloud of dust in air, is present continuously, or for long periods or frequently

3.25.2

Zone 21

a place in which an explosive dust atmosphere, in the form of a cloud of dust in air, is likely to occur in normal operation occasionally **Standards**

3.25.3

Zone 22

area in which an explosive dust atmosphere, in the form of a cloud of combustible dust in air, is not likely to occur in normal operation but, if it does occur, will persist for a short period only

Note 1 to entry: The potential of creating an explosive dust cloud from a dust layer also needs to be considered.

s://standards.iteh.ai/catalog/standards/iec/60636f20-3db4-481c-ae1c-636cd2f74b6b/iec-60079-10-2-2015 4 Area classification

4.1 General

This standard adopts the concept, similar to that used for flammable gases and vapour, of using area classification to give an assessment of the likelihood of an explosive dust atmosphere occurring.

Dusts form explosive atmospheres only at concentrations within the explosion range. Although a cloud with a very high concentration may not be explosive, the danger nevertheless exists that, should the concentration fall, it may enter the <u>explosion</u> explosive range. Depending on the circumstances, not every source of release will necessarily produce an explosive dust atmosphere. Dust clouds are also rarely of uniform density and consideration should be given to possible variances in concentration within a cloud for any condition or release.

Dusts that are not removed by mechanical extraction or ventilation, settle out at a rate depending on properties, such as particle size, into layers or accumulations. It shall be taken into account that a dilute or small continuous source of release, in time, is able to produce a potentially hazardous dust layer.

The hazards presented by dusts are as follows:

 the formation of a dust cloud from any source of release, including a layer or accumulation, to form an explosive dust atmosphere (see Clause 5);