



Edition 4.1 2019-01 CONSOLIDATED VERSION

# INTERNATIONAL STANDARD





# THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2019 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office Tel.: +41 22 919 02 11

3, rue de Varembé info@iec.ch CH-1211 Geneva 20 www.iec.ch Switzerland

#### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies

#### **About IEC publications**

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

#### IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

#### IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Aublished details all new publications released. Available online and once a month by email.

#### IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

#### Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEW) online.

#### IEC Glossary - std.iec.ch/glossary

67 000 electrotechnical terminology entries in English and French extracted from the Terms and definitions clause of IEC publications issued between 2002 and 2015. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

#### A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

#### A propos des publications IEC

Le content technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

## Recherche de publications IEC - webstore.iec.ch/advsearch/orm

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études,...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

#### IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et une fois par mois par email.

#### Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: sales@iec.ch.

#### Electropedia - www.electropedia.org

Le premier dictionnaire d'électrotechnologie en ligne au monde, avec plus de 22 000 articles terminologiques en anglais et en français, ainsi que les termes équivalents dans 16 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

#### Glossaire IEC - std.iec.ch/glossary


67 000 entrées terminologiques électrotechniques, en anglais et en français, extraites des articles Termes et définitions des publications IEC parues entre 2002 et 2015. Plus certaines entrées antérieures extraites des publications des CE 37, 77, 86 et CISPR de l'IEC.



Edition 4.1 2019-01 CONSOLIDATED VERSION

# INTERNATIONAL STANDARD

NORME INTERNATIONALE



Thermal-links - Requirements and application guide

Protecteurs thermiques – Exigences et guide d'application



INTERNATIONAL ELECTROTECHNICAL COMMISSION

COMMISSION ELECTROTECHNIQUE INTERNATIONALE

ICS 29.120.50 ISBN 978-2-8322-8954-9

Warning! Make sure that you obtained this publication from an authorized distributor.

Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.





Edition 4.1 2019-01 CONSOLIDATED VERSION

# **REDLINE VERSION**



## **-2-**

## CONTENTS

FC	DREWO	PRD	4
IN	TRODU	JCTION	6
1	Scop	pe	7
2	•	native references	
3		ns and definitions	
4		eral requirements	
5	General notes on tests		
		sification	
6			
	6.1	Electrical conditions	
	6.2	Thermal conditions.	
7	6.3	Resistance to trackinging	
7			
8	Docu	umentation	
9		structional requirements	15
	9.1	General	15
	9.2	Lead secureness tests  General	16
	9.2.1		16
	9.2.2	Tensile test	16
	9.2.3		1/
	9.2.4	Contacts used for the current path	1/
	9.3	Accessible mounting brackets or metal parts	18
	9.4 9.5	Accessible mounting brackets of metal parts	10
	9.6	Insulating materials	10
	9.7	Creepage distances and clearances	18
	9.8	Temperature and humidity cycle conditioning	
	9.9	Terminals and terminations	
10		trical requirements	
		Dielectric strength	
	10.2	Insulation resistance	
	10.3	Interrupting current	
	10.3.		
	10.3.	2 Specific conditions	21
	10.4	Transient overload current	
	10.5	Limited short-circuit test	23
	10.5.	1 General	23
	10.5.	2 Test method	23
	10.5.	3 Fuse size (rating)	23
	10.5.	4 Compliance	24
11	Temp	perature tests	24
	11.1	General	24
	11.2	Holding temperature, $T_{h}$	24
	11.3	Rated functioning temperature, $T_{f}$	25
	11.4	Maximum temperature limit, $T_{m}$	25

11.5 Ageing	25		
12 Resistance to rusting	26		
13 Manufacturer's validation programme	26		
Annex A (normative) Application guide	28		
Annex B (normative) Alternative ageing test for thermal-links with $T_{\mbox{\scriptsize h}}$ greater than 250 °C for use in electric irons	29		
Annex C (normative) Conductive heat ageing test	30		
C.1 Conductive heat ageing test	30		
C.2 Method	30		
C.3 Ageing			
C.4 Results	32		
C.5 Dielectric strength test			
C.6 Test oven			
	34		
D.1 Extended holding temperature conditioning test	_		
D.2 Load current interrupt test			
Annex E (normative) Seal ageing test			
Annex F (normative) Identification requirements			
Annex G (normative) Indelibility of markings			
Annex H (normative) Requirements for thermal-link packaged assemblies			
Bibliography	43		
(Interest States and Augustus Items and Interest and Inte			
Figure 1 – Bending/twist test	17		
Figure C.1 – Typical test fixture assembly	32		
Figure C.2 – Typical thermal-link test oven	33		
Figure D.1 – Typical terminal block support test fixture	35		
Figure E.1 – Conditioning time versus oven temperature for proposed temperature index	37		
Figure G.1 – Apparatus for testing durability of markings			
rigure G. 1 – Appearatus for testing durability of markings	59		
Table 1 Test schedule	13		
Table 2 – Strength of leads and terminal parts – Minimum required tensile and thrust			
test forces	17		
Table 3 – Creepage distances and clearances (absolute minimum values)	19		
Table 4 – Test voltages for dielectric strength	20		
Table 5 – Test current for interrupting test	21		
Table 6 – Limited short-circuit test capacity			
Table H.1 – Push and pull force			
Table H.2 – Minimum nominal cross-sectional area of conductor			

#### INTERNATIONAL ELECTROTECHNICAL COMMISSION

## THERMAL-LINKS – REQUIREMENTS AND APPLICATION GUIDE

#### **FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as hearty as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC of its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of the official IEC Standard and its amendment has been prepared for user convenience.

IEC 60691 edition 4.1 contains the fourth edition (2015-10) [documents 32C/512/FDIS and 32C/515/RVD] and its corrigendum (2016-08), and its amendment 1 (2019-01) [documents 32C/548/FDIS and 32C/559/RVD].

In this Redline version, a vertical line in the margin shows where the technical content is modified by amendment 1. Additions are in green text, deletions are in strikethrough red text. A separate Final version with all changes accepted is available in this publication.

International Standard IEC 60691 has been prepared by subcommittee 32C: Miniature fuses, of IEC technical committee 32: Fuses.

This fourth edition constitutes a technical revision.

This fourth edition includes the following significant technical changes with respect to the previous edition:

- a) requirements for thermal-link packaged assemblies;
- b) renew the requirements and definitions for  $T_h$ -test;
- c) change starting temperature for interrupt current test;
- d) clarify requirements for marking (packing label);
- e) minimum Proof Tracking Index 175 instead 120.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The basis for this standard is the harmonization of the USA national standard, UL 1020, fifth

edition (withdrawn 2003), and IEC 60691:1993, together with its Amendment 1:1995 and Amendment 2:2000.

The following differing practices of a less permanent hature exist in the country indicated below:

- Annex C is required to be declared in the USA;
- Annex E is required in the USA, if applicable;
- Annex F is required to be declared in the USA.

In this standard, the following type is used:

compliance statements: in italic type.

The committee has decided that the contents of the base publication and its amendment will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

#### INTRODUCTION

Thermal-links, defined as non-resettable devices functioning once only without refunctioning, are widely applied for the thermal protection of equipment in which, under fault (abnormal) conditions, one or more parts may reach hazardous temperatures.

As these devices have several aspects in common with miniature fuse-links and are used for obtaining a comparable degree of protection, this standard has endeavoured to lay down a number of basic requirements for such devices.



## THERMAL-LINKS – REQUIREMENTS AND APPLICATION GUIDE

#### 1 Scope

This International Standard is applicable to thermal-links intended for incorporation in electrical appliances, electronic equipment and component parts thereof, normally intended for use indoors, in order to protect them against excessive temperatures under abnormal conditions.

NOTE 1 The equipment is not designed to generate heat.

NOTE 2 The effectiveness of the protection against excessive temperatures logically depends upon the position and method of mounting of the thermal-link, as well as upon the current which it is carrying.

This standard may be applicable to thermal-links for use under conditions other than indoors, provided that the climatic and other circumstances in the immediate surroundings of such thermal-links are comparable with those in this standard.

This standard may be applicable to thermal-links in their simplest forms (e.g. melting strips or wires), provided that molten materials expelled during function cannot adversely interfere with the safe use of the equipment, especially in the case of hand-held or portable equipment, irrespective of its position.

Annex H of this standard is applicable to thermal-link packaged assemblies where the thermal-link(s) has already been approved to this standard but packaged in a metallic or non-metallic housing and provided with terminals/wiring leads.

This standard is applicable to thermal-links with a rated voltage not exceeding 690 V a.c. or d.c. and a rated current not exceeding 63 A

The objectives of this standard are:

- a) to establish uniform requirements for thermal-links,
- b) to define methods of test,
- c) to provide useful information for the application of thermal-links in equipment.

This standard is not applicable to thermal-links used under extreme conditions such as corrosive or explosive atmospheres.

This standard is not applicable to thermal-links to be used in circuits on a.c. with a frequency lower than 45 Hz or higher than 62 Hz.

#### 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60065:2014, Audio, video and similar electronic apparatus – Safety requirements

– 8 –

IEC 60112:2003, Method for the determination of the proof and the comparative tracking indices of solid insulating materials IEC 60112:2003/AMD1:2009

IEC 60127-2:2014, Miniature fuses – Part 2: Cartridge fuse-links

IEC 60216-5:2008, Electrical insulating materials – Thermal endurance properties – Part 5: Determination of relative thermal endurance index (RTE) of an insulating material

IEC 60664-1:2007, Insulation coordination for equipment within low-voltage systems – Part 1: Principles, requirements and tests

IEC 60695-2-12:2010, Fire hazard testing – Part 2-12: Glowing/hot-wire based test methods – Glow-wire flammability index (GWFI) test method for materials IEC 60695-2-12:2010/AMD1:2014

IEC 60695-2-13:2010, Fire hazard testing – Part 2-13: Glowing/hot-wire based test methods – Glow-wire ignition temperature (GWIT) test method for materials IEC 60695-2-13:2010/AMD1:2014

IEC 60695-10-2:2014, Fire hazard testing – Part 10-2: Abnormal heat – Ball pressure test method

IEC 60695-11-10:2013, Fire hazard testing - Part 11-10: Test flames - 50 W horizontal and vertical flame test methods

IEC 60730-1:2013, Automaţic electrical controls - Part 1; General requirements

IEC 61210:2010, Connecting devices – Flat quick connect terminations for electrical copper conductors – Safety requirements

#### 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

#### 3.1

#### clearance

shortest distance in air between two conductive parts

#### 3.2

#### creepage distance

shortest distance along the surface of insulating material between two conductive parts

#### 3.3

### holding temperature

Th maximum temperature of the thermal-link at which it will not change its state of conductivity during a specified time at the rated current

Note 1 to entry: The minimum permissible value of  $T_{\mbox{h}}$  is 35 °C.

#### 3 4

#### homogeneous series

series of thermal-links having the same external dimensions and common overall construction, deviating from each other only in such characteristics (including ratings) that, for a given test,

IEC 60691:2015+AMD1:2019 CSV © IEC 2019

**-9-**

the testing of one or a reduced number of particular thermal-links of that series shall be taken as representative for all the thermal-links of the series

#### 3.5

#### interrupting current

 $I_{\mathsf{b}}$ 

value of the current that the thermal-link is capable of interrupting at rated voltage and under specified circuit conditions

#### 3.6

#### maximum temperature limit

 $T_{\mathbf{m}}$ 

temperature of the thermal-link stated by the manufacturer, up to which the mechanical and electrical properties of the thermal-link, having changed its state of conductivity, will not be impaired for a given time

#### 3.7

#### pilot duty

rating assigned to a switching device that controls the coil of another electro-mechanical device such as a solenoid, relay or contactor

#### 3.8

#### portable equipment

equipment which is moved while in operation or which can easily be moved from one place to another while connected to the supply

#### 3.9

#### rated current

 $I_{\mathsf{r}}$ 

current used to classify a thermal-link

#### 2 40

#### rated functioning temperature

Tf

temperature of the thermal-link which causes it to change its state of conductivity with a detection current up to 10 mA as the only load

#### 3.11

#### rated voltage

 $U_{\mathsf{r}}$ 

voltage used to classify a thermal-link

#### 3.12

#### thermal element

metallic or non-metallic fusible material that is part of a thermal-link and is responsive to temperature by a change of state such as from solid to liquid at the temperature for which it is calibrated

#### 3.13

#### thermal-link

non-resettable device incorporating a thermal element, which will open a circuit once only when exposed for a sufficient length of time to a temperature in excess of that for which it has been designed

#### 3.14

#### transient overload current

direct current pulse train which the thermal-link is able to withstand without impairing its characteristics

#### 3.15

#### type test

conformity testing on the basis of one or more specimens of a product representative of the production

#### 3.16

#### extended holding temperature

 $T_{\mathsf{h-100}}$ 

maximum temperature at which a thermal-link can be maintained while conducting the rated load current at the rated voltage for a period of 100 weeks which will not cause the thermal-link to open circuit in accordance with extended holding temperature evaluation

Note 1 to entry: This is a rating for user consideration during the investigation of the end product.

Note 2 to entry: Annex D specifies the extended holding temperature evaluation.

#### 3.17

#### conductive heat ageing test

#### **CHAT**

test to evaluate a thermal-link for use in an appliance

Note 1 to entry: If it performs satisfactorily, the thermal-link will be assigned a CHAT rating. This rating is for end-product user consideration during the investigation of the end-use product.

Note 2 to entry: Annex C specifies the conductive heat ageing test.

#### 4 General requirements

- 4.1 Adequate protection of the equipment against excessive temperatures not only depends upon the properties of the thermal-link but also to a large extent upon the mounting of the thermal-link in the equipment. Therefore, in addition to good engineering practice, the requirements of the application guide in Annex A shall be considered.
  - 4.2 Thermal links shall have adequate electrical and mechanical strength and shall be constructed so as to withstand all conditions of handling likely to be encountered during mounting and normal use, when used within the requirements of this standard.
  - **4.3** When a thermal-link changes its state of conductivity, no arc or flame shall be maintained, nor material expelled, that might impair the surrounding area or otherwise create a risk of electric shock or fire. In addition, there shall be no emission of substances (e.g. gases, liquids, dust, mist, vapour) which could cause a hazard.

For thermal-links using melting strips or wires, care should—be taken to prevent molten material from short-circuiting or bridging creepage distances and clearances in air, so as to reduce the risk of impairing the insulation system of the equipment.

After it has functioned, the thermal-link shall not be damaged when subjected to temperatures not exceeding  $T_{\rm m}$ , in such a way that the safety of the equipment with regard to risk of electric shock hazard and electrical breakdown is impaired. The thermal-link shall not reclose after it has operated.