

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Specifications for particular types of winding wires –
Part 0-9: General requirements – Enamelled rectangular aluminium wire

Spécifications pour types particuliers de fils de bobinage –
Partie 0-9: Exigences générales – Fil de section rectangulaire émaillé en
aluminium

ITeH STANDARD PREVIEW
(standards.iteh.ai)

IEC 60317-0-9:2015

[https://standards.iteh.ai/catalog/standards/sist/c05cdc90-c706-4a0c-b189-](https://standards.iteh.ai/catalog/standards/sist/c05cdc90-c706-4a0c-b189-3f565a70d496/iec-60317-0-9-2015)

[3f565a70d496/iec-60317-0-9-2015](https://standards.iteh.ai/catalog/standards/sist/c05cdc90-c706-4a0c-b189-3f565a70d496/iec-60317-0-9-2015)





THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2015 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in 15 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

More than 60 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Catalogue IEC - webstore.iec.ch/catalogue

Application autonome pour consulter tous les renseignements bibliographiques sur les Normes internationales, Spécifications techniques, Rapports techniques et autres documents de l'IEC. Disponible pour PC, Mac OS, tablettes Android et iPad.

Recherche de publications IEC - www.iec.ch/searchpub

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études,...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire en ligne de termes électroniques et électriques. Il contient plus de 30 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans 15 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Glossaire IEC - std.iec.ch/glossary

Plus de 60 000 entrées terminologiques électrotechniques, en anglais et en français, extraites des articles Termes et Définitions des publications IEC parues depuis 2002. Plus certaines entrées antérieures extraites des publications des CE 37, 77, 86 et CISPR de l'IEC.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: csc@iec.ch.



INTERNATIONAL STANDARD

NORME INTERNATIONALE

**Specifications for particular types of winding wires –
Part 0-9: General requirements – Enamelled rectangular aluminium wire**

**Spécifications pour types particuliers de fils de bobinage –
Partie 0-9: Exigences générales – Fil de section rectangulaire émaillé en
aluminium**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 29.060.10

ISBN 978-2-8322-2667-4

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

CONTENTS

FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	7
2 Normative references	7
3 Terms, definitions, general notes and appearance.....	7
3.1 Terms and definitions.....	7
3.2 General notes	7
3.2.1 Methods of test.....	7
3.2.2 Winding wire.....	8
3.3 Appearance	8
4 Dimensions.....	8
4.1 Conductor dimensions	8
4.2 Tolerance on conductor dimensions.....	9
4.3 Rounding of corners.....	9
4.4 Increase in dimensions due to the insulation.....	11
4.5 Overall dimensions	11
4.5.1 Nominal overall dimensions.....	11
4.5.2 Minimum overall dimensions.....	11
4.5.3 Maximum overall dimensions.....	11
5 Electrical resistance	12
6 Elongation	12
7 Springiness	12
8 Flexibility and adherence.....	12
8.1 Mandrel winding test.....	12
8.2 Adherence test.....	12
9 Heat shock	12
10 Cut-through	12
11 Resistance to abrasion	13
12 Resistance to solvents.....	13
13 Breakdown voltage	13
14 Continuity of insulation	13
15 Temperature index	13
16 Resistance to refrigerants.....	13
17 Solderability	14
18 Heat or solvent bonding.....	14
19 Dielectric dissipation factor.....	14
20 Resistance to transformer oil.....	14
21 Loss of mass	14
23 Pin hole test.....	14
30 Packaging	14
Annex A (informative) Nominal cross-sectional areas for preferred and intermediate sizes.....	15
Annex B (informative) Special tolerances.....	24

Bibliography.....	25
Table 1– Conductor tolerances	9
Table 2 – Nominal cross-sectional areas of preferred sizes.....	10
Table 3 – Corner radii	11
Table 4 – Increases in dimensions	11
Table 5 – Mandrel winding	12
Table 6 – Breakdown voltage	13
Table A.1 – Nominal cross-sectional areas (<i>1 of 9</i>)	15
Table B.1 – Overall dimensional tolerances for grade 2	24

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[IEC 60317-0-9:2015](https://standards.iteh.ai/catalog/standards/sist/c65edc96-c708-4a6c-b1b9-3f565a70d496/iec-60317-0-9-2015)

<https://standards.iteh.ai/catalog/standards/sist/c65edc96-c708-4a6c-b1b9-3f565a70d496/iec-60317-0-9-2015>

INTERNATIONAL ELECTROTECHNICAL COMMISSION

SPECIFICATIONS FOR PARTICULAR TYPES OF WINDING WIRES –

Part 0-9: General requirements – Enamelled rectangular aluminium wire

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
<https://standards.iteh.ai/catalog/standards/si/65ed196e7097a611b93e5a3a3030cc53/iec-60317-0-9-2015>
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60317-0-9 has been prepared by IEC technical committee 55: Winding wires.

The text of this standard is based on the following documents:

FDIS	Report on voting
55/1519/FDIS	55/1525/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The numbering of clauses in this standard is not continuous from Clauses 21 through 30 in order to reserve space for possible future wire requirements prior to those for wire packaging.

A list of all parts in the IEC 60317 series, published under the general title *Specifications for particular types of winding wires*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

iTeh STANDARD PREVIEW **(standards.iteh.ai)**

[IEC 60317-0-9:2015](https://standards.iteh.ai/catalog/standards/sist/c65edc96-c708-4a6c-b1b9-3f565a70d496/iec-60317-0-9-2015)

<https://standards.iteh.ai/catalog/standards/sist/c65edc96-c708-4a6c-b1b9-3f565a70d496/iec-60317-0-9-2015>

INTRODUCTION

This part of IEC 60317 is one of a series which deals with insulated wires used for windings in electrical equipment. The series has three groups describing:

- 1) Winding wires – Test methods (IEC 60851 series);
- 2) Specifications for particular types of winding wires (IEC 60317 series);
- 3) Packaging of winding wires (IEC 60264 series).

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[IEC 60317-0-9:2015](https://standards.iteh.ai/catalog/standards/sist/c65edc96-c708-4a6c-b1b9-3f565a70d496/iec-60317-0-9-2015)

<https://standards.iteh.ai/catalog/standards/sist/c65edc96-c708-4a6c-b1b9-3f565a70d496/iec-60317-0-9-2015>

SPECIFICATIONS FOR PARTICULAR TYPES OF WINDING WIRES –

Part 0-9: General requirements – Enamelled rectangular aluminium wire

1 Scope

This part of IEC 60317 specifies the general requirements of enamelled rectangular aluminium winding wires.

The range of nominal conductor dimensions is given in the relevant specification sheet.

When reference is made to a winding wire according to a standard of the IEC 60317 series mentioned under Clause 2, the following information is given in the description:

- reference to IEC specification;
- nominal conductor dimensions in millimetres (width × thickness);
- grade.

EXAMPLE IEC 60317-16 – 4,00 x 1,00 Grade 1

iTeh STANDARD PREVIEW
(standards.iteh.ai)

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60172¹, *Test procedure for the determination of the temperature index of enamelled and tape wrapped winding wires*

IEC 60317-0-1, *Specifications for particular types of winding wires – Part 0-1: General requirements – Enamelled round copper wire*

IEC 60851 (all parts), *Winding wires – Test methods*

ISO 3, *Preferred numbers – Series of preferred numbers*

3 Terms, definitions, general notes and appearance

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60317-0-1 apply.

3.2 General notes

3.2.1 Methods of test

All methods of test to be used for this standard are given in IEC 60851.

¹ Fourth edition to be published.

The clause numbers used in this standard are identical to the corresponding test numbers in the IEC 60851 series of standards.

In case of inconsistencies between the publication on methods of test and this standard, IEC 60317-0-9 shall prevail.

Where no specific range of nominal conductor dimensions is given for a test, the test applies to all nominal conductor dimensions covered by the specification sheet.

Unless otherwise specified, all tests shall be carried out at a temperature from 15 °C to 35 °C and a relative humidity from 45 % to 75 %. Before measurements are made, the specimens shall be preconditioned under these atmospheric conditions for a time sufficient to allow the specimens to reach stability.

The wire to be tested shall be removed from the packaging in such a way that the wire will not be subjected to tension or unnecessary bends. Before each test, sufficient wire should be discarded to ensure that any damaged wire is not included in the test specimens.

3.2.2 Winding wire

When reference is made to a winding wire according to a standard of the IEC 60317 series mentioned under Clause 2, the following information is given in the description:

- reference to IEC specification;
- nominal conductor dimensions in millimetres (width × thickness);
- grade.

EXAMPLE IEC 60317-18 – 4,00 × 1,00 Grade 1

3.3 Appearance

The film coating shall be smooth and continuous, free from streaks, blisters and foreign material when examined with normal vision, as wound on the original spool or reel.

4 Dimensions

4.1 Conductor dimensions

The dimensions for widths and thickness of conductors of winding wires with rectangular cross-section recommended in this standard are taken from the R 20 and R 40 series according to ISO 3.

Preferred sizes are combinations of width and thickness both according to the R 20 series.

Intermediate sizes are combinations of width or thickness according to the R 20 series with the other dimension according to the R 40 series.

This standard covers:

- widths from 2,00 mm up to and including 16,00 mm;
- thicknesses from 0,80 mm up to and including 5,60 mm.

For thicknesses over 5,600 mm up to and including 10 mm and for widths over 16 mm up to and including 25 mm where, for technical reasons, additional sizes may be needed, the R 40 series shall be used. The ratio width/thickness shall be within the specified limits and combinations of R 40 by R 40 are not allowed in the case of additional sizes.

The ratio width/thickness shall be greater than or equal to 1,4:1 and shall not exceed 8:1.

The actual values of dimensions are given in Table 2.

The nominal cross-sectional areas for preferred sizes are given in Table 2, and the nominal cross-sectional areas for intermediate sizes are given in Table A.1.

4.2 Tolerance on conductor dimensions

The conductor dimensions shall not differ from the nominal values by more than the tolerance given in Table 1.

Table 1– Conductor tolerances

Nominal width or thickness of the conductor		Tolerance
mm		
Over	Up to and including	± mm
–	3,15	0,030
3,15	6,30	0,050
6,30	12,50	0,070
12,50	16,00	0,100

(standards.iteh.ai)

4.3 Rounding of corners

The arc shall merge smoothly into the flat surfaces of the conductor and the strip shall be free from sharp, rough and projecting edges. The conductor shall have radiused corners complying with Table 3. The specified radii shall be maintained within ± 25 %.

Table 2 – Nominal cross-sectional areas of preferred sizes

Width	Thickness																		
	0,80	0,90	1,00	1,12	1,25	1,40	1,60	1,80	2,00	2,24	2,50	2,80	3,15	3,55	4,00	4,50	5,00	5,60	
	Corner radius (0,5 mm*)																		
2,00	1,463	1,626	1,785	2,025	2,285	2,585	2,921	3,307	3,737	4,212	4,733	5,301	5,928	6,615	7,364	8,177	9,056	10,003	11,021
2,24	1,655	1,842	2,025	2,294	2,582	2,921	3,369	3,868	4,418	5,020	5,675	6,385	7,151	7,974	8,855	9,796	10,799	11,866	12,999
2,50	1,863	2,076	2,285	2,585	2,910	3,285	3,785	4,337	4,943	5,605	6,325	7,105	7,946	8,849	9,815	10,846	11,944	13,111	14,348
2,80	2,103	2,346	2,585	2,921	3,285	3,705	4,265	4,878	5,545	6,268	7,048	7,885	8,779	9,730	10,740	11,811	12,944	14,140	15,401
3,15	2,383	2,661	2,935	3,313	3,723	4,195	4,825	5,507	6,243	7,035	7,884	8,791	9,757	10,784	11,873	13,026	14,245	15,531	16,885
3,55	2,703	3,021	3,335	3,761	4,223	4,755	5,465	6,267	7,133	8,065	9,064	10,131	11,267	12,474	13,753	15,106	16,536	18,044	19,631
4,00	3,063	3,426	3,785	4,265	4,785	5,385	6,185	7,037	7,953	8,935	9,984	11,101	12,287	13,544	14,873	16,276	17,755	19,311	20,946
4,50	3,463	3,876	4,285	4,825	5,410	6,085	6,85	7,737	8,631	9,577	10,576	11,629	12,747	13,931	15,182	16,502	17,893	19,356	20,893
5,00	3,863	4,326	4,785	5,385	6,035	6,785	7,785	8,637	9,637	10,84	12,18	13,45	14,79	16,19	17,66	19,19	20,79	22,46	24,20
5,60	4,363	4,866	5,385	6,057	6,785	7,625	8,745	9,717	10,84	12,18	13,45	15,13	17,09	19,33	21,54	24,34	27,49	30,99	34,64
6,30	4,903	5,496	6,085	6,841	7,660	8,605	9,865	10,98	12,24	13,75	15,20	17,09	19,30	21,82	24,34	27,49	31,14	35,14	39,64
7,10		6,216	6,885	7,737	8,660	9,725	11,15	12,42	13,84	15,54	17,20	19,33	21,82	24,66	27,54	31,09	34,64	39,14	43,94
8,00			7,785	8,745	9,785	10,99	12,59	14,04	15,64	17,56	19,45	21,85	24,65	27,85	31,14	35,14	39,14	44,14	49,54
9,00				9,865	11,04	12,39	14,19	15,84	17,64	19,80	21,95	24,65	27,80	31,40	35,14	39,64	44,14	49,54	55,14
10,0					12,29	13,79	15,79	17,64	19,64	22,04	24,45	27,45	30,95	34,95	39,14	44,14	49,14	55,14	61,86
11,2						15,47	17,71	19,80	22,04	24,79	27,46	30,81	34,73	39,21	43,94	49,54	55,14	61,86	69,14
12,5							19,79	22,14	24,64	27,64	30,70	34,45	38,83	43,83	49,14	55,39	61,64	69,14	77,54
14,0								24,84	27,64	31,00	34,45	38,65	43,55	49,15	55,14	62,14	69,14	77,54	88,74
16,0									31,64	35,48	39,45	44,25	49,85	56,25	63,14	71,14	79,14	88,74	100,00

* Nominal thickness

Table 3 – Corner radii

Nominal thickness of conductor mm		Corner radius ± mm
Over	Up to and including	
–	1,00	0,50 nominal thickness
1,00	1,60	0,50*
1,60	2,24	0,65**
2,24	3,55	0,80
3,55	5,60	1,00

NOTE If agreed between purchaser and supplier, the corner radii for wires with a width greater than 4,8 mm may be:

* 0,50 nominal thickness

** 0,80 mm

4.4 Increase in dimensions due to the insulation

The increase in width or thickness due to the insulation shall be as given in Table 4.

Table 4 – Increases in dimensions
(standards.iteh.ai)

Grade	Increase in dimensions mm		
	Minimum	Nominal	Maximum
1	0,06	0,085	0,11
2	0,12	0,145	0,17

4.5 Overall dimensions

4.5.1 Nominal overall dimensions

The nominal overall dimensions shall be calculated as the sum of the nominal bare conductor and the nominal increase in dimension due to the insulation.

4.5.2 Minimum overall dimensions

The minimum overall dimensions shall be calculated as the sum of the minimum bare conductor and the minimum increase in dimension due to the insulation. See also note under 4.5.3.

4.5.3 Maximum overall dimensions

The maximum overall dimensions shall be calculated as the sum of the maximum bare conductor and the maximum increase in dimension due to the insulation.

NOTE When agreed between purchaser and supplier, special tolerances for grade 2 as given in Annex B have been established to calculate special maximum and minimum dimensions.

5 Electrical resistance

The resistance of the wire shall be expressed as the d.c. resistance at 20 °C. The method used shall provide an accuracy of 0,5 %.

The maximum value of resistance shall be not greater than the value calculated for the minimum tolerated cross-sectional area of the conductor resulting from the minimum dimensions in thickness and width and the maximum for the corner radius, and with a resistivity of 1/35,85 (0,027 894) Ω·mm²·m⁻¹.

One measurement shall be made.

6 Elongation

The minimum elongation at fracture shall be 15 %.

7 Springiness

Test appropriate but no requirements specified.

8 Flexibility and adherence

8.1 Mandrel winding test

The coating shall show no crack after the wire has been bent flatwise and edgewise on a mandrel with a diameter as specified in Table 5.

<https://standards.iteh.ai/catalog/standards/sist/c65edc96-c708-4a6c-b1b9-312270d19101/iec-60317-0-9:2015>

Table 5 – Mandrel winding

Wire bent on		Mandrel diameter
Width	Sizes up to and including 10 mm	4width
	Sizes over 10 mm	5 × width
Thickness	All sizes	4 × thickness

8.2 Adherence test

The wire shall be stretched by 15 %. The distance of loss of adhesion shall be less than one time the width.

9 Heat shock

The coating shall show no crack after the wire has been bent flatwise on a mandrel with a diameter of six times the thickness.

The minimum heat shock temperature is given in the relevant specification sheet.

10 Cut-through

Test inappropriate.

11 Resistance to abrasion

Test inappropriate.

12 Resistance to solvents

Following immersion in standard solvent, the coating shall not be removed using a pencil of hardness "H".

13 Breakdown voltage

When tested at room temperature at least four of the five specimens tested shall not break down at a voltage less than or equal to that given in Table 6, and the fifth shall not break down at less than 50 % of the values specified.

When required by the purchaser, the wire shall be tested at elevated temperature.

The elevated temperature is given in the relevant specification sheet.

Table 6 – Breakdown voltage

Grade	Minimum breakdown voltage (r.m.s.)	
	Room temperature	Elevated temperature
1	1 000	750
2	2 000	1 500

<https://standards.iteh.ai/catalog/standards/sist/c65edc96-c708-4a6c-b1b9-3f565a70d496/iec-60317-0-9-2015>

14 Continuity of insulation

Test inappropriate.

15 Temperature index

The test shall be carried out on a rectangular wire according to IEC 60172, unless otherwise agreed between purchaser and supplier.

When required by a purchaser, the supplier of the enamelled wire shall supply evidence that the wire meets the requirements for the temperature index.

NOTE 1 The temperature index requirement based on an extrapolated life of 20 000 h relates to enamelled wires tested unvarnished and not as part of an insulation system.

NOTE 2 Temperature in degrees Celsius corresponding to the temperature index is not necessarily that at which it is recommended that the wire be operated and this will depend on many factors, including the type of equipment involved.

16 Resistance to refrigerants

Test inappropriate.