

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Electromechanical telecom elementary relays of assessed quality –
Part 1: Generic specification and blank detail specification
(standards.iteh.ai)

Relais télécom électromécaniques élémentaires soumis au régime d'assurance
qualité –
Partie 1: Spécification générique et spécification particulière cadre



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2015 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in 15 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

More than 60 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Catalogue IEC - webstore.iec.ch/catalogue

Application autonome pour consulter tous les renseignements bibliographiques sur les Normes internationales, Spécifications techniques, Rapports techniques et autres documents de l'IEC. Disponible pour PC, Mac OS, tablettes Android et iPad.

Recherche de publications IEC - www.iec.ch/searchpub

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études,...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire en ligne de termes électroniques et électriques. Il contient plus de 30 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans 15 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Glossaire IEC - std.iec.ch/glossary

Plus de 60 000 entrées terminologiques électrotechniques, en anglais et en français, extraites des articles Termes et Définitions des publications IEC parues depuis 2002. Plus certaines entrées antérieures extraites des publications des CE 37, 77, 86 et CISPR de l'IEC.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: csc@iec.ch.

INTERNATIONAL STANDARD

NORME INTERNATIONALE

**Electromechanical telecom elementary relays of assessed quality –
Part 1: Generic specification and blank detail specification**

**Relais télécom électromécaniques élémentaires soumis au régime d'assurance
qualité –
Partie 1: Spécification générique et spécification particulière cadre**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 29.120.70

ISBN 978-2-8322-2235-5

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

CONTENTS

FOREWORD.....	5
1 Scope.....	7
2 Normative references	7
3 Terms and definitions	8
3.1 Type of relays	8
3.2 Types of contacts.....	8
3.3 Contact fault and contact failure.....	9
3.4 Relay malfunction, relay failure	9
3.5 Relay construction types	9
3.6 Inspection level and sample size.....	10
4 Rated values	10
4.1 General.....	10
4.2 Rated coil voltages	10
4.3 Contact-circuit resistance.....	10
4.4 Dielectric test.....	10
4.5 Impulse voltage test.....	10
4.6 Insulation resistance	11
4.7 Number of operations determining electrical endurance	11
4.8 Contact failure rate for test evaluation purposes	11
5 Marking and documentation.....	11
5.1 General.....	11
5.2 Marking of the relay.....	11
5.3 Marking of the package.....	11
5.4 Coded date of manufacture.....	11
6 Preparation of blank detail and detail specifications.....	11
7 Quality assessment procedures	13
7.1 Primary stage of manufacture	13
7.2 Structurally similar relays	13
7.3 Qualification approval procedures	13
7.4 Quality conformance inspection	13
7.4.1 Grouping of tests	13
7.4.2 Resubmission of rejected lots	14
7.4.3 Delivery of relays subjected to destructive tests or non-destructive tests	14
7.4.4 Delayed delivery	14
7.4.5 Supplementary procedure for deliveries.....	15
7.4.6 Unchecked parameters	15
7.4.7 Release for delivery before completion of group B tests.....	15
7.4.8 Screening procedures.....	15
7.4.9 Formation of inspection lots	15
7.4.10 Periodic inspection	15
7.5 Periodic inspection / Intervals between tests.....	15
8 Test schedule	16
8.1 Test sequence	16
8.2 Types of relays, based upon environmental protection (relay technology (RT))	16
8.3 Categories of application of contacts	16

8.4	Order of tests	16
8.5	Test groups and subgroups	16
9	Tests	21
9.1	Standard conditions for testing	21
9.2	Mounting of test specimens during the test	21
9.3	General conditions for testing	21
10	Ordering information	21
Annex A (informative)	Relay reliability – Failure rate data	22
A.1	General	22
A.2	Scope	22
A.3	Description of the relay	22
A.3.1	Identification	22
A.3.2	Ratings	22
A.4	Fault and failure data	23
A.4.1	Fault and failure definition	23
A.4.2	Fault application	23
A.4.3	Failure definition	23
A.4.4	Failure application	23
A.5	Source of data	23
A.6	Weibull approach	23
A.7	WeiBayes approach	24
A.7.1	Description	24
A.7.2	Method	24
A.7.3	WeiBayes without failures	24
A.7.4	WeiBayes with failures	24
A.7.5	WeiBayes case study	25
Annex B (informative)	Characteristic values of the relay	27
B.1	General data	27
B.2	Coil data	28
B.3	Contact data	28
B.3.1	Electrical endurance and switching frequency	28
B.3.2	Static contact-circuit resistance	28
B.3.3	Mechanical endurance	28
B.3.4	Timing (without suppression device)	29
B.4	Mounting	29
B.5	Environmental data	29
B.6	Package of relays for automatic handling (if applicable)	29
Annex C (informative)	Blank detail and detail specification	30
C.1	Examples for front pages	30
C.1.1	General	30
C.1.2	Type 0 – Non-standardized types and construction	30
C.1.3	Type 1 – Two change-over contacts, 20 mm × 10 mm base	31
C.1.4	Type 2 – Two change-over contacts, 14 mm × 9 mm base	32
C.1.5	Type 3 – Two change-over contacts, 15 mm × 7,5 mm base	33
C.1.6	Type 4 – Two change-over contacts, 11 mm × 7,5 mm (max.) base	34
C.1.7	Key to front page	35
C.2	Qualification approval procedures	35
C.3	Quality conformance inspection	35

C.4 Formation of inspection lots	36
Annex D (informative) Definition of subgroups	53
Bibliography.....	54
Figure A.1 – New compressor design WeiBayes versus old design	26
Table 1 – Group A	17
Table 2 – Group B	18
Table 3 – Group C	19
Table B.1 – Dielectric test voltages	27
Table B.2 – Impulse test voltages	27
Table B.3 – Coil data	28
Table B.4 – Loads, contact-circuit resistance limits, switching cycles and frequencies for electrical endurance and overload tests	28
Table C.1 – Quality conformance inspection	36
Table C.2 – Qualification approval	50
Table C.3 – Industrial qualification	52

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[IEC 61811-1:2015](https://standards.iteh.ai/catalog/standards/sist/9ef070e2-c79e-487a-a838-fc65d6e91d67/iec-61811-1-2015)

<https://standards.iteh.ai/catalog/standards/sist/9ef070e2-c79e-487a-a838-fc65d6e91d67/iec-61811-1-2015>

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**ELECTROMECHANICAL TELECOM ELEMENTARY
RELAYS OF ASSESSED QUALITY –****Part 1: Generic specification and blank detail specification**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61811-1 has been prepared by IEC technical committee 94: All-or-nothing electrical relays.

This second edition of IEC 61811-1 cancels and replaces

- IEC 61811-1 published in 1999,
- IEC 61811-10 published in 2002,
- IEC 61811-11 published in 2002,
- IEC 61811-50 published in 2002,
- IEC 61811-51 published in 2002,
- IEC 61811-52 published in 2002,
- IEC 61811-53 published in 2002,
- IEC 61811-54 published in 2002,

- IEC 61811-55 published in 2002,

and constitutes a technical revision. This edition includes the following significant technical changes with respect to the previous editions:

- a) to get one document for telecom relays;
- b) update all relevant references;

The text of this standard is based on the following documents:

FDIS	Report on voting
94/379/FDIS	94/383/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

A list of all parts in the IEC 61811 series, published under the general title *Electromechanical telecom elementary relays of assessed quality*, can be found on the IEC website.

Future standards in this series will carry the new general title as cited above. Titles of existing standards in this series will be updated at the time of the next edition.

This publication was drafted in accordance with ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed, <https://standards.iteh.ai/catalog/standards/sist/9ef070e2-c79e-487a-a838-fc65d6e91d67/iec-61811-1-2015>
- withdrawn,
- replaced by a revised edition, or
- amended.

ELECTROMECHANICAL TELECOM ELEMENTARY RELAYS OF ASSESSED QUALITY –

Part 1: Generic specification and blank detail specification

1 Scope

This part of IEC 61811 applies to electromechanical telecom elementary relays. Relays according to this standard are provided for the operation in telecommunication applications. However, as electromechanical elementary relays, they are also suitable for particular industrial and other applications.

This standard selects from IEC 61810 series and other sources the appropriate methods of test to be used in detail specifications derived from this specification, and contains basic test schedules to be used in the preparation of such specifications in accordance with this standard.

Detailed test schedules are contained in the detail specifications.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

[IEC 61811-1:2015](https://standards.iteh.ai/catalog/standards/sist/9ef070e2-c79e-487a-a838-9c77a5577755/iec-61811-1-2015)

<https://standards.iteh.ai/catalog/standards/sist/9ef070e2-c79e-487a-a838-9c77a5577755/iec-60062-2004>, *Marking codes for resistors and capacitors*

IEC 60068-1:2013, *Environmental testing – Part 1: General and guidance*

IEC 60068-2-17:1994, *Basic environmental testing procedures – Part 2-17: Tests – Test Q: Sealing*

IEC 60068-2-20:2008, *Environmental testing – Part 2-20: Tests – Test T: Test methods for solderability and resistance to soldering heat of devices with leads*

IEC 60068-2-58:2004, *Environmental testing – Part 2-58: Tests – Test Td: Test methods for solderability, resistance to dissolution of metallization and to soldering heat of surface mounting devices (SMD)*

IEC 60410:1973, *Sampling plans and procedures for inspection by attributes*

IEC 60695-11-5:2004, *Fire hazard testing – Test flames – Needle-flame test method – Apparatus, confirmatory test arrangement and guidance*

IEC 61810 (all parts), *Electromechanical elementary relays*

IEC 61810-1:2008, *Electromechanical elementary relays – Part 1: General requirements*

IEC 61810-2:2011, *Electromechanical elementary relays – Part 2: Reliability*

IEC 61810-7:2006, *Electromechanical elementary relays – Part 7: Test and measurement procedures*

ISO 2859 (all parts), *Sampling procedures for inspection by attributes*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 61810 series, as well as the following apply.

3.1 Type of relays

The most frequent types of electromechanical telecom elementary relays are defined in 3.1.1, 3.1.2, 3.1.3 and 3.1.4.

3.1.1

bistable relay

electrical relay which, having responded to an energizing quantity and having changed its condition, remains in that condition after the quantity has been removed; a further appropriate energization is required to make it change its condition.

[SOURCE:IEC 60050-444:2002, 444-01-08]

3.1.2

monostable relay

electrical relay which, having responded to an energizing quantity and having changed its condition, returns to its previous condition when that quantity is removed

[SOURCE: IEC 60050-444:2002, 444-01-07]

3.1.3

non-polarized relay

electrical relay, the change of condition of which does not depend upon the polarity of its energizing quantity

[SOURCE: IEC 60050-444:2002, 444-01-10]

3.1.4

polarized relay

polarized elementary relay

electrical relay, the change of condition of which depends upon the polarity of its d.c. energizing quantity

[SOURCE: IEC 60050-444:2002, 444-01-09; modified – In the definition, "elementary relay" has been replaced by "electrical relay".]

3.2 Types of contacts

3.2.1

change-over break-before-make contact

change-over contact, one contact circuit of which breaks before the other makes

[SOURCE: IEC 60050-444:2002,444-04-21, modified – The definition has been reworded.]

3.2.2

change-over make-before-break contact

change-over contact, one contact circuit of which makes before the other breaks

[SOURCE: IEC 60050-444:2002, 444-04-20, modified – The definition has been reworded.]

3.3 Contact fault and contact failure

3.3.1

failure to make

failure caused when no sufficient contact is ensured

Note 1 to entry: This could be a not acceptable or excessive contact resistance exceeds the maximum value stated in the detail specification as well a bouncing of the contact due to the lost of overtravel.

3.3.2

failure to break

failure caused when the current flows although it should not

Note 1 to entry: For example, This could be a contact welding/sticking as well as a delayed contact operate or release contact. Also, it is assumed that the contact does not open, when the resistance of an open contact assembly falls below the specified minimum value stated in the detail specification

3.3.3

malfunction

single event when an item does not perform a required function

3.3.4

contact failure

occurrence of break and/or make malfunctions of a contact under test, exceeding a specified number

3.4 Relay malfunction, relay failure

3.4.1

relay malfunction

the state of a relay characterized by the inability to perform a required function

<https://standards.iteh.ai/catalog/standards/sist/9ef070e2-c79e-487a-a838-66516e01d477/iec-61811-1-2015>

Note 1 to entry: A fault persists for a limited time after which the relay recovers the ability to perform a required function without being subjected to any corrective maintenance.

3.4.2

failure

termination of the ability of an item to perform a required function

[SOURCE:IEC 60050-191:1990, 191-04-01]

3.5 Relay construction types

3.5.1

type 0

non-standardized types and construction

3.5.2

type 1

two change-over contacts, 20 mm × 10 mm base

3.5.3

type 2

two change-over contacts, 14 mm × 9 mm base

3.5.4

type 3

two change-over contacts, 15 mm × 7,5 mm base

3.5.5**type 4**

two change-over contacts, 11 mm × 7,5 mm (max.) base

3.6 Inspection level and sample size**3.6.1****IL**

Special Inspection Level in accordance to the ISO 2859 series

3.6.2**AQL**

Acceptance Quality Limit in accordance to the ISO 2859 series

3.6.3**Lot-by-lot**

Period: inspection lot refers to the production volume of not more than one week

4 Rated values**4.1 General**

The following subclauses contain preferred values applicable to electromechanical telecom elementary relays.

iTeh STANDARD PREVIEW

4.2 Rated coil voltages (standards.iteh.ai)

Preferred values d.c.: 1,5 V; 3 V; 4,5 V; 5 V; 6 V; 9 V; 12 V; 24 V; 48 V or 60 V.

<https://standards.iteh.ai/catalog/standards/sist/9ef070e2-c79e-487a-a838-ic65d6e91d67/iec-61811-1-2015>

4.3 Contact-circuit resistance

- a) Preferred values in initial condition: maximum 50 mΩ; 100 mΩ or 200 mΩ.
- b) Preferred values during/after tests: maximum 0,5 Ω; 1 Ω; 5 Ω; 10 Ω; 20 Ω or 100 Ω.
- c) Preferred value for detecting faults due to non-opening of the contact circuit during tests: minimum 100 kΩ.
- d) Voltage for detecting faults due to non-opening of the contact circuit during tests; preferred maximum values: 0,03 V; 5 V; 6 V; 12 V; 24 V; 48 V or 60 V d.c.
- e) Difference of contact-circuit resistance between different contact circuits in the same relay, preferred value: maximum 100 mΩ (initial condition).

4.4 Dielectric test

Preferred values in initial condition between opened contact circuits, between separate contact circuits, between contact circuits and coil(s), between all conductive parts and mass (if applicable) in accordance with IEC 61810-1.

- a) Preferred voltages: 0,5 kV; 0,8 kV; 1,5 kV; 2,5 kV a.c.
- b) Preferred duration: 1 s or 60 s

4.5 Impulse voltage test

- a) Preferred voltages: 0,5 kV; 1,0 kV; 1,5 kV; 2 kV or 2,5 kV.
- b) Preferred waveform: 0,5 μs/700 μs, 1,2 μs/50 μs or 10 μs/700 μs.
- c) Preferred number of pulses (alternate positive and negative pulses): 10.
- d) Preferred frequency of pulses: 2 pulses/min or 4 pulses/min.

4.6 Insulation resistance

Preferred value: 1 000 M Ω at 500 V d.c. initial value.

4.7 Number of operations determining electrical endurance

Preferred values: 10 000; 20 000; 50 000; 100 000; 200 000; 500 000; 700 000; 1 000 000; 1 600 000; 2 000 000; 5 000 000; 10 000 000; 20 000 000 or 30 000 000.

4.8 Contact failure rate for test evaluation purposes

Preferred values: maximum 10^{-5} , 10^{-6} , 10^{-7} , 10^{-8} /contact/cycle.

5 Marking and documentation

5.1 General

Relays and their package supplied in accordance with detail specifications covered by this sectional specification shall be marked as follows:

5.2 Marking of the relay

- Manufacturer's name, logo or trade mark.
- Relay type and variant code.
- Coded date of manufacture, in terms of year/week according to 5.4.

5.3 Marking of the package

- Manufacturer's name, logo or trade mark.
- Relay type and variant code.
- Manufacturer's batch identification code.
- Detail specification reference if not marked on the relay.
- Quantity.

5.4 Coded date of manufacture

The marking system shall use four figures as specified in 6.2 of IEC 60062:2004. The first two figures shall be the last two figures of the year and the last two figures the numbering of the week.

EXAMPLE Fifth week of 1994 = 9405.

If stated in the detail specification only, the first two figures shall be the last two figures of the year, the month is represented by the next two figures and the day of the month is represented by the last two figures.

EXAMPLE 20th June 1994 = 940620.

6 Preparation of blank detail and detail specifications

Blank detail specifications shall conform to the test schedules given in Table 1 of this specification and the related explanations.

The blank specification as given in Annex C shall be used for the preparation and characteristic values of the relay shall be included as given in Annex B. The values shall be adjusted by the manufacturer as appropriate.

Blank detail specifications shall give the following information or call for its inclusion in the detail specification:

- a) Identification of the detail specification.
- b) Identification of the relay and information on its applications; identification shall be provided by such properties as size, sealing, whether monostable or bistable, polarized or not, or other characteristics required for identification, contact operating range and temperature range.
- c) Outline drawing of the relay and key dimensions; variants, such as for terminals, may be given in an annex to the detail specification.

Customer packaging requirements for automatic handling.

- d) Reference data of the relay.
 - 1) A limited number of values is required on the front page to describe the overall performance of the relay.
 - 2) Full information in conformance with Clause 4 and IEC 61810-1 shall be added on one of the subsequent pages. Rated values preferably should be those listed therein. Where tests refer to rated values, this shall be indicated with each test. Where tests are to be performed at other than rated values, the test values shall be indicated and clearly distinguished from the rated values.

- e) Normative references.

Reference shall be made to IEC 61810 series. When reference to further documents is necessary, such documents shall be listed with their full titles, year of edition and, unless common knowledge, the source from which they can be obtained.

- f) Assessment level.

Table 1 of this specification contains one test schedule. If additional tests not listed there have been added, this shall be stated.

- g) Periodicity of tests.
- h) Formation of inspection lots, if predictable in the sense of 7.4.9 and 8.1.
- i) Order of tests, if deviating from 8.4.
- j) General test conditions, if deviating from 4.5 of IEC 61810-7:2006.
- k) Qualification approval test schedule.
- l) Quality conformance test schedule.

For each group of tests, the final measurements and post-test requirements specified in each of them may be summarized and stated at the end of the subgroup.

It shall be stated that samples subjected to destructive tests (D) shall not be released for delivery.

If application of SPC or ppm approach is required, this should be provided the manufacturer.

- m) Specification of IL numbers (groups A and B) and sample sizes (group C).
- n) Specification of AQL numbers (groups A and B) and acceptable numbers of defectives (group C).
- o) Marking of package and/or relays beyond those listed in this specification, if necessary.
- p) Ordering information

Additional information such as curves and drawings may be given in an annex to the detail specification. Such information is not required to be verified for test purposes.

When preparing blank detail or detail specifications, the following procedures should be followed:

- select the tests to be performed from Table 1 of this sectional specification;

– if necessary, add any other necessary tests, required or not specified in IEC 61810-7.

Examples for front pages of detail specifications are given in Annex C.

7 Quality assessment procedures

7.1 Primary stage of manufacture

The primary stage of manufacture is the first process subsequent to the manufacture of finished parts and subassemblies of the relay.

NOTE A subassembly is understood to mean here the permanent assembly of two or more piece parts.

Important manufacturing steps are as follows:

- a) fabrication, heat treatment and plating of the component parts of the relay;
- b) coil winding;
- c) assembling of the electrical and electromechanical parts;
- d) adjustment of the relay contacts, if applicable;
- e) high-temperature drying, gas backfilling and sealing of the relay, if applicable;
- f) final measurements and periodic inspection of test groups A to C.

7.2 Structurally similar relays

Relays are considered structurally similar if they have no differences in design other than:

- a) wire diameter and of windings;
- b) types, numbers and material of contacts;
- c) rated coil and/or contact voltage(s);
- d) mounting and terminal variants within the limits prescribed in the data sheet or specification.
- e) biasing of the input circuit parts.

7.3 Qualification approval procedures

Qualification approval tests shall include all the tests prescribed in the detail specification and shall be performed by a schedule specifically prescribed in the detail specification.

The number of specimens for each subgroup is specified in the blank detail specification. As a general rule, a minimum of five specimens are required for each group of tests.

7.4 Quality conformance inspection

7.4.1 Grouping of tests

7.4.1.1 General

The purpose of grouping tests is to combine in one group all those tests which are of equal importance to the assessment of the usefulness of the relay. Therefore, each test in the same subgroup gets the same inspection level and acceptable quality level range, and therefore further criteria for the allocation of tests to a group are the destructiveness of the test, the duration of the test and the relation to the fabrication or design.

The frequency of testing takes account of the complexity, duration and overall cost of the test, and the effect of releasing non-conforming relays.