

# INTERNATIONAL STANDARD

ISO  
**4250-3**

Second edition  
1997-11-01

---

---

## Earth-mover tyres and rims —

### Part 3: Rims

*Pneumatiques et jantes pour engins de terrassement —*

*Partie 3: Jantes*

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO 4250-3:1997](#)

<https://standards.iteh.ai/catalog/standards/sist/39c60db4-d692-4f1d-aa1f-32d8d769339e/iso-4250-3-1997>



Reference number  
ISO 4250-3:1997(E)

## **Foreword**

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

## **iTeh STANDARD PREVIEW**

International Standard ISO 4250-3 was prepared by Technical Committee ISO/TC 31, *Tyres, rims and valves*, Subcommittee SC 6, *Off-the-road tyres and rims*.

### ISO 4250-3:1997

This second edition ~~cancels and replaces the third edition (ISO 4250-3:1987), of which it constitutes a technical revision.~~ ISO 4250-3:1997

ISO 4250 consists of the following parts, under the general title *Earth-mover tyres and rims*:

- *Part 1: Tyres designations and dimensions*
- *Part 2: Loads and inflation pressures*
- *Part 3: Rims*

Annex A of this part of ISO 4250 is for information only.

© ISO 1997

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization  
Case postale 56 • CH-1211 Genève 20 • Switzerland  
Internet central@iso.ch  
X.400 c=ch; a=400net; p=iso; o=isocs; s=central

Printed in Switzerland

## Earth-mover tyres and rims —

### Part 3: Rims

#### 1 Scope

ISO 4250 consists of three parts (see the Foreword) laying down the technical elements relating to designation and dimensions of tyres and rims for earth-moving machinery: it also gives load tables for these tyres.

This part of ISO 4250 sets out the designation, contours and dimensions for rims for narrow and wide base off-road tyres primarily intended for earth-moving machinery.

Annex A gives details of sealing ring grooves and O-rings for earth-mover rims.

NOTE — Terms used are in accordance with ISO 3911:1977, *Wheels/rims — Nomenclature, designation, marking and units of measurement*.

[ISO 4250-3:1997](#)

<https://standards.iteh.ai/catalog/standards/sist/39c60db4-d692-4f1d-aaf1f32d8d769339e/iso-4250-3-1997>

#### 2 Rim identification

**2.1** Codes shall be used to identify:

- a) specified rim diameter,  $D$  (see table 6);
- b) nominal width between flanges;
- c) nominal flange height or rim profile designations.

**2.2** The rim marking shall consist of codes for:

- a) specified rim diameter,  $D$ ;
- b) nominal width between flanges.

The markings shall be on the weather side of the rim and visible when the tyre is mounted on the rim

Where a disk is fitted by the rim/wheel manufacturer, the marking shall appear on either the disc or rim base.

Loose flanges shall be marked on an externally visible surface. The marking shall indicate nominal height and nominal diameter.

#### 3 Rim contours

Rim contours are given in figures 1 to 5 and tables 1 to 5.

## 4 Rim knurling


Rim knurling details are given in figure 6 and table 6.

## 5 Rim loads and inflation pressures

The load and inflation pressure imposed on the rim and wheel shall not exceed the rim and wheel manufacturer's recommendations, even though the tyre may be approved for a higher load or inflation pressure. Consult the rim and wheel manufacturer to determine if rim and wheel capacities are adequate for the intended service.

## 6 Rim dimensions

Rim dimensions are standardized for size and contour only, and for particular tyre and rim combinations designated to ensure proper mounting and fit of the tyre to the rim.



1) For codes < 49,  $D$  tolerance:  ${}^{+0,4}_{-0,8}$

For codes  $\geq 49$ ,  $D$  tolerance:  $\pm 0,8$

The tolerance given for the specified rim diameter,  $D$ , is for tyre design purposes only. The actual rim measurement by circumference is established by using a mandrel and a tape.

2) For codes  $\leq 49$ ,  $D_B = (D - 25,5) {}^{+0,5}_{-13}$

For codes  $\geq 51$ ,  $D_B = (D - 51) {}^{+0,5}_{-0,3}$

### NOTES

- 1 The figure applies to rim diameter codes 25, 29, 33, 35, 39, 43, 45, 49, 51 and 57. (See table 7 for specified rim diameters.)
- 2 Flange and bead seat shall be removable on one side.


**Figure 1 — Contours of 5° full tapered bead seat rims**

**Table 1 — Contours of 5° full tapered bead seat rims**

Dimensions in millimetres

Rim width code/ flange height code	A ± 13	G ± 2	B min.	P min.	R <sub>2</sub>	tol.
11.25/2.0	286	51	32,5	101	32	± 1,5
13.00/2.5	330	63,5	45,5	101	38	± 1,5
13.00/2.75 <sup>1)</sup>	330	70	48,5	101	47,5	± 1,5
15.00/3.00	381	76	55	117,5	44,5	± 1,5
15.00/3.0-49	381	76	55	117,5	51	± 2
17.00/2.0	432	51	32,5	101	32	± 1,5
17.00/3.5	432	89	58	139	51	± 2
19.50/2.0	495,5	51	32,5	101	32	± 1,5
19.50/2.5	495,5	63,5	45,5	101	38	± 1,5
19.50/4.0	495,5	101,5	66	139	57	± 2
20.00/2.0	508	51	32,5	101	32	± 1,5
22.00/3.0	559	76	55	139	44,5	± 1,5
22.00/4.0	559	101,5	66	139	57	± 2
22.00/4.5	559	114,5	74	139	63,5	± 2
22.00/4.5-51	559	114	74	190,5	63,5	± 2
24.00/3.0	609,5	76	55	139	44,5	± 1,5
24.00/5.0	609,5	127	86,5	190,5	70	± 2
25.00/3.5	635	89	58	139	51	± 2
26.00/5.0-51	660,5	127	86,5	190,5	70	± 2
27.00/3.5	686	89	58	139	51	± 2
27.00/6.0	686	152,5	97,5	190,5	84	± 2,5
28.00/3.5	711	89	58	139	51	± 2
28.00/4.0	711	101,5	66	139	57	± 2
29.00/6.0	736,5	152,5	97,5	190,5	84	± 2,5
31.00/4.0	787,5	101,5	66	139	57	± 2
32.00/4.0	813	101,5	66	139	57	± 2
32.00/4.5	813	114,5	74	139	63,5	± 2
36.00/4.5	914,5	114,5	74	139	63,5	± 2
40.00/4.5	1 016	114,5	74	139	63,5	± 2

1) For rim diameter code &gt; 49.



1) The tolerance given for the specified rim diameter,  $D$ , is for tyre design purposes only. The actual measurement by circumference is established by using a mandrel and a tape.

2) For rims 8.50/1.3 and 10.00/1.5, tolerance  $+0.5$   
 ~~$-6.5$~~

For larger rims, tolerance  $+0.5$   
 ~~$-13$~~

#### NOTES

[ISO 4250-3:1997](#)


1 This figure applies to rim diameter code 25 (see table 7 for specified rim diameters).  
<https://standards.iteh.ai/catalog/standard/sist/39c60db4-d692-4ffd-aaf1f32d8d769339e/iso-4250-3-1997>

2 Flange and brad seat shall be removable on one side.

**Figure 2 — Contours of 5° full tapered bead seat rims**

**Table 2 — Contours of 5° full tapered bead seat rims**

Rim width code/ flange height code	Dimensions in millimetres							
	A	tol.	G	tol	B	P	$R_2$	$R_3$
8.50/1.3	216	$\pm 5$	33	$\pm 1.5$	25,5	50	23	8
10.00/1.5	254	$\pm 5$	38	$\pm 1.5$	28	59	25,5	8
12.00/1.3	305	$\pm 6.5$	33	$\pm 1.5$	25,5	47	23	10
14.00/1.5	355,5	$\pm 6.5$	38	$\pm 1.5$	28	59	25,5	10
17.00/1.7	432	$\pm 13$	43	$\pm 2$	25,5	60	23	8



- 1) The tolerance given for the specified rim diameter,  $D$ , is for tyre design purposes only. The actual rim measurement by circumference is established by using a mandrel and a tape.

#### NOTES

- 1) This figure applies to rim diameter codes 24 and 25 (see table 7 for specified rim diameters).
- 2) Flange and bead seat shall be removable on one side


**ITEH STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO 4250-3:1997](#)

<https://standards.iteh.ai/catalog/standards/sist/39c60db4-d692-4f1d-aaf1f32d8d769339e/iso-4250-3-1997>

Dimensions in millimetres

Rim width code/ flange height code	A tol.	G ± 1,5	B min.	P min.	H min.	R <sub>2</sub> ± 1,5	Rim diameter code
8.00 TG SDC	203	± 3,5	35,5	17,5	47	6,5	16,5
10.00 VA SDC	254	± 5	43	25,5	59	11	23
12.00/1.3 SDC	305	± 6,5	33	25,5	47	7	23
14.00/1.3 SDC	355,5	± 6,5	33	25,5	47	7	23




- 1) The tolerance given for the specified rim diameter,  $D$ , is for tyre design purposes only. The actual rim measurement by circumference is established by using a mandrel and a tape.
- ISO 4250-3:1997  
<https://standards.iteh.ai/catalog/standards/sist/39660db4-d692-4f1d-aaf1-32d8d769339e/iso-4250-3-1997>

**Figure 4 — Contours of 15° drop-centre rims**

**Table 4 — Contours of 15° drop-centre rims**

Rim width code	Dimensions in millimetres									
	A ± 10	B min.	H <sup>1)</sup>	L <sup>1)</sup>	Q max.	P min.	R <sub>2</sub>	R <sub>3</sub> max.	R <sub>4</sub> max.	R <sub>5</sub> <sup>1)</sup>
20,0	508	57	109,5	106	201,5	120,5	32	19,5	44,5	32
22,0	559	57	109,5	157	201,5	120,5	32	19,5	44,5	32
23,5	597	66,5	131,5	111	248	152	41	25,5	48	38,5
27,0	686	66,5	131,5	200	248	152	41	25,5	48	38,5

1) These dimensions comprise the minimum well envelope for tyre mounting purposes of dimension  $Q$ .



- iTeh STANDARD PREVIEW  
(standards.iteh.ai)**
- 1) The tolerance given for the specified rim diameter,  $D$ , is for tyre design purposes only. The actual rim measurement by circumference is established by using a mandrel and a tape.
  - 2) These dimensions comprise the minimum well envelope for tyre mounting purposes.  
[ISO 4250-3:1997](#)
  - 3) Flange within  $B$  includes [edge radius of 15° min. 15° max.](#) [http://standards.iteh.ai/cod/32d8d769339e/iso-4250-3-1997](#)

NOTE — The figure applies to rim diameter codes 24 and 25 (see table 7 for specified rim diameters).

**Figure 5 — Contours of 5° drop-centre rims**

**Table 5 — Contours of 5° drop-centre rims**

Rim width code flange height code	Dimensions in millimetres																		
	A tol.		G tol.		B min.		P min.		H min.		L min.		Q max.		R <sub>1</sub>	R <sub>2</sub>	R <sub>3</sub>	R <sub>4</sub>	R <sub>5</sub>
9.00/1.5	228,5	$\pm 5,0$	38	$\pm 1,5$	25	36	49	48	25,5	102	19	8	14	22	24 max.	24			
10.00/1.3	254	$\pm 6,0$	33	$\pm 1,5$	25	40	49	45	25,5	102	23	10	12	17	15 min.	24			
12.00/1.3	305	$\pm 6,5$	33	$\pm 1,5$	25	40	40	45	30	90	23	10	12	17	15 min.	25			
13.00/1.4	330	$\pm 6,5$	36	$\pm 1,5$	25	40	40	48	30	102	23	10	12	17	15 min.	25			
14.00/1.3	355,5	$\pm 6,5$	33	$\pm 1,5$	25	40	40	45	30	90	23	10	12	17	15 min.	25			
14.00/1.5	355,5	$\pm 6,5$	38	$\pm 1,5$	27	43	40	52	30	90	25,5	10	12	17	15 min.	25			