

# INTERNATIONAL STANDARD



Capacitors for power electronics

**Standards**  
(<https://standards.iteh.ai>)  
Document Preview

[IEC 61071:2017](#)

<https://standards.iteh.ai/catalog/standards/iec/4b3aabb2-98b5-4d5c-b79b-34cb0d88cea3/iec-61071-2017>



## THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2017 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland

Tel.: +41 22 919 02 11  
Fax: +41 22 919 03 00  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)

### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

### About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

#### IEC Catalogue - [webstore.iec.ch/catalogue](http://webstore.iec.ch/catalogue)

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

#### IEC publications search - [www.iec.ch/searchpub](http://www.iec.ch/searchpub)

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

#### IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

#### Electropedia - [www.electropedia.org](http://www.electropedia.org)

The world's leading online dictionary of electronic and electrical terms containing 20 000 terms and definitions in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

#### IEC Glossary - [std.iec.ch/glossary](http://std.iec.ch/glossary)

65 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

#### IEC Customer Service Centre - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: [csc@iec.ch](mailto:csc@iec.ch).

[IEC 61071:2017](https://standards.iteh.ai/catalog/standards/iec/4b3aabb2-98b5-4d5c-b79b-34cb0d88cea3/iec-61071-2017)

<https://standards.iteh.ai/catalog/standards/iec/4b3aabb2-98b5-4d5c-b79b-34cb0d88cea3/iec-61071-2017>



IEC 61071

Edition 2.0 2017-08  
REDLINE VERSION

# INTERNATIONAL STANDARD



---

Capacitors for power electronics

ITeH Standards  
(<https://standards.iteh.ai>)  
Document Preview

[IEC 61071:2017](#)

<https://standards.iteh.ai/catalog/standards/iec/4b3aabb2-98b5-4d5c-b79b-34cb0d88cea3/iec-61071-2017>

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

---

ICS 31.060.70

ISBN 978-2-8322-4760-0

**Warning! Make sure that you obtained this publication from an authorized distributor.**

## CONTENTS

FOREWORD.....	5
1 Scope.....	7
2 Normative references .....	7
3 Terms and definitions .....	8
4 Service conditions .....	14
4.1 Normal service conditions .....	14
4.1.1 General .....	14
4.1.2 Altitude .....	14
4.1.3 Operating temperature ( $\theta_{\max}$ ).....	14
4.1.4 Operating temperature with forced cooling.....	14
4.2 Unusual service conditions .....	14
5 Quality requirements and tests .....	15
5.1 Test requirements .....	15
5.1.1 General .....	15
5.1.2 Test conditions .....	15
5.2 Classification of tests .....	15
5.2.1 General .....	15
5.2.2 Routine tests .....	15
5.2.3 Type tests.....	16
5.3 Capacitance and $\tan \delta$ measurements (routine test).....	16
5.3.1 Measuring procedure .....	16
5.3.2 Capacitance tolerances .....	17
5.3.3 Loss requirements ( $\tan \delta$ ).....	17
5.4 Measurement of the tangent of the loss angle ( $\tan \delta$ ) of a capacitor (type test).....	17
5.4.1 Measurements .....	17
5.4.2 Loss requirements .....	17
5.5 Voltage test between terminals .....	17
5.5.1 General .....	17
5.5.2 Routine test.....	18
5.5.3 Type test .....	18
5.6 AC voltage test between terminals and case .....	18
5.6.1 Routine test.....	18
5.6.2 Type test .....	19
5.7 Test of internal discharge device.....	19
5.8 Sealing test.....	19
5.9 Surge discharge test .....	19
5.10 Thermal stability test.....	20
5.10.1 General .....	20
5.10.2 Measuring procedure .....	20
5.11 Self-healing test.....	21
5.12 Resonance frequency measurement .....	21
5.13 Environmental testing .....	22
5.13.1 Change of temperature .....	22
5.13.2 Damp heat, steady state .....	22

5.14	Mechanical testing .....	22
5.14.1	Mechanical tests of terminals.....	22
5.14.2	External inspection .....	22
5.14.3	Vibration and shocks .....	22
5.15	Endurance test.....	23
5.15.1	General .....	23
5.15.2	Conditioning of the units before the test.....	23
5.15.3	Initial capacitance and loss factor measurements .....	23
5.15.4	Endurance test .....	23
5.15.5	Final capacitance and $\tan \delta$ measurement .....	24
5.15.6	Acceptance criteria .....	24
5.16	Destruction test.....	25
5.16.1	General .....	25
5.16.2	Test sequence for a.c. capacitors .....	25
5.16.3	Test sequence for d.c. capacitors .....	27
5.17	Disconnecting test on internal fuses.....	29
5.17.1	General .....	29
5.17.2	Disconnecting requirements.....	30
5.17.3	Withstand requirements .....	30
5.17.4	Test procedure .....	30
5.17.5	Capacitance measurement .....	31
5.17.6	Visual checking .....	31
5.17.7	Voltage test .....	31
6	Overloads.....	32
6.1	Maximum permissible voltages .....	32
7	Safety requirements .....	32
7.1	Discharge device .....	32
7.2	Case connections .....	32
7.3	Protection of the environment .....	33
7.4	Other safety requirements.....	33
8	Markings.....	33
8.1	Marking of the units – Rating plate.....	33
	<del>8.1.1 Rating plate .....</del>	<del>33</del>
9	Guidance on installation and operation .....	34
9.1	General.....	34
9.2	Choice of rated voltage .....	34
9.3	Operating temperature .....	35
9.3.1	General .....	35
9.3.2	Installation.....	35
9.3.3	Unusual cooling conditions .....	35
9.4	Special service conditions.....	35
9.5	Overvoltages .....	36
9.6	Overcurrents .....	36
9.7	Switching and protective devices .....	36
9.8	Choice of creepage distance and clearance .....	37
9.8.1	Creepage distance.....	37
9.8.2	Air clearances.....	37

9.9	Connections.....	37
9.10	Parallel connections of capacitors.....	37
9.11	Series connections of capacitors.....	37
9.12	Magnetic losses and eddy currents.....	38
9.13	Guidance for internal fuse and disconnecter protection in capacitors.....	38
9.14	Guidance for unprotected capacitors.....	38
Annex A (informative) Waveforms.....		39
Annex B (normative) Operational limits of capacitors with sinusoidal voltages as a function of frequency and at maximum temperature ( $\theta_{max}$ ).....		41
Annex C (normative) Resonance frequency measuring methods – Examples.....		43
C.1	Method 1.....	43
C.2	Method 2.....	44
Bibliography.....		45
Figure 1 – Destruction test arrangement.....		27
Figure 2 – <i>N</i> source DC – Type 1.....		28
Figure 3 – <i>N</i> source DC – Type 2.....		29
Figure A.1 – Example of waveforms and their circuits.....		40
Figure B.1 – Supply conditions.....		41
Figure C.1 – Measuring circuit.....		43
Figure C.2 – Relation between the voltage across the capacitor and the supply frequency.....		43
Figure C.3 – Discharge current wave shape.....		44
Table 1 – Test voltage between terminals.....		17
Table 2 – Testing the robustness of terminals.....		22
Table 3 – Endurance test.....		24
Table 4 – Destruction test as a function of type of safety system.....		25
Table 5 – Maximum permissible voltages.....		32

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

## CAPACITORS FOR POWER ELECTRONICS

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

**This redline version of the official IEC Standard allows the user to identify the changes made to the previous edition. A vertical bar appears in the margin wherever a change has been made. Additions are in green text, deletions are in strikethrough red text.**

International Standard IEC 61071 has been prepared by IEC technical committee 33: Power capacitors and their applications.

This second edition cancels and replaces the first edition published in 2007. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- Introduction of new terms and definitions
- clarifications for surge discharge test
- indications for measuring procedure during thermal stability test
- clarifications for self-healing test
- clarifications for endurance test
- clarifications for destruction test
- update of normative references
- general editorial review

The text of this International Standard is based on the following documents:

FDIS	Report on voting
33/610/FDIS	33/612/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

**IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.**



# CAPACITORS FOR POWER ELECTRONICS

## 1 Scope

This International Standard applies to capacitors for power electronics applications.

The operating frequency of the systems in which these capacitors are used is usually up to 15 kHz, while the pulse frequencies may be up to 5 to 10 times the operating frequency.

The document distinguishes between AC and DC capacitors which are considered as components when mounted in enclosures.

This document covers an extremely wide range of capacitor technologies for numerous applications, e.g. overvoltage protection, DC and ~~a.c.~~ filtering, switching circuits, ~~d.c.~~ energy storage, auxiliary inverters, etc.

The following are excluded from this document:

- capacitors for induction heat-generating plants operating at frequencies ~~between 40 Hz and 24 000 Hz~~ range up to 50 kHz (see IEC 60110-1 and IEC 60110-2);
- capacitors for motor applications and the like (see IEC 60252-1 and IEC 60252 -2);
- capacitors to be used in circuits for blocking one or more harmonics in power supply networks;
- small AC capacitors as used for fluorescent and discharge lamps (see IEC 61048 and IEC 61049);
- capacitors for suppression of radio interference (see IEC 60384-14);
- shunt capacitors for AC power systems having a rated voltage above 1 000 V (see ~~IEC 60871-1 and IEC 60871-2~~ the IEC 60871 standards);
- shunt power capacitors of the self-healing type for AC systems having a rated voltage up to and including 1 000 V (see IEC 60831-1 and IEC 60831-2);
- shunt power capacitor of the non-self-healing type for AC systems having a rated voltage up to and including 1 000 V (see ~~IEC 60931-1 and IEC 60931-2~~ the IEC 60931 standards);
- electronic capacitors not used in power circuits;
- series capacitors for power systems (see IEC 60143);
- coupling capacitors and capacitors dividers (see IEC 60358);
- capacitors for microwave ovens (see IEC 61270-1);
- capacitors for railway applications (see IEC 61881).

Examples of applications are given in 9.1.

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60068-2-6, *Environmental testing – Part 2-6: Tests – Test Fc: Vibration (sinusoidal)*

IEC 60068-2-14, *Environmental testing – Part 2-14: Tests – Test N: Change of temperature*

IEC 60068-2-20, *Environmental testing – Part 2-20: Tests – Test T: ~~Soldering~~ Test methods for solderability and resistance to soldering heat of devices with leads*

IEC 60068-2-21, *Environmental testing – Part 2-21: Tests – Test U: Robustness of terminations and integral mounting devices*

IEC 60068-2-78, *Environmental testing – Part 2-78: Tests – Test Cab: Damp heat, steady state*

~~IEC 60071-1, *Insulation coordination – Part 1: Definitions, principle and rules*~~

~~IEC 60071-2, *Insulation coordination – Part 2: Application guide*~~

IEC 60269-1, *Low-voltage fuses – Part 1: General requirements*

IEC 60664-1, *Insulation coordination for equipment within low-voltage systems – Part 1: Principles, requirements and tests*

IEC 60695-2-11, *Fire hazard testing – Part 2-11: Glowing/hot-wire based test methods – Glow-wire flammability test method for end-products (GWEPT)*

IEC 60695-2-12, *Fire hazard testing – Part 2-12: Glowing/hot-wire based test methods – Glow-wire flammability index (GWFI) test method for materials*

IEC 60947-1:2007, *Low-voltage switchgear and controlgear – Part 1: General rules*

### 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

#### 3.1

##### **capacitor element (or element)**

device consisting essentially of two electrodes separated by a dielectric

[SOURCE: IEC 60050-436:1990, 436-01-03]

#### 3.2

##### **capacitor unit (or unit)**

assembly of one or more capacitor elements in the same container with terminals brought out

[SOURCE: IEC 60050-436:1990, 436-01-04]

#### 3.3

##### **capacitor bank**

number of capacitor units connected so as to act together

[SOURCE: IEC 60050-436:1990, 436-01-06]

**3.4****capacitor**

general term used when it is not necessary to state whether reference is made to an element, a unit or a capacitor bank

**3.5****capacitor equipment**

assembly of capacitor units and their accessories intended for connection in power electronic equipment

**3.6****capacitor for power electronics**

power capacitor intended to be used in power electronic equipment and capable of operating continuously under sinusoidal and non-sinusoidal current and voltage

**3.7****metal-foil capacitor (non-self-healing)**

capacitor in which the electrodes usually consist of metal foils separated by a dielectric

Note 1 to entry: In the event of a breakdown of the dielectric, the capacitor does not restore itself.

**3.8****self-healing metallized dielectric capacitor**

capacitor, of which at least one electrode consists of a metallic deposit on the dielectric

Note 1 to entry: In the event of local breakdown of the dielectric, the electric properties of the capacitor are rapidly and essentially self-restored.

**3.9****AC capacitor**

capacitor essentially designed for operation with alternating voltage

Note 1 to entry: AC capacitors may be used with DC voltage up to the rated voltage only when authorized by the capacitor manufacturer.

**3.10****DC capacitor**

capacitor essentially designed for operation with direct voltage

Note 1 to entry: DC capacitors may be used with a specified AC voltage only where authorized by the capacitor manufacturer.

**3.11****model capacitor**

unit which simulates a complete unit or element in an electrical test, without reducing the severity of the electrical, thermal or mechanical conditions

Note 1 to entry: The model unit may be of a different size from the complete unit.

Note 2 to entry: The combined sum of stresses should always be considered, for instance the sum of temperature and mechanical conditions as well as electrical stresses.

**3.12****internal (element) fuse**

fuse connected inside a capacitor unit, in series with an element or a group of elements

[SOURCE: IEC 60050-436:1990, 436-03-16]

### 3.13 safety devices

#### 3.13.1

##### **overpressure disconnecter**

disconnecting device inside a capacitor, designed to interrupt the current path in case of abnormal increase of internal overpressure

#### 3.13.2

##### **overpressure detector**

device designed to detect abnormal increase of the internal pressure, usually used to operate an electrical switch and indirectly interrupt the current path

#### 3.13.3

##### **segmented metallization design**

**pattern** design of the metal layer over the dielectric shaped in a way to allow a small part of it to be isolated in case of local short circuit or breakdown, in order to restore the full functionality of the unit with a negligible loss of capacitance

#### 3.13.4

##### **special unsegmented metallization design**

design of the metal layer over the dielectric shaped in a way that safe self-healing features operating at a voltage up to  $U_s$  guarantee the full functionality of the unit with a negligible loss of capacitance.

### 3.14

#### **safety protection**

##### **protected capacitor**

capacitor that can be submitted to the destruction test as described at 5.16

Note 1 to entry: protected capacitors alone are not sufficient to prevent all possible dangers in case of malfunction.

### 3.15

#### **unprotected capacitor**

capacitor that don't meet the destruction test as described at 5.16

### 3.16

#### **discharge device of a capacitor**

device which may be incorporated in a capacitor, capable of reducing the voltage between the terminals practically to zero, within a given time, after the capacitor has been disconnected from a network

[SOURCE: IEC 60050-436:1990, 436-03-15, modified ("to a given value" replaced by "practically to zero")]

### 3.17

#### **rated AC voltage**

$U_N$

maximum operating peak recurrent voltage of either polarity of a reversing type waveform for which the capacitor has been designed

Note 1 to entry: The waveform can have many shapes. Examples are given in Annex A.

Note 2 to entry: The mean value of the waveform may be positive or negative.

Note 3 to entry: It is important to note that the rated AC voltage is not an r.m.s. value.

**3.18  
rated DC voltage** $U_{\text{NDC}}$ 

maximum operating peak voltage of either polarity but of a non-reversing type waveform, for which the capacitor has been designed, for continuous operation

Note 1 to entry: Damping capacitors, for gate turn-off thyristor (GTO) can be regarded as DC capacitors with a ripple voltage equal to the rated DC voltage  $U_{\text{NDC}} = U_r$ .

In the case of reversal voltage ( $U_{\text{rev}}$ ), the use should be agreed between user and manufacturer.

Note 2 to entry: If the reversal voltage is small (less than 10 %), the voltage waveform can be considered to be non-reversing. For test purposes,  $U_{\text{NDC}}$  and  $U_r$  should be increased by  $U_{\text{rev}}$ , the reversal voltage.

**3.19  
ripple voltage** $U_r$ 

peak-to-peak alternating component of the unidirectional voltage

**3.20  
non-recurrent surge voltage** $U_s$ 

peak voltage induced by a switching or any other disturbance of the system which is allowed for a limited number of times and for durations shorter than the basic period

**3.21  
insulation voltage** $U_i$ 

r.m.s. value of the sine wave voltage designed for the insulation between terminals of capacitors to case or earth

**3.22  
maximum peak current** $\hat{i}$ 

maximum repetitive peak current that can occur during continuous operation

**3.23  
maximum current** $I_{\text{max}}$ 

maximum r.m.s. current for continuous operation

**3.24  
maximum surge current** $\hat{i}_s$ 

peak non-repetitive current induced by switching or any other disturbance of the system which is allowed for a limited number of times, for durations shorter than the basic period

**3.25  
pulse frequency** $f_p$ 

repetition rate of periodic current pulses

**3.26  
current pulse width** $\tau$ 

time of current flow during charging or discharging from one voltage value to another, of the capacitor

Note 1 to entry: Pulse current waveform examples are shown in Annex A.

**3.27****resonance frequency** $f_r$ 

lowest frequency at which the impedance of the capacitor becomes minimum

**3.28****duty cycle****3.28.1****continuous duty**

operation time such that a capacitor is at thermal equilibrium for most of the time

**3.28.2****intermittent duty**

discontinuous working or operation with variable loads which should be described in terms of ON/OFF or HIGH/LOW periods with their durations

**3.27****highest operating temperature**

~~temperature of the hottest point on the case of the capacitor when in thermal equilibrium~~

**3.29****thermal equilibrium**

state of a capacitor when the temperature measured anywhere on its case or internally is less than 3K above or below that temperature which would be reached after waiting an infinitely long time under fixed conditions of ambient temperature, cooling, and internal power loss

**3.30****thermal time constant**

measure of the time required for a capacitor to reach thermal equilibrium after a change in ambient temperature, cooling, or internal power loss

**3.31****lowest operating temperature** $\theta_{\min}$ 

lowest temperature of the dielectric at which the capacitor may be energized

**3.32****container temperature rise** $\Delta\theta_{\text{case}}$ 

difference between the temperature of the hottest point of the container and the temperature of the cooling air

**3.33****cooling-air temperature** $\theta_{\text{amb}}$ 

temperature of the cooling air measured at the hottest position of the capacitor, under steady-state conditions, midway between two units

Note 1 to entry: If only one unit is involved, it is the temperature measured at a point approximately 0,1 m away from the capacitor container and at two-thirds of the height from its base.

**3.33.1****outlet fluid temperature for forced-cooled capacitors**

temperature of the cooling fluid as it leaves the capacitor, measured at the hottest point