

Edition 2.0 2014-10

INTERNATIONAL STANDARD

Liquid crystal displayedevices ANDARD PREVIEW Part 4-1: Matrix colour LCD modules – Essential ratings and characteristics (Standards.iten.al)

IEC 61747-4-1:2014 https://standards.iteh.ai/catalog/standards/sist/6ff862cb-f319-470a-870d-7f6a7caf2e30/iec-61747-4-1-2014





THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2014 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office Tel.: +41 22 919 02 11 3, rue de Varembé Fax: +41 22 919 03 00

CH-1211 Geneva 20 info@iec.ch Switzerland www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications. standard

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and 7-4f you wish to give us your feedback on this publication or

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in 14 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

More than 55 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

also once a month by emailttps://standards.itch.ai/catalog/standarmeed.further/assistance/please@contact the Customer Service 7f6a7caf2e30/iec-6 Centre: csc@iec.ch.



Edition 2.0 2014-10

INTERNATIONAL STANDARD

Liquid crystal displayed evices ANDARD PREVIEW Part 4-1: Matrix colour LCD modules - Essential ratings and characteristics

<u>IEC 61747-4-1:2014</u> https://standards.iteh.ai/catalog/standards/sist/6ff862cb-f319-470a-870d-7f6a7caf2e30/iec-61747-4-1-2014

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PRICE CODE

J

ICS 31.120 ISBN 978-2-8322-1890-7

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

F	OREWO	RD	.3
IN	TRODU	ICTION	.5
1	Scop	e	.6
2	Normative references		
3	Matrix colour liquid crystal display modules		
	3.1 Principles and material used		.6
	3.2	Modes of operation	.6
	3.2.1	Addressing mode of operation	.6
	3.2.2	Optical mode of operation	.6
	3.3	Details of outline	.6
	3.3.1	Material, mechanical description	.6
	3.3.2	Method of connection	.6
	3.3.3	Outline drawing and dimensions	.7
	3.3.4	Pin layout and/or assignment	.7
	3.3.5	Preferred or designed viewing direction	.7
	3.4	Limiting values (absolute maximum rating system) over the operating temperature range, unless otherwise stated	.7
	3.4.1	Minimum and maximum ambient operating temperature (T_{Op})	.7
	3.4.2	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	.7
	3.4.3	Minimum and maximum value of supply voltages for logic and LCD drive or supply voltage(s) for module	.7
	3.4.4	Minimum and maximum value of input signal voltage (V_{IN})	.7
	3.4.5	Where appropriate himinimum and maximum value of integrated light source voltage ($V_{\rm L}$ S) a 2 $^{$.7
	3.4.6		.7
	3.5	Electrical and optical characteristics	.7
	3.6	Supplementary information	.9
	3.6.1	Timing characteristics, timing of logic voltages and data/format interface specification	.9
	3.6.2	Supply voltages sequence condition, where appropriate	.9
	3.6.3	Operating voltage range, if appropriate, as a function of temperature at specified contrast ratio	.9
	3.6.4	Handling and operating information	.9
	3.6.5	Precautions with respect to electrostatic discharges	.9
	3.6.6	Precautions of installation, mechanical and/or electrical	.9
	3.6.7	Safety information	.9
	3.6.8	Characterization of diffused and regular reflectance and transmittance	.9
Та	able 1 –	Electrical and optical characteristics of matrix colour LCD modules	.7

INTERNATIONAL ELECTROTECHNICAL COMMISSION

LIQUID CRYSTAL DISPLAY DEVICES -

Part 4-1: Matrix colour LCD modules – Essential ratings and characteristics

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter. https://standards.iteh.ai/catalog/standards/sist/6ff862cb-f319-470a-870d-
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61747-4-1 has been prepared by IEC technical committee 110: Electronic display devices.

This second edition cancels and replaces the first edition published in 2004. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition: Adding the contents of the IEC 61747 series, adding the TFT technical kinds, revising the electrical and optical characteristics in Table 1 and correcting some editorial errors.

This standard is to be read in conjunction with IEC 61747-1-1.

The text of this standard is based on the following documents:

FDIS	Report on voting
110/589/FDIS	110/611/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 61747 series, published under the general title *Liquid crystal display devices*, can be found on the IEC website.

Future standards in this series will carry the new general title as cited above. Titles of existing standards in this series will be updated at the time of the next edition.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended. (standards.iteh.ai)

A bilingual version of this publication may be issued at a later date.

https://standards.iteh.ai/catalog/standards/sist/6ff862ch_f319_470a_870d_

The National Committees are requested to note that for this publication the stability date is 2020.

THIS TEXT IS INCLUDED FOR THE INFORMATION OF THE NATIONAL COMMITTEES AND WILL BE DELETED AT THE PUBLICATION STAGE.

INTRODUCTION

IEC 61747 consists of the following parts, under the general title "Liquid crystal display devices":

- Part 1-1: Generic Generic specification;
- Part 1-2: Generic Terminology and letter symbols;
- Part 2: Liquid crystal display modules Sectional specification¹;
- Part 2-1: Passive matrix monochrome LCD modules Blank detail specification;
- Part 2-2: Matrix colour LCD modules Blank detail specification;
- Part 3: Liquid crystal display (LCD) cells Sectional specification²;
- Part 3-1: Liquid crystal display (LCD) cells Blank detail specification3;
- Part 4: Liquid crystal display modules and cells Essential ratings and characteristics;
- Part 4-1: Matrix colour LCD modules Essential ratings and characteristics;
- Part 10-1: Environmental, endurance and mechanical test methods Mechanical;
- Part 10-2: Environmental, endurance and mechanical test methods Environmental and endurance;
- Part 20-1: Visual inspection Monochrome liquid crystal display cells (excluding all active matrix liquid crystal display cells);
- Part 20-2: Visual inspection Monochrome matrix liquid crystal display modules (excluding all active matrix liquid crystal display modules)⁴;
- Part 20-3: Visual inspection Active matrix colour liquid crystal display modules5;
- Part 30-1: Functional measurement methods for liquid crystal display modules Transmissive type; IEC 61747-4-1:2014
- Part 30-4: Measuring methods of LCD modules with dynamic backlight units6;
- Part 40-1: Mechanical testing guidelines for display cover glass for mobile devices;
- Part 40-2: Mechanical testing of display cover glass for mobile devices Uni-axial flexural strength (4-point bend)⁷;
- Part 40-3: Mechanical testing of display cover glass for mobile devices Biaxial flexural energy-to-failure (ball drop)8;
- Part 40-4: Mechanical testing of display cover glass for mobile devices Biaxial flexural strength (ring-on-ring)9;

¹ To be published.

² To be published.

³ To be published.

⁴ To be published.

⁵ Under consideration.

⁶ Under consideration.

⁷ To be published.

⁸ To be published.

⁹ To be published.

LIQUID CRYSTAL DISPLAY DEVICES -

Part 4-1: Matrix colour LCD modules – Essential ratings and characteristics

1 Scope

This part of IEC 61747 describes the essential ratings and characteristics of matrix colour liquid crystal display (LCD) modules.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61747-1-1, Liquid crystal display devices – Part 1-1: Generic – Generic specification

iTeh STANDARD PREVIEW 3 Matrix colour liquid crystal display modules (standards.iteh.ai)

3.1 Principles and material used

Example: a thin film transistor (TFT) (amorphous silicon, polycrystalline silicon, oxide, organic) active matrix display cell with electronic circuits and connector pins.

Where appropriate, a type of integrated light source.

3.2 Modes of operation

3.2.1 Addressing mode of operation

Example: passive matrix, active matrix, TFT mode, thin film diode (TFD) mode, etc.

3.2.2 Optical mode of operation

- Illumination mode: for example reflective, transmissive, transflective.
- Number of colours.
- Number of grey levels.

Normally white, normally black.

3.3 Details of outline

3.3.1 Material, mechanical description

- Examples: glass, plastic, metal, etc.
- Construction: for example integrated light source, bezel structure.

3.3.2 Method of connection

Connectors, flex cable or connection pins, etc.

3.3.3 Outline drawing and dimensions

- Overall dimensions.
- Viewing area and display centre.

3.3.4 Pin layout and/or assignment

Type of connectors.

3.3.5 Preferred or designed viewing direction

- 3.4 Limiting values (absolute maximum rating system) over the operating temperature range, unless otherwise stated
- 3.4.1 Minimum and maximum ambient operating temperature (T_{op})
- 3.4.2 Minimum and maximum storage temperature (T_{stg})
- 3.4.3 Minimum and maximum value of supply voltages for logic and LCD drive or supply voltage(s) for module
- 3.4.4 Minimum and maximum value of input signal voltage (V_{IN})
- 3.4.5 Where appropriate, minimum and maximum value of integrated light source voltage $(V_{\rm LS})$
- 3.4.6 Where appropriate, maximum soldering temperature (T_{sld})

The maximum soldering time and minimum distance to module package should be specified.

3.5 Electrical and optical characteristics

The following characteristics should be spectated in the following characteristics should be spectated by the following characteristics of the following characteristics are specifically specifically be spectated by the following characteristics are specifically specifically be specifically specifically be specifically specifically be specifically specifically specifically be specifically specifically be specifically sp

Table 1 – Electrical and optical characteristics of matrix colour LCD modules

Reference	Characteristics Supply voltages	Condition at $T_{op} = 25$ unless otherwise specified	Symbol	Requirements	
3.5.1					
	Supply voltage for logic drive		$V_{\sf DD} - V_{\sf SS}$	Min.	Max.
	Supply voltage for LCD drive		$V_{DD} - V_{EE}$	Min.	Max.
			or $V_{\sf EE}$ – $V_{\sf SS}$		
			or V_{DD} – V_{O}		
			or $V_{O} - V_{SS}$		
	Supply voltage(s) for module		V_{MDL}	Min.	Max.
3.5.2	Input signal voltages		V_{IN}	Min.	Max.
	High level input signal voltage		V_{INH}	Min.	Max.
	Low level input signal voltage		V_{INL}	Min.	Max.
	Input analogue video signals		V_{VID}	Min.	Max.
	(where appropriate)				
3.5.3	Operating backlight voltage		V_{BL}	Min.	Max.
	(where appropriate)				
	Discharge ignition voltage of				
	backlight (where appropriate)		V_{BLIG}	Min.	