

### SLOVENSKI STANDARD SIST EN 62127-1:2008 01-januar-2008

BUXca Yý U.

SIST EN 61101:2002 SIST EN 61220:2002 SIST EN 62092:2002

I `lf Unj c\_'!'<]Xfc Zcb]'!'%"XY`.'A Yf]hj Y']b'\_Uf U\_hYf]nUV]/U'a YX]VI]bg\_]\ 'i `lf Unj c b]\ dc`^Xc'(\$'A<n'f\partial 7' \* &%&+!%&\partial 8+\partial 4

Ultrasonics - Hydrophones - Part 1: Measurement and characterization of medical ultrasonic fields up to 40 MHz (IEC 62127-1:2007)

Teh STANDARD PREVIEW

Ultraschall - Hydrophone - Teil (SMessung und Charakterisierung von medizinischen Ultraschallfeldern bis zu 40 MHz (IEC 62127-1:2007)

SIST EN 62127-1:2008

https://standards.iteh.ai/catalog/standards/sist/8af72f2c-e80b-4dfb-89d6-

Ultrasons - Hydrophones - Partie 17 Mesures et caractérisation des champs ultrasonores médicaux jusqu'a 40 Mhz (IEC 62127-1:2007)

Ta slovenski standard je istoveten z: EN 62127-1:2007

ICS:

11.040.01 Medicinska oprema na Medical equipment in general

splošno

17.140.50 Elektroakustika Electroacoustics

SIST EN 62127-1:2008 en,de

# iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 62127-1:2008</u> https://standards.iteh.ai/catalog/standards/sist/8af72f2c-e80b-4dfb-89d6-470751cfd7e8/sist-en-62127-1-2008

### **EUROPEAN STANDARD**

### EN 62127-1

## NORME EUROPÉENNE **EUROPÄISCHE NORM**

October 2007

ICS 17.140.50

Partially supersedes EN 61101:1993, EN 61102:1993 + A1:1994, EN 61220:1995 and EN 62092:2001

**English version** 

### **Ultrasonics** -**Hydrophones** -Part 1: Measurement and characterization of medical ultrasonic fields up to 40 MHz

(IEC 62127-1:2007)

Ultrasons -Hydrophones -Partie 1: Mesures et caractérisation des champs ultrasonores médicaux jusqu'à 40 Mhz (CEI 62127-1:2007) Teh STANDARD PRE VIEW

Ultraschall -Hydrophone -Teil 1: Messung und Charakterisierung von medizinischen Ultraschallfeldern bis zu 40 MHz

(standards.iteh.ai)

This European Standard was approved by CENELEC on 2007-09-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

## **CENELEC**

European Committee for Electrotechnical Standardization Comité Européen de Normalisation Electrotechnique Europäisches Komitee für Elektrotechnische Normung

Central Secretariat: rue de Stassart 35, B - 1050 Brussels

#### **Foreword**

The text of document 87/352/CDV, future edition 1 of IEC 62127-1, prepared by IEC TC 87, Ultrasonics, was submitted to the IEC-CENELEC parallel Unique Acceptance Procedure and was approved by CENELEC as EN 62127-1 on 2007-09-01.

EN 62127-1, EN 62127-2 and EN 62127-3 are being published simultaneously. Together these European Standards cancel and replace EN 61101:1993, EN 61102:1993 + A1:1994, EN 61220:1995 and EN 62092:2001.

The following dates were fixed:

 latest date by which the EN has to be implemented at national level by publication of an identical national standard or by endorsement

(dop) 2008-06-01

 latest date by which the national standards conflicting with the EN have to be withdrawn

(dow) 2010-09-01

Annex ZA has been added by CENELEC.

The text of the International Standard IEC 62127-1:2007 was approved by CENELEC as a European Standard without any modification.

**Endorsement notice** 

(standards.iteh.ai)
In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 60601-2-37	NOTE https://standar	Harmonized as EN 60601-2-37;2001 (not modified). ds. itel. avcatalog/standards/sis/8a1/2f2c-e80b-4dfb-89d6-
IEC 61157	-	470751cfd7e8/sist-en-62127-1-2008 Harmonized as EN 61157:1994 (not modified).
IEC 61161	NOTE	Harmonized as EN 61161:2007 (not modified).
IEC 62359	NOTE	Harmonized as EN 62359:2005 (not modified).

\_\_\_\_\_

## Annex ZA (normative)

# Normative references to international publications with their corresponding European publications

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	EN/HD	<u>Year</u>
IEC 60050-801	1994	International Electrotechnical Vocabulary (IEV) - Chapter 801: Acoustics and electroacoustics	-	-
IEC 60565	_1)	Underwater acoustics - Hydrophones - Calibration in the frequency range 0,01 Hz to 1 MHz	EN 60565	2007 <sup>2)</sup>
IEC/TR 60854	1986	Methods of measuring the performance of ultrasonic pulse-echo diagnostic equipment	-	-
IEC 61689	- <sup>1)</sup> <b>iT</b> (	Ultrasonics - Physiotherapy systems - Field specifications and methods of measurement in the frequency range 0,5 MHz to 5 MHz	<b>L</b> N 61689	2007
IEC 61828	_1) https://sta	Ultrasonics - Focusing transducers - Definitions and measurement methods for the transmitted fields/sist/8af/2i2c-e80b-4dfb 470751cfd7e8/sist-en-62127-1-2008	EN 61828 -89d6-	2001 <sup>2)</sup>
IEC 61846	_1)	Ultrasonics - Pressure pulse lithotripters - Characteristics of fields	EN 61846	1998 <sup>2)</sup>
IEC 61847	_1)	Ultrasonics - Surgical systems - Measurement and declaration of the basic output characteristics	EN 61847	1998 <sup>2)</sup>
IEC 62127-2	_1)	Ultrasonics - Hydrophones - Part 2: Calibration for ultrasonic fields up to 40 MHz	EN 62127-2	2007 <sup>2)</sup>
IEC 62127-3	_1)	Ultrasonics - Hydrophones - Part 3: Properties of hydrophones for ultrasonic fields up to 40 MHz	EN 62127-3	2007 <sup>2)</sup>
ISO 16269-6	2005	Statistical interpretation of data - Part 6: Determination of statistical tolerance intervals	-	-
ISO/IEC Guide 98	1995	Guide to the expression of uncertainty in measurement	-	-

<sup>1)</sup> Undated reference.

<sup>&</sup>lt;sup>2)</sup> Valid edition at date of issue.

# iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 62127-1:2008</u> https://standards.iteh.ai/catalog/standards/sist/8af72f2c-e80b-4dfb-89d6-470751cfd7e8/sist-en-62127-1-2008



Edition 1.0 2007-08

# INTERNATIONAL STANDARD

# Ultrasonics – Hydrophones FANDARD PREVIEW Part 1: Measurement and characterization of medical ultrasonic fields up to 40 MHz

SIST EN 62127-1:2008 https://standards.iteh.ai/catalog/standards/sist/8af72f2c-e80b-4dfb-89d6-470751cfd7e8/sist-en-62127-1-2008

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PRICE CODE XC

ICS 17.140.50 ISBN 2-8318-9276-7

### CONTENTS

FO	REW	ORD		5	
INT	ROD	UCTION		7	
1	Scor	e and o	bject	8	
2	•		ferences		
3			itions and symbols		
			•		
4		•	ols		
5			t requirements		
	5.1	-	ements for hydrophones and amplifiers		
		5.1.1	Introduction		
		5.1.2	General		
		5.1.3	Sensitivity of a hydrophone		
		5.1.4	Directional response of a hydrophone		
		5.1.5	Effective hydrophone radius		
		5.1.6	Choice of the size of a hydrophone active element		
		5.1.7	Bandwidth		
		5.1.8	Linearity Hydrophone signal amplifier RD PREVIEW	28	
		5.1.9			
	- 0	5.1.10	Hydrophone cable length and amplifiers ements for positioning and water baths	29	
	5.2				
		5.2.1	General SIST EN 62127-12008	29	
		5.2.2 5.2.3	Positioning Systems atalog/standards/sist/8af72f2c-e80b-4dfb-89d6		
	5.3		ements for data acquisition and analysis systems		
	5.4		mendations for ultrasonic equipment being characterized		
6			it procedure		
U			·		
	6.1 6.2		al		
	0.2	6.2.1	ation and alignment  Preparation		
		6.2.1	Aligning an ultrasonic transducer and a hydrophone		
	6.3 6.4		rement		
			is		
		6.4.1	Corrections for restricted bandwidth and spatial resolution		
		6.4.2	Uncertainties		
7	Rear		eterization		
•	7.1 General				
	7.1		y pressure parameters		
	1.2	7.2.1	General		
		7.2.1	Peak-compressional acoustic pressure and peak-rarefactional		
		1.2.2	acoustic pressure	36	
		7.2.3	Spatial-peak rms acoustic pressure		
		7.2.4	Non-linear propagation parameter	36	
		7.2.5	Intensity parameters using instantaneous acoustic pressure	37	
		7.2.6	Intensity parameters using pulse-pressure-squared integral		
		7.2.7	Derived ultrasonic power		
8	Requ	uirement	s for specific ultrasonic fields	40	

	8.1	Genera	al	40
	8.2	Diagno	ostic fields	40
		8.2.1	Simplified procedures and guidelines	40
		8.2.2	Pulsed wave diagnostic equipment	
		8.2.3	Continuous wave diagnostic equipment	
	8.3	•	by fields	
		8.3.1	Physiotherapy equipment	
		8.3.2	Hyperthermia	
	8.4	•	al fields	42
		8.4.1	Lithotripters and pressure pulse sources for other therapeutic purposes	42
		8.4.2	Low frequency surgical applications	
	8.5		from other medical applications	
9	Com		statement	
	9.1		al	
	9.2		um probable values	
	9.3		ing	
		·		
Anı	nex A	(informa	ative) General rationale	45
			ative) Hydrophones and positioning	
Anı	nex C	(informa	ative) Acoustic pressure and intensity REVIEW	53
Anı	nex D	(informa	ative) Voltage to pressure conversion I	55
Anı	nex E	` (informa	ative) Voltage to pressure conversion	60
			ative) Acoustic output parameters for multi-mode medical ultrasonic	
fiel	ds in t	he abse	encerof/scarlaframe:synchgonizationist/8af72f2c-e80h-4dfb-89d6-	62
Anı	nex G	(informa	ative) Propagation medium and degassing	68
			ative) Specific ultrasonic fields	
			tive) Assessment of uncertainty in the acoustic quantities obtained by surements	72
Anı	nex J (	(informa	ative) Transducer and hydrophone positioning systems	74
Anı	nex K	(informa	ative) Beamwidth midpoint method	75
Bib	liogra	phy		76
			matic diagram of the different planes and lines in an ultrasonic field	4.4
•			828)	
_			matic diagram of the method of determining pulse duration	
_			ow diagram of the hydrophone deconvolution process	
Fig	ure D.	2 – Exa	imple of waveform deconvolution	59
			ematic diagram of the ultrasonic transducer and hydrophone degrees	7.4
or I	reedo			/ 4
Tal	_ 1 <u>م</u> اد	Acquet	tic parameters appropriate to various types of medical ultrasonic	
			parameters appropriate to various types of medical ditrasonic	34
			cal specification data for hydrophones, in this case given at 1 MHz	
			perties of distilled or de-ionized water as a function of temperature	
		•	nod of conversion from a double- to a single-sided spectrum	

62127-1 ©	IEC:2007(E)
-----------	-------------

Table D.2 – Method of conversion from a single- to a double-sided spectrum	58
Table F.1 – Main parameters defined in IEC standards	63
Table F.2 – List of parameters that are to be used or are to be deleted	64
Table K.1 – dB beamwidth levels for determining midpoints	75

# iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 62127-1:2008</u> https://standards.iteh.ai/catalog/standards/sist/8af72f2c-e80b-4dfb-89d6-470751cfd7e8/sist-en-62127-1-2008

#### INTERNATIONAL ELECTROTECHNICAL COMMISSION

#### **ULTRASONICS - HYDROPHONES -**

## Part 1: Measurement and characterization of medical ultrasonic fields up to 40 MHz

#### **FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in https://standards.itch.ai/catalog/standards/sist/8af/2/2c-e80b-4dib-89d6-
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62127-1 has been prepared by IEC technical committee 87: Ultrasonics.

IEC 62127-1, IEC 62127-2 and IEC 62127-3 are being published simultaneously. Together these cancel and replace IEC 60866:1987, IEC 61101:1991, IEC 61102:1991, IEC 61220:1993 and IEC 62092:2001.

The text of this standard is based on the following documents:

Enquiry draft	Report on voting
87/352/CDV	87/371/RVC

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of IEC 62127 series, published under the general title *Ultrasonics* – *Hydrophones*, can be found on the IEC website.

NOTE Words in **bold** in the text are defined in Clause 3.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition; or
- · amended.

A bilingual version of this publication may be issued at a later date.

# iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 62127-1:2008 https://standards.iteh.ai/catalog/standards/sist/8af72f2c-e80b-4dfb-89d6-470751cfd7e8/sist-en-62127-1-2008

#### INTRODUCTION

The main purpose of this part of IEC 62127 is to define various acoustic parameters that can be used to specify and characterize ultrasonic fields propagating in liquids, and, in particular, water, using hydrophones. Measurement procedures are outlined that may be used to determine these parameters. Specific device related measurement standards, for example IEC 61689, IEC 61157, IEC 61847 or IEC 62359, can refer to this standard for appropriate acoustic parameters.

The philosophy behind this standard is the specification of the acoustic field in terms of acoustic pressure parameters, acoustic pressure being the primary measurement quantity when piezoelectric hydrophones are used to characterize the field. Of course, if other measurement devices come into use in the future, a new standard with additional definitions and procedures will be necessary. Examples of such devices would be thermistors, thermocouples or optical hydrophones.

Intensity parameters are specified in this standard, but these are regarded as derived quantities that are meaningful only under certain assumptions related to the ultrasonic field being measured.

# iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 62127-1:2008 https://standards.iteh.ai/catalog/standards/sist/8af72f2c-e80b-4dfb-89d6-470751cfd7e8/sist-en-62127-1-2008

#### **ULTRASONICS - HYDROPHONES -**

## Part 1: Measurement and characterization of medical ultrasonic fields up to 40 MHz

#### 1 Scope and object

This part of IEC 62127 specifies methods of use of calibrated hydrophones for the measurement in liquids of acoustic fields generated by ultrasonic medical equipment operating in the frequency range up to 40 MHz.

The objectives of this standard are:

- to define a group of acoustic parameters that can be measured on a physically sound basis;
- to define a second group of parameters that can be derived under certain assumptions from these measurements, and called derived intensity parameters;
- to define a measurement procedure that may be used for the determination of acoustic pressure parameters;
- to define the conditions under which the measurements of acoustic parameters can be made in the frequency range up to 40 MHz using calibrated hydrophones;
- to define procedures for correcting, for limitations caused by the use of hydrophones with finite bandwidth and finite active element size.

NOTE 1 Throughout this standard, SI units are used. In the specification of certain parameters, such as beam areas and intensities, it may be convenient to use decimal multiples or submultiples. For example beam area may be specified in cm<sup>2</sup> and intensities in Wicm<sup>2</sup> for mW/cm<sup>2</sup> dards/sist/8af72f2c-e80b-4dfb-89d6-

 $\frac{470751 \text{cfd} 7\text{e}8/\text{sist-en-}62127\text{-}1\text{-}2008}{\text{NOTE 2}}$  The hydrophone as defined may be of a piezoelectric or an optic type. The introduction however implies that optical hydrophones are not covered.

#### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-801:1994, International Electrotechnical Vocabulary – Chapter 801: Acoustics and electroacoustics

IEC 60565, Underwater acoustics – Hydrophones – Calibration in the frequency range 0,01 Hz to 1 MHz

IEC/TR 60854:1986, Methods of measuring the performance of ultrasonic pulse-echo diagnostic equipment

IEC 61689, Ultrasonics – Physiotherapy systems – Performance requirements and methods of measurement in the frequency range 0,5 MHz to 5 MHz

IEC 61828, Ultrasonics – Focusing transducers – Definitions and measurement methods for the transmitted fields

IEC 61846, Ultrasonics – Pressure pulse lithotripters – Characteristics of fields

IEC 61847, Ultrasonics – Surgical systems – Measurement and declaration of the basic output characteristics

IEC 62127-2, Ultrasonics – Hydrophones – Part 2: Calibration for ultrasonic fields up to 40 MHz

IEC 62127-3, Ultrasonics – Hydrophones – Part 3: Properties of hydrophones for ultrasonic fields up to 40 MHz

ISO 16269-6:2005, Statistical interpretation of data – Part 6: Determination of statistical tolerance intervals

ISO, Guide to the expression of uncertainty in measurement. Geneva, Switzerland: International Organization for Standardization (ISO), 1995

NOTE The following standards rely on the proper use of this document.

IEC 61157, Standard means for the reporting of the acoustic output of medical diagnostic ultrasonic equipment

IEC 62359, Ultrasonics – Field characterization – Test methods for the determination of thermal and mechanical indices related to medical diagnostic ultrasonic fields

IEC 61847, Ultrasonics - Surgical systems - Measurement and declaration of the basic output characteristics.

## 3 Terms, definitions and symbols DARD PREVIEW

For the purposes of this document, the terms and definitions given in IEC 62127-2, IEC 62127-3 and the following apply. It also includes definitions related to subjects in this document to be used in particular medical ultrasound device standards.

SIST EN 62127-1:2008

### 3.1 https://standards.iteh.ai/catalog/standards/sist/8af72f2c-e80b-4dfb-89d6-

#### acoustic pulse waveform

470751cfd7e8/sist-en-62127-1-2008

temporal waveform of the instantaneous acoustic pressure at a specified position in an acoustic field and displayed over a period sufficiently long to include all significant acoustic information in a single pulse or tone-burst, or one or more cycles in a continuous wave

NOTE 1 Temporal waveform is a representation (e.g oscilloscope presentation or equation) of the **instantaneous acoustic pressure**.

NOTE 2 Definition adopted from IEC 60469-1.

#### 3.2

#### acoustic repetition period

arp

**pulse repetition period** for non-automatic scanning systems and the **scan repetition period** for automatic scanning systems, equal to the time interval between corresponding points of consecutive cycles for continuous wave systems

NOTE The acoustic repetition period is expressed in seconds (s).

#### 3.3

#### acoustic frequency

#### acoustic-working frequency

frequency of an acoustic signal based on the observation of the output of a hydrophone placed in an acoustic field at the position corresponding to the spatial-peak temporal-peak acoustic pressure

NOTE 1 The signal is analysed using either the **zero-crossing acoustic-working frequency** technique or a spectrum analysis method. Acoustic-working frequencies are defined in 3.3.1 and 3.3.2.