



Edition 1.0 2016-04

INTERNATIONAL STANDARD

NORME INTERNATIONALE



Mechanical structures for electrical and electronic equipment – Thermal management for cabinets in accordance with IEC 60297 and IEC 60917 series – Part 5: Cooling performance evaluation for indoor cabinets

Structures mécaniques pour équipements électriques et électroniques – Gestion thermique pour les armoires conformes aux séries IEC 60297 et IEC 60917 – Partie 5: Évaluation des performances de refroidissement pour les baies intérieures





THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2016 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office	Tel.: +41 22 919 02 11
3, rue de Varembé	Fax: +41 22 919 03 00
CH-1211 Geneva 20	info@iec.ch
Switzerland	www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a 10 variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications. 0b708dbc47ec/ecc

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing 20/000 terms and definitions in English and French, with equivalent terms in 15 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

65_000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Catalogue IEC - webstore.iec.ch/catalogue

Application autonome pour consulter tous les renseignements bibliographiques sur les Normes internationales, Spécifications techniques, Rapports techniques et autres documents de l'IEC. Disponible pour PC, Mac OS, tablettes Android et iPad.

Recherche de publications IEC - www.iec.ch/searchpub

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études,...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire en ligne de termes électroniques et électriques. Il contient 20 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans 15 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Glossaire IEC - std.iec.ch/glossary

65 000 entrées terminologiques électrotechniques, en anglais et en français, extraites des articles Termes et Définitions des publications IEC parues depuis 2002. Plus certaines entrées antérieures extraites des publications des CE 37, 77, 86 et CISPR de l'IEC.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: csc@iec.ch.



Edition 1.0 2016-04

INTERNATIONAL STANDARD

NORME INTERNATIONALE



Mechanical structures for electrical and electronic equipment – Thermal management for cabinets in accordance with IEC 60297 and IEC 60917 series – Part 5: Cooling performance evaluation for indoor cabinets

IEC 62610-5:2016

Structures mécaniques pour équipements électriques et électroniques – Gestion thermique pour les armoires conformes aux séries IEC 60297 et IEC 60917 – Partie 5: Évaluation des performances de refroidissement pour les baies intérieures

INTERNATIONAL ELECTROTECHNICAL COMMISSION

COMMISSION ELECTROTECHNIQUE INTERNATIONALE

ICS 31.240

ISBN 978-2-8322-3308-5

Warning! Make sure that you obtained this publication from an authorized distributor. Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

 Registered trademark of the International Electrotechnical Commission Marque déposée de la Commission Electrotechnique Internationale

CONTENTS

FOREWORD	3	
INTRODUCTION	5	
1 Scope	6	
2 Normative references	6	
3 Terms and definitions	6	
4 Cabinet cooling class criteria	8	
5 Cooling performance of cabinets	9	
5.1 General	9	
5.2 Cooling method of indoor cabinets	9	
5.2.1 Classification of cooling methods	9	
5.2.2 Cooling performances	10	
5.2.3 Concept for temperature rise		
5.2.4 Temperature rise limits		
5.3 Natural convection cooling		
5.4 Natural ventilation cooling		
5.5 Forced air cooling (forced ventilation)5.6 Representative examples of calculated cooling performance		
Annex A (informative) Background information P.D. P.P.F.V. I.P.W. A.1 Air velocity calculation of natural ventilation	13	
A.1 All velocity calculation of the validation test results by CFD simulations		
Figure 1 – Natural convection cooling. <u>IEC 62610-5:2016</u> https://standards.iteh.av/catalog/standards/sist/83103e5b-85a8-4066-945a-	8	
Figure 2 – Natural ventilation cooling08dbe47ec/iec-62610-5-2016	9	
Figure 3 – Forced air cooling		
Figure 4 – Velocity of natural convection as a function of cabinet height		
Figure A.1 – Balanced force on internal air of a cabinet		
Figure A.2 – Thermal simulation example – Type A		
Figure A.3 – Thermal simulation example – Type B		
Figure A.4 – Thermal simulation example – Type C		
Figure A.5 – Thermal simulation example – Type D		
Figure A.6 – Thermal simulation example – Type E		
Table 1 – Classification of cooling method	10	
-		
Table 2 – Representative examples of calculated cooling performances		

INTERNATIONAL ELECTROTECHNICAL COMMISSION

MECHANICAL STRUCTURES FOR ELECTRICAL AND ELECTRONIC EQUIPMENT – THERMAL MANAGEMENT FOR CABINETS IN ACCORDANCE WITH IEC 60297 AND IEC 60917 SERIES –

Part 5: Cooling performance evaluation for indoor cabinets

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
 IEC 62610-5:2016
- 4) In order to promoted international uniformity geo National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62610-5 has been prepared by subcommittee 48D: Mechanical structures for electrical and electronic equipment, of IEC technical committee 48:Electrical connectors and mechanical structures for electrical and electronic equipment.

The text of this standard is based on the following documents:

CDV	Report on voting	
48D/591/CDV	48D/604/RVC	

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 62610 series, published under the general title *Mechanical* structures for electrical and electronic equipment – Thermal management for cabinets in accordance with IEC 60297 and IEC 60917 series, can be found on the IEC website.

Future standards in this series will carry the new general title as cited above. Titles of existing standards in this series will be updated at the time of the next edition.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer. **Teh STANDARD PREVIEW**

(standards.iteh.ai)

<u>IEC 62610-5:2016</u> https://standards.iteh.ai/catalog/standards/sist/83103e5b-85a8-4066-945a-0b708dbc47ee/iec-62610-5-2016

INTRODUCTION

Indoor cabinets containing electronic equipment in subrack(s) and/ or chassis provide cooling by several different means, depending on the heat load of the equipment in the cabinet. In most cases air convection is used for cooling. The cabinets can be sealed or non-sealed, and may be equipped with fans for forced air cooling or rely on natural convention cooling without fans. In addition the subrack(s) or chassis may contain their own fans or rely on natural convention. Air convection systems are used to cool low to medium heat load applications. Indoor cabinets containing subrack(s) and/ or chassis assembled with high heat load electronic equipment typically are cooled by air to air heat exchangers or water supplied heat exchangers, and are not considered in this standard.

Sealed cabinets are used for systems operated in an industrial atmosphere, to protect the equipment against harsh environments, such as dust or water (IP), or provisions for EMC or acoustic noise. Non-sealed cabinets are used in offices, laboratories or data centres, where the environment is controlled.

The cooling performance of an electronic cabinet depends on the type of the cabinet, either sealed or non-sealed, with or without air moving devices, ventilated or re-circulated, and also, on the heat loads and the additional cooling systems (if any) of the equipment inside the cabinet.

Therefore, it is difficult to determine properly the cooling capabilities of empty electronic cabinets for various applications. This standard introduces a simplified method for an overall cooling performance evaluation for empty indoor cabinets in accordance with IEC 60917 or IEC 60297 series.

(standards.iteh.ai)

The purpose of this standard is to classify the cooling methods of empty indoor cabinets, to simplify the thermal hydraulic formulae for the evaluation and classification of cabinet cooling performances, and to //exemplify the acooling performances for the evaluation of cabinet sizes based on IEC 60917 or IEC 602970b708dbc47ec/iec-62610-5-2016

This enables the users to select the appropriate cabinet cooling solutions for their applications.

MECHANICAL STRUCTURES FOR ELECTRICAL AND ELECTRONIC EQUIPMENT – THERMAL MANAGEMENT FOR CABINETS IN ACCORDANCE WITH IEC 60297 AND IEC 60917 SERIES –

Part 5: Cooling performance evaluation for indoor cabinets

1 Scope

This part of IEC 62610 specifies a method for evaluating the cooling capacity mainly for air convection cooling of empty cabinets in accordance with IEC 60297 and IEC 60917 series.

2 Normative references

Void.

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

(standards.iteh.ai)

ventilation

movement of the air inside a cabinet, <u>Causing</u> replacement of the inside air by the cabinet external ambient airtps://standards.iteh.ai/catalog/standards/sist/83103e5b-85a8-4066-945a-0b708dbc47ee/iec-62610-5-2016

3.2

buoyancy

force of air in the opposite direction of gravity that is produced by the difference in density due to the temperature differences between the air inside and external to the cabinet

3.3

natural ventilation air movement produced by buoyancy

3.4

forced air cooling forced ventilation ventilation by air moving devices

3.5

natural convection cooling

cooling by natural air convection and radiation

3.6

air moving device

device creating air movement, e.g. fans, blowers, and other forced air movement equipment

3.7

sealed cabinet, without air moving devices

cabinet not provided with ventilation holes, not equipped with air moving devices, where the heat is transferred to the external environment by natural convection and radiation from the external surfaces of the cabinet

Note 1 to entry: The internal air temperature gradually increases from the bottom to the top of the cabinet.

3.8

sealed cabinet, with air moving devices

cabinet not provided with ventilation holes, equipped with air moving devices for re-circulating internal air, where the heat is transferred from the surface of the cabinet towards the outside of the cabinet both by convection (forced inside, natural outside) and by radiation

Note 1 to entry: A sealed cabinet without air moving devices which contains subracks or chassis systems with air moving devices may be equivalent to a sealed cabinet with air moving devices.

Note 2 to entry: The cooling performance of this type of cabinet is equal to that of "the sealed cabinet, without air moving devices" because the heat transfer mechanism to the external environment is identical, however the internal air temperature is equalized.

3.9

non-sealed cabinet, without air moving devices

cabinet where the heat is transferred by natural convection from the provided ventilation holes and, in addition, the heat is transferred to the external environment by natural convection and radiation from the external surfaces of the cabinet

Note 1 to entry: The source of the natural ventilation airflow is only by buoyancy of the cabinet internal air, even if there are some subracks or chassis systems with air moving devices, except if the air moving devices airflow goes directly outside of the cabinet.

3.10

non-sealed cabinet, with air moving devices

cabinet equipped with air moving devices and ventilation holes

Note 1 to entry: Two cooling modes, recirculation and forced ventilation, are utilized for this type of cabinet, depending on the location of the air moving devices.

3.11

IEC 62610-5:2016

air moving devices on the subrack site ai catalog/standards/sist/83103e5b-85a8-4066-945a-

cabinet equipped with subracks and/or chassis with air moving devices

Note 1 to entry: The air inside the cabinet is re-circulated by subrack or chassis mounted fans, but is not ventilated by the fans.

3.12

air moving devices on a cabinet <forced ventilation>

cabinet equipped with air moving devices on the top cover, bottom cover or the rear cover of the cabinet, it does not matter if the fans are mounted internal or external to the cabinet

Note 1 to entry: The air moving devices force the air to exit the cabinet through ventilation holes. If the cabinet mounted air moving devices airflow is larger than the combined airflow of the cabinet mounted subrack and/or chassis systems the temperature rise inside the cabinet may be zero.

Note 2 to entry: If the cabinet mounted air moving devices airflow is smaller than the combined airflow of the cabinet mounted subrack and/or chassis systems, this will cause cabinet internal air re-circulation. The maximum cabinet internal air temperature will be equal to the maximum cabinet mounted subrack and/or chassis system air exit temperature.

3.13

simplified cooling performance evaluation

method to estimate the heat load of a cabinet based upon the chosen cooling mechanism, the cabinet internal temperature limit, typical ambient temperature / humidity, and the overall cabinet size chosen for the application

Note 1 to entry: The criteria definition of conditions for the simplified cooling performance are shown in Clause 5.

Note 2 to entry: It is assumed that the cabinets are used in an standalone application. If cabinets are arranged side-by-side, placed along a building wall or back to back the cooling performance may be reduced due to loss of heat transfer surface area.

3.14 typical temperature rise

cabinet with a 10 K internal temperature rise with respect to the cabinet external ambient temperature

Note 1 to entry: This level should be applied for cabinets which do not contain high heat tolerant components in subrack and/or chassis systems. The cabinet application would be installed in a relatively high ambient temperature environment.

3.15

extended temperature rise


cabinet with a 20 K internal temperature rise with respect to the cabinet external ambient temperature


Note 1 to entry: This level should be applied for cabinets which contain high heat tolerant components in subrack and/or chassis systems. The cabinet application would be installed in a low ambient temperature environment typically controlled by air conditioners.

4 Cabinet cooling class criteria

To be able to estimate the cooling performance of a cabinet the following criteria are used to classify the type of cabinet.

- If the cabinet is sealed (Figure 1a and Figure 1b) or non-sealed (ventilated) (Figure 2a, Figure 2b and Figure 3).
- If the cabinet has he air moving devices (Figure 1a, Figure 2a) or has air moving devices (Figure 1b, Figure 2b and Figure 3).
- If the cabinet has air moving devices on the top cover or the rear cover (Figure 3).









Figure 1b - Sealed cabinet with air moving devices natural convection









Figure 2a – Non-sealed cabinet without air moving devices – ventilated

Figure 2b – Non-sealed cabinet with subrack and/or chassis system mounted air moving devices – ventilated



Non-sealed cabinet mounted air moving devices and with subrack and/or chassis system mounted air moving devices – ventilated

Figure 3 – Forced air cooling

5 Cooling performance of cabinets

5.1 General

In this clause, the cooling methods of indoor cabinets are classified, and the calculation procedures for each cooling performance of the cabinets are shown.

5.2 Cooling method of indoor cabinets

5.2.1 Classification of cooling methods

Classification of cooling methods is summarized as follows, see Table 1:

Figure 2 – Natural ventilation cooling

Туре	Definitio n	Sealed	Air moving devices	Ventilatio n	Reference figure	Cooling method and formula of cooling performance
А	see 3.7		no	20	Figure 1a	natural convection
В	see 3.8	yes	yes	no	Figure 1b	see 5.3
С	see 3.9		no	n otunol	Figure 2a	natural ventilation
D	see 3.11	no		natural	Figure 2b	see 5.4
E	see 3.12		yes forced		forced air cooling	
				torced	Figure 3	see 5.5

 Table 1 – Classification of cooling method

- 10 -

5.2.2 Cooling performances

The basic air-cooling calculation which is used in this standard is shown as follows.

$$Q = Q_{s} + Q_{v}$$

where

Q is the cooling performance of the indoor cabinet;

- Q_s is the heat dissipation from surfaces of the cabinet;
- Q_v is the heat dissipation by ventilation.

5.2.3 Concept for temperature rise

Let ΔT be the temperature rise of the inside air of the cabinet. Let ΔT_s be the temperature rise of the surface of the cabinet. The relation between the two can be estimated that ΔT_s is the half of ΔT .

https://standards.iteh.ai/catalog/standards/sist/83103e5b-85a8-4066-945a-0b708dbc47ee/iec-62610-5-2016

 $\Delta T_{\rm s} = \Delta T/2$

In case of the sealed cabinet, the temperature rise inside the cabinet is to be measured by an average temperature. In case of the non-sealed cabinet, the temperature rise is to be measured at the cabinet air exit.

5.2.4 Temperature rise limits

The tolerated temperature rise of the cabinet depends on how components mounted inside are tolerant to high temperature. The cabinet temperature rise should be classified into two levels listed below:

typical temperature rise $\Delta T = 10 \text{ K}$ extended temperature rise $\Delta T = 20 \text{ K}$

5.3 Natural convection cooling

The cooling performance of natural convection is applicable to a sealed cabinet without air moving devices and a sealed cabinet with air moving devices.

The cooling performance of natural convection is calculated with the following formula.

 $Q_{s} = h_{s} \times A \times \varDelta T_{s}$

where

 $h_{\rm s}$ is the heat transfer coefficient of the surface, the value of $h_{\rm s}$ shall be 8 W/m²K;

A is sum of the external surfaces area of the cabinet except the bottom.

NOTE The h_s value accounts for heat transfer due to both natural convection and radiation.

5.4 Natural ventilation cooling

The cooling performance of natural ventilation is applicable to a non-sealed cabinet without air moving devices and a non-sealed cabinet with air moving devices on the subrack or chassis (re-circulating). The cooling performance of natural convection is calculated with the following formula.

$$Q = Q_{s} + Q_{v}$$
$$Q_{s} = h_{s} \times A \times \varDelta T_{s}$$
$$Q_{v} = \rho \times C_{p} \times u \times A_{p} \times \varDelta T$$

where

- ρ is the density of the ambient air, the value should be 1,2 kg/m³;
- C_p is the specific heat of the ambient air at constant pressure, the value should be 1 005 J/kgK;
- *U* is the air velocity of natural convection;
- A_p is the surface area on top of the cabinet.

The velocity u varies according to the cabinet height and cabinet temperature rise. The value of u is determined from Figure 4.




Figure 4 – Velocity of natural convection as a function of cabinet height

The graph shows the velocity *u* of natural ventilation as a function of the cabinet height in the typical temperature rise $\Delta T = 10K$ and the extended temperature rise $\Delta T = 20 K$.

5.5 Forced air cooling (forced ventilation)

The cooling performance of the ventilated cabinet cooled via forced convection is calculated with the following formula. The cooling performance of forced air cooling is applicable to a non-sealed cabinet with air moving devices for ventilation on the top or rear of the cabinet.

$$Q = Q_{s} + Q_{v}$$
$$Q_{s} = h_{s} \times A \times \varDelta T_{s}$$
$$Q_{v} = \rho \times C_{p} \times F \times \varDelta T$$
where