

# INTERNATIONAL STANDARD



Low-voltage switchgear and controlgear –  
Part 2: Circuit-breakers

Standards  
(<https://standards.iteh.ai>)  
Document Preview

IEC 60947-2:2016

<https://standards.iteh.ai/catalog/standards/iec/02c635ab-639e-4cda-9787-afd1fb3fa0e2/iec-60947-2-2016>



## THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2016 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland

Tel.: +41 22 919 02 11  
Fax: +41 22 919 03 00  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)

### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

### About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

#### IEC Catalogue - [webstore.iec.ch/catalogue](http://webstore.iec.ch/catalogue)

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

#### IEC publications search - [www.iec.ch/searchpub](http://www.iec.ch/searchpub)

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

#### IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

#### Electropedia - [www.electropedia.org](http://www.electropedia.org)

The world's leading online dictionary of electronic and electrical terms containing 20 000 terms and definitions in English and French, with equivalent terms in 15 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

#### IEC Glossary - [std.iec.ch/glossary](http://std.iec.ch/glossary)

65 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

#### IEC Customer Service Centre - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: [csc@iec.ch](mailto:csc@iec.ch).

[IEC 60947-2:2016](https://standards.iteh.ai/catalog/standards/iec/02c635ab-639e-4cda-9787-afd1fb3fa0e2/iec-60947-2-2016)

<https://standards.iteh.ai/catalog/standards/iec/02c635ab-639e-4cda-9787-afd1fb3fa0e2/iec-60947-2-2016>



IEC 60947-2

Edition 5.0 2016-06  
REDLINE VERSION

# INTERNATIONAL STANDARD



Low-voltage switchgear and controlgear –  
Part 2: Circuit-breakers

iteh Standards  
(<https://standards.iteh.ai>)  
Document Preview

IEC 60947-2:2016

<https://standards.iteh.ai/catalog/standards/iec/02c635ab-639e-4cda-9787-afd1fb3fa0e2/iec-60947-2-2016>

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

ICS 29.130.20

ISBN 978-2-8322-3456-3

**Warning! Make sure that you obtained this publication from an authorized distributor.**

## CONTENTS

FOREWORD .....	14
1 General .....	16
1.1 Scope and object .....	16
1.2 Normative references .....	17
2 Terms and definitions .....	19
3 Classification .....	24
4 Characteristics of circuit-breakers .....	24
4.1 Summary of characteristics .....	24
4.2 Type of circuit-breaker .....	25
4.3 Rated and limiting values of the main circuit .....	25
4.3.1 General .....	25
4.3.2 Rated voltages .....	25
4.3.3 Currents .....	25
4.3.4 Rated frequency .....	26
4.3.5 Rated duty .....	26
4.3.6 Short-circuit characteristics .....	26
4.4 Utilization Selectivity categories .....	29
4.5 Control circuits .....	30
4.5.1 Electrical control circuits .....	30
4.5.2 Air-supply control circuits (pneumatic or electro-pneumatic) .....	30
4.6 Auxiliary circuits .....	30
4.7 Releases .....	30
4.7.1 Types .....	30
4.7.2 Characteristics .....	31
4.7.3 Current setting of over-current releases .....	31
4.7.4 Tripping time setting of over-current releases .....	31
4.8 Integral fuses (integrally fused circuit-breakers) .....	32
5 Product information .....	32
5.1 Nature of the information .....	32
5.2 Marking .....	32
5.3 Instructions for installation, operation and maintenance .....	33
6 Normal service, mounting and transport conditions .....	34
7 Constructional and performance requirements .....	34
7.1 Constructional requirements .....	34
7.1.1 General .....	34
7.1.2 Withdrawable circuit-breakers .....	34
7.1.3 Additional requirements for circuit-breakers suitable for isolation .....	35
7.1.4 Clearances and creepage distances .....	35
7.1.5 Requirements for the safety of the operator .....	35
7.1.6 List of construction breaks .....	35
7.1.7 Additional requirements for circuit-breakers provided with a neutral pole .....	36
7.1.8 Digital inputs and outputs for use with programmable logic controllers (PLCs) .....	36
7.2 Performance requirements .....	36
7.2.1 Operating conditions .....	36
7.2.2 Temperature-rise .....	38

7.2.3	Dielectric properties .....	39
7.2.4	Ability to make and break under no load, normal load and overload conditions .....	40
7.2.5	Ability to make and break under short-circuit conditions .....	41
7.2.6	Vacant .....	41
7.2.7	Additional requirements for circuit-breakers suitable for isolation .....	41
7.2.8	Specific requirements for integrally fused circuit-breakers .....	41
7.2.9	Co-ordination between a circuit-breaker and another short-circuit protective device .....	42
7.3	Electromagnetic compatibility (EMC) .....	42
8	Tests .....	42
8.1	Kind of tests .....	42
8.1.1	General .....	42
8.1.2	Type tests .....	42
8.1.3	Routine tests .....	42
8.2	Compliance with constructional requirements .....	43
8.3	Type tests .....	43
8.3.1	Test sequences .....	43
8.3.2	General test conditions .....	52
8.3.3	Test sequence I: General performance characteristics .....	61
8.3.4	Test sequence II: Rated service short-circuit breaking capacity .....	71
8.3.5	Test sequence III: Rated ultimate short-circuit breaking capacity .....	72
8.3.6	Test sequence IV: Rated short-time withstand current .....	74
8.3.7	Test sequence V: Performance of integrally fused circuit-breakers .....	75
8.3.8	Test sequence VI: combined test sequence .....	77
8.3.9	Critical d.c. load current test .....	78
8.4	Routine tests .....	79
8.4.1	General .....	79
8.4.2	Mechanical operation tests .....	80
8.4.3	Verification of the calibration of overcurrent releases .....	80
8.4.4	Verification of the operation of undervoltage and shunt releases .....	81
8.4.5	Additional tests for CBRs .....	81
8.4.6	Dielectric tests .....	81
8.4.7	Test for the verification of clearances less than those corresponding to case A of Table 13 of IEC 60947-1:2007 .....	82
8.5	Special tests – Damp heat, salt mist, vibration and shock .....	82
Annex A (normative)	Co-ordination <del>under short circuit conditions</del> between a circuit-breaker and another short-circuit protective device associated in the same circuit .....	85
A.1	<del>Introduction</del> General .....	85
A.2	Scope and object .....	86
A.3	General requirements for the co-ordination of a circuit-breaker with another SCPD .....	86
A.3.1	General considerations .....	86
A.3.2	Take-over current .....	86
A.3.3	Behaviour of C <sub>1</sub> in association with another SCPD .....	86
A.4	Type and characteristics of the associated SCPD .....	86
A.5	Verification of <del>discrimination</del> selectivity .....	87
A.5.1	General .....	87
A.5.2	Consideration of selectivity by desk study .....	88
A.5.3	Selectivity determined by test .....	89

A.6	Verification of back-up protection .....	89
A.6.1	Determination of the take-over current.....	89
A.6.2	Verification of back-up protection .....	89
A.6.3	Tests for verification of back-up protection .....	90
A.6.4	Results to be obtained.....	91
Annex B (normative)	Circuit-breakers incorporating residual current protection .....	97
B.1	General.....	97
B.1.1	Preamble .....	97
B.1.2	Scope and object .....	97
B.2	Terms and definitions.....	98
B.2.1	Terms and definitions relating to currents flowing from live parts to earth.....	98
B.2.2	Terms and definitions relating to the energization of a CBR .....	98
B.2.3	Terms and definitions relating to the operation and the functions of a CBR.....	99
B.2.4	Terms and definitions relating to values and ranges of energizing quantities.....	100
B.3	Classification .....	101
B.3.1	Classification according to the method of operation of the residual current function.....	101
B.3.2	Classification according to the possibility of adjusting the residual operating current.....	101
B.3.3	Classification according to time-delay of the residual current function .....	101
B.3.4	Classification according to behaviour in presence of a d.c. component.....	101
B.4	Characteristics of CBRs concerning their residual current function.....	101
B.4.1	Rated values.....	101
B.4.2	Preferred and limiting values .....	102
B.4.3	Value of the rated residual short-circuit making and breaking capacity ( $I_{\Delta m}$ ) .....	103
B.4.4	Operating characteristics in case of an earth fault current in the presence or absence of a d.c. component .....	103
B.5	Marking.....	103
B.6	Normal service, mounting and transport conditions .....	104
B.7	Design and operating requirements .....	105
B.7.1	Design requirements .....	105
B.7.2	Operating requirements.....	105
B.7.3	Electromagnetic compatibility .....	107
B.8	Tests .....	107
B.8.1	General.....	107
B.8.2	Verification of the operating characteristic .....	110
B.8.3	Verification of dielectric properties.....	111
B.8.4	Verification of the operation of the test device at the limits of rated voltage.....	112
B.8.5	Verification of the limiting value of the non-operating current under over-current conditions .....	112
B.8.6	Verification of the resistance against unwanted tripping due to surge currents resulting from impulse voltages .....	113
B.8.7	Verification of the behaviour of CBRs of type A in the case of an earth fault current comprising a d.c. component .....	114
B.8.8	Verification of the behaviour of CBRs functionally dependent on line voltage classified under B.3.1.2.1 .....	115

B.8.9	Verification of the behaviour of CBRs functionally dependent on line voltage as classified under B.3.1.2.2 in the case of failure of line voltage.....	116
B.8.10	Verification of the residual short-circuit making and breaking capacity .....	117
B.8.11	Verification of the effects of environmental conditions.....	118
B.8.12	Verification of electromagnetic compatibility .....	118
B.8.13	Test for variations or interruptions of voltage and for voltage dips .....	120
Annex C (normative)	Individual pole short-circuit test sequence .....	128
C.1	General.....	128
C.2	Test of individual pole short-circuit breaking capacity.....	128
C.3	Verification of dielectric withstand.....	128
C.4	Verification of overload releases.....	128
Annex D	Vacant .....	129
Annex E (informative)	Items subject to agreement between manufacturer and user.....	130
Annex F (normative)	Additional tests for circuit-breakers with electronic over-current protection.....	131
F.1	<b>Scope General</b> .....	131
F.2	List of tests .....	131
F.2.1	<b>General</b> .....	131
F.2.2	Electromagnetic compatibility (EMC) tests .....	131
F.2.3	Suitability for multiple frequencies .....	132
F.2.4	Dry heat test .....	132
F.2.5	Damp heat test .....	132
F.2.6	Temperature variation cycles at a specified rate of change .....	132
F.3	General test conditions.....	132
F.3.1	General.....	132
F.3.2	Electromagnetic compatibility tests .....	132
F.4	Immunity tests.....	133
F.4.1	Harmonic currents.....	133
F.4.2	Electrostatic discharges .....	134
F.4.3	Radiated <del>radio-frequency</del> <b>RF</b> electromagnetic fields .....	134
F.4.4	Electrical fast transient/burst (EFT/B) .....	134
F.4.5	Surges .....	135
F.4.6	Conducted disturbances induced by <del>radio-frequency</del> <b>RF</b> fields (common mode).....	135
F.4.7	Current dips .....	135
F.5	Emission tests.....	136
F.5.1	Harmonics .....	136
F.5.2	Voltage fluctuations.....	136
F.5.3	Conducted RF disturbances (150 kHz to 30 MHz) .....	136
F.5.4	Radiated RF disturbances (30 MHz to 1 GHz).....	136
F.6	Suitability for multiple frequencies .....	137
F.6.1	<b>General</b> .....	137
F.6.2	Test conditions.....	137
F.6.3	Test procedure.....	137
F.6.4	Test results .....	137
F.7	Dry heat test .....	137
F.7.1	Test procedure.....	137
F.7.2	Test results .....	138
F.7.3	Verification of overload releases.....	138

F.8	Damp heat test.....	138
F.8.1	Test procedure.....	138
F.8.2	Verification of overload releases.....	138
F.9	Temperature variation cycles at a specified rate of change .....	138
F.9.1	Test conditions.....	138
F.9.2	Test procedure.....	138
F.9.3	Test results .....	139
F.9.4	Verification of overload releases.....	139
Annex G (normative)	Power loss .....	153
G.1	General.....	153
G.2	Test methods .....	153
G.2.1	General case .....	153
G.2.2	AC circuit-breakers of rated current not exceeding 400 A.....	153
G.2.3	DC circuit-breakers .....	154
G.3	Test procedure.....	154
Annex H (normative)	Test sequence for circuit-breakers for IT systems .....	156
H.1	General.....	156
H.2	Individual pole short-circuit.....	156
H.3	Verification of dielectric withstand.....	157
H.4	Verification of overload releases.....	157
H.5	Marking.....	157
Annex J (normative)	Electromagnetic compatibility (EMC) – Requirements and test methods for circuit-breakers .....	158
J.1	General.....	158
J.2	Immunity.....	159
J.2.1	General.....	159
J.2.2	Electrostatic discharges .....	161
J.2.3	Radiated radio-frequency RF electromagnetic fields .....	162
J.2.4	Electrical fast transients/bursts (EFT/B).....	162
J.2.5	Surges .....	162
J.2.6	Conducted disturbances induced by radio-frequency RF fields (common mode).....	163
J.3	Emission .....	163
J.3.1	General.....	163
J.3.2	Conducted RF disturbances (150 kHz to 30 MHz).....	164
J.3.3	Radiated RF disturbances (30 MHz to 1 000 MHz).....	164
Annex K (informative)	Glossary of symbols related to products covered by this standard and graphical representation of characteristics.....	169
Annex L (normative)	Circuit-breakers not fulfilling the requirements for overcurrent protection.....	178
L.1	Scope General .....	178
L.2	Terms and definitions .....	178
L.3	Classification .....	178
L.4	Rated values .....	178
L.4.1	Rated current ( $I_n$ ).....	178
L.4.2	Rated conditional short-circuit current ( $I_{CC}$ ).....	179
L.5	Product information .....	179
L.6	Constructional and performance requirements.....	179
L.7	Tests .....	179



L.7.1	General.....	179
L.7.2	Rated conditional short-circuit tests.....	180
Annex M (normative) Modular residual current devices (without integral current breaking device).....		183
M.1	<del>Scope and object</del> General.....	183
M.1.1	Field of application.....	183
M.1.2	Field of application.....	183
M.2	Terms and definitions.....	183
M.2.1	Terms and definitions relating to the energization of an MRCD.....	183
M.2.2	Terms and definitions relating to the operation and the functions of an MRCD.....	184
M.3	Classification.....	184
M.3.1	Classification according to the configuration of the primary conductors.....	184
M.3.2	Classification according to the method of operation.....	185
M.3.3	Classification according to the possibility of adjusting the residual operating current.....	185
M.3.4	Classification according to time-delay of the residual current function.....	185
M.3.5	Classification according to behaviour in presence of a d.c. component.....	185
M.4	Characteristics of MRCDs.....	185
M.4.1	General characteristics.....	185
M.4.2	Characteristics of MRCDs concerning their residual current function.....	186
M.4.3	Behaviour under short-circuit conditions.....	187
M.4.4	Preferred and limiting values.....	187
M.5	Product information.....	188
M.6	Normal service, mounting and transport conditions.....	190
M.7	Design and operating requirements.....	190
M.7.1	Design requirements.....	190
M.7.2	Operating requirements.....	190
M.8	Tests.....	192
M.8.1	General.....	192
M.8.2	Compliance with constructional requirements.....	193
M.8.3	Verification of the operating characteristics.....	194
M.8.4	Verification of dielectric properties.....	196
M.8.5	Verification of the operation of the test device at the limits of the rated voltage.....	196
M.8.6	Verification of the limiting value of non-operating current under overcurrent conditions, in case of a single phase load.....	197
M.8.7	Resistance against unwanted tripping due to surge currents resulting from impulse voltages.....	197
M.8.8	Verification of the behaviour in case of an earth fault current comprising a d.c. component.....	197
M.8.9	Verification of the behaviour of MRCDs with separate sensing means in case of a failure of the sensing means connection.....	200
M.8.10	Verification of temperature-rise of terminal type MRCDs.....	200
M.8.11	Verification of mechanical and electrical endurance.....	200
M.8.12	Verification of the behaviour of MRCDs in case of failure of the voltage source for MRCDs classified under M.3.2.2.1.....	201
M.8.13	Verification of the behaviour of MRCDs with voltage source as classified under M.3.2.2.2 in case of failure of the voltage source.....	202
M.8.14	Verification of the behaviour of the MRCD under short-circuit conditions.....	202
M.8.15	Verification of effects of environmental conditions.....	204

M.8.16	Verification of electromagnetic compatibility .....	204
Annex N (normative)	Electromagnetic compatibility (EMC) – Additional requirements and test methods for devices not covered by Annex B, Annex F and Annex M.....	227
N.1	General.....	227
N.1.1	<b>Scope General</b> .....	227
N.1.2	General test conditions.....	227
N.2	Immunity.....	227
N.2.1	General.....	227
N.2.2	Electrostatic discharges .....	228
N.2.3	Radiated <b>radio-frequency RF</b> electromagnetic fields .....	228
N.2.4	Electrical fast transients/bursts (EFT/B).....	228
N.2.5	Surges .....	229
N.2.6	Conducted disturbances induced by <b>radio-frequency RF</b> fields (common mode).....	229
N.2.7	Voltage dips and interruptions .....	229
N.3	Emission.....	229
N.3.1	General.....	229
N.3.2	Conducted RF disturbances (150 kHz to 30 MHz).....	230
N.3.3	Radiated RF disturbances (30 MHz to 1 000 MHz).....	230
Annex O (normative)	Instantaneous trip circuit-breakers (ICB).....	231
O.1	<b>Scope General</b> .....	231
O.2	<b>Terms and definitions</b> .....	231
O.3	<b>Rated values</b> .....	231
O.3.1	<b>General</b> .....	231
O.3.2	Rated current ( $I_n$ ).....	231
O.3.3	Rated short-circuit making capacity.....	231
O.3.4	Rated short-circuit breaking capacities .....	231
O.4	Product information.....	232
O.5	Constructional and performance requirements.....	232
O.6	Tests .....	232
O.6.1	Test sequence of the ICB alone.....	232
O.6.2	ICB associated with a specified protected device (i.e. motor-starter or overload relay).....	233
Annex P (normative)	DC circuit-breakers for use in photovoltaic (PV) applications .....	234
P.1	Field of application .....	234
P.2	Terms and definitions.....	234
P.3	Classification .....	234
P.4	Characteristics of PV circuit-breakers.....	234
P.5	Product information.....	235
P.6	Normal service, mounting and transport conditions .....	235
P.7	Constructional and performance requirements.....	235
P.7.1	Constructional requirements.....	235
P.7.2	Performance requirements .....	235
P.7.3	Electromagnetic compatibility (EMC) .....	236
P.8	Tests .....	236
P.8.1	Kind of tests.....	236
P.8.2	Compliance with constructional requirements .....	236
P.8.3	Type tests .....	236
P.8.4	Routine tests.....	238
P.8.5	Special tests .....	238

Annex Q Vacant .....	239
Annex R (normative) Circuit-breakers incorporating residual current protection with automatic re-closing functions .....	240
R.1 General .....	240
R.1.1 Preamble .....	240
R.1.2 Field of application .....	240
R.2 Terms and definitions .....	241
R.3 Classification .....	242
R.3.1 According to the method of construction .....	242
R.3.2 According to the method of automatic reclosing .....	242
R.4 Characteristics .....	242
R.4.1 Rated automatic reclosing operating residual current ( $I_{\Delta ar}$ ) .....	242
R.4.2 Maximum number of consecutive reclosing operations .....	242
R.5 Marking and instructions .....	243
R.6 Normal service, mounting and transport conditions .....	243
R.7 Design and operating requirements .....	243
R.7.1 Design requirements .....	243
R.7.2 Operating requirements .....	244
R.8 Tests .....	245
R.8.1 General conditions .....	245
R.8.2 Verification of the non-reclosing after tripping under over-current conditions .....	245
R.8.3 Verification of the non-reclosing after intentional opening .....	245
R.8.4 Verification of the automatic reclosing function after tripping on earth fault .....	246
R.8.5 Verification of mechanical endurance .....	247
R.8.6 Verification of the isolation function .....	247
R.8.7 Verification of residual short-circuit making and breaking capacity .....	248
R.8.8 Verification of the automatic reclosing function after the test sequences of Clause B.8 .....	248
R.8.9 Test items for external type automatic reclosing devices .....	248
Bibliography .....	251
Figure 1 – Test arrangement (connecting cables not shown) for short-circuit tests .....	84
Figure A.1 – Over-current co-ordination between a circuit-breaker and a fuse or back-up protection by a fuse: operating characteristics .....	92
Figure A.2 – Total <del>discrimination</del> selectivity between two circuit-breakers .....	93
Figure A.3 – Back-up protection by a circuit-breaker – Operating characteristics .....	94
Figure A.4 – Example of test circuit for conditional short-circuit breaking capacity tests showing cable connections for a 3-pole circuit-breaker ( $C_1$ ) .....	95
Figure A.5 – Example of test circuit for the verification of selectivity .....	96
Figure B.1 – Test circuit for the verification of the operating characteristic (see B.8.2) .....	121
Figure B.2 – Test circuit for the verification of the limiting value of the non-operating current under over-current conditions (see B.8.5) .....	122
Figure B.3 – Test circuit for the verification of the behaviour of CBRs classified under B.3.1.2.2 (see B.8.9) .....	123
Figure B.4 – Current ring wave 0,5 $\mu$ s/100 kHz .....	124
Figure B.5 – Example of test circuit for the verification of resistance to unwanted tripping .....	125

Figure B.6 – Surge current wave 8/20  $\mu$ s ..... 125

Figure B.7 – Test circuit for the verification of resistance to unwanted tripping in case of flashover without follow-on current (B.8.6.3) ..... 126

Figure B.8 – Test circuit for the verification of the correct operation of CBRs, in the case of residual pulsating direct currents (see B.8.7.2.1, B.8.7.2.2 and B.8.7.2.3) ..... 126

Figure B.9 – Test circuit for the verification of the correct operation of CBRs, in the case of a residual pulsating direct current superimposed by a smooth direct residual current (see B.8.7.2.4) ..... 127

Figure F.1 – Representation of test current produced by back-to-back thyristors in accordance with F.4.1 ..... 140

Figure F.2 – Test circuit for immunity and emission tests in accordance with F.4.1.3, F.4.2, F.4.3, F.4.6, F.4.7.1, F.5.4 and F.6.3 – Two phase poles in series ..... 141

Figure F.3 – Test circuit for immunity and emission tests in accordance with F.4.1.3, F.4.2, F.4.3, F.4.6, F.4.7.1, F.5.4 and F.6.3 – Three phase poles in series ..... 141

Figure F.4 – Test circuit for immunity and emission tests in accordance with F.4.1.3, F.4.2, F.4.3, F.4.6, F.4.7.1, F.5.4 and F.6.3 – Three-phase connection ..... 142

Figure F.5 – Test current for the verification of the influence of the current dips and interruptions in accordance with F.4.7.1 ..... 142

Figure F.6 – Circuit for electrical fast transients/bursts (EFT/B) immunity test in accordance with F.4.4 – Two phase poles in series ..... 143

Figure F.7 – Circuit for electrical fast transients/bursts (EFT/B) immunity test in accordance with F.4.4 – Three phase poles in series ..... 143

Figure F.8 – Circuit for electrical fast transients/bursts (EFT/B) immunity test in accordance with F.4.4 – Three-phase connection ..... 144

Figure F.9 – Test circuit for the verification of the influence of surges in the main circuit (line-to-earth) in accordance with F.4.5 – Two phase poles in series ..... 144

Figure F.10 – Test circuit for the verification of the influence of surges in the main circuit (line-to-earth) in accordance with F.4.5 – Three phase poles in series ..... 145

Figure F.11 – Test circuit for the verification of the influence of surges in the main circuit (line-to-earth) in accordance with F.4.5 – Three-phase connection ..... 145

Figure F.12 – Test circuit for the verification of the influence of current surges in the main circuit in accordance with F.4.5 – Two phase poles in series ..... 146

Figure F.13 – Test circuit for the verification of the influence of current surges in the main circuit in accordance with F.4.5 – Three phase poles in series ..... 146

Figure F.14 – Test circuit for the verification of the influence of current surges in the main circuit in accordance with F.4.5 – Three-phase connection ..... 147

Figure F.15 – Temperature variation cycles at a specified rate of change in accordance with F.9.1 ..... 147

Figure F.16 – General test set-up for immunity tests ..... 148

Figure F.17 – Test set-up for the verification of immunity to radiated RF electromagnetic fields ..... 149

Figure F.18 – Test set-up for the verification of immunity to electrical fast transients/bursts (EFT/B) on power lines ..... 149

Figure F.19 – Test set-up for verification of immunity to electrical fast transients/bursts (EFT/B) on signal lines ..... 150

Figure F.20 – General test set-up for the verification of immunity to conducted disturbances induced by RF fields (common mode) ..... 150

Figure F.21 – Arrangement of connections for the verification of immunity to conducted disturbances induced by RF fields – Two phase poles in series configuration ..... 151

Figure F.22 – Arrangement of connections for the verification of immunity to conducted disturbances induced by RF fields – Three phase poles in series configuration ..... 151

Figure F.23 – Arrangement of connections for the verification of immunity to conducted disturbances induced by RF fields – Three-phase configuration .....	152
Figure G.1 – Example of power loss measurement according to G.2.1 .....	154
Figure G.2 – Example of power loss measurement according to G.2.2 and G.2.3 .....	155
Figure J.1 – EUT mounted in a metallic enclosure .....	165
Figure J.2 – Test set up for the measurement of radiated RF emissions .....	166
Figure J.3 – Test set up for the verification of immunity to electrostatic discharges .....	167
Figure J.4 – Test set up for the verification of immunity to radiated RF electromagnetic fields.....	167
Figure J.5 – Test set up for the verification of immunity to electrical fast transients/bursts (EFT/B) on power lines .....	168
Figure J.6 – Test set up for the verification of immunity to electrical fast transients/bursts (EFT/B) on signal lines .....	168
Figure K.1 – Relationship between symbols and tripping characteristics.....	171
Figure K.2 – Template for characteristics of cut-off current versus prospective current from 1 kA to 200 kA .....	172
Figure K.3 – Template for characteristics of cut-off current versus prospective current from 0,01 kA to 200 kA.....	173
Figure K.4 – Template for characteristics of let-through energy versus prospective current from 1 kA to 200 kA.....	174
Figure K.5 – Template for characteristics of let-through energy versus prospective current from 0,01 kA to 200 kA.....	175
Figure K.6 – Example of the use of template to Figure K.2.....	176
Figure K.7 – Example of the use of template to Figure K.4.....	177
Figure M.1 – Test circuits for the verification of operation in the case of a steady increase of residual current.....	206
Figure M.2 – Test circuits for the verification of operation in the case of a sudden appearance of residual current (with breaking device) .....	207
Figure M.3 – Test circuits for the verification of operation in the case of a sudden appearance of residual current (without breaking device).....	208
Figure M.4 – Test circuits for the verification of the limiting value of non-operating current under overcurrent conditions .....	209
Figure M.5 – Test circuits for the verification of the resistance to unwanted tripping in the case of loading of the network capacitance.....	210
Figure M.6 – Test circuit for the verification of the resistance to unwanted tripping in the case of flashover without follow-on current .....	211
Figure M.7 – Test circuits for the verification of operation in the case of a continuous rise of a residual pulsating direct current .....	212
Figure M.8 – Test circuits for the verification of operation in the case of a sudden appearance of residual pulsating direct current (without breaking device) .....	213
Figure M.9 – Test circuits for the verification of operation in the case of a sudden appearance of residual pulsating direct current (with breaking device) .....	214
Figure M.10 – Test circuits for the verification of operation in the case of a residual pulsating direct current superimposed by smooth direct current of 6 mA .....	215
Figure M.11 – Test circuits for the verification of operation in the case of a slowly rising residual smooth direct current .....	216
Figure M.12 – Test circuits for the verification of operation in the case of a sudden appearance of residual smooth direct current (without breaking device).....	217
Figure M.13 – Test circuits for the verification of operation in the case of a sudden appearance of residual smooth direct current (with breaking device).....	218

Figure M.14 – Test circuits for the verification of operation in the case of a slowly rising residual current resulting from a fault in a circuit fed by a three-pulse star or a six-pulse bridge connection.....	219
Figure M.15 – Test circuits for the verification of operation in the case of a slowly rising residual current resulting from a fault in a circuit fed by a two-pulse bridge connection line-to-line.....	220
Figure M.16 – Test circuit for the verification of the behaviour of MRCDs with separate sensing means in the case of a failure of the sensor means connection.....	221
Figure M.17 – Test circuit for the verification of the behaviour of MRCD with separate sensing means under short-circuit conditions.....	222
Figure M.18 – Test circuit for the verification of the behaviour of MRCD with integral sensing means under short-circuit conditions.....	223
Figure M.19 – Test circuit for the verification of the behaviour of terminal type MRCD under short-circuit conditions.....	224
Figure M.20 – Verification of immunity to radiated RF electromagnetic fields – Test set-up for MRCD with separate sensing means (additional to the test of Annex B).....	225
Figure M.21 – Verification of immunity to electrical fast transients/bursts (EFT/B) on the sensing means connection of an MRCD with separate sensing means (additional to the test of Annex B).....	226
Figure M.22 – Verification of immunity to conducted disturbances induced by RF fields – Test set up for MRCD with separate sensing means (additional to the test of Annex B).....	226
Figure R.1 – Test circuit for the verification of the automatic reclosing functions.....	250
Table 1 – <del>Standard ratios between <math>I_{CS}</math> and <math>I_{CU}</math> (void)</del> .....	27
Table 2 – Ratio $n$ between short-circuit making capacity and short-circuit breaking capacity and related power factor (for a.c. circuit-breakers).....	28
Table 3 – Minimum values of rated short-time withstand current.....	29
Table 4 – <del>Utilization categories (void)</del> .....	29
Table 5 – Preferred values of the rated control supply voltage, if different from that of the main circuit.....	30
Table 6 – Characteristics of the opening operation of inverse time-delay over-current opening releases at the reference temperature.....	38
Table 7 – Temperature-rise limits for terminals and accessible parts.....	39
Table 8 – Number of operating cycles.....	41
Table 9 – Overall schema of test sequences <sup>a</sup> .....	45
Table 9a – Applicability of test sequences according to the relationship between $I_{CS}$ , $I_{CU}$ and $I_{CW}$ <sup>a</sup> .....	47
Table 9b – Applicability of tests or test sequences to 1, 2 and 4-pole circuit-breakers according to the alternative programme 1 of 8.3.1.4.....	49
Table 9c – Applicability of tests or test sequences to 1, 2 and 3-pole circuit-breakers according to the alternative programme 2 of 8.3.1.4.....	51
Table 10 – Number of samples for test (1 of 2).....	54
Table 11 – Values of power factors and time constants corresponding to test currents.....	57
Table 12 – Test circuit characteristics for overload performance.....	69
Table B.1 – Operating characteristic for non-time-delay type.....	102
Table B.2 – Operating characteristic for time-delay type having a limiting non-actuating time of 0,06 s.....	103
Table B.3 – Requirements for CBRs functionally dependent on line voltage.....	107
Table B.4 – Additional test sequences.....	109