



# SLOVENSKI STANDARD

## SIST-TP CR 1749:2005

01-julij-2005

---

9 j fcdg Ug\ Ya UnUfUnj fy Ub^Yd`]bg\_] \ `UdUfUrcj `[ `XYbUbu ]b`cXj UUbuU  
dfcXi \_hcj `n[ cfYj Ub^Ufhjd]k

European scheme for the classification of gas appliances according to the method of evacuation of the products of combustion (Types)

Europäisches Schema für die Einteilung von Gasgeräten nach der Art der Abgasabführung (Typen)

Modele européen pour la classification des appareils utilisant les combustibles gazeux selon la méthode de l'évacuation des produits de combustion (Types)

<https://standards.iteh.ai/catalog/standards/sist/142e28a8-bcf9-491b-83e6-86a334a0ab68/sist-tp-cr-1749-2005>

Ta slovenski standard je istoveten z: CR 1749:2001

---

### ICS:

91.140.40      Sistemi za oskrbo s plinom      Gas supply systems

**SIST-TP CR 1749:2005**

**en,fr,de**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST-TP CR 1749:2005

<https://standards.iteh.ai/catalog/standards/sist/142e28a8-bcf9-491b-83e6-86a334a0ab68/sist-tp-cr-1749-2005>

CEN REPORT  
RAPPORT CEN  
CEN BERICHT

CR 1749

January 2001

ICS

Supersedes CR 1749:1998

English version

European scheme for the classification of gas appliances  
according to the method of evacuation of the products of  
combustion (Types)

Modèle européen pour la classification des appareils  
utilisant les combustibles gazeux selon la méthode de  
l'évacuation des produits de combustion (Types)

Europäisches Schema für die Einteilung von Gasgeräten  
nach der Art der Abgasabführung (Typen)

This CEN Report was approved by CEN on 29 December 2000. It has been drawn up by the Technical Committee CEN/CS SUBSECTOR H99.

CEN members are the national standards bodies of Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.

[SIST-TP CR 1749:2005](https://standards.itih.ai/catalog/standards/sist/142e28a8-bcf9-491b-83e6-86a334a0ab68/sist-tp-cr-1749-2005)

<https://standards.itih.ai/catalog/standards/sist/142e28a8-bcf9-491b-83e6-86a334a0ab68/sist-tp-cr-1749-2005>



EUROPEAN COMMITTEE FOR STANDARDIZATION  
COMITÉ EUROPÉEN DE NORMALISATION  
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

**Contents**

<b>Foreword .....</b>	<b>3</b>
<b>1 General scheme .....</b>	<b>4</b>
<b>1.1 Type A.....</b>	<b>4</b>
<b>1.2 Type B.....</b>	<b>5</b>
<b>1.3 Type C.....</b>	<b>6</b>
<b>2 Supplementary classification scheme for type A and type B appliances fitted with particular safety devices.....</b>	<b>9</b>
<b>3 Supplementary classification scheme for type B appliances for use in limited installation conditions .....</b>	<b>9</b>
<b>Annex A Classification according to the mode of evacuation of the products of combustion .....</b>	<b>11</b>
<b>Annex B Special national appliance classification (types) .....</b>	<b>26</b>

**ITeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST-TP CR 1749:2005

<https://standards.iteh.ai/catalog/standards/sist/142e28a8-bcf9-491b-83e6-86a334a0ab68/sist-tp-cr-1749-2005>

## Foreword

This technical report has been prepared under the aegis of CEN/PC 3: Gas to provide guidance to CEN Technical Committees who are preparing European Standards for appliances burning combustible gases.

It gives details of a general scheme for the classification of such appliances according to the method of evacuating the products of combustion. It must be stressed that this scheme only concerns appliances that are intended to be installed within buildings. It does not apply to outdoor appliances. This form of appliance classification is widely used in the preparation of European Standards for gas appliances to identify the requirements and methods of test that are applicable to the various methods of evacuating the products of combustion. Appliances classified in this way are generally described as "types" and this description has been retained for the purposes of this general scheme.

The main purpose of the scheme is to promote harmonization in the classification of appliance types. This should ensure that there is a clear understanding of the various appliance types and will avoid confusion arising from Technical Committees describing them in different ways. CEN Technical committees are therefore requested to use this scheme in all circumstances in which it is appropriate. They should not deviate from it unless there are sound technical reasons for so doing.

In the preparation of this scheme it was noted that there were methods of evacuating products of combustion that were particular to a specific Technical Committee or to a particular gas appliance. These particular methods have not been included in the present scheme because, as indicated above, the main purpose of the scheme is to promote harmonization across Technical Committees.

However, it is intended that this scheme should be reviewed from time to time in order to consider its extension to other, possibly new, methods of evacuating products of combustion. At that time, such specific methods of evacuating products of combustion may be included at the request of the Technical Committees concerned.

## Explanatory notes

The following notes are given in explanation of the classification scheme.

**NOTE 1:** The general scheme classifies appliances as type A, B or C according to the basic principle for the evacuation of the products of combustion. These definitions are written intentionally in very broad terms in order to cover any possible variations in the basic appliance types.

A series of subscript numbers is used in addition to these letters to identify specific variations within these basic principles.

The last subscript number of each specific variation indicates the absence or presence of an integral fan for the supply of combustion air and/or for the evacuation of the products of combustion. Where such a fan is present, the numbers 2, 3 or 4 are given. These three numbers are used solely to identify the location of this fan.

**NOTE 2:** Diagrams have been given in annex A, showing examples of the various appliance types. However, it should be noted that diagrams for type C<sub>6</sub> appliances have not been included. This is because such appliances are marketed without duct systems. When installed such an appliance will have a configuration similar to one of the arrangements shown for other type C appliances.

Appliance Technical Committees have the responsibility for inclusion of requirements and methods of test in their standards to ensure that type C<sub>6</sub> appliances are suitable for their intended method(s) of installation.

**NOTE 3:** The supplementary classification scheme for type A and type B appliances has been included to clarify the identification of such appliances when fitted with different safety devices. The subscript letters "AS" (atmosphere safety) refer to an atmosphere sensing device and the subscript letters "BS" (blocked safety) refer to a clearance monitoring device, which reacts to blockage or restriction of the flue system.

In order to provide information about appliance types that are recognized in certain CEN member states, annex B has been included in which special national appliance classifications may be identified. At present, this annex identifies appliance types that are particular to Germany.

## 1 General scheme

The general scheme for type A, type B and type C appliances is given in 1.1, 1.2 and 1.3 respectively. Diagrams are also given in annex A to assist in the identification of the various appliance types.

### 1.1 Type A

An appliance not intended for connection to a flue or to a device for evacuating the products of combustion to the outside of the room in which the appliance is installed.

**Type A<sub>1</sub>.** An appliance without a fan.

**Type A<sub>2</sub>.** An appliance with a fan downstream of the combustion chamber/heat exchanger.

**Type A<sub>3</sub>.** An appliance with a fan upstream of the combustion chamber/heat exchanger.

## 1.2 Type B

An appliance intended to be connected to a flue that evacuates the products of combustion to the outside of the room containing the appliance. The combustion air is drawn directly from the room.

**Type B<sub>1</sub>.** A type B appliance incorporating a draught diverter.

**Type B<sub>11</sub>.** A natural draught type B<sub>1</sub> appliance.

**Type B<sub>12</sub>.** A type B<sub>1</sub> appliance designed for a natural draught flue incorporating a fan downstream of the combustion chamber/heat exchanger and upstream of the draught diverter.

**Type B<sub>13</sub>.** A type B<sub>1</sub> appliance designed for a natural draught flue incorporating a fan upstream of the combustion chamber/heat exchanger.

**Type B<sub>14</sub>.** A type B<sub>1</sub> appliance having an integral fan downstream of both the combustion chamber/heat exchanger and the draught diverter.

**Type B<sub>2</sub>.** A type B appliance without a draught diverter.

**Type B<sub>21</sub>.**<sup>1</sup> A natural draught type B<sub>2</sub> appliance.

**Type B<sub>22</sub>.** A type B<sub>2</sub> appliance incorporating a fan downstream of the combustion chamber/heat exchanger.

**Type B<sub>23</sub>.** A type B<sub>2</sub> appliance incorporating a fan upstream of the combustion chamber/heat exchanger.

**Type B<sub>3</sub>.** A type B appliance without a draught diverter, which is designed for connection to a common duct system. This common duct system consists of a single natural draught flue. All pressurized parts of the appliance containing products of combustion are completely enclosed by parts of the appliance supplying combustion air. Combustion air is drawn into the appliance from the room by means of a concentric duct, which encloses the flue. The air enters through defined orifices situated in the surface of the duct.

**Type B<sub>31</sub>.** A natural draught type B<sub>3</sub> appliance.

Appliances of this type are not foreseen.

**Type B<sub>32</sub>.** A type B<sub>3</sub> appliance incorporating a fan downstream of the combustion chamber/heat exchanger.

---

<sup>1</sup> A type B<sub>21</sub> appliance will not generally be included in the scope of European Standards for gas appliances. However, it may apply in special circumstances e.g. gas-fired incinerators.

**Type B<sub>33</sub>.** A type B<sub>3</sub> appliance incorporating a fan upstream of the combustion chamber/heat exchanger.

**Type B<sub>4</sub>.** A type B appliance, incorporating a draught diverter, that is **designed for connection** via its flue duct to its flue terminal.

**Type B<sub>41</sub>.** A natural draught type B<sub>4</sub> appliance.

**Type B<sub>42</sub>.** A type B<sub>4</sub> appliance designed for a natural draught flue incorporating a fan downstream of the combustion chamber/heat exchanger and upstream of the draught diverter.

**Type B<sub>43</sub>.** A type B<sub>4</sub> appliance designed for a natural draught flue incorporating a fan upstream of the combustion chamber/heat exchanger.

**Type B<sub>44</sub>.** A type B<sub>4</sub> appliance having an integral fan downstream of both the combustion chamber/heat exchanger and the draught diverter.

iTeh STANDARD PREVIEW

**Type B<sub>5</sub>.** A type B appliance, without a draught diverter, **that is designed for connection** via its flue duct to its flue terminal.

SIST-TP CR 1749:2005

**Type B<sub>51</sub>.**<sup>2</sup> A natural draught type B<sub>5</sub> appliance.

<https://standards.iteh.ai/catalog/standards/sist/142e28a8-bc19-491b-83e6-86a534a0ab68/sist-tp-cr-1749-2005>

**Type B<sub>52</sub>.** A type B<sub>5</sub> appliance incorporating a fan downstream of the combustion chamber/heat exchanger.

**Type B<sub>53</sub>.** A type B<sub>5</sub> appliance incorporating a fan upstream of the combustion chamber/heat exchanger.

### 1.3 Type C

An appliance in which the combustion circuit (air supply, combustion chamber, heat exchanger and evacuation of the products of combustion) is sealed with respect to the room in which the appliance is installed.

**Type C<sub>1</sub>.** A type C appliance that is designed for connection via its ducts to a horizontal terminal, which at the same time admits fresh air to the burner and discharges the products of combustion to the outside through orifices that are either concentric or close enough to come under similar wind conditions.

<sup>2</sup> A type B<sub>51</sub> appliance will not generally be included in the scope of European Standards for gas appliances. However, it may apply in special circumstances e.g. gas-fired incinerators.



**Type C<sub>11</sub>.** A natural draught type C<sub>1</sub> appliance.

**Type C<sub>12</sub>.** A type C<sub>1</sub> appliance incorporating a fan downstream of the combustion chamber/heat exchanger.

**Type C<sub>13</sub>.** A type C<sub>1</sub> appliance incorporating a fan upstream of the combustion chamber/heat exchanger.

**Type C<sub>2</sub>.** A type C appliance connected via two ducts to a common duct system<sup>3</sup> serving more than one appliance. This system consists of a single duct, which supplies the combustion air and evacuates the products of combustion.

**Type C<sub>21</sub>.** A natural draught type C<sub>2</sub> appliance.

**Type C<sub>22</sub>.** A type C<sub>2</sub> appliance incorporating a fan downstream of the combustion chamber/heat exchanger.

**Type C<sub>23</sub>.** A type C<sub>2</sub> appliance incorporating a fan upstream of the combustion chamber/heat exchanger.

**Type C<sub>3</sub>.** A type C appliance that is designed for connection via its ducts to a vertical terminal, which at the same time admits fresh air to the burner and discharges the products of combustion to the outside through orifices that are either concentric or close enough to come under similar wind conditions.

**Type C<sub>31</sub>.** A natural draught type C<sub>3</sub> appliance.

**Type C<sub>32</sub>.** A type C<sub>3</sub> appliance incorporating a fan downstream of the combustion chamber/heat exchanger.

**Type C<sub>33</sub>.** A type C<sub>3</sub> appliance incorporating a fan upstream of the combustion chamber/heat exchanger.

**Type C<sub>4</sub>.** A type C appliance connected via two ducts to a common duct system<sup>4</sup> serving more than one appliance. This common duct system consists of two ducts connected to a terminal, which at the same time admits fresh air to the burner and discharges the products of combustion to the outside through orifices that are either concentric or close enough to come under similar wind conditions.

**Type C<sub>41</sub>.** A natural draught type C<sub>4</sub> appliance.

---

<sup>3</sup> This common duct system is part of the construction of the building and not supplied with the appliance.

<sup>4</sup> This common duct system is part of the construction of the building and not supplied with the appliance.

Page 8  
CR 1749:2001

**Type C<sub>42</sub>.** A type C<sub>4</sub> appliance incorporating a fan downstream of the combustion chamber/heat exchanger.

**Type C<sub>43</sub>.** A type C<sub>4</sub> appliance incorporating a fan upstream of the combustion chamber/heat exchanger.

**Type C<sub>5</sub>.** A type C appliance connected to separate ducts for the supply of combustion air and the evacuation of the products of combustion. These ducts may terminate in zones of different pressure.

**Type C<sub>51</sub>.** A natural draught type C<sub>5</sub> appliance.

**Type C<sub>52</sub>.** A type C<sub>5</sub> appliance incorporating a fan downstream of the combustion chamber/heat exchanger.

**Type C<sub>53</sub>.** A type C<sub>5</sub> appliance incorporating a fan upstream of the combustion chamber/heat exchanger.

**Type C<sub>6</sub>.** A type C appliance which is intended to be connected to a separately approved and marketed system for the supply of combustion air and discharge of the combustion products. (see note 2 given in the foreword).

**Type C<sub>61</sub>.** A natural draught type C<sub>6</sub> appliance.

**Type C<sub>62</sub>.** A type C<sub>6</sub> appliance incorporating a fan downstream of the combustion chamber/heat exchanger.

**Type C<sub>63</sub>.** A type C<sub>6</sub> appliance incorporating a fan upstream of the combustion chamber/heat exchanger.

**Type C<sub>7</sub>.** A type C appliance with vertical air supply and combustion products evacuation ducts. The combustion air is taken from a loft and the products of combustion are discharged above the roof. A draught diverter is incorporated in the combustion products evacuation duct at a location above the combustion air inlet orifice(s).

**Type C<sub>71</sub>.** A natural draught type C<sub>7</sub> appliance.

**Type C<sub>72</sub>.** A type C<sub>7</sub> appliance incorporating a fan downstream of the combustion chamber/heat exchanger.

**Type C<sub>73</sub>.** A type C<sub>7</sub> appliance incorporating a fan upstream of the combustion chamber/heat exchanger.

**Type C<sub>8</sub>.** A type C appliance connected via a duct to a common duct system<sup>5</sup>. This common duct system consists of a single natural draught duct (i.e. not incorporating a fan) that evacuates the products of combustion. The appliance is connected via a second duct to a terminal, which supplies air to the appliance from outside the building.

**Type C<sub>81</sub>.** A natural draught type C<sub>8</sub><sup>6</sup> appliance.

**Type C<sub>82</sub>.** A type C<sub>8</sub> appliance incorporating a fan downstream of the combustion chamber/heat exchanger.

**Type C<sub>83</sub>.** A type C<sub>8</sub> appliance incorporating a fan upstream of the combustion chamber/heat exchanger.

## 2 Supplementary classification scheme for type A and type B appliances fitted with particular safety devices

**Type A<sub>AS</sub>.** A type A appliance fitted with an atmosphere sensing device,

e.g. type A<sub>1AS</sub>

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)

**Type B<sub>AS</sub>.** A type B appliance fitted with an atmosphere sensing device,

e.g. type B<sub>11AS</sub>. [SIST-TP CR 1749:2005  
https://standards.iteh.ai/catalog/standards/sist/142e28a8-bcf9-491b-83e6-86a334a0ab68/sist-tp-cr-1749-2005](https://standards.iteh.ai/catalog/standards/sist/142e28a8-bcf9-491b-83e6-86a334a0ab68/sist-tp-cr-1749-2005)

**Type B<sub>BS</sub>.** A type B appliance fitted with a clearance monitoring device,

e.g. type B<sub>11BS</sub>.

## 3 Supplementary classification scheme for type B appliances for use in limited installation conditions

**3.1 Type B appliance utilising a third subscript "D"<sup>7</sup>** indicating that the appliance is designed for connection to a flexible non-metallic duct that evacuates humid air and products of combustion to the outside of the room containing the appliance.

**Type B<sub>22D</sub>.** A type B<sub>22</sub> appliance that is designed for connection to a flexible non-metallic duct that evacuates humid air and products of combustion to the outside of the room containing the appliance.

<sup>5</sup> This common duct system is part of the construction of the building and not supplied with the appliance.

<sup>6</sup> A type C<sub>81</sub> appliance will not generally be included within the scope of European Standards for gas appliances.

<sup>7</sup> At present, these types are only applicable to gas-fired tumble dryers.

**Type B<sub>23D</sub>**. A type B<sub>23</sub> appliance that is designed for connection to a flexible non-metallic duct that evacuates humid air and products of combustion to the outside of the room containing the appliance.

**3.2 Type B appliances without draught diverters utilising a third subscript "P"**<sup>8</sup> indicating that the appliance is intended to be connected to a flue system that is designed to operate at a positive pressure. **This subscript "P" is only used when installation of the appliance in accordance with the appliance manufacturer's instructions on a flue specified by the appliance manufacturer results in the flue operating at a positive pressure.** The following types exist.

**Type B<sub>22P</sub>**. A type B<sub>22</sub> appliance intended to be connected to a flue system that is designed to operate at a positive pressure.

**Type B<sub>23P</sub>**. A type B<sub>23</sub> appliance intended to be connected to a flue system that is designed to operate at a positive pressure.

**Type B<sub>52P</sub>**. A type B<sub>52</sub> appliance intended to be connected to a flue system that is designed to operate at a positive pressure.

**Type B<sub>53P</sub>**. A type B<sub>53</sub> appliance intended to be connected to a flue system that is designed to operate at a positive pressure.

[SIST-TP CR 1749:2005](https://standards.iteh.ai/catalog/standards/sist/142e28a8-bcf9-491b-83e6-86a334a0ab68/sist-tp-cr-1749-2005)

<https://standards.iteh.ai/catalog/standards/sist/142e28a8-bcf9-491b-83e6-86a334a0ab68/sist-tp-cr-1749-2005>

---

<sup>8</sup> This identification "P" is in accordance with the designation of the classes of tightness, agreed by CEN/TC 166: Chimneys, depending on the pressure of operation of the duct (e.g. see prEN 1443)