



IEC 61800-7-201

Edition 2.0 2015-11
REDLINE VERSION

INTERNATIONAL STANDARD



Adjustable speed electrical power drive systems –
Part 7-201: Generic interface and use of profiles for power drive systems –
Profile type 1 specification
<https://standards.iteh.ai>
Document Preview

[IEC 61800-7-201:2015](#)

<https://standards.iteh.ai/catalog/standards/iec/d41af779-7259-401c-a1c0-ddcc972386ca/iec-61800-7-201-2015>





THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2015 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in 15 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

More than 60 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

[IEC 61800-7-201:2015](http://iec-61800-7-201:2015)

<https://standards.iteh.ai/catalog/standards/iec/d41af779-7259-401c-a1c0-ddcc972386ca/iec-61800-7-201-2015>



IEC 61800-7-201

Edition 2.0 2015-11
REDLINE VERSION

INTERNATIONAL STANDARD



Adjustable speed electrical power drive systems –
Part 7-201: Generic interface and use of profiles for power drive systems –
Profile type 1 specification

Document Preview

[IEC 61800-7-201:2015](#)

<https://standards.iteh.ai/catalog/standards/iec/d41af779-7259-401c-a1c0-ddcc972386ca/iec-61800-7-201-2015>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 29.200; 35.100.05

ISBN 978-2-8322-3048-0

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD	17
INTRODUCTION	19
1 Scope	23
2 Normative references	23
3 Terms, definitions and abbreviated terms	23
3.1 Terms and definitions	23
3.2 Abbreviated terms	27
4 General	28
4.1 General considerations	28
4.2 Communication interface	29
4.3 Object dictionary	29
5 Data types	30
5.1 Standard data types	30
5.2 Record definitions	30
6 General object definitions	31
6.1 General	31
6.2 Communication parameter objects	31
6.3 Additional identification and information objects	32
6.3.1 Object 6402 _h : Motor type	32
6.3.2 Object 6403 _h : Motor catalogue number	33
6.3.3 Object 6404 _h : Motor manufacturer	34
6.3.4 Object 6405 _h : http motor catalogue address	35
6.3.5 Object 6406 _h : Motor calibration date	35
6.3.6 Object 6407 _h : Motor service period	36
6.3.7 Object 6503 _h : Drive catalogue number	36
6.3.8 Object 6505 _h : http drive catalogue address	37
7 Error codes and error behavior	37
7.1 Error codes	37
7.2 Error behavior	41
8 Controlling the power drive system	42
8.1 General	42
8.2 Finite state automaton	42
8.3 Modes of operation	45
8.4 Detailed object specifications	46
8.4.1 Object 6040 _h : Controlword	46
8.4.2 Object 6041 _h : Statusword	47
8.4.3 Object 603F _h : Error code	49
8.4.4 Object 6007 _h : Abort connection option code	50
8.4.5 Object 605A _h : Quick stop option code	51
8.4.6 Object 605B _h : Shutdown option code	51
8.4.7 Object 605C _h : Disable operation option code	52
8.4.8 Object 605D _h : Halt option code	53
8.4.9 Object 605E _h : Fault reaction option code	54
8.4.10 Object 6060 _h : Modes of operation	54
8.4.11 Object 6061 _h : Modes of operation display	56

8.4.12	Object 6502 _h : Supported drive modes	56
9	Factor group	57
9.1	General.....	57
9.2	Detailed object definitions	59
9.2.1	Object 608F _h : Position encoder resolution.....	59
9.2.2	Object 6090 _h : Velocity encoder resolution	60
9.2.3	Object 6091 _h : Gear ratio	62
9.2.4	Object 6092 _h : Feed constant	63
9.2.5	Object 6096 _h : Velocity factor	64
9.2.6	Object 6097 _h : Acceleration factor	64
9.2.7	Object 60A2 _h : Jerk factor	65
9.2.8	Object 607E _h : Polarity	66
9.2.9	Code table for device profile specific units	67
9.2.10	Object 60A8 _h : SI unit position.....	67
9.2.11	Object 60A9 _h : SI unit velocity	68
9.2.12	Object 60AA _h : SI unit acceleration	69
9.2.13	Object 60AB _h : SI unit jerk.....	70
10	Profile position mode	70
10.1	General information	70
10.2	Functional description	71
10.2.1	General	71
10.2.2	Single set-point	72
10.2.3	Set of set-points	73
10.2.4	Usage of halt bit in conjunction with new set-point bit	74
10.3	General definitions.....	75
10.4	Use of controlword and statusword	75
10.5	Detailed object definitions	76
10.5.1	Object 607A _h : Target position	76
10.5.2	Object 607B _h : Position range limit	77
10.5.3	Object 607D _h : Software position limit	78
10.5.4	Object 607F _h : Max profile velocity	80
10.5.5	Object 6080 _h : Max motor speed	81
10.5.6	Object 6081 _h : Profile velocity	81
10.5.7	Object 6082 _h : End velocity	82
10.5.8	Object 6083 _h : Profile acceleration	82
10.5.9	Object 6084 _h : Profile deceleration	83
10.5.10	Object 6085 _h : Quick stop deceleration.....	83
10.5.11	Object 6086 _h : Motion profile type	84
10.5.12	Object 60A3 _h : Profile jerk use	85
10.5.13	Object 60A4 _h : Profile jerk	85
10.5.14	Object 60C5 _h : Max acceleration	87
10.5.15	Object 60C6 _h : Max deceleration	88
11	Homing mode	89
11.1	General information	89
11.2	Functional description	89
11.3	General definitions.....	90
11.3.1	General	90
11.3.2	Method 1: Homing on negative limit switch and index pulse	90
11.3.3	Method 2: Homing on positive limit switch and index pulse	90

11.3.4	Method 3 and 4: Homing on positive home switch and index pulse	90
11.3.5	Method 5 and 6: Homing on negative home switch and index pulse	91
11.3.6	Method 7 to 14: Homing on home switch and index pulse	91
11.3.7	Method 15 and 16: Reserved	92
11.3.8	Method 17 to 30: Homing without index pulse	92
11.3.9	Method 31 and 32: Reserved	93
11.3.10	Method 33 and 34: Homing on index pulse	93
11.3.11	Method 35: Homing on index pulse current position (obsolete)	93
11.3.12	Method 36: Homing with touch probe Reserved for compatibility reasons	93
11.3.13	Method 37: Homing on current position	93
11.4	Use of controlword and statusword	94
11.5	Detailed object definitions	94
11.5.1	Object 607Ch: Home offset	94
11.5.2	Object 6098h: Homing method	95
11.5.3	Object 60E3h: Supported homing methods	96
11.5.4	Object 6099h: Homing speeds	97
11.5.5	Object 609Ah: Homing acceleration	98
12	Touch probe functionality	99
12.1	Object 60B8h: Touch probe function	99
12.2	Object 60B9h: Touch probe status	101
12.3	Object 60BAh: Touch probe pos1 pos value 1 positive edge	102
12.4	Object 60BBh: Touch probe pos1 neg value 1 negative edge	102
12.5	Object 60BCh: Touch probe pos2 pos value 2 positive edge	103
12.6	Object 60BDh: Touch probe pos2 neg value 2 negative edge	103
12.7	Object 60D0h: Touch probe source	104
12.8	Touch probe time stamp latch	105
12.8.1	General	105
12.8.2	Object 60D1h: Touch probe time stamp 1 positive value IEC 61800-7-201:2015	106
12.8.3	Object 60D2h: Touch probe time stamp 1 negative value	106
12.8.4	Object 60D3h: Touch probe time stamp 2 positive value	107
12.8.5	Object 60D4h: Touch probe time stamp 2 negative value	107
12.9	Touch probe edge counter for continuous mode	108
12.9.1	General	108
12.9.2	Object 60D5h: Touch probe 1 positive edge counter	108
12.9.3	Object 60D6h: Touch probe 1 negative edge counter	108
12.9.4	Object 60D7h: Touch probe 2 positive edge counter	109
12.9.5	Object 60D8h: Touch probe 2 negative edge counter	110
12.10	Timing diagram for touch probe example	110
13	Position control function	112
13.1	General information	112
13.2	Functional description	112
13.3	Detailed object definitions	115
13.3.1	Object 6062h: Position demand value	115
13.3.2	Object 6063h: Position actual internal value	115
13.3.3	Object 6064h: Position actual value	116
13.3.4	Object 6065h: Following error window	116
13.3.5	Object 6066h: Following error time out	117
13.3.6	Object 6067h: Position window	118
13.3.7	Object 6068h: Position window time	118

13.3.8	Object 60F4 _h : Following error actual value	119
13.3.9	Object 60FA _h : Control effort	119
13.3.10	Object 60FC _h : Position demand internal value.....	120
13.3.11	Object 60F2 _h : Positioning option code.....	120
14	Interpolated position mode	124
14.1	General information	124
14.2	Functional description	125
14.2.1	General	125
14.2.2	Linear interpolated position mode with several axes	125
14.2.3	Buffer strategies for the interpolated position mode	127
14.2.4	Interpolated position mode FSA	128
14.3	General definitions.....	129
14.4	Use of controlword and statusword	129
14.5	Detailed object definitions	130
14.5.1	Object 60C0 _h : Interpolation sub mode select	130
14.5.2	Object 60C1 _h : Interpolation data record.....	131
14.5.3	Object 60C2 _h : Interpolation time period	132
14.5.4	Object 60C4 _h : Interpolation data configuration	133
15	Profile velocity mode	136
15.1	General information	136
15.2	Functional description	137
15.3	General definitions.....	137
15.4	Use of controlword and statusword	137
15.5	Detailed object definitions	138
15.5.1	Object 6069 _h : Velocity sensor actual value	138
15.5.2	Object 606A _h : Sensor selection code	139
15.5.3	Object 606B _h : Velocity demand value.....	139
15.5.4	Object 606C _h : Velocity actual value.....	140
15.5.5	Object 606D _h : Velocity window	140
15.5.6	Object 606E _h : Velocity window time	141
15.5.7	Object 606F _h : Velocity threshold	141
15.5.8	Object 6070 _h : Velocity threshold time.....	142
15.5.9	Object 60FF _h : Target velocity	142
15.5.10	Object 60F8 _h : Max slippage	143
16	Profile torque mode	144
16.1	General information	144
16.2	Functional description	144
16.3	General definitions.....	145
16.4	Use of controlword and statusword	145
16.5	Detailed object definitions	145
16.5.1	Object 6071 _h : Target torque	145
16.5.2	Object 6072 _h : Max torque.....	146
16.5.3	Object 60E0 _h : Positive torque limit value.....	146
16.5.4	Object 60E1 _h : Negative torque limit value	147
16.5.5	Object 6073 _h : Max current.....	148
16.5.6	Object 6074 _h : Torque demand.....	148
16.5.7	Object 6075 _h : Motor rated current	149
16.5.8	Object 6076 _h : Motor rated torque	149
16.5.9	Object 6077 _h : Torque actual value	150

16.5.10	Object 6078 _h : Current actual value.....	150
16.5.11	Object 6079 _h : DC link circuit voltage	151
16.5.12	Object 6087 _h : Torque slope.....	151
16.5.13	Object 6088 _h : Torque profile type.....	152
17	Velocity mode.....	152
17.1	General information	152
17.2	Functional description	153
17.2.1	17.2.1 Velocity limit function.....	
17.2.1	Ramp function	153
17.2.2	Velocity control function.....	154
17.2.3	Factor function.....	154
17.3	General definitions.....	155
17.4	Use of controlword and statusword	155
17.5	Detailed object definitions.....	156
17.5.1	Object 6042 _h : vl target velocity.....	156
17.5.2	Object 6043 _h : vl velocity demand	156
17.5.3	Object 6044 _h : vl velocity actual value	157
17.5.4	Object 6046 _h : vl velocity min max amount	158
17.5.5	Object 6049 _h : vl velocity deceleration.....	159
17.5.6	Object 6048 _h : vl velocity acceleration	160
17.5.7	Object 604A _h : vl velocity quick stop.....	162
17.5.8	Object 604B _h : vl set-point factor	163
17.5.9	Object 604C _h : vl dimension factor	164
18	Cyclic synchronous position mode.....	166
18.1	General information	166
18.2	Functional description	166
18.3	Use of controlword and statusword	167
18.4	Detailed object definitions.....	168
18.4.1	Object 60B0 _h : Position offset.....	168
18.4.2	Object 60B1 _h : Velocity offset.....	168
18.4.3	Object 60B2 _h : Torque offset	169
19	Cyclic synchronous velocity mode	170
19.1	General information	170
19.2	General definitions.....	171
19.3	Functional description	171
19.4	Use of controlword and statusword	171
20	Cyclic synchronous torque mode	172
20.1	General information	172
20.2	General definitions.....	173
20.3	Functional description	173
20.4	Use of controlword and statusword	173
21	Cyclic synchronous torque mode with commutation angle (cstca)	174
21.1	General information	174
21.2	General definitions.....	175
21.3	Functional description	175
21.4	Use of controlword and statusword	176
21.5	Object 60EA _h : Commutation angle.....	177
22	Support of additional sensor interfaces	177

22.1	General.....	177
22.2	Object 60E4 _h : Additional position actual value.....	177
22.3	Object 60E5 _h : Additional velocity actual value	178
22.4	Object 60E6 _h : Additional position encoder resolution – encoder increments	179
22.5	Object 60EB _h : Additional position encoder resolution – motor revolutions.....	181
22.6	Object 60E7 _h : Additional velocity encoder resolution – encoder increments per second.....	182
22.7	Object 60EC _h : Additional velocity encoder resolution – motor revolutions per second	184
22.8	Object 60E8 _h : Additional gear ratio – motor shaft revolutions	185
22.9	Object 60ED _h : Additional gear ratio – driving shaft revolutions	186
22.10	Object 60E9 _h : Additional feed constant – feed	187
22.11	Object 60EE _h : Additional feed constant – driving shaft revolutions	188
23	Optional application FE	189
23.1	General.....	189
23.2	Object 60FD _h : Digital inputs	189
23.3	Object 60FE _h : Digital outputs	190
24	Device information.....	192
24.1	General.....	192
24.2	Object 67FE _h : Version number	192
	Bibliography.....	194

Figure 1 – Structure of IEC 61800-7.....22

Figure 2 – Value definition32

Figure 3 – Remote and local control.....42

Figure 4 – Power drive system finite state automaton

Figure 5 – Relation between different value parameters.....46

Figure 6 – Value definition

Figure 7 – Value definition

Figure 8 – Value definition

Figure 9 – Position scaling concept.....58

Figure 10 – Value definition

Figure 11 – Example for a position unit.....68

Figure 12 – Example for a velocity unit

Figure 13 – Example for an acceleration unit

Figure 14 – Example for a jerk unit

Figure 15 – Trajectory generator and position control function

Figure 16 – Trajectory generator for profile position mode

Figure 17 – Set-point example

Figure 18 – Handshaking procedure for the single set-point method

Figure 19 – Handshaking procedure for the set of set-points method

Figure 20 – Set-point handling for two set-points

Figure 21 – Erase set-point.....75

Figure 22 – Controlword for profile position (pp) mode.....75

Figure 23 – Statusword for profile position (pp) mode

Figure 24 – Software position limits

Figure 25 – Velocity/time diagram with jerk positions	86
Figure 26 – Homing mode function.....	89
Figure 27 – Homing on negative limit switch and index pulse	90
Figure 28 – Homing on positive limit switch and index pulse	90
Figure 29 – Homing on positive home switch and index pulse	91
Figure 30 – Homing on negative home switch and index pulse.....	91
Figure 31 – Homing on home switch and index pulse – positive initial motion	92
Figure 32 – Homing on home switch and index pulse – negative initial motion	92
Figure 33 – Homing on positive home switch	93
Figure 34 – Homing on index pulse.....	93
Figure 35 – Controlword for homing mode.....	94
Figure 36 – Statusword for homing mode	94
Figure 37 – Home offset definition	95
Figure 38 – Timing diagram for touch probe example	111
Figure 39 – Position control function	113
Figure 40 – Following error (functional overview)	113
Figure 41 – Position reached (functional overview)	114
Figure 42 – Position reached (definitions).....	114
Figure 43 – Following error (definitions).....	115
Figure 44 – Object structure.....	121
Figure 45 – Rotary axis positioning example	122
Figure 46 – Example for absolute movement greater than modulo value	123
Figure 47 – Example for relative movement greater than modulo value	123
Figure 48 – Interpolation controller IEC 61800-7-201:2015	125
Figure 49 – Interpolated position mode for two axes	126
Figure 50 – Linear interpolation for one axis	127
Figure 51 – Input buffer organization	128
Figure 52 – Input buffer examples.....	128
Figure 53 – Interpolated position mode FSA	129
Figure 54 – Controlword for interpolated position mode	129
Figure 55 – Statusword for interpolated position mode	130
Figure 56 – Profile velocity mode	137
Figure 57 – Controlword for profile velocity mode	137
Figure 58 – Statusword for profile velocity mode	138
Figure 59 – Structure of the profile torque mode	144
Figure 60 – Controlword for profile torque mode	145
Figure 61 – Statusword for profile torque mode.....	145
Figure 62 – Velocity mode with all objects	153
Figure 63 – Velocity mode with mandatory objects only	153
Figure 64 – Velocity profile	154
Figure 65 – Factor function	154
Figure 66 – Reverse factor function	154
Figure 67 – Controlword for profile velocity mode	155

Figure 68 – Usage of controlword bits in velocity mode	155
Figure 69 – Statusword for profile velocity mode	156
Figure 70 – Transfer characteristic of vl velocity min max amount	158
Figure 71 – Transfer characteristic of the velocity deceleration	159
Figure 72 – Transfer characteristic of the velocity acceleration	161
Figure 73 – Transfer characteristic of the quick stop deceleration	162
Figure 74 – Cyclic synchronous position mode overview	166
Figure 75 – Cyclic synchronous position control function	167
Figure 76 – Statusword for profile cyclic synchronous position mode	167
Figure 77 – Cyclic synchronous velocity mode overview	170
Figure 78 – Cyclic synchronous velocity control function	171
Figure 79 – Statusword for profile cyclic synchronous velocity mode	172
Figure 80 – Cyclic synchronous torque mode overview	173
Figure 81 – Cyclic synchronous torque control function	173
Figure 82 – Statusword for profile cyclic synchronous torque mode	174
Figure 83 – Cyclic synchronous torque mode with commutation angle overview	175
Figure 84 – Cyclic synchronous torque with commutation angle control function	176
Figure 85 – Statusword for cstca mode	176
Figure 86 – Object structure	190
Figure 87 – Object structure	191
Figure 88 – Structure of the standard version parameter	192

Table 1 – List of used data types	30
---	----

Table 2 – Interpolated Interpolation time period	31
---	----

Table 3 – Interpolated Interpolation data configuration	31
--	----

Table 4 – vl velocity acceleration/deceleration	31
---	----

Table 5 – Object description	32
------------------------------------	----

Table 6 – Entry description	32
-----------------------------------	----

Table 7 – Value definition	33
----------------------------------	----

Table 8 – Object description	33
------------------------------------	----

Table 9 – Entry description	33
-----------------------------------	----

Table 10 – Object description	34
-------------------------------------	----

Table 11 – Entry description	34
------------------------------------	----

Table 12 – Object description	34
-------------------------------------	----

Table 13 – Entry description	34
------------------------------------	----

Table 14 – Object description	35
-------------------------------------	----

Table 15 – Entry description	35
------------------------------------	----

Table 16 – Object description	35
-------------------------------------	----

Table 17 – Entry description	35
------------------------------------	----

Table 18 – Object description	36
-------------------------------------	----

Table 19 – Entry description	36
------------------------------------	----

Table 20 – Object description	36
-------------------------------------	----

Table 21 – Entry description	36
------------------------------------	----

Table 22 – Object description	37
Table 23 – Entry description	37
Table 24 – Error codes	38
Table 25 – FSA states and supported functions	43
Table 26 – Transition events and actions	44
Table 27 – Command coding	47
Table 28 – Object description	47
Table 29 – Entry description	47
Table 30 – State coding	48
Table 31 – Object description	49
Table 32 – Entry description	49
Table 33 – Object description	49
Table 34 – Entry description	50
Table 35 – Value definition	50
Table 36 – Object description	50
Table 37 – Entry description	50
Table 38 – Value definition	51
Table 39 – Object description	51
Table 40 – Entry description	51
Table 41 – Value definition	52
Table 42 – Object description	52
Table 43 – Entry description	52
Table 44 – Value definition	52
Table 45 – Object description	53
Table 46 – Entry description	53
Table 47 – Value definition	53
Table 48 – Object description	53
Table 49 – Entry description	54
Table 50 – Value definition	54
Table 51 – Object description	54
Table 52 – Entry description	54
Table 53 – Value definition	55
Table 54 – Object description	55
Table 55 – Entry description	55
Table 56 – Object description	56
Table 57 – Entry description	56
Table 58 – Object description	57
Table 59 – Entry description	57
Table 60 – Object description	60
Table 61 – Entry description	60
Table 62 – Object description	61
Table 63 – Entry description	61
Table 64 – Object description	62

Table 65 – Entry description	62
Table 66 – Object description	63
Table 67 – Entry description	63
Table 68 – Object description	64
Table 69 – Entry description	64
Table 70 – Object description	65
Table 71 – Entry description	65
Table 72 – Object description	66
Table 73 – Entry description	66
Table 74 – Object description	67
Table 75 – Entry description	67
Table 76 – Device profile specific units	67
Table 77 – Object description	68
Table 78 – Entry description	68
Table 79 – Object description	68
Table 80 – Entry description	69
Table 81 – Object description	69
Table 82 – Entry description	69
Table 83 – Object description	70
Table 84 – Entry description	70
Table 85 – Definition of bit 4, bit 5, and bit 9	76
Table 86 – Definition of bit 6 and bit 8	76
Table 87 – Definition of bit 10, bit 12, and bit 13	76
Table 88 – Object description	77
Table 89 – Entry description	77
Table 90 – Object description	77
Table 91 – Entry description	78
Table 92 – Object description	79
Table 93 – Entry description	80
Table 94 – Object description	80
Table 95 – Entry description	81
Table 96 – Object description	81
Table 97 – Entry description	81
Table 98 – Object description	82
Table 99 – Entry description	82
Table 100 – Object description	82
Table 101 – Entry description	82
Table 102 – Object description	83
Table 103 – Entry description	83
Table 104 – Object description	83
Table 105 – Entry description	83
Table 106 – Object description	84
Table 107 – Entry description	84

Table 108 – Value definition.....	84
Table 109 – Object description.....	84
Table 110 – Entry description	85
Table 111 – Object description.....	85
Table 112 – Entry description	85
Table 113 – Value assignments	86
Table 114 – Object description.....	86
Table 115 – Entry description	87
Table 116 – Object description.....	88
Table 117 – Entry description	88
Table 118 – Object description.....	88
Table 119 – Entry description	88
Table 120 – Definition of bit 4 and bit 8.....	94
Table 121 – Definition of bit 10, bit 12, and bit 13	94
Table 122 – Object description.....	95
Table 123 – Entry description	95
Table 124 – Value definition.....	96
Table 125 – Object description.....	96
Table 126 – Entry description	96
Table 127 – Object description.....	96
Table 128 – Entry description	97
Table 129 – Object description.....	98
Table 130 – Entry description	98
Table 131 – Object description.....	99
Table 132 – Entry description	99
Table 133 – Value definition.....	100
Table 134 – Object description.....	100
Table 135 – Entry description	101
Table 136 – Value definition.....	101
Table 137 – Object description.....	101
Table 138 – Entry description	102
Table 139 – Object description.....	102
Table 140 – Entry description	102
Table 141 – Object description.....	102
Table 142 – Entry description	103
Table 143 – Object description.....	103
Table 144 – Entry description	103
Table 145 – Object description.....	103
Table 146 – Entry description	104
Table 147 – Value definition.....	104
Table 148 – Object description.....	104
Table 149 – Entry description	105
Table 150 – Object description.....	106