

Edition 4.0 2015-12

# INTERNATIONAL STANDARD





### THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2015 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office Tel.: +41 22 919 02 11 3, rue de Varembé Fax: +41 22 919 03 00

CH-1211 Geneva 20 info@iec.ch Switzerland www.iec.ch

### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

### About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

### IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and

### IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

### IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications, Just Published details all new publications released. Available online and also once a month by email.

### Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in 15 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

More than 60 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.


### IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.



Edition 4.0 2015-12

# INTERNATIONAL STANDARD



Specification for the testing of balanced and coaxial information technology cabling –

Part 1: Installed balanced cabling as specified in ISO/IEC 11801 and related standards





ICS 33.120.10 ISBN 978-2-8322-3057-2

Warning! Make sure that you obtained this publication from an authorized distributor.

### CONTENTS

IN.	TRODU	JCTION	11			
1	Scop	oe	12			
2	Norn	ative references				
3	Tern	ns, definitions and abbreviations	14			
	3.1	Terms and definitions	14			
	3.2	Abbreviations				
4	Refe	rence measurement procedures for electrical properties	17			
	4.1	General				
	4.2	^\ \ \ \	17			
	4.2.1	Test equipment considerations	<u>1</u> 7			
	4.2.2		18			
	4.2.3					
	4.2.4					
	4.2.5	Reference loads for calibration				
	4.2.6					
	4.2.7	Coaxial cables and test leads for network analysers	20			
	4.2.8					
	4.2.9	Balun requirements	2			
	4.2.1	0 Network analyser measurement precautions	22			
	4.2.1	1 Data reporting and accuracy.	2			
	4.3	DC loop resistance	2			
	4.3.1					
	4.3.2	450 1155 112015				
	4.3.3	V / \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \				
	4.3.4					
	4.3.5	\ \'\\				
	4.3.6					
	4.3.7					
	4.4	Direct current (DC) resistance unbalance				
	4.4.1					
	4.4.2					
	4.4.3	and the first of the second				
	4.4.4					
	4.4.5	•				
	4.4.6	· · · · · · · · · · · · · · · · · · ·				
	4.5	Insertion loss				
	4.5.1	,				
	4.5.2					
	4.5.3	• • • • • • • • • • • • • • • • • • • •				
	4.5.4					
	4.5.5	•				
	4.5.6	,				
	4.6 4.6.1	Propagation delay and delay skew				
	4.6.2	,				

4.6.3	lest equipment and set-up	28
4.6.4	Procedure	28
4.6.5	Test report	29
4.6.6	Uncertainty	
	ar-end cross-talk (NEXT) and power sum NEXT	
4.7.1	Objective	
	•	
4.7.2	Test method	
4.7.3	Test equipment and set-up	
4.7.4	Procedure	30
4.7.5	Test report	31
4.7.6	Uncertainty	31
4.8 Atte	enuation to crosstalk ratio, near end (ACR-N) and power sum ACR-N	31
4.8.1	Objective	31
4.8.2		31
4.8.3	Test equipment and set-up	-
4.8.4	Procedure and calculation	
_		
4.8.5	Test report	
4.8.6	Uncertainty	
4.9 Far	-end cross-talk (FEXT) and power sum FEXT	
4.9.1	Objective	32
4.9.2	Test method	32
4.9.3	Test equipment and set-up	32
4.9.4	Procedure	33
4.9.5	Test report	
4.9.6	Uncertainty of FEXT measurements	
	enuation to crosstalk ratio, far end (ACR-F)	
4.10.1		
	Objective	
ttps://star4.10.2 ite	Calculation	
4.10.3	Test report	
4.10.4	Urceltainty	
/	turn loss	
4.11.1	Objective	35
4.14.2	Test method	35
4.11.3	Test equipment and set-up	35
4.11.4	Procedure	
4.11.5	Test report	
4.11.6	Uncertainty	
	•	
	Alien near end crosstalk (PS ANEXT – Exogenous crosstalk)	
4.12.1	Objective	
4.12.2	Test method	
4.12.3	Test equipment and set-up	36
4.12.4	Procedure	37
	Attenuation to alien crosstalk ratio, far end crosstalk (PS AACR-F – ogenous crosstalk)	39
4.13.1	Objective	
4.13.2	Test method	
4.13.2		
	Test equipment and set-up	
4.13.4	Procedure	
4 14   IInl	halance attenuation, near end	43

4.14.1	Objective	43
4.14.2	Test method	43
4.14.3	Test equipment and set-up	43
4.14.4	Procedure	44
4.14.5	Test report	46
4.14.6	Uncertainty	46
4.15 Un	balance attenuation, far end	47
4.15.1	Objective	47
4.15.2	Test method	47
4.15.3	Test equipment and set-up	47
4.15.4	Procedure	48
4.15.5	7	49
4.15.6		49
4.16 Co	upling attenuation	49
5 Field tes	et measurement requirements for electrical properties	49
5.1 Int	roductory remark	49
	bling configurations tested	_
	eld test parameters	
5.3.1	General	
5.3.2	Inspection of workmanship and connectivity testing	
5.3.3	Propagation delay and delay skew	
5.3.4	Length	
5.3.5	Insertion loss	53
5.3.6	NEXT nowersum NEXT	53
5.3.7	ACR-N and power sum ACR-N	54
5.3.8	ELFEXT, power sum ELFEXT, ACR-F, power sum ACR-F	
5.3.9	Refurn loss	
ttns://star5.3.10ite	Direct current (DC) loop resistance adhilasila.	
	wer sum alien crosstałk	
5.4.1	Objective	
5.4.2	Test method	
5.4.3	Test equipment and set-up	
5.4.4	Measuring ANEXT loss	
5.4.5	Measuring AFEXT loss	
5.4.6	Procedure	
5.4.7	Calculation of PS ANEXT and PS AACR-F from measured data	
5.4.8	Selection of test ports	
5.4.9	Test report	
5.4.10	Uncertainty of PS alien crosstalk measurements	
	ta reporting and accuracy	
5.5.1	General	
5.5.2	Detailed results	
5.5.3	Summary results	
5.5.4	Reporting requirements for power sum alien crosstalk	
5.5.5	General	
5.5.6	Consistency checks for field testers	
5.5.7	Evaluation of consistency tests	
5.5.8	Administration system applicability	
5.5.9	Test equipment adapter cords for link testing	
5.5.8	root equipment adapter colds for link testing	

5.5.10	User cords and channel testing	70
6 Field tes	ter measurement accuracy requirements	70
6.1 Ge	neral	70
6.2 Me	easurement accuracy specifications common to level IIE, level III, level	
	E, level IV and level V field testers	
6.3 Ac	curacy performance requirements for Level IIE field testers	74
6.4 Ac	curacy performance requirements for level III field testers	76
6.5 Ac	curacy performance requirements for level IIIE field testers	78
6.6 Ac	curacy performance requirements for level IV field testers	79
6.7 Ac	curacy performance requirements for level V field testers	81
6.8 Fie	eld tester requirements applicable to alien crosstalk measurements	83
6.9 Pro	ocedures for determining field tester parameters	83
6.9.1	General	83
6.9.2	Output signal balance (OSB)	84
6.9.3	Output signal balance (OSB)	84
6.9.4	Residual NEXT	85
6.9.5	Dynamic accuracy Source/load return loss	86
6.9.6	Source/load return loss	86
6.9.7	Random noise floor	87
6.9.8	Residual FEXT	87
6.9.9	Directivity	88
6.9.10	Tracking	88
6.9.11	Tracking  Source match  Return loss of remote termination	89
6.9.12	Return loss of remote termination	89
6.9.13	Constant error term of the propagation delay measurement function	
6.9.14	Error constant term proportional to propagation delay of the propagation	
0.5.14	delay measurement function	89
6.9.15	Constant error term of the delay skew measurement function	
6.9.16	Constant error term of the length measurement function	
6.9.17	Error constant proportional to the length of measurement function	
	(assuming the cables are taken from the same drum)	90
6.9.18	Constant error term of the DC resistance measurement function	90
6.9.19	Error constant term proportional to DC resistance of the DC resistance	
	measurement function	
6.9.20	Measurement floor for alien crosstalk testing during field testing	
6.10 Me	easurement error models	92
6.10.1	General	
6.10.2	Error model for the insertion loss measurement function	92
6.10.3	Error model for the NEXT measurement function	92
6.10.4	Error model for the power sum NEXT measurement function	93
6.10.5	Error model for the ACR-N measurement function	93
6.10.6	Error model for the power sum ACR-N measurement function	94
6.10.7	Error model for the ELFEXT or ACR-F measurement function	94
6.10.8	Error model for the power sum ELFEXT and PS ACR-F measurement	
	functions	
6.10.9	Error model for the return loss measurement function	
6.10.10	Error model for the propagation delay measurement function	
6.10.11	Error model for the delay skew measurement function	
6.10.12	Error model for the length measurement function	97
6.10.13	Error model for the DC loop resistance measurement function	97

6.11	Network analyzer measurement comparisons	97
6.11.		
6.11.	<b>'</b>	
6.11.	•	
Annex A (	informative) Uncertainty and variability of field test results	
A.1	General	
A.2	Marginal results reporting	
A.3	Nominal accuracy	
	Variability in link measurements not included in the measurement accuracy	
A.5	Variability in channel measurements	
A.6	Field tester accuracy checks	
A.6.1	General	106
A.6.2	- Print 3	106
A.6.3		106
A.6.4 A.6.5	^ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	106
A.6.5 A.6.6		
A.6.6 A.6.7		
	normative) Reference laboratory test configuration for alien crosstalk testing	
B.1	General	
	Test parameters	
	Link and channel construction.	
В.3 В.4	Determination of number of disturbing links or channels	
B.5	Computation of results	
B.6	Test report	
	informative) General information on power sum alien crosstalk performance	110
of installat	tions	111
ttps: Annex D (	informative) Baluns	.93112-
Bibliograp		
9		
Figure 1	Resistor load	1Ω
ŭ		
	Reference planes for permanent link, CP link and channel	
	180° hybrid used as a balun	
	DC loop resistance measurement	
Figure 5 –	DC resistance unbalance measurement	26
Figure 6 –	Insertion loss test configuration	27
Figure 7 –	NEXT test configuration	30
Figure 8 –	FEXT test configuration	33
	Return loss test configuration	
_	– ANEXT measurement	
_	Alien far end crosstalk measurement	
_		
	Unbalance attenuation, near end test configuration	
_	Back-to-back balun differential mode insertion loss measurement	
Figure 14	Back-to-back balun common mode insertion loss measurement	45
Figure 15	Unbalance performance test of the measurement balun	46
Figure 16	Unbalance attenuation far end test configuration	48

Figure 17 – Correct pairing	51
Figure 18 – Incorrect pairing	52
Figure 19 – Schematic diagram to measure channel ANEXT loss	57
Figure 20 – AFEXT loss measurement test configuration	58
Figure 21 – Flow chart of the alien crosstalk test procedure	62
Figure 22 – Example of equipment tolerance region (NEXT)	64
Figure 23 – Block diagram for measuring output signal balance	84
Figure 24 – Block diagram to measure common mode rejection	85
Figure 25 – Block diagram for measuring residual NEXT	86
Figure 26 – Block diagram for measuring dynamic accuracy	86
Figure 27 – Principle of measurement of residual FEXT	87
Figure 28 – Principle of alternate measurement of residual FEXT	88
Figure 29 – Alien crosstalk measurement floor test for the channel test configuration	91
Figure 30 – Alien crosstalk measurement floor test for the link test configurations	91
Figure 31 – Construction details of special patch cord adapter	98
Figure 32 – Interfaces to channel by field test and laboratory equipment to compare test results	99
Figure 33 – Interfaces to link test configuration by field test and laboratory equipment to compare test results	100
Figure 34 – Sample scatter plot	
Figure A.1 – Source of variability during link testing	105
Figure D.1 – Configurations for qualifying test baluns	
Oveny First Michigan	
Table 1 – Mixed mode S-parameter nomenclature	21
Table 2 – Test balun performance characteristics	22
Table 3 – Estimated uncertainty of unbalance, near end measurement	47
Table 4 – Estimated uncertainty of unbalance, far end measurement	49
Table 5 – Summary of reporting requirements for field test equipment (1 of 3)	66
Table 6 – Minimum reporting requirement for PS ANEXT and PS AACR-F	69
Table 7 — Worst case propagation delay, delay skew, DC resistance and length measurement accuracy for level IIE, level III, level IV and level V test instruments	71
Table 8 – Worst case insertion loss, NEXT, ACR-N, ELFEXT/ACR-F and return loss measurement accuracy for Level IIE test instruments	72
Table 9 – Worst case insertion loss, NEXT, ACR-N, ELFEXT/ACR-F and return loss measurement accuracy for Level III test instruments	72
Table 10 – Worst case insertion loss, NEXT, ACR-N, ELFEXT/ACR-F and return loss measurement accuracy for level IIIE test instruments	
Table 11 – Worst case insertion loss, NEXT, ACR-N, ELFEXT/ACR-F and return loss measurement accuracy for level IV test instruments	
Table 12 – Worst case insertion loss, NEXT, ACR-N, ACR-F and return loss measurement accuracy for level V	
Table 13 – Propagation delay, delay skew, DC resistance and length accuracy performance specifications	
Table 14 – Level IIE field tester accuracy performance parameters per IEC guidelines	
Table 15 – Level III field tester accuracy performance parameters per IEC guidelines	
Table 16 – Level IIIE field tester accuracy performance parameters per IEC guidelines	
rable to – Level inc helo tester accuracy performance parameters per ico guidelines	10

Table	: 17 – Leve	el IV field	tester	accuracy	performance	parameters	per IEC	guidelines	80
Table	: 18 – Leve	l V field	tester a	accuracv	performance	parameters	per IEC	auidelines	82



### INTERNATIONAL ELECTROTECHNICAL COMMISSION

# SPECIFICATION FOR THE TESTING OF BALANCED AND COAXIAL INFORMATION TECHNOLOGY CABLING -

# Part 1: Installed balanced cabling as specified in ISO/IEC 11801 and related standards

### **FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees, any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61935-1 has been prepared by IEC technical committee 46: Cables, wires, waveguides, R.F. connectors, R.F. and microwave passive components and accessories.

This fourth edition cancels and replaces the third edition, published in 2009, and constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) the upper frequency goes up to 1 000 MHz;
- b) test methods are now included for exogenous (alien) crosstalk;
- c) a new Annex A has been added for uncertainty and variability of field test results.

The text of this standard is based on the following documents:

FDIS	Report on voting			
46/574/FDIS	46/587/RVD			

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 61935 series, published under the general title Specification for the testing of balanced and coaxial information technology cabling, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

### INTRODUCTION

Telecommunication cabling, once specified uniquely by each telecommunications application, has evolved into a generic cabling system. Telecommunications applications now use the ISO/IEC 11801 cabling standard to meet their cabling requirements. Formerly, connectivity tests and visual inspection were deemed sufficient to verify a cabling installation. Now users need more comprehensive testing in order to ensure that the link will support telecommunications applications that are designed to operate on the generic cabling system. This part of IEC 61935 addresses reference laboratory and field test methods and provides a comparison of these methods.

Transmission performance depends on cable characteristics, connecting hardware, patch cords and cross-connect cabling, the total number of connections and the care with which they are installed and maintained. This standard provides test methods for installed cabling and pre-fabricated cable assemblies. These test methods, where appropriate, are based on those used for components of the cable assembly.

This Part 1 contains the test methods required for installed cabling. Part 2 contains the test methods required for patch cords and work area cords.

iTex Syn (a cs (https://scapaxxd.iteh.ai)
Lycuxeh. Preview
https://standards.iteh.ai
Ctandards.iteh.ai

## SPECIFICATION FOR THE TESTING OF BALANCED AND COAXIAL INFORMATION TECHNOLOGY CABLING -

## Part 1: Installed balanced cabling as specified in ISO/IEC 11801 and related standards

### 1 Scope

This part of IEC 61935 specifies reference measurement procedures for cabling parameters and the requirements for field tester accuracy to measure cabling parameters identified in ISO/IEC 11801. References in this standard to ISO/IEC 11801 mean ISO/IEC 11801 or equivalent cabling standards.

This International Standard applies when the cable assembles are constructed of cables complying with the IEC 61156 family of standards, and connecting hardware as specified in the IEC 60603-7 family of standards or IEC 61076-3-104, IEC 61076-3-110, IEC 61076-2-101 and IEC 61076-2-109. Where cables and/or connectors do not comply with these standards, then additional tests may be required.

This standard is organized as follows:

- reference laboratory measurement procedures on cabling topologies are specified in Clause 4. In some cases, these procedures may be used in the field (see IEC TR 61156-1-2:2009/AMD1:2014);
- descriptions and requirements for measurements in the field are specified in Clause 5;
- performance requirements for field testers and procedures to verify performance are specified in Clause 6.

NOTE 1 This standard does not include tests that are normally performed on the cables and connectors separately. These tests are described in IEC 61156-1 and IEC 60603-7 or IEC 61076-3-104, IEC 61076-3-110, IEC 61076-2-101 and IEC 61076-2-109, respectively.

NOTE 2 Users of this standard are advised to consult with applications standards, equipment manufacturers and system integrators to determine the suitability of these requirements for specific networking applications.

It is assumed that cables and connectors used in cable assemblies, even if they are not described in IEC 61156 or IEC 60603-7, IEC 61076-3-104, IEC 61076-3-110, IEC 61076-2-101 and IEC 61076-2-109, are tested separately according to the tests given in the relevant generic specification.

This standard relates to performance with respect to 100  $\Omega$  cabling. For 120  $\Omega$  or 150  $\Omega$  cabling, the same principles apply but the measurement system should correspond to the nominal impedance level.

Field tester types include certification, qualification and verification. Certification testing is performed for the rigorous needs of commercial/industrial buildings to this standard. Qualification testing is described in IEC 61935-3. Qualification testing determines whether the cabling will support certain network technologies (e.g. 1000BASE-T, 100BASE-TX, 10G Base-T). Qualification testers do not have traceable accuracy to national standards and provide confidence that specific applications will work. Verification testers only verify connectivity.

Throughout this standard, 4-pair cabling is assumed. The test procedures described in this standard may also be used to evaluate two pair balanced cabling. However, 2-pair cabling links that share the same sheath with other links shall be tested as 4-pair cabling.