

SLOVENSKI STANDARD SIST TBR 010 E1:2004

01-oktober-2004

FUX]'g_UcdfYa U']b'g]ghYa]'fF9GL'!'8][]hUbY']nVc'\'yUbY'VfYnjfj] bY hYY_ca i b]_UVIYYfB97HL!'Gd`cýbY'nU, hYj Y'nU'df]_`1 Yj UbY'hYfa]bU'U.'Ud`]_UVIYY'j hYYZcb]1

Digital Enhanced Cordless Telecommunications (DECT); General terminal attachment requirements: Telephony applications

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST TBR 010 E1:2004

https://standards.iteh.ai/catalog/standards/sist/2774d02e-aaa4-48d8-be3f-Ta slovenski standard je istoveten z:5092/sistBR-0010 Edition 1

ICS:

33.070.30

Öðt ánæna) ^ Ánn à [|bxæn) ^ à|^: ç|çã}^Ác^|^\[{ *} ã æ& Telecommunications (DECT)

Digital Enhanced Cordless

QVÔÓQD

SIST TBR 010 E1:2004

en

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST TBR 010 E1:2004

https://standards.iteh.ai/catalog/standards/sist/2774d02e-aaa4-48d8-be3f-3ae5cd65f092/sist-tbr-010-e1-2004



TECHNICAL BASIS for REGULATION

TBR 10

December 1993

Source: ETSI TC-RES Reference: DTBR/RES-03-10

ICS: 33.060

Key words: DECT, test specification, speech

Radio Equipment and Systems (RES);
Digital European Cordless Telecommunications (DECT)

General terminal attachment requirements:
https://standards.iteh.ai/catalog/standards/sist/2774d02e-aaa4-48d8-be3fTelephony-applications

ETSI

European Telecommunications Standards Institute

ETSI Secretariat

Postal address: F-06921 Sophia Antipolis CEDEX - FRANCE

Office address: 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

X.400: c=fr, a=atlas, p=etsi, s=secretariat - Internet: secretariat@etsi.fr

Tel.: +33 92 94 42 00 - Fax: +33 93 65 47 16

Page 2 TBR 10: December 1993

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST TBR 010 E1:2004

https://standards.iteh.ai/catalog/standards/sist/2774d02e-aaa4-48d8-be3f-3ae5cd65f092/sist-tbr-010-e1-2004

Whilst every care has been taken in the preparation and publication of this document, errors in content, typographical or otherwise, may occur. If you have comments concerning its accuracy, please write to "ETSI Editing and Committee Support Dept." at the address shown on the title page.

Contents

Fore	eword			7		
1	Scope			9		
2	Norma	tive referenc	es	10		
3	Definitions and abbreviations					
	3.1	Definition	S	12		
	3.2	Abbreviat	ions	13		
4	Interpre	etation of the	e measurement results	14		
5	General test requirements					
	5.1 Test philosophy					
		5.1.1	Equipment supporting an ETSI approved profile			
		5.1.2	Equipment not supporting an ETSI approved profile			
		5.1.3	Applicant's declaration			
	5.2	Low noise	e room			
	5.3		ester (LT)			
	0.0					
		532T	Description Connections between the EUT and the LT	17		
		5.3.3	Functions and abilities	17		
		5.3.4	Functions and abilities	17		
	5.4		ster (UT)			
	0.4	5.4.1	Description of the UT Et 2004			
			The test standby mode sisv 2774d02e-aaa4-48d8-be3f-	17		
		5.4.3	ndards.iteh:al/ealalogsMandards/sisv2774d02e-aaa4-48d8-be3F Test_messages2/sist-tbr-010-e1-2004	17		
^	T					
6	6.1		wer sources and ambient temperatures			
	6.2		est conditions			
	-	6.3 Power source				
	0.3	Power so	ource	10		
7	Speech and telephony tests					
	7.1	Test conf	igurations			
		7.1.1	General			
		7.1.2	Testing a DECT system	19		
		7.1.3	Testing a separate PP or FP	19		
		7.1.4	Reference FP, ReFP, and reference PP, RePP	20		
		7.1.5	Applicability of tests	21		
	7.2	Digital sig	nal level	21		
	7.3	General conditions of test				
	7.4	Ideal cod	ec	22		
	7.5	Electro-acoustical equipment				
	· '		oding scheme	23		
		7.6.1	Requirement for speech coding algorithm			
		7.6.2	Applicant's declaration on speech coding algorithm			
		7.6.3	Requirement for the digital PCM interface in the FP			
		7.6.4	Applicant's declaration on the digital PCM interface in the FP			
	7.7		ng frequency response			
		7.7.1	Requirement			
		7.7.1	Method of measurement			
	7.8		ring frequency response			
	7.0	7.8.1	Requirement			
		1.0.1	rsequilettietti	23		

Page 4 TBR 10: December 1993

	7.8.2	Method of meas	surement		. 25		
7.9	PP loudness	rating			. 25		
	7.9.1	Requirement			. 25		
	7.9.2						
		7.9.2.1	SLRH		. 25		
		7.9.2.2					
7.10	User Contro	lled Volume cont					
	7.10.1						
	7.10.2						
		7.10.2.1					
		7.10.2.2					
7.11	PP talker sid						
	7.11.1						
	7.11.2						
7.12	Listener Side						
	7.12.1	LSTR requireme	ent		. 27		
	7.12.2	Protocol require	ement for EUTs with	n declared noise rejection capability	. 27		
	7.12.3						
	7.12.4			otocol Requirement for EUTs with			
				applying to be approved separately	. 27		
	7.12.5			ocol requirement for EUTs applying to			
					. 28		
7.13	Terminal Co		-				
	7.13.1						
	7.13.2						
	7.13.3			for a PP being approved separately			
	7.13.4	Method of meas	surement for TCLw	for a PP being approved as part of a			
					. 29		
	7.13.5	Method of meas	surement for the pro	otocol requirement for EUTs applying to			
		Method of measurement for the protocol requirement for EUTs applying to be approved separately					
	7.13.6	Applicant's decl	aration for the proto	ocol requirement for EUTs applying to			
		be approved as	a DECT system	<u>2004</u> y2774d02e-aaa4-48d8-be3f- 10-e1-2004	. 29		
7.14	FP echo cor	trol functions wi	th a 4-wire interface	t/2//4d02e-aaa4-48d8-be3t-	. 29		
	7.14.1	Static requireme	ents	10-e1-2004	. 29		
	7.14.2	Dynamic require	ements		. 29		
		7.14.2.1	Minimum TCLw		. 29		
		7.14.2.2					
	7.14.3	Artificial echo lo	oss of a FP with a 4	-wire interface	. 30		
		7.14.3.1	Requirement for a	rtificial echo loss	. 30		
		7.14.3.2	Requirement for th	e ability to disable the artificial echo			
			loss		. 30		
		7.14.3.3	Method of measure	ement of artificial echo loss	. 30		
		7.14.3.4		ement for ability to disable artificial			
			echo loss		. 30		
			7.14.3.4.1	EUTs being approved as separate			
				items	. 30		
			7.14.3.4.2	EUTs being approved as a DECT			
				system with a PP having full TCLw	. 31		
	7.14.4	Echo control device of a FP with a 4-wire interface					
		7.14.4.1	Requirement for the echo control device				
		7.14.4.2		e ability to disable the echo control			
		7.14.4.3 7.14.4.4		ement for the echo control device	. 31		
			Method of measurement for the ability to disable the echo				
					. 31		
			7.14.4.4.1	EUTs being approved as separate			
				items	. 31		
			7.14.4.4.2	EUTs being approved as a DECT	_		
	o			system with a PP having full TCLw			
7.15	Stability loss	s - fixed geometr	y		. 32		

	7.15.1	Requirement			
	7.15.2	Method of mea	surement		32
7.16	Stability los	s variable geome	etry		32
	7.16.1				
	7.16.2				
7.17	Sending dis	tortion			
	7.17.1				
	7.17.2				
7.18	Receiving d				
	7.18.1				
	7.18.2				
7.19	Side tone d				
_	7.19.1				
	7.19.2				
7.20					
	7.20.1				
	7.20.2				
7.21	-				
	7.21.1				
	7.21.2				
7.22					
1.22	7.22.1				
	7.22.2				
7.23					
7.20	7.23.1				
	7.23.2				
7.24	-				
7.27	7 24 1	Requirement	AKU TKI		35
	7.24.1	Method of mea	surement to b		35
7.25	Sampling fro	equency level (re	rr (15.11C11.21	i)	35
7.20	7 25 1	Requirement	,001vii ig)		35
	7.25.1	Method of mea	BR 010 E1:2004	aaa4-48d8-be3f-	36
7.26	Acoustic sh	ards.iteh.ai/catalog/s	standards/sist/2774d02e	e-aaa4-48d8-be3f-	36
7.27	DECT netw	ork delay cd65f09	2/sist-tbr-010-e1-2004	ļ	36
	7.27.1				
	7.27.2				
7.28					
7.20					
	7.28.2				
7.29	_				
7.20	7.29.1				
	7.29.2				
7.30	-				
7.00	7.30.1				
	7.30.2	•			
	7.00.2	7.30.2.1			
		7.30.2.2		nterface	
		7.00.2.2	7.30.2.2.1		41
			7.30.2.2.2		42
7.31	Variation of	gain with input le			
7.01	7.31.1				
	7.31.1	•			
7.32					
1.02	7.32.1				
	7.32.1				
	1.02.2	wiction of filea			······ 44
Louden	eaking and ha	ndsfree telephon	ıv		44
_5345	January and ha		.,		

8

Page 6 TBR 10: December 1993		
Annex A (informative):	Essential requirement justification	5

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST TBR 010 E1:2004

https://standards.iteh.ai/catalog/standards/sist/2774d02e-aaa4-48d8-be3f-3ae5cd65f092/sist-tbr-010-e1-2004

Page 7 TBR 10: December 1993

Foreword

This Technical Basis for Regulation (TBR) has been produced by the Radio Equipment and Systems (RES) Technical Committee of the European Telecommunications Standards Institute (ETSI) and was adopted having passed through the ETSI standards approval procedure.

This TBR covers the general attachment requirements for terminal equipment for the Digital European Cordless Telecommunications (DECT) common interface.

This TBR contains the procedures and requirements for the type examination of Digital European Cordless Telecommunications (DECT) equipment supporting a 3,1 kHz telephony teleservice.

The requirements of TBR 6 [22] apply in addition to this TBR.

This TBR is based on the DECT Common Interface ETS 300 175 [1] - [8] and [32], and I-ETS 300 176 [31].

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST TBR 010 E1:2004 https://standards.iteh.ai/catalog/standards/sist/2774d02e-aaa4-48d8-be3f-3ae5cd65f092/sist-tbr-010-e1-2004

Page 8 TBR 10: December 1993

Blank page

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST TBR 010 E1:2004

https://standards.iteh.ai/catalog/standards/sist/2774d02e-aaa4-48d8-be3f-3ae5cd65f092/sist-tbr-010-e1-2004

Page 9 TBR 10: December 1993

1 Scope

This Technical Basis for Regulation (TBR) specifies the technical characteristics particular to telephony applications provided by terminal equipment which is capable of connection to a public telecommunications network and which uses Digital European Cordless Telecommunications (DECT). The cordless transmissions for such terminal equipment operate within the frequency band 1 880 - 1 900 MHz.

The objective of this TBR is to ensure interworking of terminal equipment via the public network.

The requirements in this TBR apply in addition to the attachment requirements for the appropriate public network (see NOTE) and the TBR for DECT general attachment requirements.

NOTE:

TBR for basic ISDN, TBR for primary rate ISDN, or national regulations (implementing ETS 300 001) for Public Switched Telephone Network (PSTN). Interconnection of a DECT terminal to a GSM network is still under study; in due course, the scope statement may need amending to reflect this point.

This TBR is applicable to simple telephony terminals as well as to the telephony function of multi-function or multi-service terminals.

This TBR includes the speech quality and transmission requirements for a 3,1 kHz telephony teleservice.

For each requirement in this TBR, a test is given, including measurement methods. The terminal equipment may be stimulated to perform the tests by additional equipment if necessary.

This TBR is not applicable to terminal equipment specially designed for the disabled (e.g. with amplification of received speech as an aid for the hard-of-hearing).

DECT comprises two equipment elements, referred to as a Fixed Part (FP) and a Portable Part (PP). This TBR is structured to allow type approval of either a) the FP and PP together, or b) the FP and PP as separate items. Where the DECT FP is connected to a PSTN, and there are any national peculiarities in the requirements for voice telephony, these shall be accommodated within the FP.

3ae5cd65f092/sist-tbr-010-e1-2004

2 Normative references

This TBR incorporates by dated or undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this TBR only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies.

[1]	ETS 300 175-1 (1992): "Radio Equipment and Systems (RES); Digital European Cordless Telecommunications (DECT) Common Interface Part 1: Overview".
[2]	ETS 300 175-2 (1992): "Radio Equipment and Systems (RES); Digital European Cordless Telecommunications (DECT) Common Interface Part 2: Physical layer".
[3]	ETS 300 175-3 (1992): "Radio Equipment and Systems (RES); Digital European Cordless Telecommunications (DECT) Common Interface Part 3: Medium access control layer".
[4]	ETS 300 175-4 (1992): "Digital European Cordless Telecommunications Common Interface Part 4: Data Link Control layer".
[5]	ETS 300 175-5 (1992): "Digital European Cordless Telecommunications Common Interface Part 5: Network layer".
[6]	ETS 300 175-6 (1992): "Digital European Cordless Telecommunications Common Interface Part 6: Identities and addressing".
[7]	ETS 300 175-7 (1992): "Radio Equipment and Systems (RES); Digital European Cordless Telecommunications ((DECT)) Common Interface Part 7: Security features".
[8]	ETS 300 175-8 (1992): "Radio Equipment and Systems (RES); Digital European Cordless Telecommunications (DECT) Common Interface Part 8: Speech coding and transmission".
[9]	ETS 300 085 (1991): "Integrated Services Digital Network (ISDN); 3,1 kHz telephony teleservice. Attachment requirements for handset terminals" (Candidate NET 33). CTR 8 will replace this ETS when available.
[10]	CCITT Revised Recommendation G.726 (IUT April 1991): "40, 32, 24, 16 kbit/s Adaptive Differential Pulse Code Modulation (ADPCM)".
[11]	CCITT Recommendation G.122 (1988): "Influence of national systems on stability, talker echo, and listener echo in international connections".
[12]	CCITT Recommendation O.132 (1988): "Quantization distortion measurement equipment using a sinusoidal input signal".
[13]	CCITT Recommendation G.223 (1988): "Assumptions for the calculation of noise on hypothetical reference circuits for telephony".
[14]	CCITT Recommendation G.714 (1988): "Separate performance characteristics for the encoding and decoding sides of PCM channels applicable to 4-wire voice frequency interfaces".
[15]	CCITT Revised Recommendation P.51 (1993): "Artificial mouth".
[16]	CCITT Revised Recommendation P.64 (1993): "Determination of sensitivity/frequency characteristics of local telephone systems to permit calculation of their loudness ratings".

[17	7]	CCITT Revised Recommendation P.79 (1993): "Calculation of loudness ratings".
[18	3]	CCITT Recommendation G.711 (1988): "Pulse Code Modulation (PCM) of voice frequencies".
[19)]	CCITT Revised Recommendation P.57 (1993): "Artificial ears".
[20)]	ISO 3 (1973): "Preferred numbers - series of preferred numbers".
[21]	CCITT Revised Recommendation P.50 (1993): "Artificial Voices".
[22	2]	TBR 6: "Radio Equipment and Systems (RES); Digital European Cordless Telecommunications (DECT) General terminal attachment requirements".
[23	3]	CCITT Revised Recommendation P.80 (1993): "Methods for subjective determination of transmission quality".
[24	!]	IEC 651: "Sound level meters".
[25	5]	ETS 300 111: "ISDN telephony 3,1 kHz teleservice; service description".
[26	5]	CCITT Recommendation G.101 (1988): "The Transmission Plan".
[27	יו	CCITT Recommendation O.133 (1988): "Specification for equipment to measure the performance of PCM encoders and decoders".
[28	iT	91/263/EEC: "Council Directive of 29 April 1991 on the approximation of the laws of the Member States concerning telecommunications terminal equipment, including the mutual recognition of their conformity". (Terminal Directive)
[29		ETS 300 001(1992): "Attachments to Public Switched Telephone Network (PSTN); General technical requirements for equipment connected to an analogue subscriber interface in the PSTN (NET 4)". 4848-be31-3ae5cd65f092/sist-tbr-010-e1-2004
[30		73/23/EEC: Council Directive of 19 February 1973 on the harmonization of the laws of the Member States relating to electrical equipment designed for use within certain voltage limits. (Low Voltage Directive)
[31	1	I-ETS 300 176 (1992): "Radio Equipment and Systems (RES); Digital European Cordless Telecommunications (DECT) Approval test specification".
[32	2]	ETS 300 175-9 (1992): "Radio Equipment and Systems (RES); Digital European Cordless Telecommunications (DECT) Common Interface Part 9: Public access profile".
[33	3]	ISO DIS 9614: "Acoustic determination of sound power levels of noise sources using sound intensity. Part 1 Measurement at discrete points.

using sound intensity, Part 1 Measurement at discrete points.