



# SLOVENSKI STANDARD

## SIST EN 301 357-1 V1.3.1:2006

01-oktober-2006

9`Y\_Ifca U[ bYfbUnXfi y`j] cgh]b`nUXYj Y`j`nj Yn]`n`fUX]`g\_`ja`gdY\_Ifca`fØFAŁĚ  
6fYnj fj ] bY`Uj X]c`bUdfUj Y`nUZY\_j Yb bc`cVa c`Ÿ`cX`&`A<n`Xc`&`\$\$\$`A<n`Ě`%  
XY.`H\ b] bY`UfU`hf]gh`Y]b`dfYg\_i gbY`a YtcXY

Electromagnetic compatibility and Radio spectrum Matters (ERM); Cordless audio devices in the range 25 MHz to 2 000 MHz; Part 1: Technical characteristics and test methods

**ITeH STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST EN 301 357-1 V1.3.1:2006](https://standards.iteh.ai/catalog/standards/sist/2f9dd689-8153-4646-8745-e98751f88a14/sist-en-301-357-1-v1-3-1-2006)

<https://standards.iteh.ai/catalog/standards/sist/2f9dd689-8153-4646-8745-e98751f88a14/sist-en-301-357-1-v1-3-1-2006>

Ta slovenski standard je istoveten z: **EN 301 357-1 Version 1.3.1**

### **ICS:**

33.060.99	Druga oprema za radijske komunikacije	Other equipment for radiocommunications
33.100.01	Elektromagnetna združljivost na splošno	Electromagnetic compatibility in general

**SIST EN 301 357-1 V1.3.1:2006** en

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST EN 301 357-1 V1.3.1:2006

<https://standards.iteh.ai/catalog/standards/sist/2f9dd689-8153-4646-8745-e98751f88a14/sist-en-301-357-1-v1-3-1-2006>

# ETSI EN 301 357-1 V1.3.1 (2006-07)

---

*European Standard (Telecommunications series)*

## **Electromagnetic compatibility and Radio spectrum Matters (ERM); Cordless audio devices in the range 25 MHz to 2 000 MHz; Part 1: Technical characteristics and test methods**

---

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST EN 301 357-1 V1.3.1:2006](https://standards.iteh.ai/catalog/standards/sist/2f9dd689-8153-4646-8745-e98751f88a14/sist-en-301-357-1-v1-3-1-2006)

<https://standards.iteh.ai/catalog/standards/sist/2f9dd689-8153-4646-8745-e98751f88a14/sist-en-301-357-1-v1-3-1-2006>



## Reference

---

REN/ERM-TG17WG3-007-1

## Keywords

---

audio, radio, radio MIC, testing

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST EN 301 357-1 V1.3.1:2006

<https://standards.iteh.ai/catalog/standards/sist/2f9dd689-8153-4646-8745-e98751f88a14/sist-en-301-357-1-v1-3-1-2006>

**Important notice**

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

[http://portal.etsi.org/chaicor/ETSI\\_support.asp](http://portal.etsi.org/chaicor/ETSI_support.asp)

---

**Copyright Notification**

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2006.  
All rights reserved.

**DECT™**, **PLUGTESTS™** and **UMTS™** are Trade Marks of ETSI registered for the benefit of its Members.  
**TIPHON™** and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members.  
**3GPP™** is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

# Contents

Intellectual Property Rights .....	7
Foreword.....	7
Introduction .....	8
1 Scope .....	9
2 References .....	10
3 Definitions, symbols and abbreviations .....	11
3.1 Definitions .....	11
3.2 Symbols.....	11
3.3 Abbreviations .....	12
4 Functional characteristics .....	12
4.1 Cordless audio .....	12
4.1.1 In-vehicle cordless .....	12
4.1.2 Personal cordless .....	12
4.1.3 Broadband multi channel systems .....	12
4.1.4 Band II LPD.....	13
4.2 Consumer radio microphones.....	13
4.3 In-ear monitoring.....	13
5 General .....	13
5.1 Presentation of equipment for testing purposes .....	13
5.1.1 Choice of model for performance testing .....	14
5.1.2 Definitions of alignment and switching ranges.....	14
5.1.3 Alignment Range .....	14
5.1.4 Choice of frequencies .....	14
5.1.5 Testing of single channel equipment .....	14
5.1.6 Testing of two channel equipment .....	14
5.1.7 Testing of multi-channel equipment (more than two channels).....	14
5.1.8 Testing of equipment with an external frequency control.....	15
5.1.9 Testing of equipment with an integral antenna .....	15
5.1.9.1 Equipment with a permanent internal RF port .....	15
5.1.9.2 Equipment with a temporary RF port.....	15
5.2 Mechanical and electrical design.....	15
5.2.1 General.....	15
5.2.2 Controls .....	15
5.2.3 Integral antenna .....	15
5.2.4 Marking .....	16
5.3 Interpretation of the measurement results .....	16
6 Test conditions, power sources and ambient conditions .....	16
6.1 Normal and extreme test-conditions .....	16
6.2 Test power source.....	16
6.3 Normal test conditions.....	16
6.3.1 Normal temperature and humidity .....	17
6.3.2 Normal test power source voltage.....	17
6.3.2.1 Mains voltage .....	17
6.3.2.2 Nickel-cadmium cells.....	17
6.3.2.3 Other power sources.....	17
6.4 Extreme test conditions .....	17
6.4.1 Extreme temperatures .....	17
6.4.1.1 Procedures for tests at extreme temperatures .....	17
6.4.2 Extreme test power source voltages.....	18
6.4.2.1 Mains voltage.....	18
6.4.2.2 Re-chargeable battery power sources.....	18
6.4.2.3 Power sources using other types of batteries.....	18

6.4.2.4	Other power sources.....	18
7	General conditions.....	18
7.1	Normal test modulation.....	18
7.2	Test fixture.....	19
7.3	Test site and general arrangements for radiated measurements.....	20
7.4	Modes of operation of the transmitter.....	20
7.5	Arrangement for test signals at the input of the transmitter.....	20
8	Methods of measurement and limits for transmitter parameters.....	20
8.1	Basic requirements for Band II LPD.....	20
8.2	Methods of measurement and limits for transmitter parameters of Band II LPD.....	21
8.2.1	Effective radiated power, occupied bandwidth, channel spacing, frequency error, and transmitter timeout.....	21
8.2.1.1	Definitions.....	21
8.2.1.2	Test equipment setup.....	21
8.2.1.3	Method of measurement.....	22
8.2.1.3.1	Test site and general arrangements for radiated measurements.....	22
8.2.1.3.2	Test modulation.....	22
8.2.1.3.3	Measurement procedure.....	22
8.2.1.4	Limits.....	22
8.2.1.5	Measurement uncertainty.....	23
8.2.1.6	Radiated spurious emissions.....	23
8.2.1.6.1	Definitions.....	23
8.2.1.6.2	Measurement procedure.....	23
8.2.1.6.3	Limits for Band II LPD.....	23
8.2.1.6.4	Limits for combined equipments.....	23
8.2.1.6.5	Measurement uncertainty.....	23
8.3	Frequency error.....	24
8.3.1	Definition.....	24
8.3.2	Method of measurement.....	24
8.3.3	Limit.....	24
8.4	Carrier power.....	24
8.4.1	Definition.....	24
8.4.2	Method of measurement for equipment with integral antenna.....	24
8.4.2.1	Method of measurement under normal test conditions.....	24
8.4.2.2	Method of measurement under extreme test conditions.....	25
8.4.3	Limit.....	25
8.5	Channel bandwidth.....	26
8.5.1	Definition.....	26
8.5.2	Measurement of Necessary Bandwidth (BN).....	26
8.5.3	Limits.....	26
8.5.4	Edge of Band Limits.....	26
8.6	Spurious emissions and cabinet radiation.....	27
8.6.1	Definitions.....	28
8.6.2	Method of measuring the effective radiated power.....	28
8.6.3	Limits.....	28
8.6.4	Measuring receiver.....	28
8.7	Cordless audio transmitter shutoff.....	29
8.7.1	Definition.....	29
8.7.2	Method of measurement.....	29
8.7.3	Limits.....	29
9	Receiver.....	30
9.1	Spurious emissions and cabinet radiation.....	30
9.1.1	Definitions.....	30
9.1.2	Method of measuring the power level in a specified load.....	30
9.1.3	Method of measuring the effective radiated power of the enclosure.....	30
9.1.4	Method of measuring the effective radiated power.....	31
9.1.5	Limits.....	31
10	Measurement uncertainty.....	31

10.1	Compliance assessment when measurement uncertainty is equal to or less than maximum acceptable uncertainty .....	31
10.2	Compliance assessment when measurement uncertainty is greater than maximum acceptable uncertainty ....	32
10.3	Maximum allowable measurement uncertainties .....	32
<b>Annex A (normative): Radiated measurement.....</b>		<b>33</b>
A.1	Test sites and general arrangements for measurements involving the use of radiated fields .....	33
A.1.1	Anechoic chamber .....	33
A.1.2	Anechoic chamber with a conductive ground plane .....	34
A.1.3	Open Area Test Site (OATS) .....	35
A.1.4	Test antenna .....	36
A.1.5	Substitution antenna .....	37
A.1.6	Measuring antenna .....	37
A.1.7	Stripline arrangement .....	37
A.1.7.1	General .....	37
A.1.7.2	Description .....	37
A.1.7.3	Calibration .....	37
A.1.7.4	Mode of use .....	37
A.2	Guidance on the use of radiation test sites .....	38
A.2.1	Verification of the test site .....	38
A.2.2	Preparation of the EUT .....	38
A.2.3	Power supplies to the EUT .....	38
A.2.4	Volume control setting for analogue speech tests .....	38
A.2.5	Range length .....	39
A.2.6	Site preparation .....	39
A.3	Coupling of signals .....	40
A.3.1	General .....	40
A.3.2	Data Signals .....	40
A.3.3	Speech and analogue signals .....	40
A.3.3.1	Acoustic coupler description .....	40
A.3.3.2	Calibration .....	41
A.4	Standard test position .....	41
A.5	Test fixture .....	41
A.5.1	Description .....	41
A.5.2	Calibration .....	42
A.5.3	Mode of use .....	43
<b>Annex B (normative): Measurement of Necessary Bandwidth (BN) .....</b>		<b>44</b>
<b>Annex C (informative): Receiver parameters.....</b>		<b>45</b>
C.1	Blocking or desensitization .....	45
C.1.1	Definition .....	45
C.1.2	Method of measurement .....	45
C.1.2.1	Measurement procedure .....	45
C.1.2.2	Definitions .....	45
C.1.2.3	Limits for applications below 1 GHz .....	46
C.1.2.4	Limits for applications above 1 GHz .....	46
C.2	Frequency mask for the receiver part .....	46
C.2.1	Definition .....	46
C.2.2	Method of measurement .....	46
C.2.3	Typical values for receivers .....	47
C.2.3.1	Typical values for receivers with analogue modulation .....	47
C.2.3.2	Typical values for receivers with digital modulation .....	47
<b>Annex D (informative): Derivation of radiated spurious emissions limit for Band II LPD .....</b>		<b>48</b>
<b>Annex E (informative): Justifications for field strength measurement.....</b>		<b>49</b>

<b>Annex F (informative):</b>	<b>Bibliography.....</b>	<b>50</b>
History .....		51

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST EN 301 357-1 V1.3.1:2006

<https://standards.iteh.ai/catalog/standards/sist/2f9dd689-8153-4646-8745-e98751f88a14/sist-en-301-357-1-v1-3-1-2006>



## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

Every EN prepared by ETSI is a voluntary standard. The present document may contain text concerning conformance testing of the equipment to which it relates. This text should be considered as guidance only and does not make the present document mandatory.

Annex A provides normative specifications concerning radiated measurements.

Annex B provides a graphic representation of the equipment and frequencies for the testing of single and multi frequency equipment.

Annex C provides informative parameters on the receiver part, which are intended to give guidance to manufacturers.

Annex D provides information on the derivation of radiated emissions limits for Band II LPD.

Annex E provides a justification for field strength limits for Band II LPD.

The present document is part 1 of a multi-part deliverable covering cordless audio devices in the range 25 MHz to 2 000 MHz; as identified below:

**Part 1:** "Technical characteristics and test methods";

Part 2: "Harmonized EN covering essential requirements of article 3.2 of the R&TTE Directive".

### National transposition dates

Date of adoption of this EN:	21 July 2006
Date of latest announcement of this EN (doa):	31 October 2006
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 April 2007
Date of withdrawal of any conflicting National Standard (dow):	30 April 2007

---

## Introduction

In preparing the present document, much attention has been given to assure a low interference probability, while at the same time allowing a maximum flexibility and service to the end-user.

The harmonized standard EN 301 357-2 provides the necessary parameters for equipment to obtain common approval throughout Europe. Common technical specifications and harmonized frequency allocations are expected to reduce the present problems of interference and illegal use.

The present document is used for conformity testing based on spectrum utilization parameters and does not include performance characteristics that may be required by the user or requirements for interfacing equipment.

The present document is intended to specify the minimum performance and the methods of measurement of cordless audio equipment in the range 25 MHz to 2 000 MHz, including:

- consumer radio microphones and in ear monitoring equipment in the range 863 MHz to 865 MHz;
- Band II LPD (low power devices) in the 87,5 MHz to 108 MHz range (Broadcasting Band II);
- and other devices and frequency bands defined within REC 70-03 or National regulation.

Consumer radio microphones and in ear monitoring equipment may be tested to either EN 300 422 [4] for equipment with maximum occupied bandwidth <200 kHz or to the present document for equipment with maximum occupied bandwidth >200 kHz with due consideration of power and operating frequency.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 301 357-1 V1.3.1:2006](https://standards.iteh.ai/catalog/standards/sist/2f9dd689-8153-4646-8745-e98751f88a14/sist-en-301-357-1-v1-3-1-2006)

<https://standards.iteh.ai/catalog/standards/sist/2f9dd689-8153-4646-8745-e98751f88a14/sist-en-301-357-1-v1-3-1-2006>

---

# 1 Scope

The present document covers the minimum characteristics considered necessary in order to make the best use of the available frequencies. It does not necessarily include all the characteristics that may be required by a user, nor does it necessarily represent the optimum performance achievable.

Cordless audio devices covered within the present document are considered by definition short-range devices, the power limits for frequency bands will be found in the current version of CEPT/ERC/REC 70-03, annex 13 (or national regulations).

Stereo equipment can be designed for required channel bandwidths of 200 kHz or less, however consumer wideband (multi channel) audio equipment and stereo equipment using e.g. Zenith-GE pilot tone systems or digital modulation may need wider bandwidths as defined in the present document.

The present document applies to cordless audio consumer radio microphones, in ear monitoring equipment using either 300 kHz bandwidth analogue modulation or:

- 300 kHz, 600 kHz, 1 200 kHz digital FDMA modulation; and
- Band II LPD (low power devices) using 200 kHz bandwidth and analogue modulation.

The frequency bands for this equipment may differ from country to country as specified in their national regulations. All equipment is intended to be used with integral antennas.

Consumer audio equipment intended for audio and voice operating below 50 MHz and using narrow band modulation are considered and tested according to EN 300 220 [6].

Electromagnetic Compatibility (EMC) requirements are covered by EN 301 489-9 [3].

The types of equipment covered by the present document are as follows:

- cordless headphones; [SIST EN 301 357-1 V1.3.1:2006](https://standards.iteh.ai/catalog/standards/sist/2f9dd689-8153-4646-8745-e98751f88a14/sist-en-301-357-1-v1-3-1-2006)
- cordless loudspeakers; <https://standards.iteh.ai/catalog/standards/sist/2f9dd689-8153-4646-8745-e98751f88a14/sist-en-301-357-1-v1-3-1-2006>
- consumer radio microphones;
- in-ear monitoring;
- in-vehicle cordless;
- personal cordless;
- broadband multi channel audio systems;
- Band II LPD.

## 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication and/or edition number or version number) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

- [1] ITU-R Recommendation BS.559-2: "Objective measurement of radio-frequency protection ratios in LF, MF and HF broadcasting".
- [2] IEC 60244-13: "Methods of measurement for radio transmitters - Part 13: Performance characteristics for FM sound broadcasting".
- [3] ETSI EN 301 489-9: "Electromagnetic compatibility and Radio spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 9: Specific conditions for wireless microphones, similar Radio Frequency (RF) audio link equipment, cordless audio and in-ear monitoring devices".
- [4] ETSI EN 300 422: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Technical characteristics and test methods for wireless microphones in the 25 MHz to 3 GHz frequency range".
- [5] ETSI TR 100 027: "ElectroMagnetic Compatibility and Radio Spectrum Matters (ERM); Methods of measurement for private mobile radio equipment".
- [6] ETSI EN 300 220 (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices (SRD); Radio equipment to be used in the 25 MHz to 1 000 MHz frequency range with power levels ranging up to 500 mW".
- [7] ETSI TR 102 273 (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties".
- [8] ANSI C63.5: "American National Standard for Electromagnetic Compatibility-Radiated Emission Measurements in Electromagnetic Interference (EMI) Control-Calibration of Antennas (9 kHz to 40 GHz)".
- [9] IEC 60489-3: "Methods of measurement for radio equipment used in the mobile services. Part 3: Receivers for A3E or F3E emissions".
- [10] ETSI EN 301 489-1: "Electromagnetic compatibility and Radio spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 1: Common technical requirements".
- [11] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).

## 3 Definitions, symbols and abbreviations

### 3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

**artificial antenna:** tuned reduced-radiating dummy load equal to the nominal impedance specified by the applicant

**channel bandwidth:** frequency band of defined width including safety margin for operation on adjacent channels, located symmetrically around the carrier frequency

**integral antenna:** antenna, with or without a connector, designed as, and declared as by the manufacturer, an indispensable part of the equipment

**integral antenna for Band II LPD only:** permanent fixed antenna, which may be built-in, designed as an indispensable part of the equipment

**necessary bandwidth:** is, for a given class of emission, the width of the frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions

NOTE: However, the necessary bandwidths of most digital modulation formats are presently not referred to ITU-R Recommendations of SM series.

**occupied bandwidth:** width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage  $\beta/2$  of the total mean power of a given emission.

NOTE: Unless otherwise specified in an ITU-R Recommendation for the appropriate class of emission, the value of  $\beta/2$  should be taken as 0,5%.

**port:** any connection point on or within the Equipment Under Test (EUT) intended for the connection of cables to or from that equipment

**radiated measurements:** measurements that involve the absolute measurement of a radiated electromagnetic field

**spurious emission:** emission on a frequency or frequencies which are outside the necessary bandwidth and the level of which may be reduced without affecting the corresponding transmission of information. Spurious emissions include harmonic emissions, parasitic emissions, intermodulation products and frequency conversion products.

### 3.2 Symbols

For the purposes of the present document, the following symbols apply:

$\lambda$	wavelength in metres
$\mu\text{F}$	micro Farad
$\mu\text{W}$	micro Watt
$\Omega$	ohm
dBc	dB relative to the carrier level
E	field strength
fc	carrier frequency
fo	operating frequency
GHz	Giga Hertz
kHz	kilo Hertz
MHz	Mega Hertz
mW	milli Watt
nW	nano Watt

### 3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ac	alternating current
B	channel Bandwidth
BN	Necessary Bandwidth
CW	Continuous Wave
dc	direct current
erp	effective radiated power
EUT	Equipment Under Test
FDMA	Frequency Division Multiple Access
FM	Frequency Modulation
HF	High Frequency
LF	Low Frequency
LPD	Low Power Device
MF	Medium Frequency
OATS	Open Area Test Site
RBW	Resolution BandWidth
RF	Radio Frequency
SINAD	(Signal + Noise + Distortion) to (Noise + Distortion)
SRD	Short Range Devices
Tx	Transmitter
VBW	Video BandWidth
VSWR	Voltage Standing Wave Ratio

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)

## 4 Functional characteristics

### 4.1 Cordless audio SIST EN 301 357-1 V1.3.1:2006

<https://standards.iteh.ai/catalog/standards/sist/2f9dd689-8153-4646-8745-987518a1f61e/sist-en-301-357-1-v1-3-1-2006>

Cordless audio equipment encompasses e.g. radio linked headphones and loudspeakers. The transmitters may be installed in a building, fitted in a vehicle or body worn. The term cordless is also used to describe infra red and other non-RF "wireless" links, but in the context of the present document it is restricted to RF operating systems only. Stereo equipment can be designed for required channel bandwidths of 200 kHz or less, however consumer wideband (multi channel) audio equipment and stereo equipment using e.g. Zenith-GE pilot tone systems or digital modulation may need wider bandwidths as defined in the present document.

Other equipment that may be connected to cordless audio equipment shall fulfil the standards applicable to that equipment (if any).

#### 4.1.1 In-vehicle cordless

In-vehicle systems are used for private listening in automobiles and other methods of transport (where permitted).

#### 4.1.2 Personal cordless

Personal cordless transmitters are to enable the body worn personal stereo equipment to be wire free.

#### 4.1.3 Broadband multi channel systems

Broadband multi channel systems are used for the transmission of high quality digital audio. These can be e.g. surround sound systems or uncompressed audio. They are intended to be used in spectrum above 1 GHz.

#### 4.1.4 Band II LPD

Short range low power FM transmitters operating in the FM Broadcast band 88 MHz to 108 MHz are used for the provision of an rf link between a personal audio device, including mobile phone, and the in-car or home entertainment system.

### 4.2 Consumer radio microphones

Consumer radio microphones are intended for non-professional applications.

### 4.3 In-ear monitoring

In-ear monitoring equipment is used by stage and studio performers to receive personal fold back (monitoring) of the performance. This can be just their own voice or a complex mix of sources. This equipment is usually stereo or 2 channel audio.

Other equipment that may be connected to in-ear monitoring equipment shall fulfil the standards applicable to that equipment (if any).

---

## 5 General

### 5.1 Presentation of equipment for testing purposes

Each equipment submitted for performance testing shall fulfil the requirements of the present document on all channels over which it is intended to operate.

The applicant shall complete the appropriate application form or test plan when submitting equipment for testing.

The applicant shall state the channel bandwidth(s) within which the equipment is designed to operate.

The applicant shall also supply all relevant interface information and any tools and test fixtures to allow:

- direct current (dc) power connection;
- analogue audio connection;
- the deviation limiting of the transmitter; and
- the setting of any input audio level controls and input signal level for normal operation, for a sinusoidal input signal of 500 Hz (or 1kHz in the case of Band II LPD). The manufacturer shall specify the settings of any other controls necessary to avoid invalidating the test measurements.

In the case of Band II LPD it may be necessary for integrated equipment to create a stored data file of 1 kHz stereo sinusoidal tones to stimulate the input to the transmitter. The amplitude of such tones should be variable (but the same amplitude for each tone) to enable the correct adjustment of  $\pm 75$  kHz FM deviation of the transmitter output.

Besides the technical documentation, the applicant should also supply an operating manual, identical in content to that supplied with the production model(s) available to the public, for the device(s).

To simplify and harmonize the testing procedures between manufacturers and test laboratories, measurements shall be performed, according to the present document, on samples of equipment defined in clauses 5.1.1 to 5.1.9.2.

These clauses are intended to give confidence that the requirements set out in the present document have been met without the necessity of performing measurements on all channels.