
**Photography — Electronic still-picture
cameras — Determination of ISO speed**

*Photographie — Appareils de prises de vue électroniques — Détermination
de la sensibilité ISO*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 12232:1998

<https://standards.iteh.ai/catalog/standards/sist/7e29c0d9-dd5a-4b08-b396-9c6389decd9e/iso-12232-1998>



Contents

Page

1	Scope.....	1
2	Normative references	1
3	Definitions	1
4	Exposure index values.....	2
5	Test conditions.....	3
6	Determination of ISO speed	4

Annexes

A	Recommended procedure for determining the noise-based ISO speed.....	10
B	Scene luminance and focal plane exposure	12
C	Calculation of noise-based minimum illumination level.....	13
D	Bibliography	14

ITeH STANDARD PREVIEW
(standards.iteh.ai)
ISO 12232:1998
<https://standards.iteh.ai/catalog/standards/sist/7e29c0d9-dd5a-4b08-b396-9c6389decd9e/iso-12232-1998>

© ISO 1998

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case postale 56 • CH-1211 Genève 20 • Switzerland
Internet iso@iso.ch

Printed in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

iTeh STANDARD PREVIEW

International Standard ISO 12232 was prepared by Technical Committee ISO/TC 42, *Photography*.

Annexes A, B, C and D of this International Standard are for information only.
<https://standards.iteh.ai/catalog/standards/sist/7e29c0d9-dd5a-4b08-b396-9c6389decd9e/iso-12232-1998>

Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patents.

Introduction

The ISO speed rating is an important attribute of photographic systems. Standardization assists users and manufacturers in obtaining proper exposures and in determining the low light capability of electronic still cameras. The camera exposure is determined by the exposure time, the lens aperture, the lens transmittance, the level and colour temperature of the scene illumination, and the scene reflectance. When an image from an electronic still-picture camera is obtained using an insufficient exposure, proper tone reproduction can generally be maintained by increasing the electronic gain, but the image will contain an unacceptable amount of noise. As the exposure is increased, the gain can be decreased, and therefore the image noise can normally be reduced to an acceptable level. If the exposure is increased excessively, the resulting signal in bright areas of the image may exceed the maximum signal level capacity of the image sensor or camera signal processing. This can cause the image highlights to be clipped to form a uniformly bright area, or to bloom into surrounding areas of the image. Therefore, it is important to guide the user in setting exposures properly. An ISO speed rating is intended to serve as such a guide. The methods for assigning an ISO speed rating to electronic cameras should harmonize with current photographic standards and practice. In order to be easily understood by photographers, the ISO speed rating for an electronic camera should directly relate to the ISO speed rating for photographic film cameras. For example, if an electronic camera has an ISO speed rating of ISO 100, then the same exposure time and aperture should be appropriate for an ISO 100 rated film/process system.

The ISO speed ratings for electronic cameras described in this International Standard are intended to harmonize with ISO speed ratings for films. However, there are differences between electronic and film imaging systems that preclude exact equivalency in use. Cameras with variable gain, and digital processing after the data has been captured, allow desired tone reproduction to be achieved over a range of camera exposures. It is therefore possible for electronic cameras to have a range of speed ratings.¹⁾ This range is defined as the ISO speed latitude. To prevent confusion, a single value is designated as the ISO speed, with the upper and lower limits of the ISO speed latitude indicating the speed range.

1) While it is also possible to use many films at a variety of camera exposures, the behaviour of film is fundamentally different from that of electronic sensors. For example, significant underexposure typically results in uncorrectable tone reproduction errors in film-based photographic systems.

The camera measurements described in this International Standard are performed in the digital domain, using digital analysis techniques. For electronic cameras that include only analog outputs, the analog signal should be digitized, so that the digital measurement can be performed. The digitizing equipment should be characterized, so that the effects of the digitization can be removed from the measurement results. When this is not possible, the type of digitizing equipment used should be reported along with the measurement results.

Since the noise performance of an image sensor may vary significantly with exposure time and operating temperature, these operating conditions are specified. The visibility of noise to human observers depends on the magnitude of the noise, the apparent tone of the area containing the noise, and the spatial frequency of the noise. The magnitude of the noise present in an output representation depends on the noise present in the stored image data and the contrast amplification or gain applied to the data in producing the output. The noise visibility is different for the luminance (or monochrome) channel and the colour (or colour difference) channels. Therefore, this International Standard accounts for these factors in measuring the noise-based speed and speed latitude values.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO 12232:1998](https://standards.iteh.ai/catalog/standards/sist/7e29c0d9-dd5a-4b08-b396-9c6389decd9e/iso-12232-1998)

<https://standards.iteh.ai/catalog/standards/sist/7e29c0d9-dd5a-4b08-b396-9c6389decd9e/iso-12232-1998>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 12232:1998

<https://standards.iteh.ai/catalog/standards/sist/7e29c0d9-dd5a-4b08-b396-9c6389decd9e/iso-12232-1998>

Photography — Electronic still-picture cameras — Determination of ISO speed

1 Scope

This International Standard specifies a method for assigning exposure index values, ISO speed ratings, and ISO speed latitude ratings to electronic still-picture cameras. The standard applies to both monochrome and colour electronic still-picture cameras.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 554:1976, *Standard atmospheres for conditioning and/or testing — Specifications*.

<https://standards.iteh.ai/catalog/standards/sist/7e29c0d9-dd5a-4b08-b396-9c6389dca9e8/iso-12232-1998>

ISO 2721:1982, *Photography — Cameras — Automatic controls of exposure*.

ISO 7589:1984, *Photography — Illuminants for sensitometry — Specifications for daylight and incandescent tungsten*.

ISO 14524:—²⁾, *Photography — Electronic still-picture cameras — Methods for measuring opto-electronic conversion functions (OECFs)*.

ITU-R BT.709:1993, *Basic parameter values for the HDTV standard for the studio and for international programme exchange*.

3 Definitions

For the purposes of this International Standard, the following definitions apply.

3.1 electronic still-picture camera: Camera incorporating an image sensor that outputs an analog or digital signal representing a still picture, and/or records an analog or digital signal representing a still picture on a removable media, such as a memory card or magnetic disk.

3.2 exposure index: Numerical value that is inversely proportional to the exposure provided to an image sensor to obtain an image. Images obtained from a camera using a range of exposure index values will normally provide a range of image quality levels.

²⁾ To be published.

3.3 exposure series: Series of images of the same subject taken using different exposure index values.

3.4 image sensor: Electronic device that converts incident electromagnetic radiation into an electronic signal; for example, a charge-coupled device (CCD) array.

3.5 ISO speed: Numerical value calculated from the exposure provided at the focal plane of an electronic camera to produce specified camera output signal characteristics using the methods described in this International Standard. The ISO speed should correlate with the highest exposure index value that provides peak image quality for normal scenes.

3.6 ISO speed latitude: Set of two numerical values calculated from the exposure provided at the focal plane of an electronic camera to produce specified camera output signal characteristics using the methods described in this International Standard. The ISO speed latitude should correlate with the range of exposure index values that provide acceptable image quality for normal scenes.

3.7 photosite integration time: Total time period during which the photosites of an image sensor are able to integrate the light from the scene to form an image.

3.8 signal processing: Operations performed by electronic circuits or algorithms that convert or modify the output of an image sensor.

4 Exposure index values

An exposure index (EI) is a numerical value that is inversely proportional to the exposure provided to an image sensor to obtain an image. Images obtained from a camera, using a range of EI values, will normally provide a range of image quality levels. The ISO speed of an electronic still-picture camera is equal to a particular exposure index value calculated from the exposure provided at the focal plane of an electronic camera to produce specified camera output signal characteristics using the methods described in this International Standard. The equations used in this International Standard have been chosen to create a link between electronic and conventional silver halide based photographic systems. Using a particular ISO speed value as the exposure index on an electronic still camera should result in the same camera exposure settings, and resulting focal plane exposures, as would be obtained using the same exposure index on a film camera or other photographic exposure meter.

4.1 Focal plane measurement

For electronic still (or other) camera exposure meters, where the arithmetic mean focal plane exposure is measured within a circle lying in the centre of the image with a diameter of 75/100 times the shorter dimension of the image field, the exposure index values should be computed using equation (1), as described in ISO 2721.

$$EI = \frac{10}{H_a} \quad \dots (1)$$

where H_a is the arithmetic mean focal plane exposure, in lux seconds ³⁾⁴⁾.

3) Note that the value of 10 as the constant in equation (1) is consistent with ISO 2721 and ISO 5763. These International Standards assume that the exposure is an arithmetic mean value, as is normally provided by a camera light meter. If the geometric mean exposure was used in place of the arithmetic mean exposure, a lower value for this constant would be appropriate. Note that the arithmetic mean exposure is obtained when the linear exposure values are averaged, while a geometric mean exposure is obtained by taking the antilog of the average of the logarithmic exposure values. An approximation to the geometric mean is also obtained by taking the antilog of the average measured film densities in conventional photographic systems, provided that the film Hurter and Driffield (H and D) curve has a straight line characteristic over the film exposure range. Note also that the brightness response of the human visual system to the luminances of objects in a scene is approximately logarithmic.

4) Note that the arithmetic mean focal plane exposure for statistically average scenes is equal to approximately 18 % of the focal plane exposure which would be obtained from a perfectly diffuse 100 % reflectance object in a statistically average scene. Therefore, the arithmetic mean focal plane exposure equals 2/10 times the focal plane exposure which would be obtained from a 90 % reflectance test card in a statistically average scene.

4.2 Scene luminance measurement

For electronic still (or other) camera exposure meters where the arithmetic mean scene luminance is measured, the expected value of the arithmetic mean focal plane exposure required in equation (1) can be computed using equation (2). The derivation of equation (2) is given in annex B.

$$H_a = \frac{65L_a t}{100A^2} \quad \dots (2)$$

where

A is the effective f -number of the lens;

L_a is the arithmetic mean luminance, in candelas per square metre;

t is the photosite integration time, in seconds.

NOTE — Note that the laboratory measurement of L_a can be simplified by using a full-frame uniformly illuminated diffuse-reflecting test card, so that the arithmetic mean luminance can be measured by simply measuring the luminance at the centre of the image.

The effective f -number of the lens for the focused image shall be calculated using the equation:

$$\text{Effective } f\text{-number} = (1 + 1/R) f\text{-number} \quad \dots (3)$$

where R is the ratio of the height of the camera field of view at the focal distance to the height of the image at the focal plane. If the camera is focused at infinity, the effective f -number is equal to the f -number of the lens.

Therefore, for electronic still (or other) camera exposure meters where the arithmetic mean scene luminance is measured, exposure index values should be computed using equation (4), derived by substituting equation (2) into equation (1).

$$EI = \frac{154A^2}{10L_a t} \quad \dots (4)$$

ISO 12232:1998
<https://standards.iteh.ai/catalog/standards/sist/7e29c0d9-dd5a-4b08-b396-9c6389decd9e/iso-12232-1998>

5 Test conditions

The following measurement conditions should be used as nominal conditions when determining the ISO speed rating of an electronic still-picture camera. If it is not possible or appropriate to achieve these nominal operating conditions, the actual operating conditions shall be listed along with the ISO speed-rating value.

5.1 Illumination

The ISO speed rating shall indicate whether the daylight or tungsten illuminant was used. ISO 7589 describes the procedures for determining if the illumination used in a specific speed-rating determination test is an acceptable match to the daylight and tungsten sensitometric illuminants.

5.1.1 Daylight illumination

For daylight ISO speed measurements without the camera lens, the ISO sensitometric daylight illuminant given in table 1 of ISO 7589:1984 shall be used. This illuminant is defined as the product of the spectral power distribution of CIE standard colorimetric illuminant D_{55} and the spectral transmittance of the International Standard camera lens. For measurements with the camera lens in place, the spectral radiance characteristics of the light used for the measurement should be equivalent to the daylight ISO standard source provided in the second column of table 1 of ISO 7589:1984. In order to apply the ISO/SDI (Spectral Distribution Index) criterion, the spectral radiance of the light shall be measured and then multiplied by the relative spectral transmittance of the ISO standard lens, which is also described in ISO 7589, prior to multiplying by the weighted spectral sensitivities.

5.1.2 Tungsten illumination

For tungsten ISO speed measurements without the camera lens, the ISO sensitometric tungsten illuminant given in table 2 of ISO 7589:1984 shall be used. This illuminant is defined as the product of the average spectral power distribution of experimentally measured sources having a colour temperature of approximately 3050 K and the spectral transmittance of the International Standard camera lens. For measurements with the camera lens in place, the spectral radiance characteristics of the light used for the measurement should be equivalent to the tungsten ISO standard source provided in the second column of table 2 of ISO 7589:1984. In order to apply the ISO/SDI (Spectral Distribution Index) criterion, the spectral radiance of the light shall be measured and then multiplied by the relative spectral transmittance of the ISO standard lens, which is also described in ISO 7589, prior to multiplying by the weighted spectral sensitivities.

5.2 Temperature and relative humidity

The ambient temperature during the acquisition of the test data shall be $23\text{ °C} \pm 2\text{ °C}$, as specified in ISO 554, and the relative humidity should be $50\% \pm 20\%$.

5.3 White balance

For a colour camera, the camera white balance should be adjusted, if possible, to provide proper white balance (equal RGB signal levels) for the illumination light source, as specified in ISO 14524.

5.4 Infrared (IR) blocking filter

If required, an infrared (IR) blocking filter shall be used, as specified in ISO 14524.

5.5 Photosite integration time

The photosite integration time should not be longer than 1/30 s.

ISO 12232:1998
<https://standards.iteh.ai/catalog/standards/sist/7e29c0d9-dd5a-4b08-b396-9c0389decd9e/iso-12232-1998>

6 Determination of ISO speed

With appropriate electrical gain, an electronic camera can provide an appropriate output signal level for a range of sensor exposure levels. The maximum exposure level is the exposure level where typical picture highlights will be clipped as a result of saturating the image sensor signal capacity or reaching the maximum signal level for camera signal processing. The minimum exposure level depends on the amount of noise that can be tolerated in the image. These situations lead to two different types of speed values, saturation-signal-based values, and noise-based values. The ISO speed is preferably determined using a noise-based method. The saturation-based value is preferably used to indicate the camera's overexposure speed latitude. A second noise-based value is preferably used to indicate the camera's underexposure speed latitude. For some types of electronic still-picture cameras, such as those employing lossy compression methods that cannot be bypassed or those with excessively high noise levels, it is not possible to correctly determine the noise-based ISO speed. In such cases, the ISO speed of the camera is determined using the saturation-based measurement, and the ISO speed latitude values are not reported.

6.1 Saturation-based speed

In photographic applications where the scene illumination level can be controlled, for example in studio photography, the photographer normally prefers to use a camera exposure index which provides the best possible image quality. In this situation, a saturation-signal-based rating is appropriate. This rating allows the user to set the camera exposure so that image highlights are just below the maximum possible (saturation) camera signal value.

6.1.1 Focal plane measurement

The saturation-based speed, S_{sat} , of an electronic still-picture camera is defined as⁵⁾:

$$S_{\text{sat}} = \frac{78}{H_{\text{sat}}} \quad \dots (5)$$

where H_{sat} is the minimum focal plane exposure, in lux seconds, that produces the maximum valid (not clipped or bloomed) camera output signal.

6.1.2 Scene luminance measurement

If the focal-plane exposure cannot be measured, S_{sat} shall be computed using equation (6).

$$S_{\text{sat}} = \frac{120A^2}{L_{\text{sat}}t} \quad \dots (6)$$

where

A is the effective f -number of the lens;

L_{sat} is the minimum luminance, in candelas per square metre, of a uniform diffuse reflecting medium;

t is the exposure time, in seconds.

6.2 Noise-based speed

STANDARD PREVIEW
(standards.iteh.ai)

In many photographic applications, it is desirable to use the highest exposure index (lowest exposure) possible, in order to maximize the depth of field, minimize the exposure time, and offer the maximum acceptable speed latitude for exposure of image highlights. An exposure index that provides an appropriately low noise image for typical electronic camera applications is called a "noise-based speed". The value is based on an objective correlation to subjective judgements of the acceptability of various noise levels in exposure series images. Two different noise-based speeds are determined, one that provides the "first excellent" image and a second that provides the "first acceptable" image. The recommended procedure for determining these noise-based speeds is given in annex A.

6.2.1 Focal plane method

The two noise-based speeds of an electronic still-picture camera, $S_{\text{noise}10}$ and $S_{\text{noise}40}$, shall be determined from the focal plane exposure required to produce specific image incremental signal-to-noise ratio values using the following equation⁶⁾:

$$S_{\text{noisex}} = \frac{10}{H_{S/Nx}} \quad \dots (7)$$

where $H_{S/Nx}$ is the exposure which provides a camera signal-to-noise ratio satisfying the following criterion:

5) Note that equation (5) provides 1/2 "stop" of headroom (41 % additional headroom) for specular highlights above the signal level that would be obtained from a theoretical 100 % reflectance object in a statistically average scene, so that a theoretical 141 % reflectance object in a statistically average scene would produce a focal plane exposure of H_{sat} . Therefore, an 18 % reflectance test card in a statistically average scene would produce a focal plane exposure of $128/1\,000 H_{\text{sat}}$. Thus, the multiplicative constant 78 in equation (5) is equal to 10 times $1\,000/128$, where the value 10 is the constant from equation (1).

6) The constants used in the numerator place the specified signal-to-noise ratio at a middle gray image tone, or approximately an 18 % reflectance value for a standard 160:1 contrast ratio scene.