

SLOVENSKI STANDARD
SIST-TS ETSI/TS 101 671 V2.10.1:2005
01-maj-2005

NU_cb]hc`dfYgkfYnUb^Yf@kE=nfc]b]ja Ygb]_nUnU_cb]hc`dfYgkfYnUb^Y
h^Y_ca i b]_UW^g_Y[Udfca YHJ

Lawful Interception (LI); Handover interface for the lawful interception of telecommunications traffic

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: SIST-TS ETSI/TS 101 671 V2.10.1:2005
<https://standards.iteh.ai/catalog/standards/sist/4b82199e-99da-4b21-867a-29a505ee860c/sist-ts-etsi-ts-101-671-v2-10-1-2005>

ICS:

33.020 Telekomunikacije na splošno Telecommunications in general

SIST-TS ETSI/TS 101 671 V2.10.1:2005 en

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST-TS ETSI/TS 101 671 V2.10.1:2005](#)

<https://standards.iteh.ai/catalog/standards/sist/4b82199e-99da-4b21-867a-29a505ee860c/sist-ts-etsi-ts-101-671-v2-10-1-2005>

ETSI TS 101 671 V2.10.1 (2004-09)

Technical Specification

Lawful Interception (LI); Handover interface for the lawful interception of telecommunications traffic

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

[SIST-TS ETSI/TS 101 671 V2.10.1:2005](#)

<https://standards.iteh.ai/catalog/standards/sist/4b82199e-99da-4b21-867a-29a505ee860c/sist-ts-etsi-ts-101-671-v2-10-1-2005>



Reference

RTS/LI-00016

Keywordsdata, handover, interface, security, speech,
Lawful Interception***ETSI***

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse N° 7303/88**iTeh STANDARD PREVIEW**
(standards.iteh.ai)[SIST-TS ETSI/TS 101 671 V2.10.1:2005](#)<https://standards.iteh.ai/catalog/standards/sist/4b82199e-99da-4b21-867a-29a505ee860c>
Important noticeIndividual copies of the present document can be downloaded from:
<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaircor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2004.
All rights reserved.

DECT™, PLUGTESTS™ and UMTS™ are Trade Marks of ETSI registered for the benefit of its Members.
TIPHON™ and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members.
3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Contents

Intellectual Property Rights	8
Foreword.....	8
1 Scope	9
2 References	9
3 Definitions and abbreviations.....	13
3.1 Definitions	13
3.2 Abbreviations	15
4 General requirements	17
4.1 Basic principles for the Handover Interface	17
4.2 Legal requirements	18
4.3 Functional requirements	18
5 Overview of Handover Interface	18
5.1 Handover Interface port 1 (HI1).....	19
5.1.1 Manual interface	20
5.1.2 Electronic interface	20
5.2 Handover Interface port 2 (HI2).....	20
5.3 Handover Interface port 3 (HI3).....	20
6 Specific identifiers for LI.....	20
6.1 Lawful Interception IDentifier (LID).....	21
6.2 Communication IDentifier (CID).....	21
6.2.1 Network IDentifier (NID)	21
6.2.2 Communication Identity Number (CIN) - optional	22
7 HI1: Interface port for administrative information.....	22
7.1 Information for the activation of lawful interception.....	22
7.2 LI notifications towards the LEMF	23
8 HI2: Interface port for Intercept Related Information.....	23
8.1 Data transmission protocols	23
8.1.1 Application for IRI (HI2 information)	24
8.2 Types of IRI records.....	24
9 HI3: Interface port for Content of Communication.....	24
10 Performance and quality.....	25
10.1 Timing	25
10.2 Quality	25
11 Security aspects	25
11.1 Security properties.....	25
11.2 Security mechanisms	26
12 Quantitative aspects.....	26
Annex A (normative): Circuit switched network handover	27
A.1 Specific identifiers for LI	27
A.1.1 CC Link IDentifier (CCLID).....	27
A.1.2 Circuit switched LI correlation between CC and IRI	27
A.1.3 Usage of Identifiers	28
A.2 HI1: interface port for administrative state	28
A.3 HI2: interface port for IRI	28
A.3.1 Definition of Intercept Related Information.....	28
A.3.2 Structure of IRI records.....	29

A.3.2.1	Control information for HI2.....	29
A.3.2.2	Basic call information.....	30
A.3.2.3	Information on Supplementary Services, related to a call in progress.....	30
A.3.2.4	Information on non-call related Supplementary Services	31
A.3.3	Selection of parameters for IRI records.....	31
A.3.4	Coding of parameters in IRI records	33
A.3.5	Information content of the IRI record types	33
A.4	HI3: interface port for Content of Communication.....	34
A.4.1	Delivery of Content of Communication	34
A.4.2	Delivery of packetized Content of Communication (general).....	35
A.4.3	Control information for circuit switched Content of Communication.....	35
A.4.4	Exception handling.....	37
A.4.4.1	Failure of CC links.....	37
A.4.4.2	Fault reporting	37
A.4.5	Security requirements at the interface port HI3.....	37
A.4.5.1	LI access verification.....	37
A.4.5.2	Access protection.....	38
A.4.5.3	Authentication.....	38
A.5	LI procedures for circuit switched supplementary services	38
A.5.1	General	38
A.5.2	CC link Impact	41
A.5.3	IRI impact, general principle for sending IRI records.....	41
A.5.4	Multi party calls - general principles, options A, B.....	41
A.5.4.1	CC links for active and non-active calls (option A).....	42
A.5.4.2	Reuse of CC links for active calls (option B)	42
A.5.5	Subscriber Controlled Input (SCI). Activation/Deactivation/Interrogation of services	43
A.6	Detailed procedures for circuit switched supplementary services.....	43
A.6.1	Advice of Charge services (AOC).....	43
A.6.2	Call Waiting (CW)	43
A.6.2.1	Call Waiting at target: CC Links.ETSI/TS.101.671.V2.10.1:2005	43
A.6.2.2	Call Waiting@ IRI/records.etsi.ai/catalog/standards/ist/4b82199c-99da-4b21-867a-0ea505ee860c/sist-ts-etsi-ts-101-671-v2-10-1-2005	43
A.6.2.2.1	Target is served user 0ea505ee860c/sist-ts-etsi-ts-101-671-v2-10-1-2005	43
A.6.2.2.2	Other party is served user.....	43
A.6.3	Call Hold/Retrieve.....	44
A.6.3.1	CC links for active and non-active calls (option A).....	44
A.6.3.2	Reuse of CC links for active calls (option B)	44
A.6.3.3	IRI records	44
A.6.3.3.1	Invocation of Call Hold or Retrieve by target	44
A.6.3.3.2	Invocation of Hold or Retrieve by other parties	44
A.6.4	Explicit Call Transfer (ECT)	44
A.6.4.1	Explicit Call Transfer, CC link	44
A.6.4.2	Explicit Call Transfer, IRI records.....	44
A.6.5	Calling Line Identification Presentation (CLIP) (IRI Records).....	45
A.6.5.1	Call originated by target (other party is served user)	45
A.6.5.2	Call terminated at target (target is served user)	45
A.6.6	Calling Line Identification Restriction (CLIR)	45
A.6.7	Connected Line identification Presentation (COLP)	45
A.6.7.1	Call terminated at target (other party is served user)	45
A.6.7.2	Call originated by target (target is served user)	45
A.6.8	Connected Line identification Restriction (COLR)	45
A.6.9	Closed User Group (CUG)	45
A.6.10	Completion of Call to Busy Subscriber (CCBS)	45
A.6.11	CONFerence call, add-on (CONF)	46
A.6.11.1	CONFerence calls, add on: CC links	46
A.6.11.2	Conference calls: IRI records.....	46
A.6.12	Three Party Service (Conference)	46
A.6.12.1	CC links	46
A.6.12.2	Three Party Service, IRI Records	46
A.6.13	Meet-Me Conference (MMC)	46
A.6.14	Direct Dialling In (DDI)	46

A.6.15	Multiple Subscriber Number (MSN)	46
A.6.16	DIVersion services (DIV)	47
A.6.16.1	Call Diversion by target	47
A.6.16.1.1	Call Diversion by target, CC links	47
A.6.16.1.2	Call Diversion by target, IRI records	47
A.6.16.2	Forwarded call terminated at target	47
A.6.16.3	Call from target forwarded	47
A.6.17	Variants of call diversion services	48
A.6.18	Void	48
A.6.19	Malicious Call IDentification (MCID)	48
A.6.20	SUBaddressing (SUB)	48
A.6.21	Terminal Portability (TP)	48
A.6.21.1	CC links	48
A.6.21.2	IRI records	48
A.6.21.2.1	Invocation of Terminal Portability by target	48
A.6.21.2.2	Invocation of Terminal Portability by other parties	48
A.6.22	User-to-User Signalling (UUS)	48
A.6.23	Abbreviated Address (AA)	48
A.6.24	Fixed Destination Call (FDC)	48
A.6.25	Alarm Call (AC)/Wake-Up Service (WUS)	49
A.6.26	Incoming Call Barring (ICB)	49
A.6.27	Outgoing Call Barring (OCB)	49
A.6.28	Completion of Calls on No Reply (CCNR)	49
A.6.29	Reverse charging	49
A.6.30	Line hunting	49
A.6.31	Message Wait Indication (MWI)	49
A.6.32	Name display	49
A.6.33	Tones, announcements	49
A.7	Fixed network technologies annex	50
A.8	GSM circuit switched technology annex	50
A.8.1	Functional architecture	50
A.8.2	Correlation of CC and IRI (see clause 6)	50
A.8.3	HI3 (delivery of CC)	51
A.8.4	HI2 (delivery of IRI)	51
A.9	TETRA technology annex	52
Annex B (normative):	Packet switched network handover	53
B.1	Specific identifiers for LI	53
B.2	HI1: interface port for administrative state	53
B.3	HI2: interface port for IRI	53
B.3.1	Definition of Interception Related Information for packet switched	53
B.3.2	Exception handling	53
B.3.3	Security aspects	53
B.4	HI3: interface port for Content of Communication	54
B.5	GPRS technology annex	54
B.5.1	Functional architecture	54
B.5.2	Correlation	55
B.5.2.1	Correlation of the present document ID's to GSM ID's	55
B.5.2.2	GPRS LI correlation between CC and IRI	55
B.5.3	HI2 (delivery of IRI)	55
B.5.4	HI3 (Delivery of CC)	56
Annex C (normative):	HI2 Delivery mechanisms and procedures	57
C.1	ROSE	57
C.1.1	Architecture	57
C.1.2	ASE_HI procedures	57

C.1.2.1	Sending part	57
C.1.2.2	Receiving part	59
C.1.2.3	Data link management	59
C.1.2.3.1	Data link establishment	59
C.1.2.3.2	Data link release	60
C.1.2.4	Handling of unrecognized fields and parameters	60
C.1.3	Profiles	60
C.2	FTP	61
C.2.1	Introduction	61
C.2.2	Usage of the FTP	61
C.2.3	Profiles	62
C.2.4	File content	64
C.2.5	Exceptional procedures	64
C.2.6	Other considerations	64

Annex D (normative): Structure of data at the Handover Interface.....66

D.1	Syntax definitions	66
D.2	Object tree	67
D.3	HI management operation	68
D.4	LI management notification	69
D.5	Intercept related information (HI2 PS and CS)	71
D.6	User data packet transfer (HI3 CS)	84
D.7	TETRA data transfer (HI3 interface)	85
D.8	Definition of the UUS1 content associated to the CC link	85
D.9	Content of Communication (HI3 GPRS)	86

[SIST-TS ETSI/TS 101 671 V2.10.1:2005](https://standards.citch.ai/standard/SIST-TS%20101-671%20V2.10.1:2005)

Annex E (informative):[Use of sub-address and calling party number to carry correlation information.....87](https://standards.citch.ai/standard/SIST-TS%20101-671%20V2.10.1:2005)

E.1	Introduction	87
E.2	Subaddress options	87
E.3	Subaddress coding	87
E.3.1	BCD values	87
E.3.2	Field order and layout	88
E.4	Field coding	94
E.4.1	Direction	94
E.4.2	Coding of the Calling Party Number	94
E.5	Length of fields	95

Annex F (informative): GPRS HI3 Interface.....96

F.1	Functional architecture	96
F.2	Correlation	96
F.3	HI3 Delivery Content of Communication (CC)	97
F.3.1	GPRS LI correlation header	97
F.3.1.1	Introduction	97
F.3.1.2	Definition of GLIC header	97
F.3.1.3	Exceptional procedure	98
F.3.1.4	Other considerations	99
F.3.2	FTP	99
F.3.2.1	Introduction	99
F.3.2.2	Usage of the FTP	99
F.3.2.3	Exceptional procedures	101

F.3.2.4	CC contents for FTP	101
F.3.2.4.1	Fields.....	101
F.3.2.4.2	Information Element syntax	103
F.3.2.5	Other considerations	105
Annex G (informative):	LEMF requirements - handling of unrecognized fields and parameters.....	106
Annex H (informative):	Bibliography	107
Annex I (informative):	Change Request History.....	109
History		112

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST-TS ETSI/TS 101 671 V2.10.1:2005](#)

<https://standards.iteh.ai/catalog/standards/sist/4b82199e-99da-4b21-867a-29a505ee860c/sist-ts-etsi-ts-101-671-v2-10-1-2005>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Lawful Interception (LI).

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST-TS ETSI/TS 101 671 V2.10.1:2005](#)

<https://standards.iteh.ai/catalog/standards/sist/4b82199e-99da-4b21-867a-29a505ee860c/sist-ts-etsi-ts-101-671-v2-10-1-2005>

1 Scope

The present document is step 3 of a three-step approach to describe a generic Handover Interface for the provision of lawful interception from a Network Operator, an Access Provider or a Service Provider (NWO/AP/SvP) to the Law Enforcement Agencies (LEAs). The provision of lawful interception is a requirement of national law, which is usually mandatory for the operation of any telecommunication service.

Step 1 contains the requirements for lawful interception from a users (LEAs) point of view and is published in TS 101 331 [1].

Step 2 describes the derived network functions and the general architecture (or functional model) and is published in ES 201 158 [2].

The present document specifies:

- the *generic flow of information* as well as the procedures and information elements, which are applicable to any future telecommunication network or service;
- the network/service specific protocols relating to the provision of lawful interception at the Handover Interface, for the following networks/services:
 - switched circuit; and
 - packet data.

The technologies covered in the present document are: GSM, TETRA, GPRS, ISDN and PSTN.

iTeh STANDARD PREVIEW

NOTE 1: Handover for TETRA is not fully developed.

NOTE 2: As new networks and/or services are developed, the present document will be expanded as the relevant standards become available.

[SIST-TS ETSI/TS 101 671 V2.10.1:2005](#)

<https://standards.iteh.ai/catalog/standards/sist-ts-etsi-ts-101-671-v2-10-1-2005>

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication and/or edition number or version number) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: The numbering of the references is kept in line with the numbering as used in version 1.1.1 and version 2.1.1 of ES 201 671.

- [1] ETSI TS 101 331: "Telecommunications security; Lawful Interception (LI); Requirements of Law Enforcement Agencies".
- [2] ETSI ES 201 158: "Telecommunications security; Lawful Interception (LI); Requirements for network functions".
- [3] ETSI ETR 330: "Security Techniques Advisory Group (STAG); A guide to legislative and regulatory environment".
- [4] Void.

- [5] ETSI EN 300 356 (all parts): "Integrated Services Digital Network (ISDN); Signalling System No.7 (SS7); ISDN User Part (ISUP) version 4 for the international interface".
- [6] ETSI EN 300 403-1 (V1.3.2): "Integrated Services Digital Network (ISDN); Digital Subscriber Signalling System No. one (DSS1) protocol; Signalling network layer for circuit-mode basic call control; Part 1: Protocol specification [ITU-T Recommendation Q.931 (1993), modified]".

NOTE: Reference [6] is specific, because the format of the sub parameters "dSS1-Format, DSS1-parameters-codeset-0", "DSS1-SS-parameters-codeset-0" and "UUS1-Content" are defined by V1.3.2.

- [7] Void.
 - [8] Void.
 - [9] Void.
 - [10] ETSI EN 300 061-1: "Integrated Services Digital Network (ISDN); Subaddressing (SUB) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
 - [11] Void.
 - [12] Void.
 - [13] Void.
 - [14] ETSI EN 300 097-1: "Integrated Services Digital Network (ISDN); Connected Line Identification Presentation (COLP) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification"
- The STANDARD PREVIEW**
(standards.iteh.ai)
- [15] Void.
 - [16] ETSI EN 300 130-1: "Integrated Services Digital Network (ISDN); Malicious Call Identification (MCID) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification"
SIST-TS/TS 101 671 V2.10.1:2005
<https://standards.iteh.ai/catalog/standards/sist/4b82199e-99da-4b21-867a-29a505ee860c/sist-ts-etsi-ts-101-671-v2-10-1-2005>
 - [17] Void.
 - [18] Void.
 - [19] ETSI EN 300 185-1: "Integrated Services Digital Network (ISDN); Conference call, add-on (CONF) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
 - [20] ETSI EN 300 188-1: "Integrated Services Digital Network (ISDN); Three-Party (3PTY) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
 - [21] ETSI EN 300 207-1 (V1.2.5): "Integrated Services Digital Network (ISDN); Diversion supplementary services; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".

NOTE: Reference [21] is specific, because the format of the sub parameters for "DSS1-SS-Invoke-Components" is defined by V1.2.5.

- [22] Void.
- [23] ETSI EN 300 286-1: "Integrated Services Digital Network (ISDN); User-to-User Signalling (UUS) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [24] Void.

- [25] ETSI EN 300 369-1 (V1.2.4): "Integrated Services Digital Network (ISDN); Explicit Call Transfer (ECT) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".

NOTE: Reference [25] is specific, because the format of the sub parameters for "DSS1-SS-Invoke-Components" is defined by V1.2.4.

- [26] Void.

- [27] Void.

- [28] Void.

- [29] ETSI EN 300 196-1 (V1.3.2): "Integrated Services Digital Network (ISDN); Generic functional protocol for the support of supplementary services; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".

NOTE: Reference [29] is specific, because several parameter format definitions point to V1.3.2.

- [30] Void.

- [31] ITU-T Recommendation Q.850 (1988): "Usage of cause and location in the Digital Subscriber Signalling System No. 1 and the Signalling System No. 7 ISDN User Part".

NOTE: Reference [31] is specific, because several parameter format definitions point to version 1988.

- [32] ETSI ETS 300 974: "Digital cellular telecommunications system (Phase 2+) (GSM); Mobile Application Part (MAP) specification (GSM 09.02)".

- [33] ITU-T Recommendation X.680: "Information technology - Abstract Syntax Notation One (ASN.1): Specification of basic notation".
iTeh STANDARD REVIEW
(standards.iteh.ai)

- [34] ITU-T Recommendation X.690: "Information technology - ASN.1 encoding rules: Specification of Basic Encoding Rules (BER), Canonical Encoding Rules (CER) and Distinguished Encoding Rules (DER)".
<https://standards.iteh.ai/catalog/standards/sist/4b82199e-99da-4b21-867a-39a505ec860c880> (SIST-TS ETSI/TS 101 671 V2.10.1:2005)

- [35] ITU-T Recommendation X.880: "Information technology - Remote Operations: Concepts, model and notation".

- [36] ITU-T Recommendation X.881: "Information technology - Remote Operations: OSI realizations - Remote Operations Service Element (ROSE) service definition".

- [37] ITU-T Recommendation X.882: "Information technology - Remote Operations: OSI realizations - Remote Operations Service Element (ROSE) protocol specification".

- [38] Void.

- [39] ETSI EN 300 122-1: "Integrated Services Digital Network (ISDN); Generic keypad protocol for the support of supplementary services; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".

- [40] ETSI EN 300 392-1: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 1: General network design".

- [41] ETSI TS 124 008: "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); Mobile radio interface Layer 3 specification; Core network protocols; Stage 3 (3GPP TS 24.008 version 5.6.0 Release 5)".

- [42] ETSI TS 101 509: "Digital cellular telecommunications system (Phase 2+) (GSM); Lawful interception; Stage 2 (3GPP TS 03.33)".

- [43] ETSI TS 100 927: "Digital cellular telecommunications system (Phase 2+); Numbering, addressing and identification (3GPP TS 03.03)".

- [44] Void.

- [45] ETSI TS 101 347: "Digital cellular telecommunications system (Phase 2+); General Packet Radio Service (GPRS); GPRS Tunnelling Protocol (GTP) across the Gn and Gp Interface (3GPP TS 09.60)".
- [46] IETF RFC 959: "File Transfer Protocol".
- [47] Void.
- [48] ITU-T Recommendation Q.763: "Signalling System No.7 - ISDN User Part formats and codes".
- [49] ETSI TS 101 393: "Digital cellular telecommunications system (Phase 2+) (GSM); General Packet Radio Service (GPRS); GPRS Charging (GSM 12.15)".
- [50] Void.
- [51] IETF RFC 791: "Internet Protocol".
- [52] IETF RFC 793: "Transmission Control Protocol".
- [53] Void.
- [54] ETSI EN 300 089: "Integrated Services Digital Network (ISDN); Calling Line Identification Presentation (CLIP) supplementary service; Service description".
- [55] ETSI TS 100 940: "Digital cellular telecommunications system (Phase 2+); Mobile radio interface; Layer 3 specification (3GPP TS 04.08)".
- [56] ITU-T Recommendation Q.931: "ISDN user-network interface layer 3 specification for basic call control".
iTeh STANDARD PREVIEW
- [57] ETSI TS 101 109: "Digital cellular telecommunications system (Phase 2+); Universal Geographical Area Description (GAD) (3GPP TS 03.32)".
- [58] ITU-T Recommendation E.164: "The international public telecommunication numbering plan".
[SIST-TS ETSI/TS 101 671 V2.10.1:2005](#)
- [59] IETF RFC 2543: "SIP: Session Initiation Protocol".
[199e-99da-4b21-867a-29a505ee860c/cist-ts-etsi-ts-101-671-v2-10-1-2005](#)
- [60] ETSI TS 129 060: "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); General Packet Radio Service (GPRS); GPRS Tunnelling Protocol (GTP) across the Gn and Gp interface (3GPP TS 29.060)".
- [61] ETSI TS 133 108: "Universal Mobile Telecommunications System (UMTS); 3G security; Handover interface for Lawful Interception (LI) (3GPP TS 33.108)".
- [62] ETSI TS 125 431: "Universal Mobile Telecommunications System (UMTS); UTRAN lub interface Layer 1 (3GPP TS 25.431)".
- [63] ITU-T Recommendation Q.731.3: "Stage 3 description for number identification supplementary services using Signalling System No. 7: Calling line identification presentation (CLIP)".
- [64] ITU-T Recommendation Q.951.1: "Stage 3 description for number identification supplementary services using DSS 1: Direct-dialling-in (DDI)".
- [65] ITU-T Recommendation Q.951.3: "Stage 3 description for number identification supplementary services using DSS 1: Calling line identification presentation".
- [66] ETSI EN 300 092 (all parts): "Integrated Services Digital Network (ISDN); Calling Line Identification Presentation (CLIP) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol".
- [67] ISO 3166-1: "Codes for the representation of names of countries and their subdivisions - Part 1: Country codes".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

access provider: provides a user of some network with access from the user's terminal to that network

NOTE: This definition applies specifically for the present document. In a particular case, the access provider and network operator may be a common commercial entity.

activation/deactivation of supplementary services: procedures for activation, which is the operation of bringing the service into the "ready for invocation" state, and deactivation, which is the complementary action

(to) buffer: temporary storing of information in case the necessary telecommunication connection to transport information to the LEMF is temporarily unavailable

call: any temporarily switched connection capable of transferring information between two or more users of a telecommunications system

NOTE: In this context a user may be a person or a machine.

CC link: communication channel for HI3 information between a mediation function and a LEMF

NOTE: It is used for transmission of the Content of Communication. This term refers to circuit switched only.

CC Link IDentifier (CCLID): See definition in clause A.1 of TS 101 671.

communication: information transfer according to agreed conventions

Communication IDentifier (CID): See definition in clause 6 of TS 101 671.

Communication Identity Number (CIN): See definition in clause 6 of TS 101 671.
<https://standards.etsi.org/catalog/standards/sist/4b82199c-99da-4b21-867a-29a505ee860/sist-ts-etsi-ts-101-671-v2.10.1-2005>

communications session: session consists of either a single self-contained transaction or a series of protocol data units that together form a single self-contained communication

Content of Communication (CC): information exchanged between two or more users of a telecommunications service, excluding Intercept Related Information

NOTE: This includes information which may, as part of some telecommunications service, be stored by one user for subsequent retrieval by another.

Handover Interface (HI): physical and logical interface across which the interception measures are requested from network operator/access provider/service provider, and the results of interception are delivered from a network operator/access provider/service provider to a law enforcement monitoring facility

identity: technical label which may represent the origin or destination of any telecommunications traffic, as a rule clearly identified by a physical telecommunications identity number (such as a telephone number) or the logical or virtual telecommunications identity number (such as a personal number) which the subscriber can assign to a physical access on a case-by-case basis

information: intelligence or knowledge capable of being represented in forms suitable for communication, storage or processing

NOTE: Information may be represented for example by signs, symbols, pictures or sounds.

interception: action (based on the law), performed by a network operator/access provider/service provider, of making available certain information and providing that information to a law enforcement monitoring facility

NOTE: In the present document the term interception is not used to describe the action of observing communications by a law enforcement agency.

interception configuration information: information related to the configuration of interception