

INTERNATIONAL STANDARD

IEC
60268-5

Third edition
2003-05

Sound system equipment –

Part 5: Loudspeakers

Équipements pour systèmes électroacoustiques –

*Partie 5:
Haut-parleurs*

[IEC 60268-5:2003](#)

<https://standards.iteh.ai/catalog/standards/iec/f4c9ff13-415b-46ce-bfd2-16f390c03fc4/iec-60268-5-2003>



Reference number
IEC 60268-5:2003(E)

Publication numbering

As from 1 January 1997 all IEC publications are issued with a designation in the 60000 series. For example, IEC 34-1 is now referred to as IEC 60034-1.

Consolidated editions

The IEC is now publishing consolidated versions of its publications. For example, edition numbers 1.0, 1.1 and 1.2 refer, respectively, to the base publication, the base publication incorporating amendment 1 and the base publication incorporating amendments 1 and 2.

Further information on IEC publications

The technical content of IEC publications is kept under constant review by the IEC, thus ensuring that the content reflects current technology. Information relating to this publication, including its validity, is available in the IEC Catalogue of publications (see below) in addition to new editions, amendments and corrigenda. Information on the subjects under consideration and work in progress undertaken by the technical committee which has prepared this publication, as well as the list of publications issued, is also available from the following:

- **IEC Web Site** (www.iec.ch)

- **Catalogue of IEC publications**

The on-line catalogue on the IEC web site (http://www.iec.ch/searchpub/cur_fut.htm) enables you to search by a variety of criteria including text searches, technical committees and date of publication. On-line information is also available on recently issued publications, withdrawn and replaced publications, as well as corrigenda.

- **IEC Just Published**

This summary of recently issued publications (http://www.iec.ch/online_news/justpub/jp_entry.htm) is also available by email. Please contact the Customer Service Centre (see below) for further information.

- **Customer Service Centre**

If you have any questions regarding this publication or need further assistance,

please contact the Customer Service Centre: -46ce-bfd2-16f390c03fe4/iec-60268-5-2003

Email: custserv@iec.ch

Tel: +41 22 919 02 11

Fax: +41 22 919 03 00

INTERNATIONAL STANDARD

IEC 60268-5

Third edition
2003-05

Sound system equipment –

Part 5: Loudspeakers

Équipements pour systèmes électroacoustiques –

*Partie 5:
Haut-parleurs*

IEC 60268-5:2003

<https://standards.iteh.ai/catalog/standards/iec/f4c9ff13-415b-46ce-bfd2-16f390c03fc4/iec-60268-5-2003>

© IEC 2003 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE

X

For price, see current catalogue

CONTENTS

FOREWORD	5
1 Scope	6
2 Normative references.....	6
3 Conditions for measurement	7
3.1 General conditions.....	7
3.2 Measuring conditions.....	7
4 Test signals	8
4.1 General	8
4.2 Sinusoidal signal	8
4.3 Broadband noise signal	8
4.4 Narrow-band noise signal	8
4.5 Impulsive signal.....	8
5 Acoustical environment.....	8
5.1 General	8
5.2 Free-field conditions	8
5.3 Half-space free-field conditions.....	9
5.4 Diffuse sound field conditions	9
5.5 Simulated free-field conditions.....	9
5.6 Half-space simulated free-field conditions.....	9
6 Unwanted acoustical and electrical noise.....	9
7 Positioning of loudspeaker and measuring microphone.....	10
7.1 Measuring distance under free-field and half-space free-field conditions.....	10
7.2 Positioning of loudspeaker in diffuse field conditions	10
7.3 Positioning of loudspeaker and microphone in simulated free-field conditions.....	10
8 Measuring equipment.....	11
9 Accuracy of the acoustical measurement	11
10 Mounting of loudspeakers	11
10.1 Mounting and acoustic loading of drive units.....	11
10.2 Mounting and acoustic loading of a loudspeaker system.....	11
11 Standard baffle and measuring enclosures	11
11.1 Standard baffle	11
11.2 Standard measuring enclosures.....	12
12 Preconditioning.....	13
13 Type description	13
13.1 General	13
13.2 Loudspeaker drive units.....	13
13.3 Loudspeaker system.....	13
14 Marking of terminals and controls	13
15 Reference plane, reference point and reference axis	13
15.1 Reference plane – characteristic to be specified	13
15.2 Reference point – characteristic to be specified	14
15.3 Reference axis – characteristic to be specified	14
16 Impedance and derivative characteristics.....	14
16.1 Rated impedance – characteristic to be specified	14

16.2	Impedance curve	14
16.3	Total Q-factor (Q_t)	14
16.4	Equivalent air volume of a loudspeaker drive unit compliance (V_{as})	16
17	Input voltage	17
17.1	Rated noise voltage	17
17.2	Short-term maximum input voltage	18
17.3	Long-term maximum input voltage	18
17.4	Rated sinusoidal voltage	19
18	Input electrical power	19
18.1	Rated noise power – characteristic to be specified	19
18.2	Short-term maximum power – characteristic to be specified	19
18.3	Long-term maximum power – characteristic to be specified	19
18.4	Rated sinusoidal power – characteristic to be specified	19
19	Frequency characteristics	20
19.1	Rated frequency range – characteristic to be specified	20
19.2	Resonance frequency	20
19.3	Tuning frequency of a bass reflex or passive radiator loudspeaker system – characteristic to be specified	20
20	Sound pressure under free-field and half-space free-field conditions	20
20.1	Sound pressure in a stated frequency band	20
20.2	Sound pressure level in a stated frequency band – characteristic to be specified	21
20.3	Characteristic sensitivity in a stated frequency band	21
20.4	Characteristic sensitivity level in a stated frequency band – characteristic to be specified	21
20.5	Mean sound pressure in a stated frequency band	21
20.6	Mean sound pressure level in a stated frequency band – characteristic to be specified	22
21	Response under free-field and half-space free-field conditions	22
21.1	Frequency response	22
21.2	Effective frequency range	23
21.3	Transfer function	23
22	Output power (acoustic power)	24
22.1	Acoustic power in a frequency band	24
22.2	Mean acoustic power in a frequency band	25
22.3	Efficiency in a frequency band	26
22.4	Mean efficiency in a frequency band	26
23	Directional characteristics	26
23.1	Directional response pattern	26
23.2	Radiation angle	27
23.3	Directivity index	27
23.4	Coverage angle or angles	28
24	Amplitude non-linearity	29
24.1	Total harmonic distortion	29
24.2	Harmonic distortion of the n^{th} order (where $n = 2$ or $n = 3$)	31
24.3	Characteristic harmonic distortion	32
24.4	Modulation distortion of the n^{th} order (where $n = 2$ or $n = 3$)	32
24.5	Characteristic modulation distortion of the n^{th} order (where $n = 2$ or $n = 3$)	33
24.6	Difference frequency distortion (of the second order only)	33

25	Rated ambient conditions.....	34
25.1	Temperature ranges	34
25.2	Humidity ranges.....	34
26	Stray magnetic fields	35
26.1	Static components	35
26.2	Dynamic components.....	36
27	Physical characteristics	36
27.1	Dimensions.....	36
27.2	Mass.....	36
27.3	Cable assemblies	37
28	Design data	37
29	Indication of the characteristics to be specified.....	37
Annex A (informative)	Standard measuring enclosure type A	43
Annex B (informative)	Standard measuring enclosure type B	45
Annex C (informative)	Definitions of terms used in Clause 13.....	48
Bibliography.....		50
Figure 1 – Impedance curve of loudspeaker		15
Figure 2 – Standard baffle, dimensions		39
Figure 3 – Standard baffle with chamfer		40
Figure 4 – Standard baffle with sub-baffle		40
Figure 5 – Standard measuring enclosure type A		41
Figure 6 – Standard measuring enclosure type B		41
Figure 7 – Block diagram of test set-up		42
Figure 8 – Measuring apparatus for stray magnetic field.....		42
Figure A.1 – An example of standard measuring enclosure type A		43
Figure A.2 – The correction curve for the diffraction effect of the standard measuring enclosure from free-field to half-space free-field		44
Figure A.3 – The correction curve for the diffraction effect of a standard measuring enclosure from free-field to half-space free-field.....		44
Figure B.1 – An example of standard measuring enclosure type B		45
Figure B.2 – Construction of scalable measuring enclosure type B.....		46
Figure B.3 – The correction curve for the diffraction effect of the standard measuring enclosure from free-field to half-space free-field.....		47
Figure B.4 – The correction curve for the diffraction effect of the standard measuring enclosure from free-field to half-space free-field.....		47
Table 1 – Indication of the characteristics to be specified.....		38
Table B.1 – Dimensions and ratios of scalable measuring enclosure type B		46

INTERNATIONAL ELECTROTECHNICAL COMMISSION

SOUND SYSTEM EQUIPMENT –

Part 5: Loudspeakers

FOREWORD

- 1) The IEC (International Electrotechnical Commission) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of the IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, the IEC publishes International Standards. Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. The IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of the IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested National Committees.
- 3) The documents produced have the form of recommendations for international use and are published in the form of standards, technical specifications, technical reports or guides and they are accepted by the National Committees in that sense.
- 4) In order to promote international unification, IEC National Committees undertake to apply IEC International Standards transparently to the maximum extent possible in their national and regional standards. Any divergence between the IEC Standard and the corresponding national or regional standard shall be clearly indicated in the latter.
- 5) The IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with one of its standards.
- 6) Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. The IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60268-5 has been prepared by IEC technical committee 100: Audio, video and multimedia systems and equipment.

This third edition of IEC 60268-5 cancels and replaces the second edition published in 1989, amendment 1 (1993) and amendment 2 (1996). This third edition constitutes a technical revision.

The text of this standard is based on the following documents:

FDIS	Report on voting
100/648/FDIS	100/674/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This standard is to be read in conjunction with IEC 60268-1, IEC 60268-2 and ISO 3741.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until 2005. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

A bilingual edition of this standard may be issued at a later date.

SOUND SYSTEM EQUIPMENT –

Part 5: Loudspeakers

1 Scope

This standard applies to sound system loudspeakers, treated entirely as passive elements. Loudspeakers with built-in amplifiers are excluded.

NOTE 1 The term “loudspeaker” used in this standard relates to loudspeaker drive units themselves and also to loudspeaker systems, which comprise one or more loudspeaker drive units provided with a baffle, enclosure or horn and such relevant devices as built-in crossover filters, transformers and any other passive element.

The purpose of this standard is to give the characteristics to be specified and the relevant methods of measurement for loudspeakers using sinusoidal or specified noise or impulsive signals.

NOTE 2 The methods of measurement given in this standard have been chosen for their appropriateness to the characteristics.

NOTE 3 If equivalent results can be obtained using other methods of measurement, details of the methods used should be presented with the results.

NOTE 4 The following items are under consideration:

- loudspeakers with built-in amplifiers;
- measurements under conditions other than free-field, half-space free-field and diffuse field;
- measurements with signals other than sinusoidal or noise or impulsive signals.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050(151), *International Electrotechnical Vocabulary (IEV) – Part 151: Electrical and magnetic devices*

IEC 60263, *Scales and sizes for plotting frequency characteristics and polar diagrams*

IEC 60268-1, *Sound system equipment – Part 1: General*

IEC 60268-2, *Sound system equipment – Part 2: Explanation of general terms and calculation methods*

IEC 60268-3, *Sound system equipment – Part 3: Amplifiers*

IEC 60268-11, *Sound system equipment – Part 11: Application of connectors for the interconnection of sound system components*

IEC 60268-12, *Sound system equipment – Part 12: Application of connectors for broadcast and similar use*

IEC 60268-14, *Part 14: Circular and elliptical loudspeakers; outer frame diameters and mounting dimensions*

IEC 60651, *Sound level meters*

IEC 61260, *Electroacoustics – Octave-band and fractional-octave-band filters*

ISO 3741, *Acoustics – Determination of sound power levels of noise sources using sound pressure – Precision methods for reverberation rooms*

ISO 3744, *Acoustics – Determination of sound power levels of noise sources using sound pressure – Engineering method in an essentially free field over a reflecting plane*

ISO 3745, *Acoustics – Determination of sound power levels of noise sources – Precision methods for anechoic and semi-anechoic rooms*

3 Conditions for measurement

3.1 General conditions

This standard is to be used in conjunction with IEC 60268-1, IEC 60268-2 and ISO 3741.

3.2 Measuring conditions

3.2.1 General

For convenience in specifying how loudspeakers are to be set up for measurement, normal measuring conditions are defined in this standard. To obtain the correct conditions for measurement, some values (known as “rated conditions”) shall be taken from the manufacturer's specification. These values themselves are not subject to measurement but they constitute the basis for measuring the other characteristics.

The following values and conditions are of this type, and shall be stated by the manufacturer:

- rated impedance;
- rated sinusoidal voltage or power;
- rated noise voltage or power;
- rated frequency range;
- reference plane;
- reference point;
- reference axis.

NOTE A full explanation of the term “rated” is given in IEC 60268-2. See also term 151-04-03 in IEC 60050(151).

3.2.2 Normal measuring conditions

A loudspeaker shall be understood to be working under normal measuring conditions when all the following conditions are fulfilled:

- a) the loudspeaker to be measured is mounted in accordance with Clause 10;
- b) the acoustical environment is specified and is selected from those specified in Clause 5;
- c) the loudspeaker is positioned with respect to the measuring microphone and the walls in accordance with Clause 7;
- d) the loudspeaker is supplied with a specified test signal, in accordance with Clause 4, of a stated voltage U , within the rated frequency range in accordance with 19.1. If required, the input power P can be calculated from the equation: $P = U^2/R$, where R is the rated impedance in accordance with 16.1;
- e) attenuators, if any, are set to their “normal” position as stated by the manufacturer. If other positions are chosen, for example those providing a maximally flat frequency response or maximum attenuation, these shall be specified;
- f) measuring equipment suitable for determining the wanted characteristics is connected in accordance with Clause 8.

4 Test signals

4.1 General

Acoustical measurements shall be made under one of the following measuring signal conditions, and the choice shall be indicated with the results.

4.2 Sinusoidal signal

The sinusoidal test signal shall not exceed the rated sinusoidal voltage (as defined in 17.4) at any frequency. The voltage across the input terminals of the loudspeaker under test shall be kept constant for all frequencies unless otherwise stated.

4.3 Broadband noise signal

NOTE This term is explained in IEC 60268-2.

The crest factor of a noise source should fall between 3 and 4 to avoid clipping of amplifiers.

A true r.m.s. voltmeter with a time constant at least as long as the “slow” constant of the sound level meter, specified in IEC 60651, shall be used to measure the amplitude of the signal.

4.4 Narrow-band noise signal

NOTE This term is explained in IEC 60268-2.

For measurement using narrow-band noise, constant relative bandwidth filters in accordance with IEC 61260 shall be used with a pink-noise generator, the relative bandwidth being usually 1/3 octave.

4.5 Impulsive signal

A short-duration pulse shall have constant spectral power per unit bandwidth over at least the bandwidth of interest in the measurement. Such a signal has low energy content relative to its peak amplitude.

NOTE To minimize the influence of acoustical and electrical noise on the measurement, the peak amplitude of the pulse should be as high as possible within the capability of the driving amplifier and consistent with linear operation of the loudspeaker.

5 Acoustical environment

5.1 General

Acoustical measurements shall be made under one of the acoustical field conditions specified in 5.2 to 5.6, and the choice shall be indicated with the results.

5.2 Free-field conditions

If acoustical conditions approach those of free-field space, an environment (for example an anechoic room) in which the sound pressure decreases with the distance (r) from a point source according to a $1/r$ law, with an accuracy of $\pm 10\%$, in the region that will be occupied by the sound field between the loudspeaker system and the microphone during the measurements shall be used. The minimum conditions shall be deemed to exist if this requirement is met along the axis joining the measuring microphone and the reference point on the loudspeaker.

Free-field conditions shall exist over the whole frequency range of measurement.

5.3 Half-space free-field conditions

If acoustical conditions are used in which the free-field exists in a half space, these conditions shall be met with a reflecting plane of sufficient size so that the sound pressure from a point source mounted in the surface of that plane decreases in the manner specified in 5.2.

5.4 Diffuse sound field conditions

NOTE 1 These conditions are normally used for band noise measurements only.

If diffuse sound field conditions are used for measurements with 1/3 octave band limited noise, as defined and specified in ISO 3741, the lower limiting frequency shall be determined as specified in ISO 3741, Appendix A.

NOTE 2 While ISO 3741 provides details of measuring instruments, it should be clearly understood that both space averaging and time averaging are required in loudspeaker power determination. This may be achieved as stated in the standard or alternatively by using continuous space and time averaging techniques.

NOTE 3 The precision of the measurement depends on a number of factors including the room volume, the room reverberation time, and the degree of diffusion.

NOTE 4 For measurement below 125 Hz, a room volume greater than 200 m³ is desirable.

5.5 Simulated free-field conditions

If acoustical conditions are used in which the simulated free-field conditions that are equivalent to those of free space for the period of time required for a measurement, these conditions shall be used.

The conditions shall be met in any environment (for example large, unobstructed rooms) in which sound emitted by a loudspeaker in response to an impulsive signal reflected from any surface or object in the environment does not reach the measuring microphone before measurement of the direct path sound at the microphone has been completed.

Any such reflection reaching the microphone shall be excluded from the measurement by gating or other means.

NOTE 1 These conditions are normally used only for measurements with impulsive signals.

NOTE 2 Under such conditions, successive measurements are separated by time intervals sufficient for the sound pressure level due to reverberation within the space to decrease to a negligible value.

5.6 Half-space simulated free-field conditions

If acoustical conditions are used in which the simulated free-field exists in a half-space, these conditions shall be used when a reflecting plane, forming one boundary of a simulated free-field environment, is of sufficient size that no reflections from its edge reach the measuring microphone within the measurement time.

NOTE 1 These conditions are normally used only for measurements with impulsive signals.

NOTE 2 Under such conditions, successive measurements are separated by time intervals sufficient for the sound pressure level due to reverberation within the space to decrease to a negligible value.

6 Unwanted acoustical and electrical noise

Unwanted acoustical and electrical noise shall be kept at the lowest possible level as its presence may obscure low-level signals.

Data related to signals which are less than 10 dB above the noise level in the frequency band considered shall be discarded.

7 Positioning of loudspeaker and measuring microphone

7.1 Measuring distance under free-field and half-space free-field conditions

7.1.1 General

Measurements under free-field and half-space free-field conditions should ideally be carried out in the far field of the loudspeaker, in order to obtain consistent results. However, in practice, imperfections of the measuring environment room and the effects of background noise set an upper limit to the distance that can be used. Therefore, the measuring distance should be 0,5 m or an integral number of m, and that result should be referred to a standard distance of 1 m.

7.1.2 Single drive unit loudspeaker

For this type of loudspeaker, a measuring distance of 1 m from the reference point shall be used unless special conditions dictate another value, which shall be stated.

7.1.3 Multi-unit loudspeaker systems

Loudspeaker systems in which two or more loudspeaker units reproduce the same frequency band create problems of acoustical interference at the measuring point due to the interaction of the sounds radiated by the units. This situation exists whether all units operate over the entire frequency band under test or whether some units operate over parts of this band (for example cross-over regions). In such cases, the measuring distance should be chosen so as to minimize the errors due to this phenomenon.

7.2 Positioning of loudspeaker in diffuse field conditions

The loudspeaker position and orientation with respect to the walls shall be described by means of a diagram appended to the measurement results.

An arrangement for the simultaneous movement of the loudspeaker and the microphone is permitted for the evaluation of the power delivered by the loudspeaker in accordance with the method prescribed in 22.1.2.2. The microphone system and the nearest microphone position shall meet the requirements of ISO 3741.

7.3 Positioning of loudspeaker and microphone in simulated free-field conditions

The measuring distance shall be chosen with reference to 7.1 for free-field conditions.

The position of the loudspeaker and microphone within the measuring environment shall be such so as to maximize the time available for measurement before the first unwanted reflection reaches the microphone.

If the measurement space is an anechoic chamber, attention shall be paid to reflections from wedge tips, personnel floor, and supports for the loudspeaker and microphone. Errors from these sources shall not exceed 0,5 dB over the frequency range of measurement.

The microphone distance and the maximum signal capture time available in the environment shall be stated.

It is necessary to ignore all the output of the microphone from the time of arrival of the first reflection onwards. Truncation errors are therefore introduced into the transfer function measurement unless the loudspeaker response to the impulsive test signal is negligible during this time. If present, such truncation errors shall not exceed 1 dB over the frequency range of measurement.

8 Measuring equipment

Measurements in free-field and half-space free-field conditions shall be made using a pressure microphone having a known calibration. For measurements under diffuse-field conditions, a pressure microphone shall be used having a directivity index less than 2 dB. Both these requirements shall be met for all frequencies in the frequency range of interest.

The signal generator, the amplifier supplying the signal to the loudspeaker, and the measuring equipment at the microphone amplifier shall have an amplitude frequency response known and constant within $\pm 0,5$ dB in the relevant frequency range, with negligible amplitude non-linearity under test conditions. All measuring instruments shall be of the r.m.s. type, having a time constant long enough to ensure an error not greater than 1 dB.

NOTE It is recommended that the frequency response be measured by an automatic method giving a continuous curve. Errors due to the chosen writing speeds (along both level and frequency axes) of the level recorder should not exceed 0,5 dB. The writing speeds along both axes should be stated.

9 Accuracy of the acoustical measurement

The frequency range over which the total errors do not exceed ± 2 dB shall be stated.

NOTE The probable error sources in both the instrumentation and the measuring environment should be identified and quantified and their contribution specified. This information should be included with the test report.

10 Mounting of loudspeakers

10.1 Mounting and acoustic loading of drive units

The performance of a drive unit is determined by the properties of the unit itself and its acoustic loading. The acoustic loading depends upon the mounting arrangement, which shall be clearly described in the presentation of results.

One of the following three types of mounting shall be used:

- a) a standard baffle, standard measuring enclosure (type A or type B), or specified enclosure;
- b) in free air without a baffle or enclosure;
- c) in half-space free-field, flush with the reflecting plane.

NOTE Mounting condition a) approaches that of a half-space free-field down to a lower limiting frequency, the value of which depends on the chosen measuring distance. Measurements made at frequencies below this limiting value may be used for comparative purposes only.

10.2 Mounting and acoustic loading of a loudspeaker system

Loudspeaker systems are usually measured without any additional baffle. If the manufacturer specifies a special type of mounting for the loudspeaker systems, this shall be used for the measurement; the mounting method used shall be specified with the results.

11 Standard baffle and measuring enclosures

11.1 Standard baffle

The standard baffle shall be made with a plane front surface that is acoustically reflective. The baffle shall have the dimensions shown in Figure 2.

NOTE The standard baffle should be of a material of thickness adequate to ensure negligible vibration. The edge of the radiating element should be substantially flush with the front surface of the baffle. This may be achieved by means of a chamfer as shown in Figure 3 or by the use of a thin rigid sub-baffle, with or without a chamfer, as shown in Figure 4.

11.2 Standard measuring enclosures

11.2.1 General

One of the two types of standard measuring enclosures specified in 11.2.3 (type A) and 11.2.4 (type B) shall be used. The type chosen for testing shall be stated by the manufacturer.

11.2.2 Conditions

The enclosure shall have plane or curved surfaces which have an acoustically reflective characteristic.

NOTE 1 The material shall be appropriately thick so that the effect of vibrations can be disregarded for measurement. If necessary, braces should be used for reinforcement between facing surfaces at and around their centres so as to avoid panel vibrations.

NOTE 2 The enclosure should be airtight.

NOTE 3 The edge of the loudspeaker should be set on the same plane as that of the front part of the baffle.

NOTE 4 To remove standing waves that may otherwise occur in the enclosure, an appropriate sound absorbing material shall be used. Handles or joints may be installed if their effect on acoustical reflections and undesired vibrations can be ignored.

NOTE 5 When the loudspeaker is mounted in the enclosure, care should be taken to avoid air leakage from the inside of the enclosure.

11.2.3 Standard measuring enclosure type A

The standard measuring enclosure type A shall be as shown in Figure 5.

NOTE 1 The characteristic of the correction curves for the standard measuring enclosure diffraction effect at a measuring distance of 1 m on the reference axis from free-field to half-space free-field is shown in Annex A.

NOTE 2 All the surfaces of this type of enclosure are plane and the joints of the surfaces are made at right angles. No change in size is allowed. This causes the diffraction characteristic to be repeatable. Therefore, type A is useful when analysing, studying or comparing the characteristics of loudspeakers in detail.

11.2.4 Standard measuring enclosure type B

The standard measuring enclosure type B shall be as shown in Figure 6.

NOTE 1 The characteristic of the correction curves for the standard measuring enclosure diffraction effect at a measuring distance of 1 m on the reference axis from free-field to half-space free-field is shown in Annex B.

NOTE 2 If a smaller or larger measuring enclosure of type B is required, it should meet the requirement for proportional scaling as shown in Annex B, Figure B.2 and Table B.1. In this case, the report should state the outside dimensions and the net volume of the enclosure.

NOTE 3 A change in scale is allowed. It is recommended to use the standard measuring enclosure as shown in Figure 6 for acoustical measurements. Properly scaled enclosures are useful for subjective testing.