

INTERNATIONAL STANDARD

NORME INTERNATIONALE



Sound system equipment –
Part 5: Loudspeakers

Équipements pour systèmes électroacoustiques –
Partie 5: Haut-parleurs

IEC 60268-5:2003

<https://standards.iteh.ai/catalog/standards/iec/f4c9ff13-415b-46ce-bfd2-16f390c03fc4/iec-60268-5-2003>





THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2007 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC online collection - oc.iec.ch

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 18 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Recherche de publications IEC - webstore.iec.ch/advsearchform

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études, ...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC online collection - oc.iec.ch

Découvrez notre puissant moteur de recherche et consultez gratuitement tous les aperçus des publications. Avec un abonnement, vous aurez toujours accès à un contenu à jour adapté à vos besoins.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire d'électrotechnologie en ligne au monde, avec plus de 22 000 articles terminologiques en anglais et en français, ainsi que les termes équivalents dans 16 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: sales@iec.ch.



IEC 60268-5

Edition 3.1 2007-09
CONSOLIDATED VERSION

INTERNATIONAL STANDARD

NORME INTERNATIONALE



Sound system equipment –
Part 5: Loudspeakers

Équipements pour systèmes électroacoustiques –
Partie 5: Haut-parleurs

IEC 60268-5:2003

<https://standards.iteh.ai/catalog/standards/iec/f4c9ff13-415b-46ce-bfd2-16f390c03fc4/iec-60268-5-2003>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 33.160.50

ISBN 2-8318-9286-4

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

REDLINE VERSION

VERSION REDLINE



**Sound system equipment –
Part 5: Loudspeakers**

**Equipements pour systèmes électroacoustiques –
Partie 5: Haut-parleurs**

IEC 60268-5:2003

<https://standards.iteh.ai/catalog/standards/iec/f4c9ff13-415b-46ce-bfd2-16f390c03fc4/iec-60268-5-2003>

CONTENTS

| | |
|--|----|
| FOREWORD..... | 5 |
| 1 Scope..... | 7 |
| 2 Normative references | 7 |
| 3 Conditions for measurement..... | 8 |
| 3.1 General conditions | 8 |
| 3.2 Measuring conditions | 8 |
| 4 Test signals..... | 9 |
| 4.1 General..... | 9 |
| 4.2 Sinusoidal signal..... | 9 |
| 4.3 Broadband noise signal..... | 9 |
| 4.4 Narrow-band noise signal | 9 |
| 4.5 Impulsive signal | 9 |
| 5 Acoustical environment | 9 |
| 5.1 General..... | 9 |
| 5.2 Free-field conditions | 9 |
| 5.3 Half-space free-field conditions..... | 10 |
| 5.4 Diffuse sound field conditions | 10 |
| 5.5 Simulated free-field conditions | 10 |
| 5.6 Half-space simulated free-field conditions | 10 |
| 6 Unwanted acoustical and electrical noise | 10 |
| 7 Positioning of loudspeaker and measuring microphone..... | 11 |
| 7.1 Measuring distance under free-field and half-space free-field conditions..... | 11 |
| 7.2 Positioning of loudspeaker in diffuse field conditions..... | 11 |
| 7.3 Positioning of loudspeaker and microphone in simulated free-field conditions | 11 |
| 8 Measuring equipment | 12 |
| 9 Accuracy of the acoustical measurement..... | 12 |
| 10 Mounting of loudspeakers..... | 12 |
| 10.1 Mounting and acoustic loading of drive units | 12 |
| 10.2 Mounting and acoustic loading of a loudspeaker system | 12 |
| 11 Standard baffle and measuring enclosures | 13 |
| 11.1 Standard baffle | 13 |
| 11.2 Standard measuring enclosures | 13 |
| 12 Preconditioning..... | 14 |
| 13 Type description | 14 |
| 13.1 General..... | 14 |
| 13.2 Loudspeaker drive units | 14 |
| 13.3 Loudspeaker system | 14 |
| 14 Marking of terminals and controls | 14 |
| 14.1 General..... | 14 |
| 14.2 Positive terminal | 14 |
| 15 Reference plane, reference point and reference axis | 15 |
| 15.1 Reference plane – characteristic to be specified | 15 |
| 15.2 Reference point – characteristic to be specified | 15 |
| 15.3 Reference axis – characteristic to be specified | 15 |

| | | |
|------|--|----|
| 16 | Impedance and derivative characteristics | 15 |
| 16.1 | Rated impedance – characteristic to be specified | 15 |
| 16.2 | Impedance curve | 16 |
| 16.3 | Total Q-factor (Q_t) | 16 |
| 16.4 | Equivalent air volume of a loudspeaker drive unit compliance (V_{as}) | 17 |
| 17 | Input voltage | 18 |
| 17.1 | Rated noise voltage | 18 |
| 17.2 | Short-term maximum input voltage | 19 |
| 17.3 | Long-term maximum input voltage | 20 |
| 17.4 | Rated sinusoidal voltage | 20 |
| 18 | Input electrical power | 21 |
| 18.1 | Rated noise power – characteristic to be specified | 21 |
| 18.2 | Short-term maximum power – characteristic to be specified | 21 |
| 18.3 | Long-term maximum power – characteristic to be specified | 21 |
| 18.4 | Rated sinusoidal power – characteristic to be specified | 21 |
| 19 | Frequency characteristics | 21 |
| 19.1 | Rated frequency range – characteristic to be specified | 21 |
| 19.2 | Resonance frequency | 21 |
| 19.3 | Tuning frequency of a bass reflex or passive radiator loudspeaker system – characteristic to be specified | 22 |
| 20 | Sound pressure under free-field and half-space free-field conditions | 22 |
| 20.1 | Sound pressure in a stated frequency band | 22 |
| 20.2 | Sound pressure level in a stated frequency band – characteristic to be specified | 22 |
| 20.3 | Characteristic sensitivity in a stated frequency band | 23 |
| 20.4 | Characteristic sensitivity level in a stated frequency band – characteristic to be specified | 23 |
| 20.5 | Mean sound pressure in a stated frequency band | 23 |
| 20.6 | Mean sound pressure level in a stated frequency band – characteristic to be specified | 23 |
| 21 | Response under free-field and half-space free-field conditions | 23 |
| 21.1 | Frequency response | 23 |
| 21.2 | Effective frequency range | 24 |
| 21.3 | Transfer function | 25 |
| 22 | Output power (acoustic power) | 26 |
| 22.1 | Acoustic power in a frequency band | 26 |
| 22.2 | Mean acoustic power in a frequency band | 27 |
| 22.3 | Efficiency in a frequency band | 27 |
| 22.4 | Mean efficiency in a frequency band | 27 |
| 23 | Directional characteristics | 28 |
| 23.1 | Directional response pattern | 28 |
| 23.2 | Radiation angle | 28 |
| 23.3 | Directivity index | 29 |
| 23.4 | Coverage angle or angles | 30 |
| 24 | Amplitude non-linearity | 30 |
| 24.1 | Total harmonic distortion | 30 |
| 24.2 | Harmonic distortion of the n^{th} order (where $n = 2$ or $n = 3$) | 32 |
| 24.3 | Characteristic harmonic distortion | 33 |
| 24.4 | Modulation distortion of the n^{th} order (where $n = 2$ or $n = 3$) | 33 |

| | | |
|---|--|-----------|
| 24.5 | Characteristic modulation distortion of the n^{th} order (where $n = 2$ or $n = 3$)..... | 34 |
| 24.6 | Difference frequency distortion (of the second order only)..... | 34 |
| 25 | Rated ambient conditions | 35 |
| 25.1 | Temperature ranges..... | 35 |
| 25.2 | Humidity ranges..... | 35 |
| 26 | Stray magnetic fields | 36 |
| 26.1 | Static components | 36 |
| 26.2 | Dynamic components..... | 36 |
| 27 | Physical characteristics | 37 |
| 27.1 | Dimensions | 37 |
| 27.2 | Mass..... | 37 |
| 27.3 | Cable assemblies..... | 37 |
| 28 | Design data | 38 |
| 29 | Indication of the characteristics to be specified..... | 38 |
| | | |
| Annex A (informative) | Standard measuring enclosure type A | 44 |
| Annex B (informative) | Standard measuring enclosure type B | 46 |
| Annex C (informative) | Definitions of terms used in Clause 13 | 49 |
| Annex D (informative) | Listening tests..... | 51 |
| | | |
| Bibliography..... | | 52 |
| | | |
| Figure 1 – Impedance curve of loudspeaker..... | | 17 |
| Figure 2 – Standard baffle, dimensions..... | | 40 |
| Figure 3 – Standard baffle with chamfer..... | | 40 |
| Figure 4 – Standard baffle with sub-baffle..... | | 41 |
| Figure 5 – Standard measuring enclosure type A..... | | 41 |
| Figure 6 – Standard measuring enclosure type B..... | | 42 |
| Figure 7 – Block diagram of test set-up..... | | 42 |
| Figure 8 – Measuring apparatus for stray magnetic field | | 43 |
| Figure A.1 – An example of standard measuring enclosure type A | | 44 |
| Figure A.2 – The correction curve for the diffraction effect of the standard measuring enclosure from free-field to half-space free-field | | 45 |
| Figure A.3 – The correction curve for the diffraction effect of a standard measuring enclosure from free-field to half-space free-field | | 45 |
| Figure B.1 – An example of standard measuring enclosure type B | | 46 |
| Figure B.2 – Construction of scalable measuring enclosure type B | | 47 |
| Figure B.3 – The correction curve for the diffraction effect of the standard measuring enclosure from free-field to half-space free-field | | 48 |
| Figure B.4 – The correction curve for the diffraction effect of the standard measuring enclosure from free-field to half-space free-field | | 48 |
| | | |
| Table 1 – Indication of the characteristics to be specified | | 39 |
| Table B.1 – Dimensions and ratios of scalable measuring enclosure type B..... | | 47 |

INTERNATIONAL ELECTROTECHNICAL COMMISSION

SOUND SYSTEM EQUIPMENT –**Part 5: Loudspeakers****FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of the official IEC Standard and its amendment has been prepared for user convenience.

IEC 60268-5 edition 3.1 contains the third edition (2003) [documents 100/648/FDIS and 100/674/RVD] and its amendment 1 (2007) [documents 100/1189/CDV and 100/1245/RVC].

In this Redline version, a vertical line in the margin shows where the technical content is modified by amendment 1. Additions and deletions are displayed in red, with deletions being struck through. A separate Final version with all changes accepted is available in this publication.

International Standard IEC 60268-5 has been prepared by IEC technical committee 100: Audio, video and multimedia systems and equipment.

The bilingual version (2013-08) of this standard corresponds to the monolingual English version, published in 2007-09.

This standard is to be read in conjunction with IEC 60268-1, IEC 60268-2 and ISO 3741.

The French versions of this standard and its amendment 1 have not been voted upon.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of the base publication and its amendments will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

[IEC 60268-5:2003](#)

<https://standards.iteh.ai/catalog/standards/iec/f4c9ff13-415b-46ce-bfd2-16f390c03fc4/iec-60268-5-2003>

SOUND SYSTEM EQUIPMENT –

Part 5: Loudspeakers

1 Scope

This standard applies to sound system loudspeakers, treated entirely as passive elements. Loudspeakers with built-in amplifiers are excluded.

NOTE 1 The term “loudspeaker” used in this standard relates to loudspeaker drive units themselves and also to loudspeaker systems, which comprise one or more loudspeaker drive units provided with a baffle, enclosure or horn and such relevant devices as built-in crossover filters, transformers and any other passive element.

The purpose of this standard is to give the characteristics to be specified and the relevant methods of measurement for loudspeakers using sinusoidal or specified noise or impulsive signals.

NOTE 2 The methods of measurement given in this standard have been chosen for their appropriateness to the characteristics.

NOTE 3 If equivalent results can be obtained using other methods of measurement, details of the methods used should be presented with the results.

NOTE 4 The following items are under consideration:

- loudspeakers with built-in amplifiers;
- measurements under conditions other than free-field, half-space free-field and diffuse field;
- measurements with signals other than sinusoidal or noise or impulsive signals.

2 Normative references

[IEC 60268-5:2003](https://standards.iteh.ai/catalog/standards/iec/f4c9ff13-415b-46ce-bfd2-16f390c03fc4/iec-60268-5-2003)

<https://standards.iteh.ai/catalog/standards/iec/f4c9ff13-415b-46ce-bfd2-16f390c03fc4/iec-60268-5-2003>

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050(151), *International Electrotechnical Vocabulary (IEV) – Part 151: Electrical and magnetic devices*

IEC 60263, *Scales and sizes for plotting frequency characteristics and polar diagrams*

IEC 60268-1, *Sound system equipment – Part 1: General*

IEC 60268-2, *Sound system equipment – Part 2: Explanation of general terms and calculation methods*

IEC 60268-3, *Sound system equipment – Part 3: Amplifiers*

IEC 60268-11, *Sound system equipment – Part 11: Application of connectors for the interconnection of sound system components*

IEC 60268-12, *Sound system equipment – Part 12: Application of connectors for broadcast and similar use*

IEC 60268-14, *Part 14: Circular and elliptical loudspeakers; outer frame diameters and mounting dimensions*

IEC 60651, *Sound level meters*

IEC 61260, *Electroacoustics – Octave-band and fractional-octave-band filters*

ISO 3741, *Acoustics – Determination of sound power levels of noise sources using sound pressure – Precision methods for reverberation rooms*

ISO 3744, *Acoustics – Determination of sound power levels of noise sources using sound pressure – Engineering method in an essentially free field over a reflecting plane*

ISO 3745, *Acoustics – Determination of sound power levels of noise sources – Precision methods for anechoic and semi-anechoic rooms*

3 Conditions for measurement

3.1 General conditions

This standard is to be used in conjunction with IEC 60268-1, IEC 60268-2 and ISO 3741.

3.2 Measuring conditions

3.2.1 General

For convenience in specifying how loudspeakers are to be set up for measurement, normal measuring conditions are defined in this standard. To obtain the correct conditions for measurement, some values (known as “rated conditions”) shall be taken from the manufacturer's specification. These values themselves are not subject to measurement but they constitute the basis for measuring the other characteristics.

The following values and conditions are of this type, and shall be stated by the manufacturer:

- rated impedance;
- rated sinusoidal voltage or power;
- rated noise voltage or power;
- rated frequency range;
- reference plane;
- reference point;
- reference axis.

NOTE A full explanation of the term “rated” is given in IEC 60268-2. See also term 151-04-03 in IEC 60050(151).

3.2.2 Normal measuring conditions

A loudspeaker shall be understood to be working under normal measuring conditions when all the following conditions are fulfilled:

- a) the loudspeaker to be measured is mounted in accordance with Clause 10;
- b) the acoustical environment is specified and is selected from those specified in Clause 5;
- c) the loudspeaker is positioned with respect to the measuring microphone and the walls in accordance with Clause 7;
- d) the loudspeaker is supplied with a specified test signal, in accordance with Clause 4, of a stated voltage U , within the rated frequency range in accordance with 19.1. If required, the input power P can be calculated from the equation: $P = U^2/R$, where R is the rated impedance in accordance with 16.1;
- e) attenuators, if any, are set to their “normal” position as stated by the manufacturer. If other positions are chosen, for example those providing a maximally flat frequency response or maximum attenuation, these shall be specified;

- f) measuring equipment suitable for determining the wanted characteristics is connected in accordance with Clause 8.

4 Test signals

4.1 General

Acoustical measurements shall be made under one of the following measuring signal conditions, and the choice shall be indicated with the results.

4.2 Sinusoidal signal

The sinusoidal test signal shall not exceed the rated sinusoidal voltage (as defined in 17.4) at any frequency. The voltage across the input terminals of the loudspeaker under test shall be kept constant for all frequencies unless otherwise stated.

4.3 Broadband noise signal

NOTE This term is explained in IEC 60268-2.

The crest factor of a noise source should fall between 3 and 4 to avoid clipping of amplifiers.

A true r.m.s. voltmeter with a time constant at least as long as the “slow” constant of the sound level meter, specified in IEC 60651, shall be used to measure the amplitude of the signal.

4.4 Narrow-band noise signal

NOTE This term is explained in IEC 60268-2.

For measurement using narrow-band noise, constant relative bandwidth filters in accordance with IEC 61260 shall be used with a pink-noise generator, the relative bandwidth being usually 1/3 octave.

4.5 Impulsive signal

A short-duration pulse shall have constant spectral power per unit bandwidth over at least the bandwidth of interest in the measurement. Such a signal has low energy content relative to its peak amplitude.

NOTE To minimize the influence of acoustical and electrical noise on the measurement, the peak amplitude of the pulse should be as high as possible within the capability of the driving amplifier and consistent with linear operation of the loudspeaker.

5 Acoustical environment

5.1 General

Acoustical measurements shall be made under one of the acoustical field conditions specified in 5.2 to 5.6, and the choice shall be indicated with the results.

5.2 Free-field conditions

If acoustical conditions approach those of free-field space, an environment (for example an anechoic room) in which the sound pressure decreases with the distance (r) from a point source according to a $1/r$ law, with an accuracy of $\pm 10\%$, in the region that will be occupied by the sound field between the loudspeaker system and the microphone during the measurements shall be used. The minimum conditions shall be deemed to exist if this requirement is met along the axis joining the measuring microphone and the reference point on the loudspeaker.

Free-field conditions shall exist over the whole frequency range of measurement.

5.3 Half-space free-field conditions

If acoustical conditions are used in which the free-field exists in a half space, these conditions shall be met with a reflecting plane of sufficient size so that the sound pressure from a point source mounted in the surface of that plane decreases in the manner specified in 5.2.

5.4 Diffuse sound field conditions

NOTE 1 These conditions are normally used for band noise measurements only.

If diffuse sound field conditions are used for measurements with 1/3 octave band limited noise, as defined and specified in ISO 3741, the lower limiting frequency shall be determined as specified in ISO 3741, Appendix A.

NOTE 2 While ISO 3741 provides details of measuring instruments, it should be clearly understood that both space averaging and time averaging are required in loudspeaker power determination. This may be achieved as stated in the standard or alternatively by using continuous space and time averaging techniques.

NOTE 3 The precision of the measurement depends on a number of factors including the room volume, the room reverberation time, and the degree of diffusion.

NOTE 4 For measurement below 125 Hz, a room volume greater than 200 m³ is desirable.

5.5 Simulated free-field conditions

If acoustical conditions are used in which the simulated free-field conditions that are equivalent to those of free space for the period of time required for a measurement, these conditions shall be used.

The conditions shall be met in any environment (for example large, unobstructed rooms) in which sound emitted by a loudspeaker in response to an impulsive signal reflected from any surface or object in the environment does not reach the measuring microphone before measurement of the direct path sound at the microphone has been completed.

Any such reflection reaching the microphone shall be excluded from the measurement by gating or other means.

NOTE 1 These conditions are normally used only for measurements with impulsive signals.

NOTE 2 Under such conditions, successive measurements are separated by time intervals sufficient for the sound pressure level due to reverberation within the space to decrease to a negligible value.

5.6 Half-space simulated free-field conditions

If acoustical conditions are used in which the simulated free-field exists in a half-space, these conditions shall be used when a reflecting plane, forming one boundary of a simulated free-field environment, is of sufficient size that no reflections from its edge reach the measuring microphone within the measurement time.

NOTE 1 These conditions are normally used only for measurements with impulsive signals.

NOTE 2 Under such conditions, successive measurements are separated by time intervals sufficient for the sound pressure level due to reverberation within the space to decrease to a negligible value.

6 Unwanted acoustical and electrical noise

Unwanted acoustical and electrical noise shall be kept at the lowest possible level as its presence may obscure low-level signals.