

SLOVENSKI STANDARD PSIST ETS 300 436-1:1996

01-november-1996

Širokopasovno digitalno omrežje z integriranimi storitvami (B-ISDN) -Signalizacijska ATM-prilagodilna plast (SAAL) - Storitveno specifičen povezavni protokol (SSCOP) - 1. del: Specifikacija protokola [Priporočilo ITU-T Q.2110 (1995),spremenjeno]

Broadband Integrated Services Digital Network (B-ISDN); Signalling ATM Adaptation Layer (SAAL); Service Specific Connection Oriented Protocol (SSCOP); Part 1: Protocol specification [ITU-T Recommendation Q.2110 (1995), modified]

Ta slovenski standard je istoveten z: ETS 300 436-1 E1.% -) !%

ICS:

33.080 Digitalno omrežje z integriranimi storitvami (ISDN)

Integrated Services Digital Network (ISDN)

PSIST ETS 300 436-1:1996

en

PSIST ETS 300 436-1:1996

PSIST ETS 300 436-1:1996



EUROPEAN TELECOMMUNICATION STANDARD

ETS 300 436-1

November 1995

Source: ETSI TC-SPS

Reference: DE/SPS-02023-1

ICS: 33.080

*

Key words: B-ISDN, ATM, AAL, SSCF, SSCOP, NNI, UNI

Broadband Integrated Services Digital Network (B-ISDN); Signalling ATM Adaptation Layer (SAAL); Service Specific Connection Oriented Protocol (SSCOP); Part 1: Protocol specification

[ITU-T Recommendation Q.2110 (1995), modified]

ETSI

European Telecommunications Standards Institute

ETSI Secretariat

Postal address: F-06921 Sophia Antipolis CEDEX - FRANCE **Office address:** 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE **X.400:** c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 92 94 42 00 - Fax: +33 93 65 47 16

Copyright Notification: No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1995. All rights reserved.

Page 2 ETS 300 436-1: November 1995

Foreword

This European Telecommunication Standard (ETS) has been produced by the Signalling Protocols and Switching (SPS) Technical Committee of the European Telecommunications Standards Institute (ETSI).

This ETS is part 1 of a multi-part standard covering the Service Specific Connection Oriented Protocol (SSCOP) for the Broadband Integrated Services Digital Network (B-ISDN) as described below:

Part 1: "Protocol specification [ITU-T Recommendation Q.2110, modified]";

Part 2: "Protocol Implementation Conformance Statement (PICS) proforma specification".

NOTE: Further parts covering conformance testing will be identified later.

Transposition dates				
Date of adoption of this ETS:	17 November 1995			
Date of latest announcement of this ETS (doa):	28 February 1996			
Date of latest publication of new National Standard or endorsement of this ETS (dop/e):	31 August 1996			
Date of withdrawal of any conflicting National Standard (dow):	31 August 1996			

Endorsement notice

The text of ITU-T Recommendation Q.2110 (1995) was approved by ETSI as an ETS with agreed modifications as given below.

NOTE: New or modified text is indicated using sidebars. In addition, underlining and/or strikeout are used to highlight detailed modifications where necessary.

Whilst every care has been taken in the preparation and publication of this document, errors in content, typographical or otherwise, may occur. If you have comments concerning its accuracy, please write to "ETSI Editing and Committee Support Dept." at the address shown on the title page.

Page 1, clause 1

Replace clause 1 by:

1 Scope

This European Telecommunication Standard (ETS) specifies the Service Specific Connection Oriented Protocol (SSCOP) for the pan-European Broadband Integrated Services Digital Network (B-ISDN) as provided by European public telecommunications operators.

This ETS specifies the peer-to-peer protocol for the transfer of information between any pair of SSCOP entities, the interactions between the SSCOP and the ATM Adaptation Layer (AAL) common part, and the interactions between the SSCOP and the AAL management plane.

Further parts of this ETS specify the method of testing required to identify conformance to this ETS.

This ETS is applicable as defined in the appropriate Service Specific Co-ordination Function (SSCF).

Page 1, clause 2, first paragraph

Replace the first paragraph of clause 2 by:

This ETS incorporates by dated and undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this ETS only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies.

Page 1, clause 2

Insert the following references at the end of clause 2:

[11]	ETS 300 437-1: "Broadband Integrated Services Digital Network (B-ISDN); Signalling ATM Adaptation Layer (SAAL); Service Specific Co-ordination Function (SSCF) for support of signalling at the User-Network Interface (UNI); Part 1: Specification of SSCF at UNI [ITU-T Recommendation Q.2130 (1995), modified]".
[12]	ETS 300 438-1: "Broadband Integrated Services Digital Network (B-ISDN); Signalling ATM Adaptation Layer (SAAL); Service Specific Co-ordination Function (SSCF) for support of signalling at the Network-Node Interface (NNI); Part 1: Specification of SSCF at NNI [ITU-T Recommendation Q.2140 (1995), modified]".
[13]	ETS 300 443-1: "Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; B-ISDN user- network interface layer 3 specification for basic call/bearer control; Part 1: Protocol specification [ITU-T Recommendation Q.2931 (1995), modified]".

Throughout the text of ITU-T Recommendation Q.2110

Replace references as shown in the following table.

Reference in ITU-T Recommendation Q.2110	Modified reference
ITU-T Recommendation Q.2130 [9]	ITU-T Recommendation Q.2130 as modified by ETS 300 437-1 [11]
ITU-T Recommendation Q.2140 [10]	ITU-T Recommendation Q.2140 as modified by ETS 300 438-1 [12]
ITU-T Recommendation Q.2931 [5]	ITU-T Recommendation Q.2931 as modified by ETS 300 443-1 [13]

Page 4 ETS 300 436-1: November 1995

Page 21, subclause 7.8.1

Insert after the third paragraph:

In order to prevent potential deadlock situations, the size of the operating window of the protocols at the transmitter should be upper bounded by the value

10 × Timer_POLL × μ ,

where $\boldsymbol{\mu}$ is the maximum allowed mean signalling cellrate.

Page 78, annex A

Annex A has the status of a normative annex.

Pages 79 to 82, annex B

Delete annex B. It is substituted by ETS 300 436-2.

Pages 83 to 85, appendix I

Appendix I has the status of an informative annex.

Pages 85 to 92, appendix II

Appendix II has the status of an informative annex.

Pages 93 to 94, appendix III

Appendix III has the status of an informative annex.

Page 95, appendix IV

Appendix IV has the status of an informative annex.

History

Document history					
August 1994	Public Enquiry	PE 68:	1994-08-08 to 1994-12-02		
September 1995	Vote	V 87:	1995-09-11 to 1995-11-03		
November 1995	First Edition				