

INTERNATIONAL
STANDARD

ISO/IEC
12248

First edition
1993-12-15

**Information technology — 3,81 mm wide
magnetic tape cartridge for information
interchange — Helical scan recording —
DATA/DAT-DC format using 60 m and
90 m length tapes**

ISO/IEC 12248:1993

<https://standards.iteh.ai/catalog/standards/si/149db707-7be9-4f22-a99e-63c1ba16bc04/iso-iec-12248-1993>
**Technologies de l'information — Cartouche de bande magnétique de
3,81 mm de large pour l'échange d'information — Enregistrement par
balayage en spirale — Format DATA/DAT-DC utilisant des bandes
de 60 m et 90 m de long**



Reference number
ISO/IEC 12248:1993(E)

Contents		Page
1	Scope	1
2	Conformance	1
2.1	Magnetic tape cartridge	1
2.2	Generating system	1
2.3	Receiving system	1
3	Normative references	1
4	Definitions	2
4.1	Absolute Frame Number (AFN)	2
4.2	algorithm	2
4.3	Area ID	2
4.4	Automatic Track Finding (ATF)	2
4.5	Average Signal Amplitude	2
4.6	azimuth	2
4.7	back surface	2
4.8	byte	2
4.9	cartridge	2
4.10	Channel Bit	2
4.11	Codeword	2
4.12	Data Format ID	2
4.13	End of Data (EOD)	2
4.14	End of Information (EOI)	2
4.15	End of Partition (EOP)	2
4.16	entity	2
4.17	Error Correcting Code (ECC)	2
4.18	flux transition position	2
4.19	flux transition spacing	2
4.20	frame	2
4.21	group	2
4.22	Logical Beginning of Tape (LBOT)	2

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 12248:1993](https://standards.iteh.ai/catalog/standards/sist/449db707-7be9-4f32-ae9e-66e41bc16bc0/iso-iec-12248-1993)

<https://standards.iteh.ai/catalog/standards/sist/449db707-7be9-4f32-ae9e-66e41bc16bc0/iso-iec-12248-1993>

© ISO/IEC 1993

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

4.23	Logical End of Tape (LEOT)	2
4.24	magnetic tape	3
4.25	master reference	3
4.26	Master Standard Amplitude Calibration Tape	3
4.27	Master Standard Reference Tape	3
4.28	Optimum Recording Field	3
4.29	partition	3
4.30	partition reference	3
4.31	Physical Beginning of Tape (PBOT)	3
4.32	Physical End of Tape (PEOT)	3
4.33	physical recording density	3
4.34	pre-recording condition	3
4.35	processed record	3
4.36	processed record sequence	3
4.37	processing	3
4.38	record	3
4.39	Reference Recording Field	3
4.40	Secondary Standard Amplitude Calibration Tape	3
4.41	Secondary Standard Reference Tape	3
4.42	Separator Mark	3
4.43	Standard Reference Amplitude	4
4.44	tape noise amplitude	4
4.45	Tape Reference Edge	4
4.46	track	4
5	Environment and safety	4
5.1	Testing environment	4
5.2	Operating environment	4
5.3	Storage environment	4
5.4	Transportation	4
5.5	Safety	5
5.6	Flammability	5
Section 2 - Requirements for the case		5
6	Dimensional and mechanical characteristics of the case	5
6.1	General	5
6.2	Overall dimensions	5
6.3	Loading grip	6
6.4	Holding areas	6
6.5	Notches of the lid	6
6.6	Lid dimensions	6
6.7	Optical detection of the beginning and end of tape	7
6.8	Bottom side	8
6.8.1	Locking mechanism of the slider	8
6.8.2	Access holes	9
6.8.3	Recognition, sub-datum and write-inhibit holes	9
6.8.4	Datum holes	10
6.8.5	Access room for tape guides	11
6.8.6	Holes for accessing the hubs	11

6.8.7	Internal structure of the lower half	11
6.8.8	Light path	12
6.8.9	Support areas	13
6.8.10	Datum areas	13
6.8.11	Relationship between support and datum areas and Reference Plane Z	13
6.9	Hubs	13
6.10	Leader and trailer attachment	14
6.11	Interface between the hubs and the drive spindles	14
6.12	Opening of the lid	14
6.13	Release of the hub locking mechanism	14
6.14	Label areas	15
Section 3	- Requirements for the unrecorded tape	26
7	Mechanical, physical and dimensional characteristics of the tape	26
7.1	Materials	26
7.2	Tape length	26
7.2.1	Length of magnetic tape	26
7.2.2	Length of leader and trailer tapes	26
7.3	Tape width	26
7.4	Discontinuities	26
7.5	Total thickness	26
7.6	Longitudinal curvature	26
7.7	Cupping	26
7.8	Coating adhesion	27
7.9	Layer-to-layer adhesion	27
7.10	Tensile Strength	28
7.10.1	Breaking Strength	28
7.10.2	Yield Strength	28
7.11	Residual elongation	28
7.12	Electrical resistance of coated surfaces	28
7.13	Light transmittance of tape	29
8	Magnetic recording characteristics	29
8.1	Optimum recording field	30
8.2	Signal amplitude	30
8.3	Resolution	30
8.4	Overwrite	30
8.4.1	Physical recording densities of 750,6 and 3 002 ftpmm	30
8.4.2	Physical recording densities of 83,4 ftpmm and 1 001 ftpmm	31
8.5	Ease of erasure	31
8.6	Tape quality	31
8.6.1	Missing pulses	31
8.6.2	Missing pulse zone	31
8.7	Signal-to-noise ratio (S/N) characteristic	31

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 12248:1993](https://standards.iteh.ai/catalog/standards/sist/449db707-7be9-4f32-ae9e-66e41bc16bc0/iso-iec-12248-1993)

<https://standards.iteh.ai/catalog/standards/sist/449db707-7be9-4f32-ae9e-66e41bc16bc0/iso-iec-12248-1993>

Section 4 - Format		32
9 DATA/DAT-DC format		32
9.1 General		32
9.2 Basic Groups		32
9.2.1 Basic Groups for Group Format 0		32
9.2.2 Basic Groups for Group Format 1		34
9.3 Sub-groups		35
9.3.1 G1 Sub-group		35
9.3.2 G2 Sub-group		36
9.3.3 G3 Sub-group		36
9.3.4 G4 Sub-group		37
9.3.5 Main Data Block		42
9.4 Sub-Data area		43
9.4.1 Pack Item No. 1		44
9.4.2 Pack Item No. 2		45
9.4.3 Pack Item No. 3		47
9.4.4 Pack Item No. 4		48
9.4.5 Pack Item No. 5		48
9.4.6 Pack Item No. 6		49
9.4.7 Pack Item No. 7		50
9.4.8 Sub Data Block	https://standards.iteh.ai/catalog/standards/sist/449db707-7be9-4f32-ac9e-66e41bc16bc0/iso-iec-12248-1993	50
9.5 Basic Group structure		52
9.5.1 User Data		52
9.5.2 System Data		53
9.5.3 Record ID list		57
9.5.4 Heuristic Recovery Data Area		62
10 Method of recording		62
10.1 Physical recording density		62
10.2 Long-Term average bit cell length		62
10.3 Short-Term average bit cell length		62
10.4 Rate of change		62
10.5 Bit shift		62
10.6 Read signal amplitude		62
10.7 Maximum recorded levels		62
11 Track geometry		63
11.1 Track configuration		63
11.2 Average track pitch		63
11.3 Variations of the track pitch		63
11.4 Track width		64
11.5 Track angle		64
11.6 Track edge linearity		64
11.7 Track length		64
11.8 Ideal tape centreline		64
11.9 Azimuth angles		64

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 12248:1993](https://standards.iteh.ai/catalog/standards/sist/449db707-7be9-4f32-ac9e-66e41bc16bc0/iso-iec-12248-1993)

<https://standards.iteh.ai/catalog/standards/sist/449db707-7be9-4f32-ac9e-66e41bc16bc0/iso-iec-12248-1993>

12	Recording of blocks on the tape	64
12.1	Recorded Main Data Block	64
12.2	Recorded Sub Data Block	64
12.3	Margin Blocks, Preamble Blocks and Postamble Blocks	65
12.4	Spacer Blocks	65
13	Format of a track	65
13.1	Track capacity	65
13.2	Positioning accuracy	65
13.3	Tracking scheme	65
14	Group Formats	68
14.1	Group Format 0	68
14.2	Group Format 1	68
14.3	Extended Gap Frames	69
14.3.1	Extended Leading Gap Frames	69
14.3.2	Extended Trailing Gap Frames	69
14.4	Types of Groups	69
14.4.1	Normal Groups	70
14.4.2	Spare Groups	70
14.4.3	Amble Groups	70
14.4.4	Header Groups	70
15	Magnetic tape layout	71
15.1	Load/Unload Area	71
15.2	Lead-in Area	72
15.2.1	Preamble	72
15.2.2	Header	72
15.2.3	Format Parameter Set	74
15.2.4	Master Reference	79
15.2.5	Postamble	84
15.3	Partition	85
15.3.1	Partition Preamble	85
15.3.2	Partition Reference	85
15.3.3	Partition Postamble	96
15.3.4	Partition Data	96
15.3.5	End of Partition (EOP)	96
15.3.6	Unused Area	97
15.4	EOI	97
15.5	Repeated Groups	97
15.6	Repeated Frames within a Normal Group	97
15.7	Relocation of Defective Groups	98
15.8	Appending	98
15.8.1	Seamless appending	98
15.8.2	Non-seamless appending	100
15.9	Overwrite	101

iTeh STANDARD PREVIEW
(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/449db707-7be9-4f32-ac9e-66e41bc16bc0/iso-iec-12248-1993>

15.9.1	Overlapped track width	102
15.9.2	Non-overlapped track width	102
15.9.3	Rules for overwrite	102
Annexes		
A	- Measurement of the light transmittance of the prisms	103
B	- Recognition holes	105
C	- Means for opening the lid	106
D	- Measurement of light transmittance of tape and leaders	107
E	- Measurement of Signal-to-Noise Ratio	110
F	- Method for determining the nominal and the maximum allowable recorded levels	111
G	- Representation of 8-bit bytes by 10-bit pattern	112
H	- Measurement of bit shift	118
J	- Recommendations for transportation	121
K	- Method of measuring track edge linearity	122
L	- Read-After-Write	123
M	- Data allocation and C3 parity	124

[ISO/IEC 12248:1993](https://standards.iteh.ai/catalog/standards/sist/449db707-7be9-4f32-ae9e-66e41bc16bc0/iso-iec-12248-1993)
<https://standards.iteh.ai/catalog/standards/sist/449db707-7be9-4f32-ae9e-66e41bc16bc0/iso-iec-12248-1993>

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

International Standard ISO/IEC 12248 was prepared by the European Computer Manufacturers Association (ECMA) (as Standard ECMA-171) and was adopted, under a special “fast-track procedure”, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

Annexes A, D, E, F, G, H, K and M form an integral part of this International Standard. Annexes B, C, J and L are for information only.

Introduction

ISO/IEC have produced a series of International Standards for cassettes and cartridges containing magnetic tapes of different width and characteristics. Of these, the following relate to helical scan recording.

ISO/IEC 10777:1991, *3,81 mm wide magnetic tape cartridge for information interchange - Helical scan recording - DDS format*

ISO/IEC 11319:1993, *8 mm wide magnetic tape cartridge for information interchange - Helical scan recording*

ISO/IEC 11321:1992, *3,81 mm wide magnetic tape cartridge for information interchange - Helical scan Recording - DATA/DAT format*

ISO/IEC 11557:1992, *3,81 mm wide magnetic tape cartridge for information interchange - Helical scan recording - DDS-DC format using 60 m and 90 m length tapes, 2nd edition*

ISO/IEC 12246:1993, *8 mm wide magnetic tape cartridge, dual azimuth format for information interchange - Helical scan recording*

ISO/IEC 12247:1993, *3,81 mm wide magnetic tape cartridge for information interchange - Helical scan recording - DDS format using 60 m and 90 m length tapes*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

This page intentionally left blank

[ISO/IEC 12248:1993](#)

<https://standards.iteh.ai/catalog/standards/sist/449db707-7be9-4f32-ac9e-66e41bc16bc0/iso-iec-12248-1993>

Information technology - 3,81 mm wide magnetic tape cartridge for information interchange - Helical scan recording - DATA/DAT-DC format using 60 m and 90 m length tapes

Section 1 - General

1 Scope

This International Standard specifies the physical and magnetic characteristics of a 3,81 mm wide magnetic tape cartridge to enable interchangeability of such cartridges. It also specifies the quality of the recorded signals, the recorded format and the recording method, thereby allowing data interchange between drives by means of such magnetic tape cartridges. The format used is known as DATA/DAT-DC.

This International Standard specifies two types of cartridges which, for the purpose of this International Standard, are referred to as Type A and Type B.

For Type A, the magnetic tape has a nominal thickness of 13 μm and a nominal length of up to 60,5 m.

For Type B, the magnetic tape has a nominal thickness of 9 μm a length of up to 92,0 m.

Information interchange between systems by means of this International Standard also requires the use, at a minimum, of a labelling and file structure and an interchange code which are agreed upon by the interchange parties. It is not within the scope of this International Standard to specify the labelling and file structure, or the interchange code.

(standards.iteh.ai)

2 Conformance

ISO/IEC 12248:1993

2.1 Magnetic tape cartridge

<https://standards.iteh.ai/catalog/standards/sist/449db707-7be9-4f32-ae9e-66e41bc16bc0/iso-iec-12248-1993>

A tape cartridge shall be in conformance with this International Standard if it meets all mandatory requirements specified herein for either Type A or Type B. The tape requirements shall be satisfied throughout the extent of the tape.

2.2 Generating system

A system generating a magnetic tape cartridge for interchange shall be entitled to claim conformance to this International Standard if all recordings on the tape meet the mandatory requirements of this International Standard. A claim of conformance shall state whether cartridges of Type A or Type B or both are supported.

2.3 Receiving system

A system receiving a magnetic tape cartridge for interchange shall be entitled to claim conformance with this International Standard if it is able to handle any recording made on the tape according to this International Standard. A claim of conformance shall state whether cartridges of Type A or Type B or both are supported.

3 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards listed below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO/R 527:1966, *Plastics - Determination of tensile properties*.

ISO/IEC 646:1991, *Information technology - ISO 7-bit coded character set for information interchange*.

ISO 1302:1992, *Technical drawings - Method of indicating surface texture*.

ISO/IEC 11576:1993, *Information technology - Procedure for the registration of algorithms for the lossless compression of data.*

IEC 950:1991, *Safety of information technology equipment, including electrical business equipment*

4 Definitions

For the purposes of this International Standard, the following definitions apply.

- 4.1 Absolute Frame Number (AFN):** A sequence number allocated to, and recorded in, each frame.
- 4.2 algorithm:** A set of rules for transforming the logical representation of data.
- 4.3 Area ID:** An identifier for each area of the tape specifying the types of frame written therein.
- 4.4 Automatic Track Finding (ATF):** A method by which tracking is achieved.
- 4.5 Average Signal Amplitude:** The average peak-to-peak value of the output signal from the read head at the fundamental frequency of the specified physical recording density, over a minimum of 7,8 mm of track, exclusive of missing pulses.
- 4.6 azimuth:** The angular deviation, in degrees, minutes and seconds of arc, made by the mean flux transition line with the line normal to the centreline of the recorded track.
- 4.7 back surface:** The surface of the tape opposite to the magnetic coating which is used to record data.
- 4.8 byte:** An ordered set of bits acted upon as a unit.
- 4.9 cartridge:** A case containing magnetic tape stored on twin hubs.
- 4.10 Channel Bit:** A bit after 8-to-10 transformation.
- 4.11 Codeword:** A word which is generated by a processing algorithm. The number of bits in a Codeword is variable, and is not specified in this International Standard.
- 4.12 Data Format ID:** An identifier specifying which data format is being used on the tape.
- 4.13 End of Data (EOD):** The point where the host stopped writing data on the tape.
- 4.14 End of Information (EOI):** A group which indicates the end of partition area in a tape.
- 4.15 End of Partition (EOP):** A group which indicates the end of data area in a partition.
- 4.16 entity:** A unit of recorded data, comprising a processed record sequence resulting from the application of a common processing algorithm.
- 4.17 Error Correcting Code (ECC):** A mathematical algorithm yielding check bytes used for the detection and correction of errors.
- 4.18 flux transition position:** That point which exhibits maximum free-space flux density normal to the tape surface.
- 4.19 flux transition spacing:** The distance along a track between successive flux transitions.
- 4.20 frame:** A pair of adjacent tracks with azimuth of opposite polarity, in which the track with the positive azimuth precedes that with the negative azimuth.
- 4.21 group:** A number of frames constituting a recorded unit.
- 4.22 Logical Beginning of Tape (LBOT):** The point along the length of the tape where the recording of data for interchange commences.
- 4.23 Logical End of Tape (LEOT):** A point along the length of the tape which indicates the approach, in the direction of tape motion, of the partition boundary or physical end of tape.

4.24 magnetic tape: A tape which will accept and retain magnetic signals intended for input, output, and storage purposes on computers and associated equipment.

4.25 master reference: The area which contains partition information in the tape.

4.26 Master Standard Amplitude Calibration Tape: A pre-recorded tape on which the standard signal amplitudes have been recorded in the tracks of positive azimuth, 23,0 µm wide, at nominal track pitch, on an AC-erased tape.

NOTE 1 - The tape includes recordings made at 83,4 ftpmm, 333,6 ftpmm, 500,4 ftpmm, 1001 ftpmm and 1501 ftpmm.

NOTE 2 - The Master Standard Amplitude Calibration Tape has been established by the Sony Corporation.

4.27 Master Standard Reference Tape: A tape selected as the standard for Reference Recording Field, Signal Amplitude, Resolution Overwrite and Signal-to-Noise Ratio.

NOTE 3 - The Master Standard Reference Tape has been established by the Sony Corporation.

4.28 Optimum Recording Field: In the plot of Average Signal Amplitude against the recording field at the physical recording density of 3002 ftpmm, the field that causes the maximum Average Signal Amplitude.

4.29 partition: Partition of a tape in which user data is recorded.

4.30 partition reference: The area which contains group information in the partition.

4.31 Physical Beginning of Tape (PBOT): The point where the leader tape is joined to the magnetic tape.

4.32 Physical End of Tape (PEOT): The point where the trailer tape is joined to the magnetic tape.

4.33 physical recording density: The number of flux transitions per unit length of track, expressed in flux transitions per millimetre (ftpmm).

4.34 pre-recording condition (maximum recorded levels): The recording levels above which a tape intended for interchange shall not previously have been recorded.

4.35 processed record: A sequence of Codewords which result from the application of processing to data.

4.36 processed record sequence: A sequence of one or more processed records which start on an 8-bit boundary and end on a subsequent 8-bit boundary.

4.37 processing: The use of an algorithm to transform host data into Codewords.

4.38 record: Related data treated as a unit of information.

4.39 Reference Recording Field: The optimum recording field of the Master Standard Reference Tape.

4.40 Secondary Standard Amplitude Calibration Tape: A tape pre-recorded as defined for the Master Standard Amplitude Calibration Tape; the outputs of which are known and stated in relation to that of the Master Standard Amplitude Calibration Tape.

NOTE 4 - The Secondary Standard Amplitude Calibration Tape can be ordered from the Sony Corporation, Audio Device Business Department, Component Marketing Group 4-10-18, Takanawa, Minato-ku, Tokyo 108, Japan, under Part Number TY-7000 G until the year 2000. It is intended that these be used for calibrating tertiary tapes for use in routine calibration.

4.41 Secondary Standard Reference Tape: A tape the performance of which is known and stated in relation to that of the Master Standard Reference Tape.

NOTE 5 - A Secondary Standard Reference Tape can be ordered from the Sony Corporation, Audio Device Business Department, Component Marketing Group 4-10-18, Takanawa, Minato-ku, Tokyo 108, Japan, under Part Number RSD 1079 until the year 2000. It is intended that these be used for calibrating tertiary tapes for use in routine calibration.

4.42 Separator Mark: A record containing no user data, which is used to separate data.

4.43 Standard Reference Amplitude: The Average Signal Amplitude from the tracks of positive azimuth of the Master Standard Amplitude Calibration Tape at a specified physical recording density.

4.44 tape noise amplitude: The tape noise amplitude is the subtractive value of amplifier noise from total noise in rms.

4.45 Tape Reference Edge: The bottom edge of the tape when viewing the recording side of the tape with the PEOT of the tape to the observer's right.

4.46 track: A diagonally positioned area on the tape along which a series of magnetic signals may be recorded.

5 Environment and safety

Unless otherwise stated, the conditions specified below refer to ambient conditions in the air immediately surrounding the cartridge.

5.1 Testing environment

Unless otherwise stated, tests and measurements made on the tape cartridge to check the requirements of this International Standard shall be carried out under the following conditions:

temperature : 23 °C ± 2 °C
relative humidity : 40 % to 60 %
conditioning period before testing : 24 h

STANDARD PREVIEW
(standards.iteh.ai)

5.2 Operating environment

Cartridges used for data interchange shall be capable of operating under the following conditions:

temperature : 5 °C to 45 °C
relative humidity : 20 % to 80 %
wet bulb temperature : 26 °C max.

There shall be no deposit of moisture on or in the cartridge.

Conditioning before operating:

If a cartridge has been exposed during storage and/or transportation to a condition outside the above values, before use the cartridge shall be conditioned in the operating environment for a time at least equal to the period during which it has been out of the operating environment, up to a maximum of 24 h.

NOTE 6 - Rapid variations of temperature should be avoided.

5.3 Storage environment

For long term or archived storage of cartridges the following conditions shall be observed:

temperature : 5 °C to 32 °C
relative humidity : 20 % to 60 %
maximum wet bulb temperature : 26 °C max.

The stray magnetic field at any point on the tape shall not exceed 4 000 A/m. There shall be no deposit of moisture on or in the cartridge.

5.4 Transportation

Recommended limits for the environment to which a cartridge may be subjected during transportation, and the precautions to be taken to minimize the possibility of damage, are provided in annex J.

5.5 Safety

The cartridge and its components shall satisfy the requirements of IEC 950.

5.6 Flammability

The cartridge and its components shall be made from material which, if ignited from a match flame, do not continue to burn in a still carbon dioxide atmosphere.

Section 2 - Requirements for the case

6 Dimensional and mechanical characteristics of the case

6.1 General

The case of the cartridge shall comprise:

- an upper half- a lower half,
- a slider movably mounted on the lower half,
- a lid pivotally mounted on the upper half.

In the drawings, using third angle projection, an embodiment of the cartridge is shown as an example.

- Figure 1 is a perspective view of the cartridge seen from the top.
- Figure 2 is a perspective view of the cartridge seen from the bottom.
- Figure 3 is a partial view of the rear side.
- Figure 4 is a schematic view showing the Reference Planes X, Y, and Z.
- Figure 5 shows the front side.
- Figure 6 shows the top side with the lid in closed position.
- Figure 7 shows the left side.
- Figure 8 shows the top side with the lid in open position.
- Figure 9 shows the left side with the lid in open position.
- Figure 10 shows the bottom side with the lid and the slide in closed position.
- Figure 11 shows the bottom side with the lid and the slider in open position.
- Figure 12 is a view from the top of the inside of the lower half with the upper half removed.
- Figure 13 is a view of the bottom half with the lid and the slider in open position.
- Figure 14 is a view of the left side with the lid and the slider in open position.
- Figure 15 is a top view of a hub.
- Figure 16 is a side view of a hub with partial cross section.
- Figure 17 is a partial cross-section through a hub and both halves of the case showing the interface with the drive spindle.
- Figure 18 shows at a larger scale the lid in the open position.
- Figure 19, 20 show at a larger scale the functional relationship between the lid and the locking mechanism of the hubs.
- Figure 21, 22 show the label areas on the top and the rear side.

The dimensions are referred to three orthogonal Reference Planes X, Y, and Z (figure 4).

6.2 Overall dimensions (figures 6 and 7)

The overall dimensions of the case with the lid in the closed position shall be:

$$L_1 = 73,0 \text{ mm} \pm 0,3 \text{ mm}$$

$$L_2 = 54,0 \text{ mm} \pm 0,3 \text{ mm}$$

$$L_3 = 10,5 \text{ mm} \pm 0,2 \text{ mm}$$