

Edition 1.0 2015-02

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Electromechanical elementary relays ARD PREVIEW Part 3: Relays with forcibly guided (mechanically linked) contacts Standards.iten.al)

Relais électromécaniques élémentaires – Partie 3: Relais à contacts guidés (lies mécaniquement)_{438e-9fdb-}

df2bea6bddf7/iec-61810-3-2015





THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2015 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office	Tel.: +41 22 919 02 11
3, rue de Varembé	Fax: +41 22 919 03 00
CH-1211 Geneva 20	info@iec.ch
Switzerland	www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on TEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a 10 variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in 15 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

More than 60 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Catalogue IEC - webstore.iec.ch/catalogue

Application autonome pour consulter tous les renseignements bibliographiques sur les Normes internationales, Spécifications techniques, Rapports techniques et autres documents de l'IEC. Disponible pour PC, Mac OS, tablettes Android et iPad.

Recherche de publications IEC - www.iec.ch/searchpub

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études,...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire en ligne de termes électroniques et électriques. Il contient plus de 30 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans 15 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Glossaire IEC - std.iec.ch/glossary

Plus de 60 000 entrées terminologiques électrotechniques, en anglais et en français, extraites des articles Termes et Définitions des publications IEC parues depuis 2002. Plus certaines entrées antérieures extraites des publications des CE 37, 77, 86 et CISPR de l'IEC.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: csc@iec.ch.



Edition 1.0 2015-02

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Electromechanical elementary relays ARD PREVIEW Part 3: Relays with forcibly guided (mechanically linked) contacts

Relais électromécaniques élémentaires Partie 3: Relais à contacts guidés (liés mécaniquement) df2bea6bddf7/iec-61810-3-2015

INTERNATIONAL ELECTROTECHNICAL COMMISSION

COMMISSION ELECTROTECHNIQUE INTERNATIONALE

ICS 29.120.70

ISBN 978-2-8322-2236-2

Warning! Make sure that you obtained this publication from an authorized distributor. Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

 Registered trademark of the International Electrotechnical Commission Marque déposée de la Commission Electrotechnique Internationale

CONTENTS

FOREWORD
INTRODUCTION
1 Scope
2 Normative references
3 Terms and definitions
4 Functional requirements
4.1 Forcibly guided (mechanically linked) operation7
4.2 Changeover contacts
4.3 Mechanical endurance
4.4 Electrical endurance
4.5 Operating conditions8
4.5.1 Ambient temperature8
4.5.2 Energizing quantity8
4.6 Characteristic values and marking8
4.6.1 Characteristic values
4.6.2 Marking
5 Verification and type tests
5.1 Design verification STANDARD PREVIEW 9
5.2Type tests.95.3Test procedure
5.3 Test procedure
5.3.1 Testing for failure to open _{EC 61810-3.2015} 10
5.3.2 Mechanical and electrical endurancest 98 debed6-820d-438e-96 db
Bibliography
Figure 1 – Symbol for a forcibly guided (mechanically linked) contact set, type A
Figure 2 – Symbols for use on type B relays9

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ELECTROMECHANICAL ELEMENTARY RELAYS -

Part 3: Relays with forcibly guided (mechanically linked) contacts

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter. https://standards.iteh.ai/catalog/standards/sist/98dcbed6-820d-438e-9fdb-
- 5) IEC itself does not provide any attestation of conformity independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61810-3 has been prepared by IEC technical committee 94: All-ornothing electrical relays.

The content of this standard was already published in EN 50205:2002. The revisions in this standard only involve editorial changes and update of references.

The text of this standard is based on the following documents:

FDIS	Report on voting
94/378/FDIS	94/382/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of IEC 61810 series, published under the general title *Electromechanical elementary relays* can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>IEC 61810-3:2015</u> https://standards.iteh.ai/catalog/standards/sist/98dcbed6-820d-438e-9fdbdf2bea6bddf7/iec-61810-3-2015

INTRODUCTION

This Standard applies to elementary relays in which special design and constructional measures are used to ensure that make (normally-open) contacts cannot assume the same state as break (normally-closed) contacts. These relays can be used in self-monitoring control systems, e.g. safety-related control systems.

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>IEC 61810-3:2015</u> https://standards.iteh.ai/catalog/standards/sist/98dcbed6-820d-438e-9fdbdf2bea6bddf7/iec-61810-3-2015

ELECTROMECHANICAL ELEMENTARY RELAYS -

Part 3: Relays with forcibly guided (mechanically linked) contacts

1 Scope

This part of IEC 61810 specifies special requirements and tests for elementary relays with forcibly guided contacts, also known as mechanically linked contacts. These special requirements apply in addition to the general requirements of IEC 61810-1.

NOTE 1 This standard does not apply to electromechanical control circuit devices as described in IEC 60947-5-1.

NOTE 2 IEC 61810-2-1 provides guidelines for the assignment of reliability values.

NOTE 3 Contacts that are not mechanically linked (forcibly guided) are not considered in this standard.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

(standards.iteh.ai)

IEC 60947-5-1, Low-voltage switchgear and controlgear – Part 5-1: Control circuit devices and switching elements – Electromechanical control circuit devices

https://standards.iteh.ai/catalog/standards/sist/98dcbed6-820d-438e-9fdb-IEC 61810-1:2015, Electromechanical elementary 10 relays - Part 1: General and safety requirements

IEC 61810-7, *Electromechanical elementary relays – Part 7: Test and measurement procedures*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

elementary relay

non-specified time all-or-nothing relay

Note 1 to entry: In this document the word "elementary" is sometimes omitted for clarity.

[SOURCE: IEC 60050-444:2002, 444-01-03, modified – modification of the definition]

3.2

failure to open

fault condition when a contact does not open when expected to do so

3.3

failure criteria

specified conditions to judge if a fault or malfunction is a failure

3.4

fault

fault condition

deviation of the existing condition from the expected condition

3.5

failure

termination of the ability of an item to perform a required function as defined in the failure criteria

3.6

relay with mechanically linked contacts relay with forcibly guided contacts

elementary relay with at least one make contact and at least one break contact and including mechanical measures to prevent any make contact(s) and any break contact(s) being in the closed position simultaneously

3.7

type A

relay in which all contacts are mechanically linked

3.8

type B

relay containing contacts that are mechanically linked to each other as well as contacts that are not mechanically linked

(standards.iteh.ai)

4 Functional requirements

IEC 61810-3:2015

4.1 Forcibly guided/(mechanically/linked)/operation/bed6-820d-438e-9fdb-

df2bea6bddf7/iec-61810-3-2015

The relay shall be designed such that if a make contact is closed, none of the mechanically linked break contacts can close and that if a break contact is closed, none of the mechanically linked make contacts can close. These requirements apply throughout the lifetime of the relay and under reasonably foreseeable failure conditions.

The effects of reasonably foreseeable breakage of and/or wear to parts of the elementary relay shall not nullify the function of forcibly guided (mechanically linked) operation.

Contact gaps of open contacts shall be greater than 0,5 mm for single break contacts and 0,3 mm each for double break contacts throughout the manufacturer's specified endurance of the relay.

Operation of forcibly guided (mechanically linked) contacts means that if any make contact fails to open when the relay is de-energized, none of the break contacts shall close. If any break contact fails to open when the relay is energized, no make contact shall close.

4.2 Changeover contacts

Only break contacts and make contacts are covered by this standard; in the case of relays that include changeover contacts, either the make circuit or the break circuit of a changeover contact can be considered to meet the requirements of this standard.

Changeover contacts shall be break-before-make. It shall be assured that the forcibly guided operation is maintained, as described under the fault conditions described in 5.1.

NOTE Special care is taken in the design of the application to ensure that the integrity of the safety-related circuit is maintained in the event of a failure.

4.3 Mechanical endurance

Elementary relays containing forcibly guided (mechanically linked) contacts shall have a mechanical endurance of at least 10⁷ operating cycles.

4.4 Electrical endurance

The electrical endurance shall be as specified by the manufacturer in accordance with IEC 61810-1.

4.5 Operating conditions

4.5.1 Ambient temperature

Elementary relays with forcibly guided (mechanically linked) contacts shall function correctly over an ambient temperature range of at least -10 °C to +55 °C.

4.5.2 Energizing quantity

Unless otherwise stated by the manufacturer, elementary relays with forcibly guided (mechanically linked) contacts shall at least correspond to class '2' in the operative range of their rated coil voltage (see 5.3.1 of IEC 61810-1:2015).

4.6 Characteristic values and marking

4.6.1 Characteristic values STANDARD PREVIEW

The manufacturer shall state in his documentation the following:

- a) whether the relay is type A or type B: <u>ln the case</u> of type B relays, which contacts are mechanically linked and which contacts are not mechanically <u>dinked</u>; <u>of the contacts</u> are <u>disked</u>; <u>of the contacts</u>; <u>of </u>
- b) the vibration resistance over the frequency range at least from f = 10 Hz to 200 Hz (see IEC 61810-7);
- c) the shock resistance of the relay in accordance with IEC 61810-7;
- d) the contact load(s) according to IEC 61810-1:2015, Annex B or the utilization category(ies) in accordance with IEC 60947-5-1;

NOTE Commonly utilisation categories AC15 and DC13 are applied.

e) the limits of the operative range.

4.6.2 Marking

Relays with forcibly guided (mechanically linked) contacts shall be marked to indicate whether they are type A or type B. If a contact schematic is marked on the relay then the following marking shall be placed adjacent to the schematic.

Type A relays with forcibly guided (mechanically linked) contacts shall be marked either with the words "type A" or with the symbol given in the Figure 1 below:



Figure 1 – Symbol for a forcibly guided (mechanically linked) contact set, type A

Type B relays with forcibly guided (mechanically linked) contacts shall be marked either with the words "type B" or with the symbols given in the Figure 2 (Source ISO 7000:2014/Figure 0434) below:



Figure 2 – Symbols for use on type B relays

5 Verification and type tests

5.1 Design verification

A failure mode and effect analysis shall be performed considering all parts that are involved in the forcibly guided (mechanically linked) operation. The analysis shall consider the breakage and wear of these parts as well as failure to open.

All reasonably foreseeable single faults shall be assumed and their effects considered. If the fault of a part leads directly to a second fault then the two faults shall be considered. If the fault of a part is excluded as a failure criteria, the manufacturer shall justify the exclusion, for example by design calculations or measurements showing over-dimensioning. The failure criteria "spring broken" shall not be excluded.

(standards.iteh.ai)

It shall be considered whether, in case any electrically conductive parts break or come loose, the construction of the elementary relay prevents any short-circuits or conductive connections from occurring which would nullify the function is of forcibly oguided (mechanically linked) operation.

NOTE 1 Bridging by conductive parts can be prevented by such means as, for example, insulation or other appropriate methods applied between the conducting parts.

NOTE 2 Examples of conductive parts are contacts, contact springs and return springs.

The failure of movable functional parts as a result of, for example, breakage or wear shall be considered and the result expected shall be evaluated.

NOTE 3 An example of a movable functional part is the actuator of the contact set.

5.2 Type tests

Type tests shall be performed to verify the function of forcibly guided (mechanically linked) operation.

The tests shall be performed on new relays and also on relays that have been subjected to the electrical and mechanical endurance tests.

The test shall be conducted by simulating the welding of a contact of the elementary relay. The simulated welding shall be performed under worst case conditions using a separate sample for each make contact and each break contact. A separate sample shall be used for each simulated contact welding unless it can be demonstrated by analysis that a reduced number of samples will give an equivalent test result.

Welding of the contacts shall be simulated by such means as, for example, soldering the contacts together or using an appropriate glue. The thickness of the contact tips shall not change by more than 0,02 mm as a result of having been soldered or glued. Break contacts