

AMERICAN SOCIETY FOR TESTING AND MATERIALS 100 Barr Harbor Dr., West Conshohocken, PA 19428 Reprinted from the Annual Book of ASTM Standards. Copyright ASTM

Standard Specification for Resilient Connectors Between Reinforced Concrete Manhole Structures, Pipes, and Laterals [Metric]¹

This standard is issued under the fixed designation C 923M; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

- 1.1 This specification covers the minimum performance and material requirements for resilient connectors used for connections between precast reinforced concrete manholes conforming to Specification C 478 and pipes, and between precast reinforced concrete pipe and laterals.
- 1.1.1 These connectors are designed to minimize leakage between the pipe and manhole, and between the pipe and lateral.
- 1.2 This specification is the metric counterpart of Specification C 923.

Note 1—This specification covers the design, material, and performance of the resilient connection only. Connections covered by this specification are adequate for hydrostatic pressures up to 70 kPa (7.1 m) without leakage when tested in accordance with Section 7. Infiltration or exfiltration quantities for an installed system are dependent upon many factors other than the connections between manhole structures and pipe, and allowable quantities must be covered by other specifications and suitable testing of the installed pipeline and system.

1.3 The following precautionary caveat pertains only to the test methods portion, Section 7, of this specification: *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.* For a specific precaution statement, see 7.2.5.

2. Referenced Documents

- 2.1 ASTM Standards:
- A 167 Specification for Stainless and Heat–Resisting Chromium—Nickel Steel Plate, Sheet, and Stripe²
- C 478 Specification for Precast Reinforced Concrete Manhole Sections³
- ¹ This specification is under the jurisdiction of ASTM Committee C-13 on Concrete Pipe and is the direct responsibility of Subcommittee C13.06 on Manholes and Specials.
 - Current edition approved July 10, 1998. Published March 1999.
 - Originally published as C923M-80. Last previous edition C923M-96.
 - ² Annual Book of ASTM Standards, Vol 01.03.
 - ³ Annual Book of ASTM Standards, Vol 04.05.

- C 822 Terminology Relating to Concrete Pipe and Related Products³
- D 395 Test Methods for Rubber Property—Compression Set⁴
- D 412 Test Methods for Vulcanized Rubber and Thermoplastic Rubbers and Thermoplastic Elastomers—Tension⁴
- D 471 Test Method for Rubber Property—Effect of Liquids⁴
- D 543 Test Method for Resistance of Plastics to Chemical Reagents⁵
- D 573 Test Method for Rubber—Deterioration in an Air Oven⁴
- D 624 Test Method for Tear Strength of Conventional Vulcanized Rubber and Thermoplastic Elastomer⁴
- D 746 Test Method for Brittleness Temperature of Plastics and Elastomers by Impact⁵
- D 883 Terminology Relating to Plastics⁵
- D 1171 Test Method for Rubber Deterioration—Surface Ozone Cracking Outdoors or Chamber (Triangular Specimens)⁴
- D 1566 Terminology Relating to Rubber⁴
- D 2240 Test Method for Rubber Property—Durometer Hardness⁴

3. Terminology

- 3.1 Definitions:
- 3.1.1 Terms relating to plastics and rubber shall be as defined in Terminologies D 883 and D 1566, respectively.
- 3.1.2 Terms relating to precast concrete pipe, manholes, and related products shall be as defined in Terminology C 822 and as modified in 3.1.3-3.1.6.
- 3.1.3 *connector*—the entire assembly including resilient seals and metallic or nonmetallic mechanical devices, if any, used therein.
- 3.1.4 *lateral*—the small diameter pipe connected to the main line.
- 3.1.5 *pipe*—the inlet or outlet pipe connected to the manhole.

⁴ Annual Book of ASTM Standards, Vol 09.01.

⁵ Annual Book of ASTM Standards, Vol 08.01.