

# INTERNATIONAL STANDARD

## AMENDMENT 2

**Household and similar electrical appliances – Safety –  
Part 2-89: Particular requirements for commercial refrigerating appliances  
with an incorporated or remote refrigerant unit or compressor**

IEC 60335-2-89:2010/AMD2:2015

<https://standards.iteh.ai/catalog/standards/iec/60335-2-89-2010/AMD2:2015>



## THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2015 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland

Tel.: +41 22 919 02 11  
Fax: +41 22 919 03 00  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)

### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

### About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

#### IEC Catalogue - [webstore.iec.ch/catalogue](http://webstore.iec.ch/catalogue)

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

#### IEC publications search - [www.iec.ch/searchpub](http://www.iec.ch/searchpub)

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

#### IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

#### Electropedia - [www.electropedia.org](http://www.electropedia.org)

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in 15 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

#### IEC Glossary - [std.iec.ch/glossary](http://std.iec.ch/glossary)

More than 60 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

#### IEC Customer Service Centre - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: [csc@iec.ch](mailto:csc@iec.ch).

<https://standards.iteh.ai/catalog/standards/iec/60335-2-89-2010/AMD2:2015>

<https://standards.iteh.ai/catalog/standards/iec/60335-2-89-2010/AMD2:2015>

# INTERNATIONAL STANDARD

## AMENDMENT 2

**Household and similar electrical appliances – Safety –  
Part 2-89: Particular requirements for commercial refrigerating appliances  
with an incorporated or remote refrigerant unit or compressor**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

ICS 97.130.20

ISBN 978-2-8322-2655-1

**Warning! Make sure that you obtained this publication from an authorized distributor.**

## FOREWORD

This amendment has been prepared by sub-committee 61C: Safety of refrigeration appliances for household and commercial use, of IEC technical committee 61: Safety of household and similar electrical appliances.

The text of this amendment is based on the following documents:

FDIS	Report on voting
61C/598/FDIS	61C/604/RVD

Full information on the voting for the approval of this amendment can be found in the report on voting indicated in the above table.

The committee has decided that the contents of this amendment and the base publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

NOTE The attention of National Committees is drawn to the fact that equipment manufacturers and testing organizations may need a transitional period following publication of a new, amended or revised IEC publication in which to make products in accordance with the new requirements and to equip themselves for conducting new or revised tests.

It is the recommendation of the committee that the content of this publication be adopted for implementation nationally not earlier than 12 months or later than 36 months from the date of publication.

## 1 Scope

In Note 104 replace "ISO 5149" by "ISO 5149-1".

## 2 Normative references

Delete references IEC 60079-4A and IEC 60079-20 from the existing list.

Add the following new reference:

IEC 60079-20-1, *Explosive atmospheres – Part 20-1: Material characteristics for gas and vapour classification – Test methods and data*

Replace the reference to ISO 817 by the following new reference:

ISO 817, *Refrigerants – Designation and safety classification*

Replace the reference to ISO 5149 by the following new reference:

### 3 Terms and definitions

- 3.101** *In the term definition delete “enclosed”.*
- 3.105** *In the term definition replace “ISO 5149” by “ISO 5149-1”.*
- 3.109** *Add the following Note to entry.*

Note 1 to entry: The **design pressure** assigned should take into account pressures that could be expected during transportation of the **transcritical refrigeration system**.

- 3.111** *Add “during abnormal operation” to the end of the term definition.*

### 5 General conditions for the tests

- 5.2** *Add the following paragraph to the addition.*

*Unless the motor-compressor complies with IEC 60335-2-34, at least one additional specially prepared sample is required for the tests of 22.103.*

- 5.10** *Delete the second paragraph of the addition.*

*In the existing third paragraph of the addition replace “Other appliances” by “Appliances, other than **built-in appliances**.”*

*Add the following as a new third paragraph to the addition.*

*For appliances incorporating remote **refrigerant units** or remote motor-compressors, the refrigerant line between the **refrigerant unit** or motor-compressor and the **refrigerated display and storage cabinet** shall have a length of 5 m to 7,5 m. The refrigerant line shall be installed with thermal insulation applied in accordance with the instructions. If the appliance employs a **transcritical refrigeration system**, a **pressure relief device** shall be installed on the high pressure side between the motor-compressor and the **gas cooler** unless it is pre-fitted to the motor-compressor.*

### 7 Markings and instructions

- 7.1** *In the paragraph after Note 101, replace “the symbol “Caution: risk of fire” with “symbol ISO 7010 W021”.*

- 7.6** *In the note, replace “the symbol “Caution: risk of fire” with “symbol ISO 7010 W021”.*

- 7.12** *Add the following:*

If symbol ISO 7010 W021 is used, its meaning shall be explained.

**7.14** *In the first paragraph, replace “the symbol “Caution: risk of fire” with “symbol ISO 7010 W021”.*

**7.15** *In the third paragraph, replace “symbol “Caution: risk of fire” with “symbol ISO 7010 W021”.*

## 22 Construction

**22.103** *Add the following sentence to the end of the second paragraph of the requirement “This requirement is not applicable where the pressure is controlled automatically by shutting down the motor-compressor.”*

*In the second paragraph of the test specification replace “raised gradually” by “gradually increased hydraulically” and change the style of the first dashed item to italic type.*

**22.104** *Replace the text by the following:*

**Accessible glass panels** with an area having any two orthogonal dimensions exceeding 75 mm shall be made from

- glass that breaks into small pieces when it fractures; or
  - glass that is not released or dropped from its normal position when broken.
- a) *For glass that breaks into small pieces when it fractures, compliance is checked by the following test which is performed on two samples.*

*Frames or other parts attached to the glass panel to be tested are removed and the glass is placed on a rigid horizontal flat surface.*

NOTE 1 The edges of the sample to be tested are contained within a frame of adhesive tape in such a manner that the broken pieces remain in place after breakage but without hindering expansion of the sample.

*The sample under test is broken by means of a test punch having a head with a mass of 75 g ± 5 g and a conical tungsten carbide tip with an angle of 60° ± 2°. The punch shall be positioned approximately 13 mm in from the longest edge of the glass at the midpoint of that edge. The punch is then hit by a hammer so that the glass breaks.*

*A transparent mask of 50 mm × 50 mm is placed on the fractured glass except within a peripheral margin of 25 mm from the edge of the sample.*

*The assessment shall be undertaken on at least two areas of the sample, and the areas chosen shall contain the largest particles.*

*The number of crack free particles within the mask are counted and for each assessment shall not be less than 40. The particle count shall be made within 5 minutes of the fracture. Each particle wholly contained within the area of the mask shall be counted as one particle and each particle that is partially within the mask shall be counted as a half particle.*

NOTE 2 In the case of curved glass, plane pieces of the same material can be used for the test.

- b) *For glass that is not released or dropped from its normal position when broken, compliance is checked by braking the glass when mounted in its normal position in the appliance by means of a test punch having a head with a mass of 75 g ± 5 g and a conical tungsten carbide tip with an angle of 60° ± 2°. The punch shall be positioned approximately 13 mm in from the longest edge of the glass at the midpoint of that edge. The punch is then hit by a hammer so that the glass breaks.*

*At the conclusion of this test, the glass shall not be broken or cracked in such a way that pieces are released or dropped from their normal position. Glass that is released within the immediate vicinity of the punch tip as a result of the punch impacting the sample under test is ignored.*