

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Secondary cells and batteries containing alkaline or other non-acid electrolytes – Secondary sealed cells and batteries for portable applications – Part 1: Nickel-cadmium

Accumulateurs alcalins et autres accumulateurs à électrolyte non acide – Accumulateurs étanches pour applications portables – Partie 1: Nickel-cadmium



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2017 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms, containing 20 000 terms and definitions in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

65 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Catalogue IEC - webstore.iec.ch/catalogue

Application autonome pour consulter tous les renseignements bibliographiques sur les Normes internationales, Spécifications techniques, Rapports techniques et autres documents de l'IEC. Disponible pour PC, Mac OS, tablettes Android et iPad.

Recherche de publications IEC - www.iec.ch/searchpub

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études,...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire en ligne de termes électroniques et électriques. Il contient 20 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans 16 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Glossaire IEC - std.iec.ch/glossary

65 000 entrées terminologiques électrotechniques, en anglais et en français, extraites des articles Termes et Définitions des publications IEC parues depuis 2002. Plus certaines entrées antérieures extraites des publications des CE 37, 77, 86 et CISPR de l'IEC.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: csc@iec.ch.

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Secondary cells and batteries containing alkaline or other non-acid electrolytes – Secondary sealed cells and batteries for portable applications – Part 1: Nickel-cadmium

Accumulateurs alcalins et autres accumulateurs à électrolyte non acide – Accumulateurs étanches pour applications portables – Partie 1: Nickel-cadmium

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 29.220.30

ISBN 978-2-8322-4010-6

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

CONTENTS

| | |
|---|----|
| FOREWORD..... | 5 |
| 1 Scope..... | 7 |
| 2 Normative references | 7 |
| 3 Terms and definitions | 7 |
| 4 Parameter measurement tolerances | 9 |
| 5 Cell and battery designation and marking | 9 |
| 5.1 Cell and battery designation..... | 9 |
| 5.1.1 Small prismatic cells and cylindrical cells..... | 9 |
| 5.1.2 Button cells..... | 11 |
| 5.1.3 Batteries..... | 11 |
| 5.2 Cell or battery termination..... | 11 |
| 5.3 Marking..... | 11 |
| 5.3.1 Small prismatic cells and cylindrical cells..... | 11 |
| 5.3.2 Button cells..... | 12 |
| 5.3.3 Batteries..... | 12 |
| 5.4 Exemption of wording..... | 12 |
| 6 Dimensions..... | 12 |
| 6.1 Small prismatic cells and cylindrical cells..... | 12 |
| 6.1.1 General..... | 12 |
| 6.1.2 Small prismatic cells..... | 13 |
| 6.1.3 Cylindrical cells..... | 13 |
| 6.2 Button cells..... | 15 |
| 7 Electrical tests..... | 16 |
| 7.1 General..... | 16 |
| 7.2 Charging procedure for test purposes | 16 |
| 7.2.1 Charging procedure for cell..... | 16 |
| 7.2.2 Charging procedure for battery | 16 |
| 7.3 Discharge performance | 17 |
| 7.3.1 General | 17 |
| 7.3.2 Discharge performance at 20 °C | 17 |
| 7.3.3 Discharge performance at –18 °C | 19 |
| 7.3.4 Discharge performance for rapid charge cells (R cells)..... | 20 |
| 7.4 Charge (capacity) retention..... | 20 |
| 7.5 Endurance | 20 |
| 7.5.1 Endurance in cycles..... | 20 |
| 7.5.2 Permanent charge endurance..... | 24 |
| 7.6 Charge acceptance at constant voltage..... | 28 |
| 7.7 Overcharge | 28 |
| 7.7.1 Small prismatic cells..... | 28 |
| 7.7.2 L, M, H or X cylindrical and button cells..... | 29 |
| 7.7.3 LT/LU, MT/MU or HT/HU cylindrical cells..... | 29 |
| 7.7.4 J cylindrical cells | 29 |
| 7.7.5 JT cylindrical cells | 30 |
| 7.7.6 R cylindrical cells..... | 30 |
| 7.8 Safety device operation | 31 |

| | | |
|--------|---|----|
| 7.9 | Button cells or batteries storage, small prismatic cells or batteries storage, cylindrical cells or batteries storage | 31 |
| 7.10 | Charge acceptance at +55 °C for LT, MT or HT cylindrical cells | 32 |
| 7.11 | Trickle charge acceptance for JT cylindrical cells | 32 |
| 7.12 | Internal resistance | 33 |
| 7.12.1 | General | 33 |
| 7.12.2 | Measurement of the internal AC resistance | 33 |
| 7.12.3 | Measurement of the internal DC resistance | 34 |
| 8 | Mechanical tests | 34 |
| 9 | Safety requirements | 34 |
| 10 | Type approval and batch acceptance | 34 |
| 10.1 | General | 34 |
| 10.2 | Type approval | 35 |
| 10.2.1 | Type approval for small prismatic cells | 35 |
| 10.2.2 | Type approval for cylindrical and button cells | 35 |
| 10.2.3 | Type approval for batteries | 37 |
| 10.3 | Batch acceptance | 38 |
| | Bibliography | 40 |
| | Figure 1 – Jacketed cylindrical cells | 13 |
| | Figure 2 – Jacketed small prismatic cells | 13 |
| | Figure 3 – Jacketed cells dimensionally interchangeable with primary cells | 14 |
| | Figure 4 – Button cells | 15 |
| | Table 1 – Dimensions of jacketed small prismatic cells | 13 |
| | Table 2 – Dimensions of jacketed cylindrical cells dimensionally interchangeable with primary cells | 14 |
| | Table 3 – Dimensions of jacketed cylindrical cells not dimensionally interchangeable with primary cells | 15 |
| | Table 4 – Dimensions of button cells | 16 |
| | Table 5 – Discharge performance at 20 °C for small prismatic cells and cylindrical cells | 17 |
| | Table 6 – Discharge performance at 20 °C for button cells | 18 |
| | Table 7 – Discharge performance at 20 °C for batteries | 18 |
| | Table 8 – Rated capacity (mAh) compliance test (example) | 19 |
| | Table 9 – Discharge performance at –18 °C for small prismatic cells | 19 |
| | Table 10 – Discharge performance at –18 °C for cylindrical cells | 19 |
| | Table 11 – Discharge performance at –18 °C for button cells | 20 |
| | Table 12 – Endurance in cycles for small prismatic cells and cylindrical cells not dimensionally interchangeable with primary cells | 21 |
| | Table 13 – Endurance in cycles for cylindrical cells dimensionally interchangeable with primary cells | 21 |
| | Table 14 – Endurance in cycles for H or X cells | 22 |
| | Table 15 – Endurance in cycles for cylindrical X cells | 22 |
| | Table 16 – Endurance in cycles for HR or XR cells | 23 |
| | Table 17 – Endurance in cycles for button cells | 23 |
| | Table 18 – Permanent charge endurance for L, M, J, H or X cylindrical cells | 24 |

| | |
|---|----|
| Table 19 – Permanent charge endurance for button cells..... | 24 |
| Table 20 – Permanent charge endurance for LT, MT, or HT cylindrical cells | 26 |
| Table 21 – Permanent charge endurance for LU, MU, or HU cylindrical cells | 28 |
| Table 22 – Overcharge at 0 °C..... | 29 |
| Table 23 – Capacity deterioration due to storage period for cells or batteries..... | 32 |
| Table 24 – Charge and discharge at +55 °C..... | 32 |
| Table 25 – Trickle charge acceptance for JT cylindrical cells | 33 |
| Table 26 – Constant discharge currents used for measurement of DC resistance | 34 |
| Table 27 – Sequence of tests for type approval for small prismatic cells | 35 |
| Table 28 – Sequence of tests for type approval for cylindrical cells..... | 36 |
| Table 29 – Sequence of tests for type approval for button cells..... | 37 |
| Table 30 – Sequence of tests for type approval for batteries | 38 |
| Table 31 – Recommended test sequence for batch acceptance | 39 |

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[IEC 61951-1:2017](https://standards.iteh.ai/catalog/standards/sist/77f96561-6318-4d57-b0a0-6665acd0c9fa/iec-61951-1-2017)

<https://standards.iteh.ai/catalog/standards/sist/77f96561-6318-4d57-b0a0-6665acd0c9fa/iec-61951-1-2017>

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**SECONDARY CELLS AND BATTERIES CONTAINING
ALKALINE OR OTHER NON-ACID ELECTROLYTES –
SECONDARY SEALED CELLS AND BATTERIES
FOR PORTABLE APPLICATIONS –****Part 1: Nickel-cadmium**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61951-1 has been prepared by subcommittee 21A: Secondary cells and batteries containing alkaline or other non-acid electrolytes, of IEC technical committee 21: Secondary cells and batteries.

This fourth edition cancels and replaces the third edition published in 2013 of which it constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- addition of battery type;
- revision of Figure 3 (6.1.3.1);

- addition of “Optional pip” note to positive contact;
- changed leader line position from pip to flats of positive contact (B and G).

The text of this standard is based on the following documents:

| FDIS | Report on voting |
|--------------|------------------|
| 21A/622/FDIS | 21A/630/RVD |

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 61951 series can be found, under the general title *Secondary cells and batteries containing alkaline or other non-acid electrolytes – Secondary sealed cells and batteries for portable applications*, on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[IEC 61951-1:2017](https://standards.iteh.ai/catalog/standards/sist/77f96561-6318-4d57-b0a0-6665acd0c9fa/iec-61951-1-2017)

<https://standards.iteh.ai/catalog/standards/sist/77f96561-6318-4d57-b0a0-6665acd0c9fa/iec-61951-1-2017>

SECONDARY CELLS AND BATTERIES CONTAINING ALKALINE OR OTHER NON-ACID ELECTROLYTES – SECONDARY SEALED CELLS AND BATTERIES FOR PORTABLE APPLICATIONS –

Part 1: Nickel-cadmium

1 Scope

This part of IEC 61951 specifies marking, designation, dimensions, tests and requirements for secondary sealed nickel-cadmium small prismatic, cylindrical and button cells and batteries, suitable for use in any orientation, for portable applications.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-482:2004, *International Electrotechnical Vocabulary (IEV) – Part 482: Primary and secondary cells and batteries*

IEC 60086-1, *Primary batteries – Part 1: General*

IEC 60086-2, *Primary batteries – Part 2: Physical and electrical specifications*

IEC 61959, *Secondary cells and batteries containing alkaline or other non-acid electrolytes – Mechanical tests for sealed portable secondary cells and batteries*

IEC 62133-1, *Secondary cells and batteries containing alkaline or other non-acid electrolytes – Safety requirements for portable sealed secondary cells and for batteries made from them, for use in portable applications – Part 1: Nickel systems*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60050-482 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1

nominal voltage

suitable approximate value of voltage used to designate or identify a cell or a battery

Note 1 to entry: The nominal voltage of a sealed nickel-cadmium rechargeable single cell: 1,2 V.

Note 2 to entry: The nominal voltage of a battery of n series connected cells is equal to n times the nominal voltage of a single cell.

[SOURCE: IEC 60050-482:2004, 482-03-31, modified – Addition of Notes 1 and 2 to entry.]

3.2

rated capacity

capacity value of a cell or a battery determined under specified conditions and declared by the manufacturer

Note 1 to entry: The rated capacity is the quantity of electricity C_5 Ah (ampere-hours) declared by the manufacturer which a single cell can deliver during a 5 h period when charging, storing and discharging under the conditions specified in 7.3.2.

Note 2 to entry: The capacity of a battery is the quantity of electricity C_5 Ah (ampere-hours) declared by the manufacturer which a battery can deliver during a 5 h period, when charged, stored and discharged under the conditions specified in 7.3.2.

[SOURCE: IEC 60050-482:2004, 482-03-15, modified – Addition of Notes 1 and 2 to entry.]

3.3

small prismatic cell

cell in the form of a rectangular parallelepiped whose width and thickness dimensions are not more than 25 mm

3.4

cylindrical cell

cell of circular cross-section in which the overall height is equal to, or greater than, the overall diameter

3.5

button cell

cell of a circular cross-section in which the overall height is less than the overall diameter

3.6

nickel-cadmium cell

cell containing a nickel hydroxide compound for the positive electrode, a cadmium compound for the negative electrode, and potassium hydroxide or other alkaline solution as electrolyte

Note 1 to entry: Positive electrodes are isolated from negative electrodes by a separator.

3.7

nickel-cadmium battery

assembly of secondary cell(s) as a source of electrical energy characterized by its voltage, size, terminal arrangement, capacity and rate capability

3.8

sealed cell

cell which remains closed and does not release either gas or liquid when operated within the limits of charge and temperature specified by the manufacturer

Note 1 to entry: The cell is equipped with a safety device to prevent dangerously high internal pressure.

Note 2 to entry: The cell does not require addition to the electrolyte and is designed to operate during its life in its original sealed state.

[SOURCE: IEC 60050-482:2004, 482-05-17, modified – The existing note has been developed into Notes 1 and 2 to entry.]

3.9

portable cell

cell designed mainly for use in an easily hand-carried battery

3.10

battery for portable applications

battery for use in device or appliance which is conveniently hand-carried

4 Parameter measurement tolerances

The overall accuracy of controlled or measured values, relative to the specified or actual values, shall be within the following tolerances:

- a) ± 1 % for voltage;
- b) ± 1 % for current;
- c) ± 1 % for capacity;
- d) ± 2 °C for temperature;
- e) $\pm 0,1$ % for time;
- f) $\pm 0,1$ mm for dimensions;
- g) ± 5 % for humidity.

These tolerances comprise the combined accuracy of the measuring instruments, the measurement techniques used and all other sources of error in the test procedure.

The details of the instrumentation used shall be provided in each report of results.

[IEC 61951-1:2017](https://standards.iteh.ai/catalog/standards/sist/77f96561-6318-4d57-b0a0-6665acd0c91a/iec-61951-1-2017)

5 Cell and battery designation and marking

<https://standards.iteh.ai/catalog/standards/sist/77f96561-6318-4d57-b0a0-6665acd0c91a/iec-61951-1-2017>

5.1 Cell and battery designation

5.1.1 Small prismatic cells and cylindrical cells

5.1.1.1 General

Sealed nickel-cadmium small prismatic rechargeable single cells and cylindrical rechargeable single cells shall be designated by a letter L, M, J, H or X which signifies:

- low rate of discharge (L);
- medium rate of discharge (M);
- medium high rate of discharge (J);
- high rate of discharge (H);
- very high rate of discharge (X).

NOTE 1 These cells are typically but not exclusively used for the following discharge rates:

- L up to $0,5 I_t$ A;
- M up to $3,5 I_t$ A;
- J up to $5,0 I_t$ A;
- H up to $7,0 I_t$ A;
- X up to and above $15 I_t$ A.

NOTE 2 These currents are expressed as multiples of I_t A, where I_t A = C_5 Ah/1 h (see IEC 61434).

When a cell is intended for permanent charge at elevated temperatures, typically higher than 40 °C, a letter "T" is placed after the letter L, M, J, H or X.

When a cell is intended for permanent charge at elevated temperatures, typically higher than 50 °C, a letter "U" is placed after the letter L, M, J, H or X.

When a cell is intended for rapid charge, typically at 1,0 I_t A, a letter "R" is placed after the letter L, M, J, H or X.

5.1.1.2 Small prismatic cells

Sealed nickel-cadmium small prismatic rechargeable single cells shall be designated by the letters "KF" followed by a letter L, M, J, H or X followed by three groups of figures, each one separated by a solidus:

- the two figures to the left of the first solidus shall indicate the maximum width specified for the cell, expressed in millimetres, rounded up to the next whole number;
- the two figures in the middle shall indicate the maximum thickness specified for the cell, expressed in millimetres, rounded up to the next whole number;
- the two figures to the right of the second solidus shall indicate the maximum height specified for the cell, expressed in millimetres, rounded up to the next whole number.

EXAMPLE KFL 18/07/49 designation identifies a small prismatic cell of low discharge rate capability, with a maximum width of 18 mm, a maximum thickness of 7 mm and a maximum height of 49 mm.

5.1.1.3 Cylindrical cells

Sealed nickel-cadmium cylindrical rechargeable single cells shall be designated by the letters "KR" followed by a letter L, M, J, H or X followed by two groups of figures, each one separated by a solidus:

- the two figures to the left of the solidus shall indicate the maximum diameter specified for the cell, expressed in millimetres, rounded up to the next whole number;
- the two figures to the right of the solidus shall indicate the maximum height specified for the cell, expressed in millimetres, rounded up to the next whole number.

When a manufacturer designs a cell with dimensions and tolerances which make it interchangeable with a primary cell, the designation of Table 2 shall also be marked on the cell.

EXAMPLE 1 KRL 33/62 designation identifies a cylindrical cell of low discharge rate capability, with a maximum diameter of 33 mm and a maximum height of 61,5 mm.

EXAMPLE 2 KRLT 33/62 designation identifies a cylindrical cell of low discharge rate capability, intended for permanent charge at elevated temperatures, with a maximum diameter of 33 mm and a maximum height of 61,5 mm.

EXAMPLE 3 KRHR 23/43 designation identifies a cylindrical cell of high discharge rate capability, intended for rapid charge, with a maximum diameter of 23 mm and a maximum height of 43 mm.

For cells dimensionally interchangeable with primary cells, the following single or double figures following the letter L, M or R may indicate:

- 20- size D;
- 14- size C;
- 6- size AA;
- 03- size AAA.

EXAMPLE 4 KRMR03 designation identifies a sealed nickel-cadmium cylindrical rechargeable single cell, of medium discharge rate capability, also intended for rapid charge, dimensionally interchangeable with primary cell and whose type designation is AAA.

5.1.2 Button cells

Sealed nickel-cadmium button rechargeable single cells shall be designated by the letters “KB” followed by a letter L, M or H which signifies:

- low rate of discharge (L);
- medium rate of discharge (M);
- high rate of discharge (H).

The group of three letters shall then be followed by two groups of figures separated by a solidus:

- a) the three figures to the left of the solidus shall indicate the maximum diameter specified for the cell, expressed in tenths of millimetres, rounded up to the next whole number;
- b) the three figures to the right of the solidus shall indicate the maximum height specified for the cell, expressed in tenths of millimetres, rounded up to the next whole number.

EXAMPLE KBL 116/055 designation identifies a button cell of low discharge rate capability, with a maximum diameter of 11,6 mm and a maximum height of 5,5 mm.

5.1.3 Batteries

Sealed nickel-cadmium rechargeable batteries shall be designated with the following form:

N1 single cell designation -N2

where

N1 is the number of series connected cells in the battery;

N2 is the number of parallel connected cells if 2 or greater (not shown if value is 1).

Sealed nickel-cadmium battery designation will be identified based on single cells within the series and not the battery as a whole.

- Small prismatic cells in batteries

EXAMPLE 1 2KFL 18/07/49 designation identifies a small prismatic cell of low discharge rate capability, with a maximum width of 18 mm, a maximum thickness of 7 mm and a maximum height of 49 mm with two series connected cells.

- Cylindrical cells in batteries

EXAMPLE 2 3KRL 33/62 designation identifies a cylindrical cell of low discharge rate capability, with a maximum diameter of 33 mm and a maximum height of 61,5 mm with three series connected cells

- Cells interchangeable with primary cells in batteries

EXAMPLE 3 KRMR03-3 designation identifies a sealed nickel-cadmium cylindrical rechargeable single cell, of medium discharge rate capability, also intended for rapid charge, dimensionally interchangeable with primary cell whose type designation is AAA with three parallel connected cells.

- Button cells in batteries

EXAMPLE 4 KB116/055-3 designation identifies a button cell, with a maximum diameter of 11,6 mm and a maximum height of 5,5 mm with three parallel connected cells.

5.2 Cell or battery termination

This standard does not specify cell or battery termination.

5.3 Marking

5.3.1 Small prismatic cells and cylindrical cells

Each jacketed cell supplied without connections shall carry durable markings giving the following minimum information:

- sealed rechargeable nickel-cadmium or Ni-Cd;

- rated capacity;
- nominal voltage;
- polarity (+ and –);
- date of manufacture (which may be in code);
- name or identification of manufacturer or supplier;
- mark for promoting useful use of cell resources.

NOTE 1 This mark is applied where a recycling programme is available.

NOTE 2 In general, sealed nickel-cadmium rechargeable single cells with connection tabs need no labels if they form an integral part of a battery, in which case, the battery itself is marked with the above information.

5.3.2 Button cells

Each button cell supplied without connection shall carry durable markings giving the following minimum information:

- designation as specified in 5.1;
- polarity (+ and –);
- date of manufacture (which may be in code);
- name or identification of manufacturer or supplier.

5.3.3 Batteries

Each battery shall carry durable markings giving the following minimum information:

- sealed rechargeable nickel- cadmium or Ni-Cd;
- rated capacity; [IEC 61951-1:2017](https://standards.iteh.ai/catalog/standards/sist/77f96561-6318-4d57-b0a0-6665acd0c9fa/iec-61951-1-2017)
- nominal voltage; <https://standards.iteh.ai/catalog/standards/sist/77f96561-6318-4d57-b0a0-6665acd0c9fa/iec-61951-1-2017>
- date of manufacture (which may be in code).

5.4 Exemption of wording

Each cell or battery shall include minimum information on the label as specified in 5.3.1/ 5.3.3. Therefore, additional information such as safety cautions should be included in the form of a manual not on the cell or battery label.

Each cell or battery shall include minimum information on the label as specified in 5.3.1/ 5.3.3. Therefore, cells or batteries encased in soft or hard plastic with the safety cautions printed on the outside, should not include caution details on the cell or battery label.

6 Dimensions

6.1 Small prismatic cells and cylindrical cells

6.1.1 General

Figure 1 and Figure 2 show the shape of the cells.




Figure 1 – Jacketed cylindrical cells Figure 2 – Jacketed small prismatic cells

6.1.2 Small prismatic cells (standards.iteh.ai)

Table 1 shows the dimensions for jacketed small prismatic cells.

Table 1 – Dimensions of jacketed small prismatic cells

| Cell designation | Width mm | Thickness mm | Height mm |
|------------------|-------------|-----------------|--------------|
| KF 18/07/41 | 17,3 | 6,1 | 40,2 |
| KF 18/07/49 | 17,3 | 6,1 | 48,2 |
| KF 18/09/49 | 17,3 | 8,3 | 48,2 |
| KF 18/07/68 | 17,3 | 6,1 | 67,3 |
| KF 18/09/68 | 17,3 | 8,3 | 67,3 |
| KF 18/11/68 | 17,3 | 10,5 | 67,3 |
| KF 18/18/68 | 17,3 | 17,3 | 67,3 |
| KF 23/15/68 | 23,0 | 14,7 | 67,3 |

Width tolerance: 0, -1,0
 Thickness tolerance: 0, -0,7, -1,0
 Height tolerance: 0, -1,0, -1,5

6.1.3 Cylindrical cells

6.1.3.1 Cells dimensionally interchangeable with primary cells

Table 2 and Figure 3 give the requirements relative to the dimensions for jacketed cylindrical cells which are dimensionally interchangeable with primary cells.