

# SLOVENSKI STANDARD

## SIST EN 61158-5-10:2008

01-julij-2008

Nadomešča:  
SIST EN 61158-5:2004

---

**Industrijska komunikacijska omrežja - Specifikacije za procesno vodilo - 5-10. del:  
Definicija opravil na aplikacijskem nivoju - Elementi tipa 10 (IEC 61158-5-10:2007)**

Industrial communication networks - Fieldbus specifications - Part 5-10: Application layer service definition - Type 10 elements

Industrielle Kommunikationsnetze - Feldbusse - Teil 5-10: Dienstfestlegungen des Application Layer (Anwendungsschicht) - Typ 10-Elemente  
[standards.iteh.ai](http://standards.iteh.ai)

Réseaux de communication industriels - Spécifications des bus de terrain - Partie 5-10:  
Définition des services des couches d'application - Éléments de type 10  
88ed01da535e/sist-en-61158-5-10-2008

**Ta slovenski standard je istoveten z: EN 61158-5-10:2008**

---

**ICS:**

25.040.40	Merjenje in krmiljenje industrijskih postopkov	Industrial process measurement and control
35.100.70	Uporabniški sloj	Application layer
35.110	Omreževanje	Networking

**SIST EN 61158-5-10:2008**

**en,de**

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 61158-5-10:2008](#)

<https://standards.iteh.ai/catalog/standards/sist/92963a8d-4e0a-4e28-8baf-88ed01da535e/sist-en-61158-5-10-2008>

March 2008

ICS 35.100.70; 25.040.40

Partially supersedes EN 61158-5:2004

English version

**Industrial communication networks -  
Fieldbus specifications -  
Part 5-10: Application layer service definition -  
Type 10 elements  
(IEC 61158-5-10:2007)**

Réseaux de communication industriels -  
Spécifications des bus de terrain -  
Partie 5-10: Définition des services  
des couches d'application -  
Eléments de type 10  
(CEI 61158-5-10:2007)

Industrielle Kommunikationsnetze -  
Feldbusse -  
Teil 5-10: Dienstfestlegungen  
des Application Layer  
(Anwendungsschicht) -  
Typ 10-Elemente  
(IEC 61158-5-10:2007)

**The STANDARD PDF (FW)  
(standards.iteh.ai)**

SIST EN 61158-5-10:2008

<https://standards.iteh.ai/catalog/standards/sist/92963a8d-4e0a-4e28-8baf>

This European Standard was approved by CENELEC on 2008-02-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

**CENELEC**

European Committee for Electrotechnical Standardization  
Comité Européen de Normalisation Electrotechnique  
Europäisches Komitee für Elektrotechnische Normung

**Central Secretariat: rue de Stassart 35, B - 1050 Brussels**

## Foreword

The text of document 65C/475/FDIS, future edition 1 of IEC 61158-5-10, prepared by SC 65C, Industrial networks, of IEC TC 65, Industrial-process measurement, control and automation, was submitted to the IEC-CENELEC parallel vote and was approved by CENELEC as EN 61158-5-10 on 2008-02-01.

This and the other parts of the EN 61158-5 series supersede EN 61158-5:2004.

With respect to EN 61158-5:2004 the following changes were made:

- deletion of Type 6 fieldbus and Type 1 fieldbus application layer, for lack of market relevance;
- addition of new fieldbus types;
- partition into multiple parts numbered 5-2, 5-3, ..., 5-20.

The following dates were fixed:

- latest date by which the EN has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2008-11-01
- latest date by which the national standards conflicting with the EN have to be withdrawn (dow) 2011-02-01

NOTE Use of some of the associated protocol types is restricted by their intellectual-property-right holders. In all cases, the commitment to limited release of intellectual-property-rights made by the holders of those rights permits a particular data-link layer protocol type to be used with physical layer and application layer protocols in type combinations as specified explicitly in the EN 61784 series. Use of the various protocol types in other combinations may require permission from their respective intellectual-property-right holders.

Annex ZA has been added by CENELEC [CST EN 61158-5-10:2008](#)

<https://standards.iteh.ai/catalog/standards/sist/92963a8d-4e0a-4e28-8baf-88ed01da535e/sist-en-61158-5-10-2008>

## Endorsement notice

The text of the International Standard IEC 61158-5-10:2007 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 61784-1	NOTE Harmonized as EN 61784-1:2008 (not modified).
IEC 61784-2	NOTE Harmonized as EN 61784-2:2008 (not modified).
ISO/IEC 8877	NOTE Harmonized as EN 28877:1993 (not modified).
ISO 8601	NOTE Harmonized as EN 28601:1992 (not modified).

## Annex ZA

(normative)

### Normative references to international publications with their corresponding European publications

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60559	- <sup>1)</sup>	Binary floating-point arithmetic for microprocessor systems	HD 592 S1	1991 <sup>2)</sup>
IEC 61131-1	- <sup>1)</sup>	Programmable controllers - Part 1: General information	EN 61131-1	2003 <sup>2)</sup>
IEC 61131-3	- <sup>1)</sup>	Programmable controllers - Part 3: Programming languages	EN 61131-3	2003 <sup>2)</sup>
IEC 61158-6-3	- <sup>1)</sup>	Industrial communication networks - Fieldbus specifications - Part 6-3: Application layer protocol specification - Type 3 elements	EN 61158-6-3	2008 <sup>2)</sup>
IEC 61158-6-10	- <sup>1)</sup>	Industrial communication networks - Fieldbus specifications - Part 6-10: Application layer protocol specification - Type 10 elements	EN 61158-6-10	2008 <sup>2)</sup>
ISO/IEC 646	- <sup>1)</sup>	Information technology - ISO 7-bit coded character set for information interchange	-	-
ISO/IEC 7498-1	- <sup>1)</sup>	Information technology - Open Systems Interconnection - Basic Reference Model: The Basic Model	EN ISO/IEC 7498-1	1995 <sup>2)</sup>
ISO/IEC 8802-1	- <sup>1)</sup>	Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Specific requirements - Part 1: Overview of Local Area Network Standards	-	-
ISO/IEC 8802-3	- <sup>1)</sup>	Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Specific requirements - Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications	-	-

<sup>1)</sup> Undated reference.

<sup>2)</sup> Valid edition at date of issue.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
ISO/IEC 8822	- <sup>1)</sup>	Information technology - Open Systems Interconnection - Presentation service definition	-	-
ISO/IEC 8824-1	- <sup>1)</sup>	Information technology - Abstract Syntax Notation One (ASN.1): Specification of basic notation	-	-
ISO/IEC 8859-1	- <sup>1)</sup>	Information technology - 8-bit single-byte coded graphic character sets - Part 1: Latin alphabet No.1	-	-
ISO/IEC 9545	- <sup>1)</sup>	Information technology - Open Systems Interconnection - Application Layer structure	-	-
ISO/IEC 10646-1	- <sup>1)</sup>	Information technology - Universal Multiple-Octet Coded Character Set (UCS) - Part 1: Architecture and Basic Multilingual Plane	-	-
ISO/IEC 10731	- <sup>1)</sup>	Information technology - Open Systems Interconnection - Basic reference model - Conventions for the definition of OSI services	-	-
IEEE 802	2001	IEEE standard for local and metropolitan area networks; overview and architecture	-	-
IEEE 802.1AB	2005	IEEE Standard for Local and metropolitan area networks. Station and Media Access Control Connectivity Discovery	-	-
IEEE 802.1D	2004 <a href="https://standards.ieee.org/catalog/standards/sist-en-61158-5-10-2008">https://standards.ieee.org/catalog/standards/sist-en-61158-5-10-2008</a>	IEEE standard for local and metropolitan area networks - Media access control (MAC) Bridges	-	-
IEEE 802.1Q	2005	IEEE Standard for Local and Metropolitan Area Networks - Virtual Bridged Local Area Networks	-	-
IEEE 802.3	2005	IEEE Standard for Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Specific requirements - Part 3: Carrier Sense Multiple Access with Collision Detection	-	-
IEEE 802.15.1	2005	IEEE Standard for Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Specific requirement - Part 15.1: Wireless medium access control (MAC) and physical layer (PHY) specifications for wireless personal area networks (WPANs)	-	-
IETF RFC 768	- <sup>1)</sup>	User Datagram Protocol	-	-
IETF RFC 791	- <sup>1)</sup>	Internet Protocol	-	-
IETF RFC 792	- <sup>1)</sup>	Internet Control Message Protocol	-	-

**iTech STANDARD PREVIEW**  
*(Get standards right)*

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IETF RFC 826	- <sup>1)</sup>	Ethernet Address Resolution Protocol	-	-
IETF RFC 1034	- <sup>1)</sup>	Domain names - concepts and facilities	-	-
IETF RFC 1112	- <sup>1)</sup>	Host Extensions for IP Multicasting	-	-
IETF RFC 2131	- <sup>1)</sup>	Dynamic Host Configuration Protocol	-	-
IETF RFC 2674	- <sup>1)</sup>	Definitions of Managed Objects for Bridges with Traffic Classes, Multicast Filtering and Virtual LAN Extensions	-	-
IETF RFC 2737	- <sup>1)</sup>	Entity MIB (Version 2)	-	-
IETF RFC 2863	- <sup>1)</sup>	The Interfaces Group MIB	-	-
IETF RFC 3418	- <sup>1)</sup>	Management Information Base (MIB) for the Simple Network Management Protocol (SNMP)	-	-
IETF RFC 3490	- <sup>1)</sup>	Internationalizing Domain Names in Applications (IDNA)	-	-
IETF RFC 3621	- <sup>1)</sup>	Power Ethernet MIB	-	-
IETF RFC 3636	- <sup>1)</sup>	Definitions of Managed Objects for IEEE 802.3 Medium Attachment Units (MAUs)	-	-
The Open Group C706	- <sup>1)</sup>	CAE Specification DCE11: Remote Procedure Call	-	-

**iTeb STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST EN 61158-5-10:2008  
<https://standards.iteh.ai/catalog/standards/sist/92963a8d-4e0a-4e28-8baf-88ed01da535e/sist-en-61158-5-10-2008>

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 61158-5-10:2008](#)

<https://standards.iteh.ai/catalog/standards/sist/92963a8d-4e0a-4e28-8baf-88ed01da535e/sist-en-61158-5-10-2008>



IEC 61158-5-10

Edition 1.0 2007-12

# INTERNATIONAL STANDARD

---

Industrial communication networks – Fieldbus specifications –  
Part 5-10: Application layer service definition – Type 10 elements  
([standards.iteh.ai](https://standards.iteh.ai))

SIST EN 61158-5-10:2008  
<https://standards.iteh.ai/catalog/standards/sist/92963a8d-4e0a-4e28-8baf-88ed01da535e/sist-en-61158-5-10-2008>

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

PRICE CODE XU

---

ICS 35.100.70; 25.040.40

ISBN 2-8318-9459-X

## CONTENTS

FOREWORD .....	16
INTRODUCTION .....	18
1 Scope .....	19
1.1 Overview .....	19
1.2 Specifications .....	20
1.3 Conformance .....	20
2 Normative references .....	20
3 Terms, definitions, abbreviations, symbols and conventions .....	22
3.1 Referenced terms and definitions .....	22
3.2 Additional terms and definitions for distributed automation .....	23
3.3 Additional terms and definitions for decentralized periphery .....	25
3.4 Additional terms and definitions for media redundancy .....	33
3.5 Abbreviations and symbols .....	34
3.6 Additional abbreviations and symbols for distributed automation .....	35
3.7 Additional abbreviations and symbols for decentralized periphery .....	35
3.8 Additional abbreviations and symbols for media redundancy .....	36
3.9 Conventions .....	36
4 Concepts .....	39
5 Data type ASE .....	39
5.1 General .....	39
5.2 Formal definition of data type objects .....	42
5.3 FAL defined data types .....	43
5.4 Data type ASE service specification .....	86
6 Communication model for common services .....	86
6.1 Concepts .....	86
6.2 ASE data types .....	86
6.3 ASEs .....	87
7 Communication model for distributed automation .....	184
7.1 Concepts .....	184
7.2 ASE data types .....	191
7.3 ASEs .....	195
7.4 ARs .....	412
7.5 Summary of FAL classes .....	416
7.6 Summary of FAL services .....	417
8 Communication model for decentralized periphery .....	420
8.1 Concepts .....	420
8.2 ASE data types .....	436
8.3 ASEs .....	436
8.4 Behavior of an IO device .....	671
8.5 Behavior of an IO controller .....	737
8.6 Application characteristics .....	744

Annex A (informative) Device instances .....	746
Annex B (informative) Components of an Ethernet interface .....	748
Annex C (informative) Scheme of MAC address assignment .....	752
Annex D (informative) Collection of objects .....	753
Annex E (informative) Measurement of the fast startup time .....	754
Bibliography .....	755
Figure 1 – Data type class hierarchy example .....	40
Figure 2 – NetworkTime date relation .....	63
Figure 3 – UTF-8 coding of four different characters .....	67
Figure 4 – PTCP applications .....	100
Figure 5 – Clock drift measurement .....	110
Figure 6 – Multiple synchronization .....	110
Figure 7 – MRP stack .....	112
Figure 8 – Ring topology with one manager and clients .....	123
Figure 9 – MRM in an open ring .....	123
Figure 10 – More than one MRM in the ring .....	125
Figure 11 – Media redundancy diagnosis dependencies .....	126
Figure 12 – Locating the destination for redundant RT frames .....	165
Figure 13 – Example of periods at a local port .....	172
Figure 14 – FAL ASEs communication architecture .....	187
Figure 15 – Runtime object model .....	188
Figure 16 – Relationship between engineering and runtime .....	189
Figure 17 – Navigation in the runtime object model .....	190
Figure 18 – Operating state block diagram .....	229
Figure 19 – Device status model for the common diagnosis .....	230
Figure 20 – ACCO ASE structure .....	261
Figure 21 – Productive operation of data connections .....	262
Figure 22 – Quality code transfer – standard behavior .....	274
Figure 23 – Startup of a connection .....	275
Figure 24 – Quality code with communication fault .....	275
Figure 25 – Quality code when a connection is cleared .....	276
Figure 26 – Quality code when a connection is deactivated .....	276
Figure 27 – Quality code during the transfer of "incorrect" connection data .....	277
Figure 28 – Quality code for provider in "CBAReady" state .....	278
Figure 29 – Quality code when clearing an object from the provider .....	278
Figure 30 – Quality code when a connection is forced .....	279
Figure 31 – Quality code at QoS violation .....	279
Figure 32 – Push mode .....	286
Figure 33 – Pull mode overview .....	287

Figure 34 – Detailed sequence chart of the pull mode .....	288
Figure 35 – QoS and ORPC communication channel.....	289
Figure 36 – QoS Violation within Pull Mode.....	290
Figure 37 – Monitoring the providers heartbeat .....	291
Figure 38 – State machine RemoteAcco .....	293
Figure 39 – State machine RemoteAccoProvider.....	293
Figure 40 – State machine RemoteAccoProvider <sub>ORPC</sub> .....	294
Figure 41 – State machine AR <sub>ORPC</sub> – Provider .....	294
Figure 42 – State machine GetConnectionData – Provider .....	295
Figure 43 – State machine ProviderConnection.....	295
Figure 44 – State machine ProvConnActivation.....	296
Figure 45 – State machine WorkerORPC .....	296
Figure 46 – Communication stack of distributed automation devices .....	297
Figure 47 – Application relations between devices .....	298
Figure 48 – Communication relations .....	298
Figure 49 – RT communication channel .....	300
Figure 50 – Interaction between provider and consumer .....	302
Figure 51 – State machine AR <sub>SRT</sub> – Consumer .....	304
Figure 52 – State machine AR <sub>SRT</sub> – Provider .....	304
Figure 53 – State machine AccoDataCR – Consumer.....	305
Figure 54 – State machine AccoDataCR – Provider .....	306
Figure 55 – RT frame play out <sup>SISTEN 61158-5-10:2008</sup> iteh.ai/catalog/standards/sist/92963a8d-4e0a-4e28-8baf- <sup>88ed01da535e/sist-en-61158-5-10-2008</sup> .....	307
Figure 56 – Establishing an AccoDataCR.....	308
Figure 57 – Flowchart of the copy cycle for local connections .....	309
Figure 58 – State machine connect attempt .....	313
Figure 59 – Productive operation of data connections (ORPC channel).....	320
Figure 60 – Productive operation of data connections (RT channel) .....	321
Figure 61 – Productive operation of data connections (Local channel) .....	321
Figure 62 – Data flow for cyclic RT .....	322
Figure 63 – Failure of the provider in productive operation (ORPC push mode).....	324
Figure 64 – Failure of the provider in productive operation (ORPC pull mode) .....	325
Figure 65 – Scenario 1: Provider failure in productive operation (RT).....	326
Figure 66 – Scenario 2: Recovery from provider failure in productive operation (RT).....	327
Figure 67 – Failure of the consumer (push mode) .....	327
Figure 68 – Failure of the consumer (pull mode) .....	328
Figure 69 – Failure of the consumer.....	329
Figure 70 – Failure of the provider when setting up connections .....	331
Figure 71 – Information levels .....	332
Figure 72 – ACCO ASE status model for the common diagnosis .....	332
Figure 73 – ACCO ASE status model for the detailed diagnosis .....	333
Figure 74 – Structure of the transmitted connection data .....	375

Figure 75 – Example of communication between controlling devices and field devices .....	421
Figure 76 – Example of communication between an engineering station and several controlling and field devices .....	421
Figure 77 – Example of communication between field devices and a server station.....	422
Figure 78 – Example of communication between field devices .....	422
Figure 79 – Structural units of one arbitrary API of an IO device (general) .....	424
Figure 80 – Example 1 structural units for interfaces and ports within API 0.....	425
Figure 81 – Example 2 structural units for interfaces and ports within API 0.....	426
Figure 82 – Overview of application processes .....	428
Figure 83 – IO device with APs, slots and subslots .....	429
Figure 84 – Application Process with application objects (APOs) .....	432
Figure 85 – Access to a remote APO .....	433
Figure 86 – Access to a remote APO for provider/consumer association .....	434
Figure 87 – Example of one AR with two AREPs .....	435
Figure 88 – Relation of a record data object to one real object.....	437
Figure 89 – Relation of a record data object to two real objects .....	438
Figure 90 – Overview IO ASE service interactions .....	448
Figure 91 – Example of a resource model at the alarm source .....	525
Figure 92 – General isochronous application model (example).....	560
Figure 93 – ASE relations in an IO device operating in isochronous mode .....	566
Figure 94 – State machine relations in an IO device operating in isochronous mode .....	566
Figure 95 – SyncCtl state diagram .....	570
Figure 96 – Output state diagram .....	572
Figure 97 – Input state diagram .....	577
Figure 98 – Assignment of communication relationship to application relationship .....	650
Figure 99 – Implicit application relationship.....	653
Figure 100 – Example IO application relationship (one-to-one) .....	655
Figure 101 – Example IO application relationship one-to-many .....	656
Figure 102 – Overview ASE state machines for IO device .....	672
Figure 103 – State diagram application startup IO device.....	673
Figure 104 – State diagram startup manager IO device .....	681
Figure 105 – State diagram IRT port state IO device (standard).....	684
Figure 106 – State diagram IRT port state IO device (optimized).....	696
Figure 107 – State diagram neighborhood check.....	703
Figure 108 – State diagram PD parameter check IO device .....	712
Figure 109 – State diagram for a submodule .....	722
Figure 110 – State diagram IO controller during startup .....	738
Figure 111 – State diagram startup manager IO controller .....	741
Figure 112 – Example of network topology including slower wireless segments .....	745
Figure 113 – Example of media redundancy including wireless segments .....	745
Figure A.1 – Instance model .....	746

Figure B.1 – Scheme of an Ethernet interface .....	748
Figure B.2 – Scheme of an Ethernet interface with bridging ability .....	749
Figure B.3 – Scheme of an Ethernet interface with optical ports .....	750
Figure B.4 – Scheme of an Ethernet interface with bridging ability using radio communication .....	751
Figure B.5 – Scheme of an Ethernet interface with radio communication .....	751
Figure C.1 – Scheme of MAC address assignment .....	752
Figure D.1 – Example for an intersection of IO device, slot, and AR .....	753
Figure E.1 – Measurement of the fast startup time .....	754
 Table 1 – PERSISTDEF .....	46
Table 2 – VARTYPE .....	47
Table 3 – ITEMQUALITYDEF .....	47
Table 4 – STATEDEF .....	51
Table 5 – GROUPERRORDEF .....	51
Table 6 – ACCESSRIGHTSDEF .....	51
Table 7 – HRESULT .....	52
Table 8 – N2 value range .....	56
Table 9 – N2 octets .....	56
Table 10 – N4 value range .....	57
Table 11 – N4 octets .....	57
Table 12 – X2 value range .....	58
Table 13 – X2 octets .....	58
Table 14 – X4 value range .....	58
Table 15 – X4 octets .....	58
Table 16 – Unipolar2.16 value range .....	59
Table 17 – Unipolar2.16 octets .....	59
Table 18 – E2 value range .....	59
Table 19 – E2 octets .....	59
Table 20 – C4 value range .....	60
Table 21 – V2 octets .....	60
Table 22 – L2 octets .....	60
Table 23 – UUID for decentralized peripherals .....	61
Table 24 – UUID for distributed automation .....	62
Table 25 – NetworkTime values .....	63
Table 26 – NetworkTime octets .....	63
Table 27 – T2 values .....	64
Table 28 – T4 values .....	64
Table 29 – D2 values .....	65
Table 30 – R2 values .....	65
Table 31 – UNICODEString values .....	66

Table 32 – UTF-8 character encoding scheme .....	67
Table 33 – OctetString2+Unsigned8 octets .....	78
Table 34 – Float32+Unsigned8 octets .....	79
Table 35 – Unsigned8+Unsigned8 octets .....	79
Table 36 – Data Types for Value in a VARIANT .....	82
Table 37 – Unsigned16_S octets.....	83
Table 38 – Unsigned16_S meaning.....	83
Table 39 – Integer16_S octets .....	84
Table 40 – Integer16_S meaning .....	84
Table 41 – Unsigned8_S octets .....	84
Table 42 – Unsigned8_S meaning.....	84
Table 43 – OctetString_S octets .....	85
Table 44 – OctetString_S status bits .....	85
Table 45 – F message trailer with 4 octets .....	85
Table 46 – F message trailer with 5 octets .....	86
Table 47 – Get .....	92
Table 48 – Set .....	94
Table 49 – Identify .....	97
Table 50 – Hello.....	98
Table 51 – Clock stratum .....	102
Table 52 – Start bridge .....	104
Table 53 – Start slave .....	105
Table 54 – Start master .....	106
Table 55 – Stop bridge.....	107
Table 56 –Stop slave .....	107
Table 57 – Stop master.....	108
Table 58 – State change .....	109
Table 59 – Start MRM .....	117
Table 60 – Stop MRM .....	119
Table 61 – Change state .....	119
Table 62 – Start MRC .....	120
Table 63 – Stop MRC.....	121
Table 64 – Neighborhood changed.....	122
Table 65 – MRP network/connection parameters .....	127
Table 66 – MRM parameters .....	127
Table 67 – MRC parameters .....	127
Table 68 – Set prov data.....	128
Table 69 – Set prov status .....	129
Table 70 – PPM activate .....	130
Table 71 – Close.....	131
Table 72 – Start .....	131