

INTERNATIONAL STANDARD



**Maritime navigation and radiocommunication equipment and systems –
Data interfaces –
Part 1: S-421 route plan based on S-100**

ITeH STANDARD PREVIEW
(standards.iteh.ai)
IEC 63173-1:2021
<https://standards.iteh.ai/catalog/standards/sist/9b61764a-face-4909-8073-23ea8f3aa782/iec-63173-1-2021>



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2021 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC online collection - oc.iec.ch

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 18 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

[IEC 63173-1:2021](https://standards.iteh.ai/catalog/standards/sist/9b61764a-face-4909-8073-23ea8f3aa782/iec-63173-1-2021)

<https://standards.iteh.ai/catalog/standards/sist/9b61764a-face-4909-8073-23ea8f3aa782/iec-63173-1-2021>

INTERNATIONAL STANDARD



**Maritime navigation and radiocommunication equipment and systems –
Data interfaces –
Part 1: S-421 route plan based on S-100**

STANDARD PREVIEW
(standards.iteh.ai)
<https://standards.iteh.ai/catalog/standards/sist/9b61764a-face-4909-8073-23ea8f3aa782/iec-63173-1-2021>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 47.020.70

ISBN 978-2-8322-9888-6

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	10
INTRODUCTION.....	12
1 Scope.....	13
2 Normative references	13
3 Terms and definitions	13
4 Abbreviated terms	14
5 General description	15
5.1 General data product description	15
5.2 Data product specification metadata	15
5.3 Product specification maintenance.....	16
5.4 Specification scopes	16
5.5 Dataset identification	16
6 Data content and structure	16
6.1 General.....	16
6.2 Application schema.....	17
6.4 Geometry.....	19
6.5 Coordinate reference systems.....	19
7 Feature catalogue.....	19
7.1 General.....	19
7.2 Feature types.....	20
7.2.1 Geographic.....	20
7.2.2 Meta.....	20
7.2.3 Route.....	20
7.2.4 RouteActionPoints	20
7.2.5 RouteActionPoint.....	21
7.2.6 RouteWaypoints	25
7.2.7 RouteWaypoint	25
7.2.8 RouteWaypointLeg	28
7.3 Information types	33
7.3.1 General	33
7.3.2 RouteSchedules	33
7.3.3 RouteSchedule	33
7.3.4 RouteScheduleManual/RouteScheduleCalculated/ RouteScheduleRecommended	36
7.3.5 RouteScheduleElement	36
7.3.6 RouteInfo.....	36
7.4 Association roles of feature catalogue.....	45
7.5 Associations of feature catalogue	46
7.5.1 General	46
7.5.2 Feature association	46
7.5.3 Information association.....	46
7.6 Attributes	47
7.6.1 General	47
7.6.2 Simple attribute types	47
7.6.3 Complex attributes	48
7.6.4 Spatial attribute types	49

ITeH STANDARD PREVIEW

(standards.iteh.ai)

[IEC 63173-1:2021](https://standards.iteh.ai/catalog/standards/sist/9b61764a-facc-4909-8073-23ca8f3aa782/iec-63173-1-2021)

[https://standards.iteh.ai/catalog/standards/sist/9b61764a-facc-4909-8073-](https://standards.iteh.ai/catalog/standards/sist/9b61764a-facc-4909-8073-23ca8f3aa782/iec-63173-1-2021)

[23ca8f3aa782/iec-63173-1-2021](https://standards.iteh.ai/catalog/standards/sist/9b61764a-facc-4909-8073-23ca8f3aa782/iec-63173-1-2021)

7.7	Binding	49
7.7.1	General	49
7.7.2	Feature binding	49
7.7.3	Information binding	50
8	Data type and structure of transmission format	51
9	Maintenance	51
9.1	Feature and portrayal catalogue management	51
9.1.1	Feature catalogue management.....	51
9.1.2	Portrayal catalogue management.....	51
9.2	Data source	52
9.3	Production process	52
10	Portrayal.....	52
10.1	General.....	52
10.2	Portrayal catalogue.....	52
11	Data product delivery.....	53
11.1	General.....	53
11.2	Single XML file.....	53
11.3	Compressed data container	54
11.4	S-100-compliant exchange set.....	54
11.4.1	General.....	54
11.4.2	Exchange set.....	54
11.4.3	Dataset.....	55
11.4.4	Exchange catalogue.....	55
11.4.5	Digital signature	55
11.4.6	Encryption.....	55
11.4.7	Metadata	56
12	Test methods and expected results	59
12.1	General.....	59
12.2	Test data	60
12.2.1	Test material	60
12.2.2	Minimum generic test data.....	60
12.2.3	Basic generic test data	61
12.2.4	Full generic test data	62
12.3	Route plan test	63
12.3.1	General	63
12.3.2	Minimum generic route plan test.....	63
12.3.3	Basic generic route plan test	64
12.3.4	Full generic route plan test	68
Annex A	(normative) Examples of use cases for route	75
A.1	General.....	75
A.2	Route cross check	75
A.2.1	Description	75
A.2.2	Information exchange diagram.....	76
A.2.3	State transition diagram.....	77
A.2.4	Required objects and attributes and their usage	78
A.2.5	Test methods and expected results	84
A.3	Flow management.....	86
A.3.1	Description	86

A.3.2	Information exchange diagram.....	87
A.3.3	State transition diagram.....	88
A.3.4	Required objects and attributes and their usage	90
A.3.5	Test methods and expected results	94
A.4	Enhanced monitoring	95
A.4.1	Description	95
A.4.2	Information exchange diagram.....	96
A.4.3	State transition diagram.....	97
A.4.4	Required objects and attributes and their usage	98
A.4.5	Test methods and expected results	102
A.5	Ice navigation	103
A.5.1	Description	103
A.5.2	Information exchange diagram.....	104
A.5.3	State transition diagram ship side.....	105
A.5.4	Shore side	106
A.5.5	Required objects and attributes and their usage	106
A.5.6	Test methods and expected results	109
A.6	Under keel clearance management	110
A.6.1	Description	110
A.6.2	Information exchange diagram.....	112
A.6.3	State transition diagram.....	113
A.6.4	Required objects and attributes and their usage	116
A.6.5	Test methods and expected results	120
A.7	Fleet route planning	123
A.7.1	Description	123
A.7.2	Information exchange diagram.....	123
A.7.3	State transition diagram.....	124
A.7.4	Required objects and attributes and their usage	126
A.7.5	Test methods and expected results	130
A.8	Chart management	131
A.8.1	Description	131
A.8.2	Information exchange diagram.....	132
A.8.3	State transition diagram.....	132
A.8.4	Functional requirement	133
A.8.5	Required objects and attributes and their usage	133
A.8.6	Test methods and expected results	135
A.9	Route optimization	136
A.9.1	Description	136
A.9.2	Information exchange diagram.....	137
A.9.3	State transition diagram.....	138
A.9.4	Required objects and attributes and their usage	139
A.9.5	Test methods and expected results	144
A.10	Port call synchronization	145
A.10.1	Description	145
A.10.2	Information exchange diagram.....	146
A.10.3	State transition diagram.....	148
A.10.4	Required objects and attributes and their usage	150
A.10.5	Test methods and expected results	153
A.11	Reference route	154

ITeH STANDARD PREVIEW
(standards.iteh.ai)

[IEC 63173-1:2021](https://standards.iteh.ai/catalog/standards/sist/9b61764a-face-4909-8073-3ca0151702/iec-63173-1-2021)

[https://standards.iteh.ai/catalog/standards/sist/9b61764a-face-4909-8073-](https://standards.iteh.ai/catalog/standards/sist/9b61764a-face-4909-8073-3ca0151702/iec-63173-1-2021)

[3ca0151702/iec-63173-1-2021](https://standards.iteh.ai/catalog/standards/sist/9b61764a-face-4909-8073-3ca0151702/iec-63173-1-2021)

A.11.1	Description	154
A.11.2	Information exchange diagram.....	155
A.11.3	State transition diagram.....	156
A.11.4	Required objects and attributes and their usage	158
A.11.5	Test methods and expected results	163
A.12	Search and rescue.....	164
A.12.1	Description	164
A.12.2	Information exchange diagram.....	165
A.12.3	State transition diagram.....	166
A.12.4	Required objects and attributes and their usage	167
A.12.5	Test methods and expected results	169
A.13	Summary of objects and attributes used by service scenarios	170
Annex B (normative)	Data classification and encoding guide.....	178
B.1	General.....	178
B.1.1	Overview	178
B.1.2	Descriptive characteristics	178
B.1.3	Spatial characteristics	179
B.2	Attributes	179
B.2.1	General	179
B.2.2	Simple attribute types with acronym.....	180
B.2.3	Mandatory attributes by schema	181
B.2.4	Missing attribute values	182
B.2.5	Multiplicity	183
B.2.6	Spatial attribute types	183
B.2.7	Textual information	183
B.2.8	Attributes referencing external files.....	183
B.2.9	Dates.....	184
B.3	Associations	185
B.3.1	General	185
B.3.2	Association names.....	186
B.3.3	Association roles	186
B.3.4	Use of various associations	186
B.4	Datasets	186
B.5	Metadata	186
B.5.1	General	186
B.5.2	Dataset metadata	187
B.5.3	Support file metadata	189
B.5.4	Exchange set metadata	190
B.5.5	Catalogue file metadata.....	190
B.6	Description of table format for feature and information formats	191
B.7	Feature types.....	193
B.7.1	Feature type in general.....	193
B.7.2	Route	193
B.7.3	RouteActionPoints	195
B.7.4	RouteActionPoint.....	195
B.7.5	RouteWaypoints	197
B.7.6	RouteWaypoint.....	198
B.7.7	RouteWaypointLeg	198
B.8	Information types	200

B.8.1	InformationType in general	200
B.8.2	RouteInfo.....	201
B.8.3	RouteSchedules	202
B.8.4	RouteSchedule	203
B.8.5	RouteScheduleManual.....	204
B.8.6	RouteScheduleCalculated.....	205
B.8.7	RouteScheduleRecommend.....	205
B.8.8	RouteScheduleElement	206
Annex C (informative)	Examples of how to fulfil the requirements of IMO voyage planning.....	208
C.1	General.....	208
C.2	Reference points.....	208
C.3	Astronomical events.....	209
C.4	Under keel clearance	210
C.5	Overhead clearance.....	211
C.6	Regulated areas	213
Annex D (normative)	Route plan feature catalogue and example	216
D.1	Application schema.....	216
D.2	Example	240
Annex E (informative)	Guidelines for GML ID allocation	245
Bibliography	247
<p>iTeh STANDARD PREVIEW (standards.iteh.ai)</p>		
Figure 1	– Route plan application schema.....	18
Figure 2	– RouteWaypointID usage examples: Delete.....	26
Figure 3	– RouteWaypointID usage examples: Insert.....	26
Figure 4	– RouteWaypointLegDistance between WP2 and WP3.....	28
Figure 5	– RouteWaypointLeg parameters belonging to WP3.....	28
Figure 6	– Under-keel clearance example	29
Figure 7	– RouteWaypointLeg limits example.....	30
Figure 8	– State diagram for route status from ship perspective	38
Figure 9	– State diagram of route status from shore perspective.....	38
Figure 10	– S-100 exchange set structure.....	54
Figure 11	– Realization of the exchange set classes	56
Figure 12	– Route exchange set catalogue	57
Figure 13	– Route exchange set	57
Figure 14	– Route exchange set – Example of class details	58
Figure A.1	– Route cross check example	76
Figure A.2	– Interaction diagram.....	77
Figure A.3	– State transition diagram for the route plan onboard.....	78
Figure A.4	– State transition diagram for the route plan onshore.....	78
Figure A.5	– Flow management example	87
Figure A.6	– Data interaction diagram.....	88
Figure A.7	– State transition diagram for the route plan onboard.....	89
Figure A.8	– State transition diagram for the route plan onshore.....	89
Figure A.9	– Enhanced monitoring example	96

Figure A.10 – Information exchange diagram	97
Figure A.11 – State transition diagram for the route plan onboard	97
Figure A.12 – State transition diagram for the route plan onshore	98
Figure A.13 – Ice navigation example	104
Figure A.14 – Interaction diagram on request	105
Figure A.15 – State transition diagram for a ship	105
Figure A.16 – State transition diagram for a shore	106
Figure A.17 – Example of UKCM area	111
Figure A.18 – Example of portrayal of S-421 part of UKCM	111
Figure A.19 – Example of portrayal of S-129 overlay part of UKCM	112
Figure A.20 – Information exchange diagram	113
Figure A.21 – State transition diagram of UKCM for a ship	114
Figure A.22 – State transition diagram of UKCM for a shore	115
Figure A.23 – Information sequence diagram	124
Figure A.24 – State transition diagram for a ship	125
Figure A.25 – State transition diagram for a shore	125
Figure A.26 – Interaction diagram	132
Figure A.27 – Route optimization example	136
Figure A.28 – Interaction diagram on request	137
Figure A.29 – State transition diagram for a ship	138
Figure A.30 – State transition diagram for a shore	139
Figure A.31 – Interaction diagram	147
Figure A.32 – State transition diagram for a ship	149
Figure A.33 – State transition diagram for shore	150
Figure A.34 – Example of reference routes	155
Figure A.35 – Data interaction diagram	156
Figure A.36 – State transition diagram for a ship requesting a reference route	157
Figure A.37 – State transition diagram for a shore center providing a reference route	158
Figure A.38 – A search and rescue example	165
Figure A.39 – Interaction diagram	165
Figure A.40 – State transition diagram for a ship	166
Figure A.41 – State transition diagram for shore	167
Figure B.1 – Association routeInfoComposition	185
Figure B.2 – Metadata packages	187
Figure C.1 – Example of reference point	208
Figure C.2 – Example of presentation of added textual information	209
Figure C.3 – Example of astronomical event	210
Figure C.4 – Example of presentation of added textual information	211
Figure C.5 – Example of presentation of added textual information	214
Figure C.6 – Example of graphical presentation of regulated area	215
Table 1 – Informal description of the data product	15
Table 2 – Data product specification metadata	15

Table 3 – Route plan product specification scope	16
Table 4 – Dataset identification.....	16
Table 5 – Route plan coordinate reference systems.....	19
Table 6 – Route object attributes	22
Table 7 – RouteActionPoints object attributes.....	22
Table 8 – RouteActionPoint object attributes.....	23
Table 9 – Definition of RouteActionPointRequiredAction	24
Table 10 – RouteWaypoints object attributes	24
Table 11 – RouteWaypoint object attributes.....	27
Table 12 – RouteWaypointLeg object attributes	31
Table 13 – RouteSchedules object attributes	34
Table 14 – RouteScheduleManual object attributes.....	34
Table 15 – RouteScheduleCalculated object attributes.....	34
Table 16 – RouteScheduleRecommended object attributes.....	34
Table 17 – RouteSchedule object attributes	35
Table 18 – RouteScheduleElement object attributes	39
Table 19 – RouteInfo object attributes	40
Table 20 – Definition of RouteInfoStatus.....	42
Table 21 – Type of ship	43
Table 22 – Roles of the route plan	45
Table 23 – Feature association for route plan	46
Table 24 – Information association for route plan	47
Table 25 – Simple attribute types	48
Table 26 – RouteExtensions attributes.....	49
Table 27 – Spatial attributes	49
Table 28 – Feature binding for the route plan.....	50
Table 29 – Information binding for the route plan	51
Table 30 – Information binding for the route plan portrayal catalogue	52
Table 31 – Dataset metadata	59
Table A.1 – Objects and attributes used by route cross check.....	79
Table A.2 – Test procedures for route cross check	84
Table A.3 – Objects and attributes used by flow management.....	91
Table A.4 – Test procedures for flow management	94
Table A.5 – Objects and attributes used by enhanced monitoring	99
Table A.6 – Test procedures for enhanced monitoring	102
Table A.7 – Objects and attributes used by ice navigation	107
Table A.8 – Test procedures for ice navigation	109
Table A.9 – Objects and attributes used by UKCM.....	117
Table A.10 – Test procedures for UKCM.....	120
Table A.11 – Objects and attributes used by fleet route planning.....	127
Table A.12 – Test procedures for fleet route planning.....	130
Table A.13 – Objects and attributes used by chart management	134
Table A.14 – Test procedures for chart management.....	135

ITeH STANDARD PREVIEW
(standards.iteh.ai)

IEC 63173-1:2021
<https://standards.iteh.ai/catalog/standards/sist/9b61764a-facc-4909-8073-33ca8f3aa782/iec-63173-1-2021>

Table A.15 – Objects and attributes used by route optimization	140
Table A.16 – Test procedures for route optimization	144
Table A.17 – Objects and attributes used by port call synchronization	151
Table A.18 – Test procedures for port call synchronization	153
Table A.19 – Objects and attributes used by reference route	159
Table A.20 – Test procedures for reference route	163
Table A.21 – Objects and attributes used by Search and Rescue	168
Table A.22 – Test procedures for Search and Rescue	169
Table A.23 – Objects and attributes used by service scenarios as seen from the ship	170
Table B.1 – Feature types	179
Table B.2 – Simple attribute types	180
Table B.3 – Mandatory attribute types	182
Table B.4 – Multiplicity	183
Table B.5 – Predefined derived types	184
Table B.6 – File format	184
Table B.7 – Truncated dates	185
Table B.8 – Dataset types	186
Table B.9 – Metadata for route plan	188
Table B.10 – Support files for route plan	190
Table B.11 – File metadata for route plan	191
Table B.12 – Example of table format for feature	192
Table B.13 – General feature types	193
Table B.14 – Table format for Route	194
Table B.15 – Table format for RouteActionPoints	195
Table B.16 – Table format for RouteActionPoint	196
Table B.17 – Table format for RouteWayPoints	197
Table B.18 – Table format for RouteWaypoint	198
Table B.19 – Table format for RouteWaypointLeg	199
Table B.20 – General information types	200
Table B.21 – Table format for RouteInfo	201
Table B.22 – Table format for RouteSchedules	202
Table B.23 – Table format for RouteSchedule	203
Table B.24 – Table format for RouteScheduleManual	204
Table B.25 – Table format for RouteScheduleCalculated	205
Table B.26 – Table format for RouteScheduleRecommend	206
Table B.27 – Table format for RouteScheduleElement	207
Table E.1 – Example of GML ID	245

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**MARITIME NAVIGATION AND RADIOCOMMUNICATION
EQUIPMENT AND SYSTEMS – DATA INTERFACES –**

Part 1: S-421 route plan based on S-100

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 63173-1 has been prepared by IEC technical committee 80: Maritime navigation and radiocommunication equipment and systems. It is an International Standard.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
80/997/FDIS	80/1000/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

A list of all parts in the IEC 63173 series, published under the general title *Maritime navigation and radiocommunication equipment and systems – Data interfaces*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

ITeH STANDARD PREVIEW
(standards.iteh.ai)

[IEC 63173-1:2021](https://standards.iteh.ai/catalog/standards/sist/9b61764a-face-4909-8073-23ea8f3aa782/iec-63173-1-2021)

<https://standards.iteh.ai/catalog/standards/sist/9b61764a-face-4909-8073-23ea8f3aa782/iec-63173-1-2021>

INTRODUCTION

The voyage plan is a key element of a vessel's voyage and can be used to optimize safety and processes, as well as for the interaction of participants and stakeholders.

The core element of the voyage plan is the route.

The exchange of routes (whether it be between ship-to-ship, ship-to-shore or shore-to-shore) may improve

- situational awareness,
- reduction in the number of accidents and incidents (by proactively de-conflicting routes),
- resource utilization by knowing the intentions of other actors,
- secured passages by knowing the intentions of other actors,
- predictability of arrivals and departures by early information sharing,
- planning for involved actors leading to reduced idle time for resources, and
- just-in-time operations by enabling stakeholders and service providers to be efficiently organized for handling vessel movements, port resources, and hinterland connections.

This document has been registered with the IHO S-100 registry as product specification S-421. A S-100 product specification is a description of the features, attributes and relationships of an application and their mapping to a dataset. It is a complete description of all the elements required to define a particular geographic data product.

IHO S-97 describes readiness levels of product specifications to show a progression from an idea to regular use. S-421 is currently at the initial level 1 pending demonstration in a real-world environment.

[IEC 63173-1:2021](https://standards.iteh.ai/catalog/standards/sist/9b61764a-face-4909-8073-23ca8f3aa782/iec-63173-1-2021)

[https://standards.iteh.ai/catalog/standards/sist/9b61764a-face-4909-8073-](https://standards.iteh.ai/catalog/standards/sist/9b61764a-face-4909-8073-23ca8f3aa782/iec-63173-1-2021)

S-100 uses camelCase for naming. CamelCase names are made up of words joined together without spaces and capitalised within the compound using a limited set of English letters. Feature and information types begin with uppercase A-Z and attributes and values begin with lowercase a-z.

MARITIME NAVIGATION AND RADIOCOMMUNICATION EQUIPMENT AND SYSTEMS – DATA INTERFACES –

Part 1: S-421 route plan based on S-100

1 Scope

This part of IEC 63173 specifies an S-100 compliant product specification for route plan intended for exchange of information. It specifies the content, structure, and metadata needed for creating fully S-100 compliant route plan information and its portrayal within an S-100-based application. The IHO manages all numbers for S-100 compliant product specifications and has assigned S-421 for this route plan IEC standard.

This document specifies only a data format for the route plan exchange. This document does not specify a data format of vessel monitoring and logging information. This information can be provided by other mechanisms or be specified in other standards.

The format of the route plan exchange includes some limited vessel static information. When more static information is required, it can be obtained by other methods such as AIS.

2 Normative references

iTeh STANDARD PREVIEW
(standards.iteh.ai)

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

S-100:2018, *IHO Universal Hydrographic Data Model* (edition 4.0.0)

3 Terms and definitions

For the purposes of this document, the following terms, definitions and abbreviated terms apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1

active route

route which is currently monitored for the voyage which may contain the schedule information

3.2

actor

human or machine that takes part in the route plan exchange process

3.3

feature

abstraction of real-world phenomena

Note 1 to entry: A feature may occur as a type or an instance. A feature type or a feature instance should be used when only one is meant as described in S-100.