

INTERNATIONAL STANDARD

ISO
4548-1

First edition
1997-09-15

Methods of test for full-flow lubricating oil filters for internal combustion engines —

Part 1:

Differential pressure/flow characteristics

*Méthodes d'essai des filtres à huile de lubrification à passage intégral pour
moteurs à combustion interne —*

Partie 1: Caractéristique débit/pression différentielle

(<https://standards.iteh.ai/>)
Document Preview

ISO 4548-1:1997

<https://standards.iteh.ai/catalog/standards/iso/56a4a5ec-723b-4674-9a0d-774d2c7a17ba/iso-4548-1-1997>



Reference number
ISO 4548-1:1997(E)

Contents

1 Scope	1
2 Normative references	1
3 Definitions	1
4 Graphical Symbols	1
5 Operational characteristics to be tested	1
6 Filter to be tested	2
6.1 Filter type	2
6.2 Filter element	2
7 Test rig	2
7.1 Sump	2
7.2 Regulating valves	2
7.3 Flow meter	2
7.4 Filter mounting	4
8 Test liquids	4
9 Accuracy of test condition measurements	7
10 Test procedure	7
10.1 Test of the complete filter	7
10.2 Test of the filter element	7
11 Report of test results	7
Annex A (informative) Bibliography	9

© ISO 1997

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case postale 56 • CH-1211 Genève 20 • Switzerland
Internet central@iso.ch
X.400 c=ch; a=400net; p=iso; o=isocs; s=central

Printed in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 4548-1 was prepared by Technical Committee ISO/TC 70, *Internal combustion engines*, Subcommittee SC 7, *Tests for lubricating oil filters*.

This second edition cancels and replaces the first edition (ISO 4548-1:1982), which has been technically revised.

ISO 4548 consists of the following parts, under the general title *Methods of test for full-flow lubricating oil filters for internal combustion engines*:

- Part 1: Differential pressure/flow characteristics
- Part 2: Element by-pass valve characteristics
- Part 3: Resistance to high differential pressure and to elevated temperature
- Part 4: Initial particle retention efficiency, life and cumulative efficiency (gravimetric method)
- Part 5: Cold start simulation and hydraulic pulse durability test
- Part 6: Static burst pressure test
- Part 7: Vibration fatigue test
- Part 9: Inlet and outlet anti-drain valve tests
- Part 10: Life and cumulative efficiency in the presence of water in oil
- Part 11: Self-cleaning filters
- Part 12: Particle retention ability and contaminant holding capacity using particle counting

Annex A of this part of ISO 4548 is for information only.

Introduction

ISO 4548 establishes standard test procedures for measuring the performance of full-flow lubricating oil filters for internal combustion engines. It has been prepared in separate parts, each part relating to a particular performance characteristic.

Together the tests provide the information necessary to assess the characteristics of a filter, but if agreed between the purchaser and the manufacturer, the tests may be conducted separately.

This revision of this part of ISO 4548 has been undertaken in order to align the presentation with the requirements of the current ISO Directives. The principal changes are editorial, affecting the layout and the text. Minor technical changes comprise the inclusion of ISO VG and SAE oil grades for the test liquids, and revision of the test rig dimensions to make them consistent with those specified in ISO 3968. In addition, the flow meter on the test rig has been repositioned downstream of the throttle valve.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO 4548-1:1997](https://standards.iteh.ai/catalog/standards/iso/56a4a5ec-723b-4674-9a0d-774d2c7a17ba/iso-4548-1-1997)

<https://standards.iteh.ai/catalog/standards/iso/56a4a5ec-723b-4674-9a0d-774d2c7a17ba/iso-4548-1-1997>

Methods of test for full-flow lubricating oil filters for internal combustion engines —

Part 1: Differential pressure/flow characteristics

1 Scope

This part of ISO 4548 specifies tests for determining the differential pressure/flow characteristics of full-flow lubricating oil filters for internal combustion engines.

Tests are specified with oils at two viscosities, one to assess the performance of a filter with a cold oil and the other to assess its performance with an oil at a typical operating temperature.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this part of ISO 4548. At the time of publication, the editions indicated were valid. All standards are subject to revision and parties to agreement based on this part of ISO 4548 are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 1219-1:1991, *Fluid power systems and components — Graphic symbols and circuit diagrams — Part 1: Graphic symbols*.

ISO 11841-1:—¹⁾, *Road vehicles and internal combustion engines — Filter vocabulary — Part 1: Definitions of filters and filter components*.

ISO 11841-2:—¹⁾, *Road vehicles and internal combustion engines — Filter vocabulary — Part 2: Definitions of characteristics of filters and their components*.

3 Definitions

For the purposes of this part of ISO 4548, the definitions given in ISO 11841-1 and ISO 11841-2 apply.

4 Graphical Symbols

The graphical symbols used in this part of ISO 4548 are in accordance with ISO 1219-1.

5 Operational characteristics to be tested

A full-flow lubricating oil filter in an internal combustion engine, interposed between the oil pump and the working parts of the engine, necessarily reduces the effective oil pressure available to the engine below the pressure delivered by the pump.

1) To be published.

In order to ensure an adequate oil pressure to the engine, it is customary for the filter to be designed to pass its full rated flow with no more than a specified differential pressure. The tests specified in this part of ISO 4548 measure the differential pressure across a complete filter assembly, in a clean condition, over the whole range of oil flow rates.

The differential pressure across the complete filter is due to the pressure at the inlet and outlet of the filter, including any casting or adaptor which is part of the filter assembly, and at the anti-drain back valve, if one is fitted, as well as to the differential pressure across the filter element itself. For some purposes, it is necessary to know the differential pressure across the filter alone, for example in assessing the performance of the element in the case of some combinations of filter medium and contaminant. In addition to the tests indicated above, the tests specified measure the differential pressure across a clean filter element over the whole range of oil flow rates.

6 Filter to be tested

6.1 Filter type

For the purpose of mounting the filter under test in the test rig, the following types of filter are recognised:

- a) spin-on filters in which the replaceable unit does not include a filter head (it may or may not include the element by-pass valve);
- b) spin-on filters in which the replaceable unit incorporates a filter head that includes the element by-pass valve;
- c) other filters, usually of the replacement element type and usually including their own filter head.

6.2 Filter element

The filter element for the test shall be unused and the test liquid and the test rig shall be clean. For the purposes of this part of ISO 4548, the term "clean" means that there is no detectable increase in differential pressure across a filter of the type under test when the test liquid at the test temperature is circulated through the test rig and the filter, at the rated flow of the filter, for 5 min.

7 Test rig

The test rig is shown diagrammatically in figure 1. It shall include the components described in 7.1 to 7.4, together with the necessary tubing, connectors and supports.

7.1 Sump

The sump shall be capable of holding sufficient oil and shall be equipped with a thermostatically controlled heater and cooler capable of maintaining the test temperature. The heater shall be arranged so that local overheating of the oil is avoided. The by-pass return to the sump and the filter outlet pipe shall terminate below the surface of the oil in the sump when the oil is in circulation. The temperature shall be arranged so that the stipulated viscosity is maintained.

7.2 Regulating valves

The regulating valves, 3 and 11, shall be used for the purposes of pressure and flow control. Needle valves of diaphragm type valves are recommended.

7.3 Flow meter

The flow meter shall be suitable for use with oils of 24 mm²/s²⁾ and 500 mm²/s kinematic viscosity and shall register the flow in the pipeline leading to the filter. As an alternative, the flow meter may be installed at the filter outlet pipe. A calibrated measuring vessel and stop watch may be used.

2) 1 mm²/s = 1 cSt