INTERNATIONAL STANDARD

ISO/IEC 8632-3

Second edition 1992-10-01 **AMENDMENT 1** 1994-12-15

Information technology — Computer graphics — Metafile for the storage and transfer of picture description information —

iTeh STart 3DARD PREVIEW (Standards.iteh.ai)

AMENDMENT 1: Rules for profiles

https://standards.iteh.ai/catalog/standards/sist/04d14a73-1c5f-475a-be3c-9ad3df3b4705/iso-iec-8632-3-1992-amd-1-1994

Technologies de l'information — Infographie — Métafichier de stockage et de transfert des informations de description d'images —

Partie 3: Codage binaire

AMENDEMENT 1: Règles pour profils



Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75% of the national bodies casting a vote.

Amendment 1 to International Standard ISO/IEC 8632-3:1992 was prepared by Joint Technical Committee ISO/IEC JTC 1, Information technology, Subcommittee 24, Computer graphics and image processing 3:1992/Amd 1:1994

ndards.iteh.ai/catalog/standards/sist/04d14a73-1c5f-475a-be3c-9ad3df3b4705/iso-iec-8632-3-1992-amd-1-1994

© ISO/IEC 1994

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case postale 56 • CH-1211 Genève 20 • Switzerland Printed in Switzerland

Page iii

Information technology — Computer graphics — Metafile for the storage and transfer of picture description information —

Part 3: Binary encoding

AMENDMENT 1: Rules for profiles

Add to Contents: "10 Encoding rules, proforma, and Model Profile

Clause 9, page 59

Add a new sentence before the first sentence:

iTeh STANDARD PREVIEW

"Conformance of metafiles to ISO/IEC 8632 is defined in terms of profiles."

Change the first sentence to read: ISO/IEC 8632-3:1992/Amd 1:1994

"A metafile conforms to this binary encoding strait conforms to a profile and meets the following requirements."

Change the first bullet item to read:

"— Each metafile element described in this part is coded in the manner described in this International Standard and a profile."

Add a new clause 10 after page 59

"10 Encoding rules, proforma, and Model Profile

10.1 General principles

10.1.1 Encodings

Precisions are defined consistently with the principles of the encodings, not necessarily for inter-encoding translation. Where both considerations might apply, compatibility with the principles of the encoding are considered first and inter-encoding translation second.

10.1.2 Metafile defaults

Clause 8 addresses all elements which have default values. While no profile can change these values, an equivalent effect may be achieved by use of the METAFILE DEFAULTS REPLACEMENT element. Profiles may require that a metafile contain a METAFILE DEFAULTS REPLACEMENT element with well-defined content.

10.1.3 Floating point values

Profiles shall prohibit the values NaN, positive infinity, and negative infinity for ANSI/IEEE 754 floating point numbers (see 5.5). For 32-bit floating point, NaN corresponds to e=255 and $f\neq 0$. For 64-bit floating point, NaN corresponds to e=2047 and $f\neq 0$. For 32-bit floating point, positive and negative infinity are defined respectively by s=0 and s=1, with e=255 and f=0. For 64-bit floating point, positive and negative infinity are defined respectively by s=0 and s=1, with e=2047 and f=0.

10.2 Profile Poforma tables

The Profile Proforma is contained in table 12 and table 13. These tables, when completed by the author of the profile, contain the normative specifications of the profile.

iTeh STANDARD PREVIEW

The PPF tables have 3 columns:

(standards.iteh.ai)

- The first identifies the element to be addressed.
 - ISO/IEC 8632-3:1992/Amd 1:1994
- The second is the template for the profile writer to complete.
- The third is the completed specification for the Model Profile.

Each element to be addressed comprises a "row" of the table.

The first column of each row contains:

- 1) A unique identifier for that row, T.n.m, indicating that this is row "m" of table "n". For example, row T.12.2 is the second row of table 12 (for the REAL PRECISION element).
- 2) The name of the element for that row, for example, REAL PRECISION.
- 3) The lowest metafile version (v1, v2, or v3) for which each element is defined.
- 4) References to other sections of this clause, for additional normative or informative material.

A second column is the PPF template for profile authors. Each row contains:

5) A check box indicating that all specifications for this row for this profile are exactly the same as those for this row in the Model Profile.

- 6) Check boxes to indicate whether the element is required, permitted, or prohibited in metafiles conforming to the profile. If the check box choice is limited, then only the allowable check boxes are given. For example, if the element shall not be prohibited, then the "prohibited" check box is omitted.
- 7) One or more specific specifications which are to be addressed by all profile authors.
- 8) A general category, "Other:", in which profile authors may add any additional specifications which are consistent with the rules for profiles in this clause.

A third column is the Model Profile specification. Each row contains:

- 9) A checked box indicating the element status.
- 10) The specifications of the Model Profile.

The check box to indicate the element status (i.e., required, permitted, or prohibited) shall be consistent with the element status in the PPF completed for part 1 of ISO/IEC 8632.

If the "Same as Model Profile" box is checked for a row, then no further information need be supplied for the profile in that row — all specifications for that row match the Model Profile.

Teh STANDARD PREVIEW

Otherwise, the profile shall have complete information for all column 2 items within a row. It is acceptable in most cases to simply refer to the Model Profile, with the words "as Model Profile".

Rules presented as statements and ending with a semicolin (":"), shall be completed with specific information. In most cases, these rules may be prefaced with "Profiles shall specify...". Rules presented as questions and ending with a question mark ("?"), are optional, and shall be completed with either specific information or the word "none". In most cases, these rules may be prefaced with "Profiles may specify any ...".

The category "Other:" shall be completed with either: the word "none"; or, with specific information.

It is possible that specific information for some items may be too much to fit into the table space provided. In this case, the table entry shall specify (assuming that this is row T.n.m), "see Attachment n.m", and the specification shall be put into an attachment labelled "Attachment n.m".

Profile authors shall complete all required information in the template, column 2 of the PPF tables. Profiles may contain any other specifications, parameter restrictions, etc., unless explicitly prohibited by the rules of this clause and the PPF tables.

Table 12 - Delimiter elements

	Specifications - PPF	Specifications - Model Profile
T.12.1 Same	Same as Model Profile	
no-op iTeh Eleme [v1]	Teh Element is: Required [Permitted [] [] []	Element is: Required Permitted
nces:	Any restrictions on the parameter value?	Any restrictions on the parameter value? None.
7.2 Other	Other. 150/IEC 8632-3:1992/Amd 1:1994 Is iteh ai/cataloo/standards/sist/04d14a73-1c5f-475a-he3c-	Other: None.

Table 13 - Metafile descriptor elements

Element	Specifications - PPF	Specifications - Model Profile
T.13.1	Same as Model Profile	
INTEGER Teh	eh Element is Required D Permitted DIE W	Element is: Required Permitted
[v1]	Any restrictions on the parameter value?	Any restrictions on the parameter value? 8, 16, or 32.
References: 7.3 https://standar	ces: Other: SO/IEC 8632-3:1992/Amd 1:1994 Intro-Vistandards iteh ai/cataloc/standards/sist/0.0d/1.4a73_1.c5£475a_he3c_	Other: None.
T.13.2 9ad	13dBb4705/iso-jec-8632-f=1992-amd-1-1994 Same as Model Profile	
REAL PRECISION [v1]	Element is: Required Permitted Prohibited	Element is: Required 🔲 Permitted 🗹
References: 7.3	Any restrictions on the parameter value?	Any restrictions on the parameter value? (I, 16, 16) or (0, 9, 23).
	Other:	Other: None.
T.13.3	Same as Model Profile	
INDEX PRECISION	Element is: Required 🔲 Permitted 📋	Element is: Required 🔲 Permitted 🗹
[v1]	Any restrictions on the parameter value?	Any restrictions on the parameter value? 8, 16, or 32.
References: 7.3	Other:	Other: None.

Table 13 - Metafile descriptor elements (continued)

Element	Specifications - PPF	Specifications - Model Profile
T.13.4	Same as Model Profile	
COLOUR ITTEH PRECISION [v1]	Element is: Required Permitted Standards iteh ail Any restrictions on the parameter value?	Element is: Required Permitted M Any restrictions on the parameter value?
References: 7.3 https://standar	letps://standardsoinlee.i/catalog/standards/sist/04d14a73-1c5f-475a-be3c-9ad3di3b4705/iso-iec-8632-3-1992-amd-1-1994	8 or 16. Other: None.
T.13.5	Same as Model Profile	
COLOUR INDEX PRECISION [v1]	Element is: Required 🔲 Permitted 🔲	Element is: Required 🔲 Permitted 🗹
References: 7.3	Any restrictions on the parameter value?	Any restrictions on the parameter value? 8 or 16.
	Other:	Other: None.
T.13.6	Same as Model Profile	
NAME PRECISION	Element is: Required 🔲 Permitted 📋	Element is: Required 🔲 Permitted 🗹
[v2]	Any restrictions on the parameter value?	Any restrictions on the parameter value? 16 or 32.
7.3	Other:	Other: None.

Table 14 - Control elements

Element	Specifications - PPF	Specifications - Model Profile
T.14.1	Same as Model Profile	
INTEGER I	Element is Required Demitted DIF W	Element is: Required 🔲 Permitted 🗹
[v1]	Any restrictions on the parameter value?	Any restrictions on the parameter value? 16 or 32.
References: 7.5	Other: Other: SO/IEC 8632-3:1992/Amd 1:1994	Other: None.
T.14.2	9ad3df3b4705/iso-jec-8632-3-1992-amd-1-1994 Same as Model Profile	
VDC REAL PRECISION	Element is: Required	Element is: Required Permitted
[v1]	Any restrictions on the parameter value?	Any restrictions on the parameter value? (I, 16, 16) or
References: 7.5	Other:	(v, y, 32). Other: <i>None</i> .