



Edition 3.1 2015-11 CONSOLIDATED VERSION

INTERNATIONAL STANDARD

NORME INTERNATIONALE



High-voltage test techniques – Partial discharge measurements

Techniques des essais à haute tension - Mesures des décharges partielles

Document Preview

IEC 60270:2000

https://standards.iteh.ai/catalog/standards/iec/62c87e98-bd7d-455a-b69a-b643fb0f7fld/iec-60270-2000





THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2015 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office	Tel.: +41 22 919 02 11
3, rue de Varembé	Fax: +41 22 919 03 00
CH-1211 Geneva 20	info@iec.ch
Switzerland	www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished 602

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in 15 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

More than 60 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Catalogue IEC - webstore.iec.ch/catalogue

Application autonome pour consulter tous les renseignements bibliographiques sur les Normes internationales, Spécifications techniques, Rapports techniques et autres documents de l'IEC. Disponible pour PC, Mac OS, tablettes Android et iPad.

Recherche de publications IEC - www.iec.ch/searchpub

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études,...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire en ligne de termes électroniques et électriques. Il contient plus de 30 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans 15 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Glossaire IEC - std.iec.ch/glossary

Plus de 60 000 entrées terminologiques électrotechniques, en anglais et en français, extraites des articles Termes et Définitions des publications IEC parues depuis 2002. Plus certaines entrées antérieures extraites des publications des CE 37, 77, 86 et CISPR de l'IEC.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: csc@iec.ch.





Edition 3.1 2015-11 CONSOLIDATED VERSION

INTERNATIONAL STANDARD

NORME INTERNATIONALE



High-voltage test techniques - Partial discharge measurements

Techniques des essais à haute tension – Mesures des décharges partielles

IEC 60270:2000

https://standards.iteh.ai/catalog/standards/iec/62c87e98-bd7d-455a-b69a-b643fb0f7fld/iec-60270-2000

INTERNATIONAL ELECTROTECHNICAL COMMISSION

COMMISSION ELECTROTECHNIQUE INTERNATIONALE

ICS 17.220.20; 19.080

ISBN 978-2-8322-3053-4

Warning! Make sure that you obtained this publication from an authorized distributor. Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

 Registered trademark of the International Electrotechnical Commission Marque déposée de la Commission Electrotechnique Internationale

iTeh Standards (https://standards.iteh.ai) Document Preview

IEC 60270:2000

https://standards.iteh.ai/catalog/standards/iec/62c87e98-bd7d-455a-b69a-b643fb0f7f1d/iec-60270-2000





Edition 3.1 2015-11 CONSOLIDATED VERSION

REDLINE VERSION

VERSION REDLINE



High-voltage test techniques – Partial discharge measurements

Techniques des essais à haute tension - Mesures des décharges partielles

Document Preview

IEC 60270:2000

https://standards.iteh.ai/catalog/standards/iec/62c87e98-bd7d-455a-b69a-b643fb0f7fld/iec-60270-2000



CONTENTS

	FO	FOREWORD				
	1 Scope					
	2	Norm	ative re	ferences	7	
Ē	3	Term	s and de	efinitions	8	
l	4	Test circuits and measuring systems				
	•	1 1	Genera	and modeling operations	12	
		4.1	Test ci	requirements	12 13	
		4.3	Measu	ring systems for apparent charge	13	
		4.0	4.3.1	General	13	
			4.3.2	Coupling device	13	
			4.3.3	Pulse train response of instruments for the measurement of apparent charge		
			4.3.4	Wide-band PD instruments	14	
			4.3.5	Wide-band PD instruments with active integrator	15	
			4.3.6	Narrow-band PD instruments	15	
		4.4	Require	ements for measurements with digital PD-instruments	15	
			4.4.1	Requirements for measurement of apparent charge <i>q</i>	16	
			4.4.2	Requirements for measurement of test voltage magnitude and phase	16	
		4.5	Measu	ring systems for derived quantities	16	
			4.5.1	Coupling device	16	
			4.5.2	Instruments for the measurement of pulse repetition rate n	16	
			4.5.3	Instruments for the measurement of average discharge current /	16	
			4.5.4	Instruments for the measurement of discharge power P	17	
			4.5.5	Instruments for the measurement of quadratic rate D	17	
			4.5.6	Instruments for the measurement of the radio disturbance voltage	70-1700	
		4.6	Ultra-w	vide-band instruments for PD detection	17	
	5	Calib	alibration of a measuring system in the complete test circuit		18	
		5.1	Genera	al	18	
		5.2	Calibra	tion procedure	18	
	6 Calibrators				19	
	6.1 General		al	19		
6.2 Calibrators for the calibration		Calibra	tors for the calibration of a measuring system in the complete test circuit	20		
		6.3	Calibra	tors for performance tests on measuring systems	20	
	7	Main	taining t	he characteristics of calibrators and measuring systems	20	
		7.1	Schedu	ule of tests	21	
		7.2	Maintai	ining the characteristics of calibrators	21	
			7.2.1	Type tests on calibrators	21	
			7.2.2	Routine tests on calibrators	21	
			7.2.3	Performance tests on calibrators	21	
			7.2.4	Performance checks on calibrators	21	
			7.2.5	Record of performance	22	
		7.3	Maintai	ining the characteristics of measuring systems	22	
			7.3.1	I ype tests on PD measuring systems	22	
			7.3.2	Routine tests on measuring systems	23	
			7.3.3	Performance tests on measuring systems	23	
			7.3.4	Performance checks for measuring systems	23	

©II	EC 20	15		
		7.3.5	Checks for additional capabilities of digital measuring systems	2
		7.3.6	Record of performance	2
8	Tests			2
	8.1	Gener	al requirements	2
	8.2	Condit	tioning of the test object	2
	8.3	Choice	e of test procedure	2
		8.3.1 8.3.2	Determination of the partial discharge inception and extinction voltages Determination of the partial discharge magnitude at a specified test voltage	s 2 2
9	Meas	uring u	ncertainty and sensitivity	2
10	Distu	rbance	s	2
11	Parti	al disch	arge measurements during tests with direct voltage	2
•••	11 1	Conor	al	2 ເ
	11.1		antities <u>-related to partial discharges</u>	22
	11.3	Voltad	es related to partial discharges	2 2
		11.3.1	Partial discharge inception and extinction voltages	2
		11.3.2	Partial discharge test voltage	2
	11.4	Test c	ircuits and measuring systems	2
	11.5	Tests.		2
		11.5.1	Choice of test procedures	2
		11.5.2	Disturbances	2
Anr	nex A	(norma 		3
Anr	nex B	(inform	ative) Test circuits	4
Anr cap	nex C bacitor	(inform s and o	ative) Measurements on cables, gas insulated switchgear, power n test objects with windings	4
Anr for	nex D the de	(inform etection	ative) The use of radio disturbance (interference) meters of partial discharges	4
Anr PD	nex E meas	(inform uring in	ative) Guidelines to digital acquisition of partial discharge quantities struments	4
Anr	nex F	(informa	ative) Non-electrical methods of PD detection	5
Anr	nex G	(inform	ative) Disturbances	5
Anr	nex H	(inform	ative) Evaluation of PD test results during tests with direct voltage	5
Bib	liograp	ohy		5
Fig	ure 1 -	- Basic	partial discharge test circuits	3
Fig	ure 2 -	– Test o	circuit for measurement at a tapping of a bushing	3
Fig	ure 3 -	– Test o	circuit for measuring self-excited test objects	3
Fig	ure 4 -	- Conn	ections for the calibration of the complete test arrangement	3
Fig inte	ure 5 - egratio	- Corre n errors	ct relationship between amplitude and frequency to minimize s for a wide-band system	3
Fia	ure 6 -	- Step y	voltage parameters of a calibrator	
Fig	ure A	1 – Cal	ibration of pulse calibrators	3
Fig		2 _ Sot	up for performance tests of calibrators using the numerical integration	סס ב
' iy	uie A.	2 - 381	up for performance lesis of calibrators using the numerical integration	

Figure A.4 – Impact of the series resistor R_s on the step voltage response appearing across C_m using the circuit according to Figure A.3, where the oscilloscope was connected to the calibrator via a 50 Ω measuring cable of 1 m long.	40
Figure D.1 – Variation of CISPR radio disturbance meter reading $f(N)$ with repetition frequency N , for constant pulses	45
Figure E.1 – Output voltage signals U_{out} of two different PD measuring systems for apparent charge (double pulse)	48
Figure E.2 – Block diagram of an analogue PD instrument equipped with an electronic integrator	49
Figure E.3 – Block diagram of digital PD instruments	50
Figure E.4 – Example for a phase-resolved PD pattern	51
Figure H.1 – Display modes of apparent pulses against measuring time	56
Figure H.2 – Histograms of PD pulse count <i>m</i> against apparent charge intervals	57

Table 1 – Pulse train response of PD instruments	. 14
Table 2 – Tests required for calibrators	.21
Table 3 – Tests required for measuring systems	. 24

iTeh Standards (https://standards.iteh.ai) Document Preview

IEC 60270:2000

https://standards.iteh.ai/catalog/standards/iec/62c87e98-bd7d-455a-b69a-b643fb0f7fld/iec-60270-2000

INTERNATIONAL ELECTROTECHNICAL COMMISSION

HIGH-VOLTAGE TEST TECHNIQUES – PARTIAL DISCHARGE MEASUREMENTS

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies. 0.2000
- 6) All users should ensure that they have the latest edition of this publication. 9a-b643 (b0)711 d/ac-60270-2000
 - 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
 - 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
 - 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of the official IEC Standard and its amendment has been prepared for user convenience.

IEC 60270 edition 3.1 contains the third edition (2000-12) [documents 42/162/FDIS and 42/165/ RVD] and its corrigendum 1 (2001-10), and its amendment 1 (2015-11) [documents 42/338/FDIS and 42/340/RVD].

In this Redline version, a vertical line in the margin shows where the technical content is modified by amendment 1. Additions are in green text, deletions are in strikethrough red text. A separate Final version with all changes accepted is available in this publication.

International Standard IEC 60270 has been prepared by IEC technical committee 42: High-voltage test techniques.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 3.

Annex A forms an integral part of this standard.

Annexes B, C, D, E, F and G are for information only.

Terms used throughout this standard which have been defined in clause 3: **bold roman type**.

The committee has decided that the contents of the base publication and its amendment will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

Document Preview

IEC 60270:2000

https://standards.iteh.ai/catalog/standards/iec/62c87e98-bd7d-455a-b69a-b643fb0f7f1d/iec-60270-2000

HIGH-VOLTAGE TEST TECHNIQUES –

PARTIAL DISCHARGE MEASUREMENTS

1 Scope

This International Standard is applicable to the measurement of **partial discharges** which occur in electrical apparatus, components or systems when tested with alternating voltages up to 400 Hz or with direct voltage.

This standard

- defines the terms used;
- defines the quantities to be measured;
- describes test and measuring circuits which may be used;
- defines analogue and digital measuring methods required for common applications;
- specifies methods for calibration and requirements of instruments used for calibration;
- gives guidance on test procedures;
- gives some assistance concerning the discrimination of partial discharges from external interference.

The provisions of this standard should be used in the drafting of specifications relating to **partial discharge** measurements for specific power apparatus. It deals with electrical measurements of impulsive (short-duration) **partial discharges**, but reference is also made to non-electrical methods primarily used for **partial discharge** location (see annex F).

Diagnosis of the behaviour of specific power apparatus can be aided by digital processing of **partial discharge** data (see annex E) and also by non-electrical methods that are primarily used for **partial discharge** location (see annex F). 2000

https://standards.iteh.a/catalog/standards/iec/62c87e98-bd7d-455a-b69a-b643/b0/7f1d/iec-60270-2000 This standard is primarily concerned with electrical measurements of partial discharges made during tests with alternating voltage, but specific problems which arise when tests are made with direct voltage are considered in clause 11.

The terminology, definitions, basic test circuits and procedures often also apply to tests with other frequencies, but special test procedures and measuring system characteristics, which are not considered in this standard, may be required.

Annex A provides normative requirements for performance tests on calibrators.

2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this International Standard. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of IEC and ISO maintain registers of currently valid International Standards.

IEC 60060-1, *High-voltage test techniques – Part 1: General definitions and test requirements.*

IEC 60060-2, High-voltage test techniques – Part 2: Measuring systems

CISPR 16-1:1993, Specification for radio disturbance and immunity measuring apparatus and methods – Part 1: Radio disturbance and immunity measuring apparatus

- 8 -

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

partial discharge (PD)

localized electrical discharge that only partially bridges the insulation between conductors and which can or can not occur adjacent to a conductor

NOTE 1 **Partial discharges** are in general a consequence of local electrical stress concentrations in the insulation or on the surface of the insulation. Generally, such discharges appear as pulses having a duration of much less than 1 μ s. More continuous forms can, however, occur, such as the so-called pulse-less discharges in gaseous dielectrics. This kind of discharge will normally not be detected by the measurement methods described in this standard.

NOTE 2 "Corona" is a form of **partial discharge** that occurs in gaseous media around conductors which are remote from solid or liquid insulation. "Corona" should not be used as a general term for all forms of PD.

NOTE 3 **Partial discharges** are often accompanied by emission of sound, light, heat, and chemical reactions. For further information, see annex F.

3.2

partial discharge pulse (PD pulse)

current or voltage pulse that results from a **partial discharge** occurring within the object under test. The pulse is measured using suitable detector circuits, which have been introduced into the test circuit for the purpose of the test

NOTE A **partial discharge** which occurs in the test object produces a current pulse. A detector in accordance with the provisions of this standard produces a current or a voltage signal at its output, proportional to the charge of the current pulse at its input.

3.3

quantities related to partial discharge pulses 70:2000

ttps://standards.iteh.ai/catalog/standards/iec/62c87e98-bd7d-455a-b69a-b643fb0f7f1d/iec-60270-2000 3.3.1

apparent charge *q*

of a **PD pulse** is that charge which, if injected within a very short time between the terminals of the test object in a specified test circuit, would give the same reading on the measuring instrument as the **PD current pulse** itself. The **apparent charge** is usually expressed in picocoulombs (pC)

NOTE The **apparent charge** is not equal to the amount of charge locally involved at the site of the discharge, which cannot be measured directly.

3.3.2

pulse repetition rate n

ratio between the total number of **PD pulses** recorded in a selected time interval and the duration of this time interval

NOTE In practice, only pulses above a specified magnitude or within a specified range of magnitudes are considered.

3.3.3

pulse repetition frequency *N*

number of **partial discharge** pulses per second, in the case of equidistant pulses

NOTE **Pulse repetition frequency** *N* is associated with the situation in calibration.

IEC 60270:2000+AMD1:2015 CSV © IEC 2015

3.3.4 phase angle ϕ_i and time t_i of occurrence of a PD pulse is

 $\phi_{\rm i} = 360 \ (t_{\rm i}/T)$

where t_i is the time measured between the preceding positive going transition of the test voltage through zero and the **partial discharge pulse** and T is the period of the test voltage

The phase angle is expressed in degrees (°).

3.3.5

average discharge current /

derived quantity and the sum of the absolute values of individual **apparent charge** magnitudes q_i during a chosen reference time interval T_{ref} divided by this time interval:

$$I = \frac{1}{T_{\text{ref}}} \left(\left| q_1 \right| + \left| q_2 \right| + \dots + \left| q_i \right| \right)$$

The **average discharge current** is generally expressed in coulombs per second (C/s) or in amperes (A).

3.3.6

discharge power *P*

derived quantity that is the average pulse power fed into the terminals of the test object due to **apparent charge** magnitudes q_i during a chosen reference time interval T_{ref} :

$$P = \frac{1}{T_{\text{ref}}} (q_1 u_1 + q_2 u_2 + ... + q_i u_i)$$

where u_1 , u_2 ... u_i are instantaneous values of the test voltage at the instants of occurrence t_i of the individual **apparent charge** magnitudes q_i . The sign of the individual values must be observed

The discharge power is generally expressed in watts (W).

3.3.7

quadratic rate D

derived quantity that is the sum of the squares of the individual **apparent charge** magnitudes q_i during a chosen reference time interval T_{ref} divided by this time interval:

$$D = \frac{1}{T_{\text{ref}}} \left(q_1^2 + q_2^2 + ... + q_m^2 \right)$$

The **quadratic rate** is generally expressed in (coulombs)² per second (C²/s).

3.3.8

radio disturbance meter

quasi-peak measuring receiver for frequency band B in accordance with the provisions of CISPR 16-1:1993

NOTE This type of instrument was earlier called a radio interference (or influence) meter.

3.3.9

radio disturbance voltage URDV

derived quantity that is the reading of a **radio disturbance meter** when used for indicating the **apparent charge** q of partial discharges. For further information, see 4.5.6 and annex D

The radio disturbance voltage U_{RDV} is generally expressed in μV .

3.4

largest repeatedly occurring PD magnitude

largest magnitude recorded by a measuring system which has the pulse train response as specified in 4.3.3

The concept of the **largest repeatedly occurring PD magnitude** is not applicable to tests with direct voltage.

3.5

specified partial discharge magnitude

largest magnitude of any quantity related to **PD pulses** permitted in a test object at a specified voltage following a specified conditioning and test procedure. For alternating voltage tests, the specified magnitude of the **apparent charge** q is the **largest repeatedly occurring PD magnitude**

NOTE The magnitude of any **PD pulse** quantity can vary stochastically in successive cycles and also show a general increase or decrease with time of voltage application. The **specified PD magnitude**, the test procedure and also the test circuit and instrumentation should therefore be appropriately defined by the relevant technical committees.

3.6

background noise

signals detected during PD tests, which do not originate in the test object

NOTE **Background noise** can be composed of either white noise in the measurement system, broadcast radio or other continuous or impulsive signals. For further information, see annex G.

3.7

iTeh Standards

applied test voltages related to partial discharge pulse quantities

as defined in IEC 60060-1. The following voltage levels are of particular interest

3.7.1

partial discharge inception voltage U_i

applied voltage at which repetitive **partial discharges** are first observed in the test object, when the voltage applied to the object is gradually increased from a lower value at which no **partial discharges** are observed

In practice, the inception voltage U_i is the lowest applied voltage at which the magnitude of a **PD pulse** quantity becomes equal to or exceeds a specified low value.

NOTE For tests with direct voltage, the determination of U_i needs special considerations. See clause 11.

3.7.2

partial discharge extinction voltage U_e

applied voltage at which repetitive **partial discharges** cease to occur in the test object, when the voltage applied to the object is gradually decreased from a higher value at which **PD pulse** quantities are observed

In practice, the extinction voltage U_e is the lowest applied voltage at which the magnitude of a chosen **PD pulse** quantity becomes equal to, or less than, a specified low value.

NOTE For tests with direct voltage, the determination of Ue needs special considerations. See clause 11.

3.7.3

partial discharge test voltage

specified voltage, applied in a specified **partial discharge** test procedure, during which the test object should not exhibit PD exceeding a **specified partial discharge magnitude**

3.8

partial discharge measuring system

system consisting of a coupling device, a transmission system and a measuring instrument