



Edition 4.0 2015-05

INTERNATIONAL STANDARD

Automatic electrical controls – Part 2-9: Particular requirements for temperature sensing controls

Document Preview

IEC 60730-2-9:2015





THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2015 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

| IEC Central Office | Tel.: +41 22 919 02 11 | |
|--------------------|------------------------|--|
| 3, rue de Varembé | Fax: +41 22 919 03 00 | |
| CH-1211 Geneva 20 | info@iec.ch | |
| Switzerland | www.iec.ch | |

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in 15 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

More than 60 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc If you wish to give us your feedback on this publication or

need further assistance, please contact the Customer Service Centre: csc@iec.ch.

<u>EC 60730-2-9:2015</u>





Edition 4.0 2015-05

INTERNATIONAL STANDARD

Automatic electrical controls – Standards Part 2-9: Particular requirements for temperature sensing controls

Document Preview

IEC 60730-2-9:2015

https://standards.iteh.ai/catalog/standards/iec/ccb14a6a-bdcd-413b-b9b0-8f6bc566cfda/iec-60730-2-9-2015

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 97.120

ISBN 978-2-8322-2673-5

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

| FC | DREWORD | 4 |
|----|--|----|
| 1 | Scope and normative references | 7 |
| 2 | Terms and definitions | 8 |
| 3 | General requirements | 10 |
| 4 | General notes on tests | 10 |
| 5 | Rating | 11 |
| 6 | Classification | 11 |
| 7 | Information | 12 |
| 8 | Protection against electric shock | 14 |
| 9 | Provision for protective earthing | 14 |
| 10 | Terminals and terminations | 14 |
| 11 | Constructional requirements | 14 |
| 12 | Moisture and dust resistance | 17 |
| 13 | Electric strength and insulation resistance | 18 |
| | e Heating | |
| | Manufacturing deviation and drift | |
| 16 | - I Ien Standards | |
| 17 | Endurance | 20 |
| | Mechanical strength | |
| | Threaded parts and connections | |
| 20 | | |
| 21 | Resistance to heat, fire and tracking | |
| | Resistance to corrosion indands/iec/cch14a6a-bdcd-413b-b9b0-8f6bc566cfda/iec-607. | |
| | Electromagnetic compatibility (EMC) requirements – Emission | |
| | Components | |
| | Normal operation | |
| | Electromagnetic compatibility (EMC) requirements – Immunity | |
| | Abnormal operation | |
| | Guidance on the use of electronic disconnection | |
| | inexes | |
| | nnex G (normative) Heat and fire resistance tests | |
| | nnex H (normative) Requirements for electronic controls | |
| | nnex J (normative) Requirements for thermistor elements and controls using | |
| | ermistors | 38 |
| Ar | nnex AA (informative) Maximum manufacturing deviation and drift ^{a, b} | 39 |
| Ar | nnex BB (informative) Time factor | 40 |
| Ar | nnex CC (informative) Number of cycles | 43 |
| Ar | nnex DD (normative) Controls for use in agricultural confinement buildings | 44 |
| | nnex EE (informative) Guide to the application of temperature sensing controls within e scope of IEC 60730-2-9 | 47 |
| Bi | bliography | 63 |

| Figure 101 – Impact tool | 16 |
|--|----|
| Figure 102 – Aluminium cylinder for temperature change method | 26 |
| Figure BB.1 – Determination of time factor in the case of a sudden temperature change | 41 |
| Figure BB.2 – Determination of time factor in the case of a linear rise of test-bath temperature | 42 |
| Figure EE.1 – Thermostat | 55 |
| Figure EE.2 – Self-resetting temperature limiter | 56 |
| Figure EE.3 – Non-self-resetting temperature limiter | 57 |
| Figure EE.4 – Self-resetting thermal cut-out | 58 |
| Figure EE.5 – Manual reset thermal cut-out | 58 |
| Figure EE.6 – Single operation device | 60 |
| Figure EE.7 – Three-stage control system | 61 |
| Table 1 – Required information and methods of providing information | |

- 3 -

| Table 1 – Required information and methods of providing information | .13 |
|--|------|
| Table H.101 – Compliance criteria | . 33 |
| Table BB.1 – Method to determine and verify time factor values (see 11.101) | .42 |
| Table EE.1 – Typical examples of the classification of temperature sensing controls in accordance with IEC 60730-2-9 | . 62 |

(https://standards.iteh.ai) Document Preview

IEC 60730-2-9:2015

- 4 -

INTERNATIONAL ELECTROTECHNICAL COMMISSION

AUTOMATIC ELECTRICAL CONTROLS –

Part 2-9: Particular requirements for temperature sensing controls

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committee; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies. 200.2015
- 6) All users should ensure that they have the latest edition of this publication. 0-816bc566ctda/lec-60730-2-9-2015
 - 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
 - 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
 - 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60730-2-9 has been prepared by technical committee TC 72: Automatic electrical controls.

The text of this standard is based on the following documents:

| FDIS | Report on voting |
|-------------|------------------|
| 72/990/FDIS | 72/998/RVD |

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This fourth edition cancels and replaces the third edition published in 2008, and its Amendment 1:2011. This edition constitutes a technical revision. This edition includes alignment with the text of 60730-1 fifth edition and the following significant technical changes with respect to the previous edition:

- a) modification of heating-freezing tests in Clause 12;
- b) alignment of the EMC requirements in H.26 to those in other part 2 standards;
- c) addition of requirements in Clause H.27 to cover class B and C control functions of temperature sensing controls;

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

This Part 2-9 is intended to be used in conjunction with IEC 60730-1. It was established on the basis of the fifth edition (2013) of that publication. Consideration may be given to future editions of, or amendments to, IEC 60730-1.

This Part 2-9 supplements or modifies the corresponding clauses in IEC 60730-1 so as to convert that publication into the IEC standard: Particular requirements for temperature sensing controls.

Where this Part 2-9 states "addition", "modification", or "replacement", the relevant requirement, test specification or explanatory matter in part 1 should be adapted accordingly.

Where no change is necessary, this part 2 indicates that the relevant clause or subclause applies.

In the development of a fully international standard, it has been necessary to take into consideration the differing requirements resulting from practical experience in various parts of the world and to recognize the variation in national electrical systems and wiring rules.

The "in some countries" notes regarding differing national practices are contained in the following subclauses:

| 4.1.101 | DC17.8.4.101 Previe Annex AA | | |
|-------------------------------------|------------------------------|--|--|
| 7.2, Table 1 | 17.16.101 | Clause CC.2 | |
| 11.4.101 | 17.16.102 0730-2-9:2015 | DD.9.2 | |
| 11.101 https://standards.iteh.ai/ca | 17.16.105 | b9b0 8t6bc566cfda/iec-60730-2-9-2015 EE.3.6 | |
| 12.101.3 | 18.102.3 | | |

| 13.2 | 23.101 |
|------|--------|

In this publication:

1) The following print types are used:

- Requirements proper: in roman type;
- Test specifications: in italic type;
- Notes; in small roman type;
- Words defined in Clause 2: **bold**.
- 2) Subclauses, notes, tables and figures which are additional to those in part 1 are numbered starting from 101, additional annexes are lettered AA, BB, etc.

A list of all parts of the IEC 60730 series, published under the title *Automatic electrical controls* can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

iTeh Standards (https://standards.iteh.ai) Document Preview

IEC 60730-2-9:2015

AUTOMATIC ELECTRICAL CONTROLS -

Part 2-9: Particular requirements for temperature sensing controls

1 Scope and normative references

This clause of Part 1 is applicable except as follows:

1.1 Scope

Replacement:

This part of IEC 60730 applies to automatic electrical temperature **sensing controls** for use in, on or in association with equipment, including **electrical controls** for heating, air-conditioning and similar applications. The equipment may use electricity, gas, oil, solid fuel, solar thermal energy, etc., or a combination thereof.

NOTE Throughout this standard, the word "equipment" includes "appliance" and "control system".

This standard is applicable to automatic electrical temperature **sensing controls** forming part of a building automation **control system** within the scope of ISO 16484.

This standard also applies to automatic electrical temperature **sensing controls** for equipment that may be used by the public, such as equipment intended to be used in shops, offices, hospitals, farms and commercial and industrial applications.

This standard does not apply to automatic electrical temperature **sensing controls** intended exclusively for industrial process applications, unless explicitly mentioned in the relevant equipment standard.

1.1.1

Replacement:

This standard applies to the inherent safety, to the **operating values**, **operating times**, and **operating sequences** where such are associated with equipment safety, and to the testing of automatic electrical temperature **sensing control** devices used in, or in association with, equipment.

NOTE Examples of such controls include boiler thermostats, fan controls, temperature limiters and thermal cut-outs.

This standard is also applicable to the functional safety of low complexity safety-related temperature **sensing controls** and **systems**.

1.1.2

Addition:

This standard also applies to the electrical safety of temperature sensing controls with nonelectrical outputs such as refrigerant flow and gas **controls**.

1.1.3 Not applicable.

1.1.4

Replacement:

This standard applies to **manual controls** when such are electrically and/or mechanically integral with automatic temperature **sensing controls**.

- 8 -

NOTE Requirements for manual switches not forming part of an **automatic control** are contained in IEC 61058-1.

1.1.5

Replacement:

This standard applies to a.c. or d.c. powered temperature **sensing controls** with a rated voltage not exceeding 690 V a.c. or 600 V d.c.

1.1.6

Replacement:

This standard does not take into account the **response value** of an **automatic action** of a temperature **sensing control**, if such a **response value** is dependent upon the method of mounting it in the equipment. Where a **response value** is of significant purpose for the protection of the **user**, or surroundings, the value defined in the appropriate equipment standard or as determined by the manufacturer shall apply.

1.1.7

Replacement:

This standard applies also to temperature **sensing controls** incorporating **electronic devices**, requirements for which are contained in Annex H and to temperature **sensing controls** using **NTC thermistors** or **PTC thermistors**, requirements for which are contained in Annex J.

Additional subclause:

1.1.101 This standard applies to **single operation devices** as defined in this standard.

1.1 Normative references

Addition:

IEC 60216-1:2013, *Electrical insulating materials – Thermal endurance properties – Part 1:* Ageing procedures and evaluation of test results

IEC 60691, Thermal links – Requirements and application guide

IEC 60730-2-4, Automatic electrical controls for household and similar use – Part 2-4: Particular requirements for thermal motor protectors for motor-compressors of hermetic and semi-hermetic type

2 Terms and definitions

This clause of Part 1 is applicable except as follows:

2.2 Definitions of types of control according to purpose

2.2.19 operating control

operating control

Add, to the definition, the following note:

Note 1 to entry: In general, a thermostat is an operating control.

2.2.20 protective control

Add, to the definition, the following note:

Note 1 to entry: In general, a thermal cut-out is a protective control.

Additional definitions:

2.2.101 single-operation device SOD

control having a temperature **sensing element** which is intended to operate only once and then requires complete replacement

2.2.101.1

bimetallic single-operation device single operation device (SOD) having a bimetallic temperature sensing element

Note 1 to entry: A **bimetallic single operation device** (**SOD**) does not reset above a declared temperature (see 11.4.103).

Note 2 to entry: Requirements for thermal links (which are not allowed to reset) are contained in IEC 60691.

2.2.101.2

non-bimetallic single-operation device 60730-2-9:2015

single operation device (SOD) having a temperature sensing element which is part of a 2015 combination action control, the operation of which cannot be separated from other functions of the control and having a non-bimetallic thermal element that operates only once and then requires complete or partial replacement

Note 1 to entry: When such parts can be tested separately, they are considered to be thermal links within the scope of IEC 60691.

Note 2 to entry: The ageing period and thermal response of the device is dependent on the intended use of the device. As a result, the nature of the testing applicable to the device is representative of the application conditions for which the **protective control** is intended (see 7.2).

Note 3 to entry: Non-bimetallic SODs provide the equivalent of micro-disconnection.

2.2.101.2.1

rated functioning temperature

Tf

temperature of the **sensing element** of a **non-bimetallic SOD** which causes it to change the state of conductivity of the **control** when measured under specified conditions as declared by the manufacturer

2.2.102 room thermostat

independently mounted or incorporated **thermostat** intended to control the temperature of habitable space

2.2.103

fan control

automatic temperature sensing control intended to control the operation of a fan or blower

- 10 -

2.2.104

boiler thermostat

thermostat intended to control boiler/liquid temperature

2.2.105

modulating thermostat

thermostat which controls the temperature between two limits by continuously controlling the input to the load

2.2.106

voltage maintained thermal cut-out

thermal cut-out which is maintained in its operated condition by the voltage which appears across it in that condition

2.2.107

agricultural thermostat

thermostat intended for use in agricultural confinement buildings

2.3 Definitions relating to the function of controls

2.3.14 Additional definition:

(https://standards.iteh.

2.3.14.101 time factor

transient response of temperature sensing controls by defined change of the activating quantity

2.5 Definitions of types of control according to construction

Additional definitions:

Additional definition

2.5.101

push-and-turn actuation

two-step actuation accomplished by first pushing, then rotating the **actuating member** of the control

2.5.102

pull-and-turn actuation

two-step actuation accomplished by first pulling, then rotating the actuating member of the control

3 General requirements

This clause of Part 1 is applicable.

4 General notes on tests

4.1 Conditions of test

This clause of Part 1 is applicable except as follows:

IEC 60730-2-9:2015 © IEC 2015 - 11 -

4.1 Conditions of test

Additional subclauses:

4.1.101 For the purposes of the tests of this standard and unless otherwise indicated, ambient temperature excursions beyond T_{max} during abnormal **operation** as a precursor to the **operation** of a manual reset **thermal cut-out** or a **bimetallic SOD** are ignored.

NOTE In Canada and the USA, the preceding applies only to **bimetallic SODs**.

4.1.102 For manual reset **thermal cut-outs** and **bimetallic SODs** which have an **operating value** above T_{max} , the temperature at the **sensing element** is raised, as necessary, to achieve any cycling required during the tests.

4.2 amples required

4.2.1 Addition:

Six samples of **bimetallic SODs** are used for the test of Clause 15 and a further six for the test of Clause 17.

5 Rating

This clause of Part 1 is applicable. Ch Standards

6 Classification (https://standards.iteh.ai)

This clause of Part 1 is applicable except as follows: Teview

6.4 According to features of automatic action _0.0015

https:/ 6.4.3 Additional subclauses: ards/iec/ccb14a6a-bdcd-413b-b9b0-8f6bc566cfda/iec-60730-2-9-2015

6.4.3.101 – for sensing actions, no increase in the **operating value** as a result of any leakage from the **sensing element**, or from parts connecting the **sensing element** to the **switch head** (type 2.N);

6.4.3.102 – an action which operates after a declared thermal cycling test as specified in 17.101 (type 2.P);

NOTE In general, **thermal cut-outs** for specific applications, such as pressurized water heating systems, may be classified as having Type 2.P action.

6.4.3.103 – an action which is initiated only after a **push-and-turn actuation** or **pull-and-turn actuation** and in which only rotation is required to return the **actuating member** to the **OFF position** or rest position (type 1.X or 2.X);

6.4.3.104 – an action which is initiated only after a **push-and-turn actuation** or **pull-and-turn actuation** (type 1.Z or 2.Z);

6.4.3.105 – an action which cannot be reset under electrically loaded conditions (type 1.AK or 2.AK);

6.4.3.106 – an action which operates after declared agricultural environmental exposures (type 1.AM or 2.AM).

6.7 According to ambient temperature limits of the switch head

Additional subclauses:

6.7.101 Controls for use in or on cooking appliances.

6.7.102 Controls for use in or on ovens of the self-cleaning type.

6.7.103 Controls for use in or on food-handling appliances.

6.7.104 The **non-bimetallic SODs** are limited for use in appliances for heating or employing liquids or steam. It is not suitable for instantaneous water heaters and storage water heaters.

6.8.3 Modification:

Replace the first paragraph by:

For an **in-line cord control**, a free standing control, an **independently mounted control** or a **control** integrated or incorporated in an assembly utilizing a non-electrical energy source:

6.15 According to construction

Additional subclause:

6.15.101 – controls having parts containing liquid metal.

(https://standards.iteh.

7 Information

This clause of Part 1 is applicable except as follows:

IEC 60730-2-9:2015