

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION MET AND ADDIAN OPPAHUSAUUS TO CTAHDAPTUSAUUS ORGANISATION INTERNATIONALE DE NORMALISATION

Road vehicles – Symbols for controls, indicators and tell-tales – Part III

Véhicules routiers - Symboles pour les commandes, indicateurs et témoins - Partie III

First edition - 1975-12-15

UDC 629.113 : 003.62

Ref. No. ISO 2575/III-1975 (E)

Descriptors : road vehicles, control devices, tell-tales, symbols.

FOREWORD

ISO (the International Organization for Standardization) is a worldwide federation of national standards institutes (ISO Member Bodies). The work of developing International Standards is carried out through ISO Technical Committees. Every Member Body interested in a subject for which a Technical Committee has been set up has the right to be represented on that Committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the Technical Committees are circulated to the Member Bodies for approval before their acceptance as International Standards by the ISO Council.

International Standard ISO 2575/III was drawn up by Technical Committee ISO/TC 22, *Road vehicles*, and circulated to the Member Bodies in October 1974.

It has been approved by the Member Bodies of the following countries :

| a, Rep. of |
|------------|
| |
| 1 |
| |
| gdom |
| - |
| |
| |
| |

No Member Body expressed disapproval of the document.

© International Organization for Standardization, 1975 •

Printed in Switzerland

Road vehicles – Symbols for controls, indicators and tell-tales – Part III

The following list of symbols is a continuation of ISO 2575/II.

| No. | Control, indicator or tell-tale designation | Symbol | Additional specifications |
|------|--|--------|---------------------------|
| 4.20 | Lighter | 2 | |
| 4.21 | Front fog light ¹⁾ | 手D | |
| 4.22 | Rear fog light ¹⁾ | Q≢ | |
| 4.23 | Master lighting switch | -Ö- | |
| 4.24 | Windscreen demisting and defrosting | | |
| 4.25 | Rear window demisting and defrosting | | |

1) If one control is used for both front and rear fog lights, the symbol used shall be the one designated "front fog light".

1