
**Ergonomic requirements for the design of
displays and control actuators —**

Part 1:

**Human interactions with displays and control
actuators**

iTeh STANDARD PREVIEW

*Spécifications ergonomiques pour la conception des dispositifs
de signalisation et des organes de service —*

*Partie 1: Interactions entre l'homme et les dispositifs de signalisation
et organes de service*

[https://standards.iteh.ai/catalog/standards/sist/98799aaa-8792-4a3c-a1e1-
dc0255a38874/iso-9355-1-1999](https://standards.iteh.ai/catalog/standards/sist/98799aaa-8792-4a3c-a1e1-dc0255a38874/iso-9355-1-1999)



Contents

1 Scope	1
2 Normative references	1
3 Definitions	1
4 Design principles for operator-task relationships.....	2
4.1 Suitability for the task	2
4.1.1 Principle of function allocation	2
4.1.2 Principle of complexity.....	3
4.1.3 Principle of grouping.....	3
4.1.4 Principle of identification.....	3
4.1.5 Principle of operational relationship	4
4.2 Self-descriptiveness	4
4.2.1 Principle of information availability	4
4.3 Controllability.....	4
4.3.1 Principle of redundancy.....	4
4.3.2 Principle of accessibility.....	4
4.3.3 Principle of movement space	5
4.4 Conformity with user expectations.....	5
4.4.1 Principle of compatibility with learning.....	5
4.4.2 Principle of compatibility with practice	5
4.4.3 Principle of consistency.....	5
4.5 Error tolerance	6
4.5.1 Principle of error correction	6
4.5.2 Principle of error handling time	6
4.6 Suitability for individualization and learning	6
4.6.1 Principle of flexibility.....	6
Annex A (informative) Human information processing.....	7

iteh STANDARD PREVIEW
(standards.iteh.ai)

ISO 9355-1:1999
<https://standards.iteh.ai/catalog/standards/sist/98799aaa-8792-4a3c-a1e1-dc0255a38874/iso-9355-1-1999>

© ISO 1999

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case postale 56 • CH-1211 Genève 20 • Switzerland
Internet iso@iso.ch

Printed in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 9355-1 was prepared by the European Committee for Standardization (as European Standard EN 894-1:1997) and was adopted, under a special "fast-track procedure" by Technical Committee ISO/TC 159, *Ergonomics*, Subcommittee SC 4, *Ergonomics of human-system interaction*, in parallel with its approval by the ISO member bodies.

ISO 9355 consists of the following parts, under the general title *Ergonomic requirements for the design of displays and control actuators*:

— Part 1: *Human interactions with displays and control actuators*

— Part 2: *Displays*

— Part 3: *Control actuators*

— Part 4: *Location and arrangement of displays and control actuators*

Annex A of this part of ISO 9355 is for information only.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 9355-1:1999](https://standards.iteh.ai/catalog/standards/sist/98799aaa-8792-4a3c-a1e1-iso/9355-1:1999)

[https://standards.iteh.ai/catalog/standards/sist/98799aaa-8792-4a3c-a1e1-](https://standards.iteh.ai/catalog/standards/sist/98799aaa-8792-4a3c-a1e1-iso/9355-1:1999)

[iso/9355-1:1999](https://standards.iteh.ai/catalog/standards/sist/98799aaa-8792-4a3c-a1e1-iso/9355-1:1999)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 9355-1:1999

<https://standards.iteh.ai/catalog/standards/sist/98799aaa-8792-4a3c-a1e1-dc0255a38874/iso-9355-1-1999>

Ergonomic requirements for the design of displays and control actuators —

Part 1: Human interactions with displays and control actuators

1 Scope

This part of ISO 9355 applies to the design of displays and control actuators on machinery. It specifies general principles for human interaction with displays and control actuators, to minimize operator errors and to ensure an efficient interaction between the operator and the equipment. It is particularly important to observe these principles when an operator error may lead to injury or damage to health.

2 Normative references

<https://standards.iteh.ai/catalog/standards/sist/98799aaa-8792-4a3c-a1e1-dc0253a38874/iso-9355-1-1999>

The following normative documents contain provisions which, through reference in this text, constitute provisions of this part of ISO 9355. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this part of ISO 9355 are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

EN 418, *Safety of machinery — Emergency stop equipment, functional aspects — Principles for design*

EN 614-1, *Safety of machinery — Ergonomic design principles — Part 1: Terminology and general principles*

ISO 9355-2, *Ergonomic requirements for the design of displays and control actuators — Part 2: Displays*

ISO 9355-3, *Ergonomic requirements for the design of displays and control actuators — Part 3: Control actuators*

ISO 9241-10, *Ergonomic requirements for office work with visual display terminals (VDTs) — Part 10: Dialogue principles*

3 Definitions

For the purposes of this part of ISO 9355, the following definitions apply:

3.1

control actuator

The part of the control actuating system that is directly actuated by the operator, e.g. by applying pressure.

3.2 display

Device for presenting information that can change with the aim of making things visible, audible or discriminable by touch (tactile).

3.3 operator

The person or persons given the task of installing, operating, adjusting, maintaining, cleaning, repairing or transporting machinery [EN 292-1¹⁾].

4 Design principles for operator-task relationships

Human-machine systems are considered here as closed loops: the machine displays information to the operator who uses control actuators to affect the machine, which in turn provides feedback to the operator, etc.

Human-machine systems can comprise any number of man-machine units or subsystems, in which a single operator interacts with a machine or process. Several subsystems may act independently or interact with each other. When considering the requirements for a particular human-machine subsystem it is important to assess how it interacts with the system as a whole.

Moreover, human-machine systems are part of more complex systems. For example, the physical environment (noise, lighting, etc.) as well as the social and organisational environment can affect the efficient operation of human-machine systems.

Knowledge of ergonomics principles is the basis for a successful implementation of a human-machine system. In particular, it is important to ensure that systems are designed as an iterative process between the designer and the users. EN 614-1 provides a framework for incorporating ergonomics principles in the design process that shall be taken into account when designing machines. This framework can help designers to take account of the principles in this standard.

ISO 9355-1:1999

An important factor to consider is the degree to which the human operator is needed in the system in order to accomplish the given task. The informative Annex A summarizes information on the capabilities of humans when interacting with machines. The designer shall consider if the planned allocation of a particular function in a man-machine system is in accordance with human capabilities. If this is not the case, the designer shall redesign the system. A result of the redesign may be a (sub) system without the involvement of an operator.

The overall principle which concerns human-machine systems is that the machine and its associated elements (displays, controls, instructions, etc.) shall be suitable for the operator and the given task. In order to realise this general principle, the machine system shall be so designed that human characteristics with respect to physical, psychological and social aspects are considered. The following clauses present ergonomics principles that shall be considered when designing a human-machine system. Some guidance on methods which can be used to achieve the principles is also given. It should be noted that this list is not exhaustive but provides a good indication of practical measures which should be considered. ISO 9241-10 gives further information on these principles when applied to software.

When trying to comply with these requirements it is important that the selected solutions shall be tested under realistic conditions (see EN 614-1).

4.1 Suitability for the task

A human-machine system is suitable for the task if it supports the operator in the safe, effective and efficient completion of the task.

4.1.1 Principle of function allocation

The most suitable allocation of functions between the operator and the machine should be decided after considering the requirements of the task and the strengths and limitations of the human operator.

¹⁾ EN 292-1, *Safety of machinery — Basic concepts, general principles for design — Part 1: Basic terminology, methodology*.

Application:

Ensure the machine does not place unacceptable demands on the operator in terms of, for example, speed and accuracy of response, forces required to operate control actuators, vigilance for small changes in display status.

4.1.2 Principle of complexity

As far as consistent with the task requirements, possibilities shall be offered to reduce complexity. Special consideration shall be given to the complexity of the task structure and the type and amount of the information to be processed by the operator.

Application:

When designing human-machine interaction then speed and accuracy are important variables to consider. Those factors which influence these variables need to be determined.

For example, in check reading, the operator makes a qualitative assessment that the system is within acceptable boundaries. The accuracy of such readings may be enhanced if the pointers of the displays are arranged into a pattern so that it is easy to determine if one or several of the pointers deviate from the normal pattern (see ISO 9355-2).

4.1.3 Principle of grouping

Arrange displays and control actuators so that they are easy to use in combination by following procedures for grouping items.

Application:

Where control actuators and displays are operated in a certain fixed sequence, they shall be arranged in that sequence. This arrangement helps the operator to remember the sequence and it decreases response time and leads to fewer errors.

<https://standards.iteh.ai/catalog/standards/sist/98799aaa-8792-4a3c-a1e1-100000000000/iso-9355-1-1999>

Where control actuators and displays are not operated in a fixed sequence then the grouping should be determined using the following aspects:

- a) The importance for the safe use of the machine;
- b) The frequency of use in regular machine operation;
- c) The use of elements in a sub-sequence (for example, start up controls like the ignition, choke and starter on a car);
- d) The functional relationship between elements (for example, the wiper and wash controls on a car).

The above aspects are not mutually exclusive and several elements may appear in more than one category.

Consequently the location of displays and control actuators should be arranged so that:

- a) The important and frequently used items are in the most accessible positions;
- b) Items in sub-sequences are then placed together;
- c) Functionally related items are placed in groups with visual and spatial separation from other items.

Important displays and control actuators, such as those used for emergencies shall be designed and positioned so that they can be used quickly and accurately. Guidance on emergency stop devices is given in EN 418.

4.1.4 Principle of identification

Control actuators and displays should be readily identifiable.

Application:

Labels, signs and other informative texts or symbols should be located on or adjacent to their associated control actuators and displays in such a position that they are visible when the control actuators are operated. It is generally preferable to place such means of identification either above or on the control actuator or display.

4.1.5 Principle of operational relationship

Associated control actuators and displays should be arranged to reflect their operational relationships.

Application:

Control actuators should be located adjacent to associated displays so as to make their relationship obvious to the operator.

The direction of control actuator operation shall be consistent with the direction of associated system responses and/or display movements (see ISO 9355-2 and ISO 9355-3).

If a system failure occurs, it shall be identified to the operator as quickly as possible.

4.2 Self-descriptiveness

The human-machine interface should be designed so as to be self-descriptive, this means that the operator can easily recognise the displays and controls and understand the underlying process.

4.2.1 Principle of information availability

Information about the status of the system shall be readily available at the request of the operator without the need to interfere with other activities.

Application:

ISO 9355-1:1999
<https://standards.iteh.ai/catalog/standards/sist/98799aaa-8792-4a3c-a1e1-dc0255a38874/iso-9355-1-1999>

Verification that an operator action has been accepted by the system shall be presented to the operator without unnecessary delay. If the execution is prolonged, the operator should be informed. When appropriate the system shall respond instantly and simultaneously to an operator's actuation of the associated control actuator. With delays greater than 1 s, the perceived association is reduced and preliminary feedback becomes necessary.

4.3 Controllability

The operator shall dominate the system. This means that the system and its components shall guide the operator throughout the task during periods when the system is under direct operator control. The operator shall not be dominated by the workcycle rhythm inherent in the system.

4.3.1 Principle of redundancy

Provision should be made for additional displays and controls where such redundancy may benefit overall system safety.

Application:

In certain situations the efficiency and safety of a system depends upon the system's ability to present redundant information to the operator. Important information should be available from different sources. With respect to control actuators, some system requirements may demand that a given function can be operated from different locations in order to maintain speed, accuracy, health and safety.

4.3.2 Principle of accessibility

Information should be readily accessible.

Application:

Ensure the layout places the displays within the operator's field of vision. The important information in terms of safety and frequently consulted information shall be located in the central areas most frequently scanned by the eye (see ISO 9355-2).

In addition to this general requirement consider that the information may be obscured because of the positioning of the operator's arms.

4.3.3 Principle of movement space

The body movements that are required to operate control actuators should not cause discomfort for the operator.

Application:

The space between individual control actuators shall be optimal in order to ensure efficient operation, since too much space may demand unnecessary movements, while too little space may cause accidental operation. In order to determine the optimal space it is essential to consider the specific characteristics of each individual control actuator as well as the overall context in which the control actuators are to be operated, e.g. some systems are operated by persons wearing gloves.

4.4 Conformity with user expectations

Population stereotypes and other user expectations of how the human-machine interface operates are powerful influences in determining how an operator will use a particular control actuator or display. Under stress operators can be expected to revert to population stereotypes even if they have been trained to act in a contrary manner.

4.4.1 Principle of compatibility with learning

The function, movement, and position of control actuator and display elements shall correspond to what the operator expects from previous work experience or training. [ISO 9355-1:1999](https://standards.iteh.ai/catalog/standards/sist/98799aaa-8792-4a3c-a1e1-dc0255a38874/iso-9355-1-1999)

<https://standards.iteh.ai/catalog/standards/sist/98799aaa-8792-4a3c-a1e1-dc0255a38874/iso-9355-1-1999>

Application:

What is expected from conventions is important when applying this principle. For example, there is a stereotype to rotate a dial clockwise to increase a value on a display and to move a control actuator upwards or to the right to increase the value.

4.4.2 Principle of compatibility with practice

The function, movement, and position of control actuator and display elements shall correspond to expectancies based on practical experience in using the system and the relevant manual.

Application:

After some time the operator becomes accustomed to the particular response times exhibited by the system and develops expectations regarding them. Similar operations shall thus exhibit the same general pattern with respect to response times. The operator shall be informed if the response time of the system deviates from what would normally be expected.

4.4.3 Principle of consistency

Similar parts of the human-machine system should operate in a consistent manner.

Application:

The arrangement, function and movement of control actuators, displays, and other devices of the system shall be consistent and not interchanged throughout the system or systems, e.g. related control actuators and displays shall be arranged in the same order.

A consistent set of codes and symbols shall be used.

4.5 Error tolerance

A system is said to be error tolerant if, despite evident errors in operation, the intended result is achieved with either no or minimal corrective action.

4.5.1 Principle of error correction

Systems should be able to perform error checking and provide the operator with the means for handling such errors.

Application:

If the system can correct an operator error in several ways, the operator shall have the chance to select from these possibilities. However, it could be important to inform the operator about the correct procedure to be followed.

Enough information shall be provided in critical situations to ensure optimal error handling. If a system failure occurs it shall be identified to the operator as quickly as possible. Error messages shall be easily understood. The operator shall be able to execute the necessary actions without extensive information processing and help from manuals etc. The operator should be able to choose between brief and detailed error information.

4.5.2 Principle of error handling time

The system should provide sufficient time for an operator to reliably recover from any errors.

Application:

Ensure that the operator has sufficient opportunity to identify any errors and make appropriate corrective actions before the consequences of the errors become critical.

Guidance on how to minimize the likelihood of inadvertent operation of control actuators is presented in ISO 9355-3.

4.6 Suitability for individualization and learning

<https://standards.iteh.ai/catalog/standards/sist/98799aaa-8792-4a3c-a1e1->

A system is suitable for individualization and learning if it can be adjusted to individual needs.

4.6.1 Principle of flexibility

The system shall be flexible enough to be adapted to differences in personal needs, general physiological and psychological abilities, learning abilities and cultural differences.

Application:

Where possible, the operator shall be able to influence the speed of interaction.

The experienced operator shall be able to structure the feedback so that it conforms to their level of expertise. By the same token the inexperienced operator should be able to set the level of feedback at an appropriate level.

In a complex system, the system should provide the operator with the choice of brief or detailed information about the system.

Regarding operation, most control actuators can be operated equally well with both hands. However, control actuators that demand accurate, and/or fast, operation should either be capable of being operated by either hand or be so designed to allow accurate and/or fast operation by the non-preferred hand.

Annex A (informative)

Human information processing

Human information processing

A.0 Introduction

Many criteria and principles of ergonomics are derived from knowledge acquired in the fields of human-machine systems and general psychology. This Annex presents some of this basic knowledge in terms of an overview of some principles of human information processing. However, it is to be noted that due to the rapid theoretical and empirical development in the field, there are many diverging opinions regarding these matters. The following presentation should thus be regarded as a set of tentative suggestions based on some current ideas about these issues.

The following approach considers the human mind as an information processing system. In this system three interacting subsystems are distinguished, namely:

- a) The perceptual system;
- b) The cognitive system;
- c) The motor system.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Although, as mentioned above, it is practice to distinguish among different systems of information processing, it is important to realize that some of these distinctions often become blurred in the observation of an operator in a real situation. It is therefore essential to realize that human performance always reflects the interaction and combinations of many different information processing subsystems and that these interactions may produce unpredictable results.

A.1 Overview

The presentation below is arranged under the following main sections; attention, perception, cognition, motor performance and performance shaping factors. Due to the close interrelationship among the systems discussed under each section, the order of presentation is somewhat arbitrary and is mainly adopted for heuristic reasons. For example, the issue of memory is discussed under the cognitive section, but, as mentioned above, the characteristics of memory are involved in many of the systems discussed, such as attention, expectation etc.

A.2 Attention

In many situations, e.g. those involving a human operator in a human-machine system, the person can be viewed as a single channel processor with capacity to process information from no more than a few sources at a time.

Attention is normally confined to two main sources, the internal world i.e. thoughts and sensations from the body, and the external world. Since attention can be described as a limited resource, there may be competition among attentional resources. For example, an operator who is occupied with thoughts or decision making may suffer attentional deficits regarding events happening in the outside world. A consequence for the design of human-machine systems is that it is essential not to overload the attentional resources of the operator.