



IEC 61158-3-4

Edition 2.0 2014-08

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Industrial communication networks – Fieldbus specifications –
Part 3-4: Data-link layer service definition – Type 4 elements

Réseaux de communication industriels – Spécifications des bus de terrain –
Partie 3-4: Définition des services de la couche liaison de données – Eléments
de type 4

<https://standards.iteh.ai/ctd/qg/standards/1c7be4abdbf-8457-4ad8-a305-e899695b786d/iec-61158-3-4-2014>



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2014 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - [www.iec.ch/searchpub](https://webstore.iec.ch/searchpub)

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/jupublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in 14 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

More than 55 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Catalogue IEC - webstore.iec.ch/catalogue

Application autonome pour consulter tous les renseignements bibliographiques sur les Normes internationales, Spécifications techniques, Rapports techniques et autres documents de l'IEC. Disponible pour PC, Mac OS, tablettes Android et iPad.

Recherche de publications IEC - [www.iec.ch/searchpub](https://webstore.iec.ch/searchpub)

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études,...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/jupublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire en ligne de termes électroniques et électriques. Il contient plus de 30 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans 14 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Glossaire IEC - std.iec.ch/glossary

Plus de 55 000 entrées terminologiques électrotechniques, en anglais et en français, extraites des articles Termes et Définitions des publications IEC parues depuis 2002. Plus certaines entrées antérieures extraites des publications des CE 37, 77, 86 et CISPR de l'IEC.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: csc@iec.ch.

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Industrial communication networks – Fieldbus specifications –
Part 3-4: Data-link layer service definition – Type 4 elements

Réseaux de communication industriels – Spécifications des bus de terrain –
Partie 3-4: Définition des services de la couche liaison de données – Eléments
de type 4

<https://standards.iteh.ai/ctf/eg/standards/IC/be4adbf-8457-4ad8-a305-e899695b786d/iec-61158-3-4-2014>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

PRICE CODE
CODE PRIX

U

ICS 25.040.40; 35.100.20; 35.110

ISBN 978-2-8322-1712-2

Warning! Make sure that you obtained this publication from an authorized distributor.

Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

CONTENTS

FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	7
1.1 General	7
1.2 Specifications	7
1.3 Conformance.....	7
2 Normative references	8
3 Terms, definitions, symbols, abbreviations and conventions	8
3.1 Reference model terms and definitions.....	8
3.2 Service convention terms and definitions.....	9
3.3 Data-link service terms and definitions	10
3.4 Symbols and abbreviations.....	12
3.5 Conventions	13
4 Data-link service and concepts	14
4.1 Overview	14
4.2 Types and classes of data-link service.....	15
4.3 Functional classes.....	15
4.4 Facilities of the connectionless mode data-link service	15
4.5 Model of the connectionless-mode data-link service	15
4.6 Sequence of primitives	16
4.7 Connectionless-mode data transfer functions	18
5 DL-management service.....	20
5.1 Scope and inheritance.....	20
5.2 Facilities of the DL-management service	20
5.3 Model of the DL-management service.....	21
5.4 Constraints on sequence of primitives	21
5.5 Set	21
5.6 Get	22
5.7 Action	23
5.8 Event	24
Bibliography.....	25
Figure 1 – Relationship of PhE, DLE and DLS-users.....	14
Figure 2 – Confirmed and unconfirmed UNITDATA request time-sequence diagram	17
Figure 3 – Repeated confirmed request time-sequence diagram	17
Figure 4 – State transition diagram for sequences of primitives at one DLSAP	18
Figure 5 – Sequence of primitives for the DLM action service	21
Table 1 – Summary of DL-connectionless-mode primitives and parameters	17
Table 2 – Unitdata transfer primitives and parameters	18
Table 3 – Control-status error codes	20
Table 4 – Summary of DL-management primitives and parameters	21
Table 5 – DLM-Set primitive and parameters	22

Table 6 – DLM-Get primitive and parameters	22
Table 7 – DLM-Action primitive and parameters	23
Table 8 – DLM-Event primitive and parameters	24



<https://standards.iteh.ai/v2/02/standards/Ic/be4audbf-8457-4ad8-a305-e899695b786d/iec-61158-3-4-2014>

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**INDUSTRIAL COMMUNICATION NETWORKS –
FIELDBUS SPECIFICATIONS –****Part 3-4: Data-link layer service definition –
Type 4 elements****FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

Attention is drawn to the fact that the use of the associated protocol type is restricted by its intellectual-property-right holders. In all cases, the commitment to limited release of intellectual-property-rights made by the holders of those rights permits a layer protocol type to be used with other layer protocols of the same type, or in other type combinations explicitly authorized by its intellectual-property-right holders.

NOTE Combinations of protocol Types are specified in IEC 61784-1 and IEC 61784-2.

International Standard IEC 61158-3-4 has been prepared by subcommittee 65C: Industrial networks, of IEC technical committee 65: Industrial-process measurement, control and automation.

This second edition cancels and replaces the first edition published in 2007. This edition constitutes an editorial revision with only minor editorial changes.

This edition includes the following significant changes with respect to the previous edition:

- a) editorial improvements;
- b) editorial corrections.

The text of this standard is based on the following documents:

FDIS	Report on voting
65C/759/FDIS	65C/769/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with ISO/IEC Directives, Part 2.

A list of all the parts of the IEC 61158 series, under the general title *Industrial communication networks – Fieldbus specifications*, can be found on the IEC web site.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under <http://webstore.iec.ch> in the data related to the specific publication. At this date, the publication will be:

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

<https://standards.iteh.ai/iec61158-3-4:2014>

INTRODUCTION

This part of IEC 61158 is one of a series produced to facilitate the interconnection of automation system components. It is related to other standards in the set as defined by the “three-layer” fieldbus reference model described in IEC 61158-1.

Throughout the set of fieldbus standards, the term “service” refers to the abstract capability provided by one layer of the OSI Basic Reference Model to the layer immediately above. Thus, the data-link layer service defined in this standard is a conceptual architectural service, independent of administrative and implementation divisions.



<https://standards.iteh.ai/v2/02/standards/0c/be4audbf-8457-4ad8-a305-e899695b786d/iec-61158-3-4-2014>

INDUSTRIAL COMMUNICATION NETWORKS – FIELDBUS SPECIFICATIONS –

Part 3-4: Data-link layer service definition – Type 4 elements

1 Scope

1.1 General

This part of IEC 61158 provides common elements for basic time-critical messaging communications between devices in an automation environment. The term “time-critical” is used to represent the presence of a time-window, within which one or more specified actions are required to be completed with some defined level of certainty. Failure to complete specified actions within the time window risks failure of the applications requesting the actions, with attendant risk to equipment, plant and possibly human life.

This standard defines in an abstract way the externally visible services provided by the Type 4 fieldbus data-link layer in terms of

- a) the primitive actions and events of the services;
- b) the parameters associated with each primitive action and event, and the form which they take; and
- c) the interrelationship between these actions and events, and their valid sequences.

The purpose of this standard is to define the services provided to

- the Type 4 fieldbus application layer at the boundary between the application and data-link layers of the fieldbus reference model;
- systems management at the boundary between the data-link layer and systems management of the fieldbus reference model.

1.2 Specifications

The principal objective of this standard is to specify the characteristics of conceptual data-link layer services suitable for time-critical communications, and thus supplement the OSI Basic Reference Model in guiding the development of data-link protocols for time-critical communications. A secondary objective is to provide migration paths from previously-existing industrial communications protocols.

This specification may be used as the basis for formal DL-Programming-Interfaces. Nevertheless, it is not a formal programming interface, and any such interface will need to address implementation issues not covered by this specification, including

- a) the sizes and octet ordering of various multi-octet service parameters;
- b) the correlation of paired request and confirm, or indication and response, primitives.

1.3 Conformance

This standard does not specify individual implementations or products, nor does it constrain the implementations of data-link entities within industrial automation systems.

There is no conformance of equipment to this data-link layer service definition standard. Instead, conformance is achieved through implementation of the corresponding data-link protocol that fulfills the Type 1 data-link layer services defined in this standard.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE All parts of the IEC 61158 series, as well as IEC 61784-1 and IEC 61784-2 are maintained simultaneously. Cross-references to these documents within the text therefore refer to the editions as dated in this list of normative references.

ISO/IEC 7498-1, *Information technology – Open Systems Interconnection – Basic Reference Model: The Basic Model*

ISO/IEC 7498-3, *Information technology – Open Systems Interconnection – Basic Reference Model: Naming and addressing*

ISO/IEC 10731:1994, *Information technology – Open Systems Interconnection – Basic Reference Model – Conventions for the definition of OSI services*

3 Terms, definitions, symbols, abbreviations and conventions

For the purposes of this document, the following terms, definitions, symbols, abbreviations and conventions apply.

3.1 Reference model terms and definitions

This standard is based in part on the concepts developed in ISO/IEC 7498-1 and ISO/IEC 7498-3, and makes use of the following terms defined therein.

3.1.1 **DL-address** [7498-3]

3.1.2 **DL-address-mapping** [7498-1]

3.1.3 **called-DL-address** [7498-3]

3.1.4 **calling-DL-address** [7498-3]

3.1.5 **centralized multi-end-point-connection** [7498-1]

3.1.6 **DL-connection** [7498-1]

3.1.7 **DL-connection-end-point** [7498-1]

3.1.8 **DL-connection-end-point-identifier** [7498-1]

3.1.9 **DL-connection-mode transmission** [7498-1]

3.1.10 **DL-connectionless-mode transmission** [7498-1]

3.1.11 **correspondent (N)-entities** [7498-1]

correspondent DL-entities (N=2)

correspondent Ph-entities (N=1)

3.1.12 **DL-duplex-transmission** [7498-1]

3.1.13 **(N)-entity** [7498-1]

DL-entity (N=2)

Ph-entity (N=1)

3.1.14	DL-facility	[7498-1]
3.1.15	flow control	[7498-1]
3.1.16	(N)-layer DL-layer (N=2) Ph-layer (N=1)	[7498-1]
3.1.17	layer-management	[7498-1]
3.1.18	DL-local-view	[7498-3]
3.1.19	DL-name	[7498-3]
3.1.20	naming-(addressing)-domain	[7498-3]
3.1.21	primitive name	[7498-3]
3.1.22	DL-protocol	[7498-1]
3.1.23	DL-protocol-connection-identifier	[7498-1]
3.1.24	DL-protocol-data-unit	[7498-1]
3.1.25	DL-relay	[7498-1]
3.1.26	reset	[7498-1]
3.1.27	responding-DL-address	[7498-3]
3.1.28	routing	[7498-1]
3.1.29	segmenting	[7498-1]
3.1.30	(N)-service DL-service (N=2) Ph-service (N=1)	[7498-1]
3.1.31	(N)-service-access-point DL-service-access-point (N=2) Ph-service-access-point (N=1)	[7498-1]
3.1.32	DL-service-access-point-address	[7498-3]
3.1.33	DL-service-connection-identifier	[7498-1]
3.1.34	DL-service-data-unit	[7498-1]
3.1.35	DL-simplex-transmission	[7498-1]
3.1.36	DL-subsystem	[7498-1]
3.1.37	systems-management	[7498-1]
3.1.38	DLS-user-data	[7498-1]

3.2 Service convention terms and definitions

This standard also makes use of the following terms defined in ISO/IEC 10731 as they apply to the data-link layer:

3.2.1 acceptor

3.2.2 **confirm (primitive);
requestor.deliver (primitive)**

3.2.3 **deliver (primitive)**

3.2.4 **DL-confirmed-facility**

3.2.5 **DL-facility**

3.2.6 **DL-local-view**

3.2.7 **DL-mandatory-facility**

3.2.8 **DL-non-confirmed-facility**

3.2.9 **DL-service-primitive;
primitive**

3.2.10 **DL-service-provider**

3.2.11 **DL-service-user**

3.2.12 **DLS-user-optional-facility**

3.2.13 **indication (primitive);
acceptor.deliver (primitive)**

3.2.14 **request (primitive);
requestor.submit (primitive)**

3.2.15 **requestor**

3.2.16 **response (primitive);
acceptor.submit (primitive)**

3.2.17 **submit (primitive)**

<https://standards.iteh.ai/etd/02/standards/10/b470dbf-8457-4ad8-a305-e899695b786d/iec-61158-3-4-2014>

3.3 Data-link service terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.3.1 **broadcast-node-address**

address used to designate all DLEs on a link

Note 1 to entry: All DLEs on a link receive all DLPDUs where the first node-address is equal to the broadcast-node-address. Such DLPDUs are always unconfirmed, and their receipt is never acknowledged. The value of the broadcast-node-address is 126.

3.3.2 **destination-DL-route**

sequence of DL-route-elements, describing the complete route to the destination

Note 1 to entry: This includes both the destination DLSAP and a local component meaningful to the destination DLS-user.

3.3.3 **DL-route-element**

octet holding a node DL-address or an address used by the DLS-user

3.3.4

DLSAP

distinctive point at which DL-services are provided by a single DL-entity to a single higher-layer entity

3.3.5**DL(SAP)-address**

individual DLSAP-address, designating a single DLSAP of a single DLS-user

3.3.6**DLS-user address**

uniquely identifies a DLS-user locally

3.3.7**frame**

denigrated synonym for DLPDU

3.3.8**full DL-route**

combination of a destination-DL-route and a source-DL-route

3.3.9**Local link**

single DL-subnetwork in which any of the connected DLEs may communicate directly, without any intervening DL-relaying, whenever all of those DLEs that are participating in an instance of communication are simultaneously attentive to the DL-subnetwork during the period(s) of attempted communication

3.3.10**maximum-indication-delay**

indicates to the DLS-user the maximum time interval for the DLS-user to prepare a response after receiving an indication requiring a response

Note 1 to entry: If the DLS-user is unable to prepare a response within maximum-indication-delay, the DLS-user is required to issue a DL-UNITDATA request with a DLSDU type indicating ACKNOWLEDGE. As a result the DLE will transmit an acknowledging DLPDU on the link.

3.3.11**maximum-retry-time**

indicates to the DLE for how long time retransmission of the request may be performed, as a result of Wait acknowledges from the remote DLE or DLS-user

3.3.12**no-confirm-node-address**

indicates that a request or response is unconfirmed

Note 1 to entry: The value of the no-confirm-node-address is 0

3.3.13**node**

single DL-entity as it appears on one local link

3.3.14**node-address**

uniquely identifies a DLE on a link

Note 1 to entry: The value of a Node-address is in the range of 0-127. The values 0, 126 and 127 are reserved for special purposes

3.3.15**normal class device**

device which replies to requests from other normal class devices, and initiates transmissions

Note 1 to entry: Such a device can act as a server (responder) and as a client (requestor) – this is also called a peer.

3.3.16**receiving DLS-user**

DL-service user that acts as a recipient of DLS-user-data

Note 1 to entry: A DL-service user can be concurrently both a sending and receiving DLS-user.

3.3.17**sending DLS-user**

DL-service user that acts as a source of DLS-user-data

3.3.18**service-node-address**

an address reserved for service purposes only

Note 1 to entry: All DLEs on a link receive all DLPDUs where the first Node-address is equal to the service-node-address. Such DLPDUs can be Confirmed or Unconfirmed, and their receipt may or may not be acknowledged. The service-node-address can be used on links with only two DLEs – the requesting Normal class DLE and the responding simple-class or normal-class DLE. The value of the service-node-address is 127.

3.3.19**simple-class device**

device which replies to requests from normal class devices

Note 1 to entry: Such a device can act as a server or responder only.

3.3.20**source-DL-route**

holds a sequence of DL-route-elements, describing the complete route back to the source

3.4 Symbols and abbreviations

NOTE Many symbols and abbreviations are common to more than one protocol Type; they are not necessarily used by all protocol Types.

3.4.1 DL- Data-link layer (as a prefix)

3.4.2 DLC DL-connection

3.4.3 DLCEP DL-connection-end-point

3.4.4 DLE DL-entity (the local active instance of the data-link layer)

3.4.5 DLL DL-layer

3.4.6 DLPCI DL-protocol-control-information

3.4.7 DLPDU DL-protocol-data-unit

3.4.8 DLM DL-management

3.4.9 DLME DL-management Entity (the local active instance of DL-management)

3.4.10 DLMS DL-management Service

3.4.11 DLS DL-service

3.4.12 DLSAP DL-service-access-point

3.4.13 DLSDU DL-service-data-unit

3.4.14 FIFO First-in first-out (queuing method)

3.4.15 OSI Open systems interconnection