



SLOVENSKI STANDARD
SIST EN 14670:2005

01-november-2005

Površinsko aktivne snovi – Natrijev dodecil sulfat – Analitska metoda

Surface active agents - Sodium dodecyl sulfates - Analytical method

Grenzflächenaktive Stoffe - Natriumdodecylsulfat - Analysenverfahren

Agents de surface - Dodécylsulfate de sodium - Méthode d'analyse

Ta slovenski standard je istoveten z: EN 14670:2005

SIST EN 14670:2005
<https://standards.iteh.ai/catalog/standards/sist/08614807-6417-4a4c-94e6-fcd1ff6d82f/sist-en-14670-2005>

ICS:

71.100.40 Površinsko aktivna sredstva Surface active agents

SIST EN 14670:2005

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 14670:2005](https://standards.iteh.ai/catalog/standards/sist/08614807-6417-4a4c-94e6-fcd1ff6d82f/sist-en-14670-2005)

<https://standards.iteh.ai/catalog/standards/sist/08614807-6417-4a4c-94e6-fcd1ff6d82f/sist-en-14670-2005>

EUROPEAN STANDARD

EN 14670

NORME EUROPÉENNE

EUROPÄISCHE NORM

June 2005

ICS 71.100.40

English version

Surface active agents - Sodium dodecyl sulfate - Analytical method

Agents de surface - Dodécylsulfate de sodium - Méthode d'analyse

Grenzflächenaktive Stoffe - Natriumdodecylsulfat - Analysenverfahren

This European Standard was approved by CEN on 19 May 2005.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

[SIST EN 14670:2005](https://standards.iteh.ai/catalog/standards/sist/08614807-6417-4a4c-94e6-fcd1ff6d82f/sist-en-14670-2005)

<https://standards.iteh.ai/catalog/standards/sist/08614807-6417-4a4c-94e6-fcd1ff6d82f/sist-en-14670-2005>



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

Contents

	Page
Foreword	3
1 Scope	4
2 Normative references	4
3 Principle.....	4
4 Reagents.....	4
5 Apparatus	5
6 Sampling and preparation of the sample	5
7 Procedure	5
8 Expression of results.....	6
9 Precision.....	7
10 Test report	7
Annex A (informative) Typical gas chromatogram.....	8
Annex B (informative) Results of inter-laboratory test.....	9
Bibliography.....	10

[SIST EN 14670:2005](https://standards.iteh.ai/catalog/standards/sist/08614807-6417-4a4c-94e6-fcd1ff6d82f/sist-en-14670-2005)

<https://standards.iteh.ai/catalog/standards/sist/08614807-6417-4a4c-94e6-fcd1ff6d82f/sist-en-14670-2005>

Foreword

This European Standard (EN 14670:2005) has been prepared by Technical Committee CEN/TC 276 “Surface active agents”, the secretariat of which is held by AFNOR.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by December 2005, and conflicting national standards shall be withdrawn at the latest by December 2005.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 14670:2005](https://standards.iteh.ai/catalog/standards/sist/08614807-6417-4a4c-94e6-fcd1ff6d82f/sist-en-14670-2005)

<https://standards.iteh.ai/catalog/standards/sist/08614807-6417-4a4c-94e6-fcd1ff6d82f/sist-en-14670-2005>

EN 14670:2005 (E)

1 Scope

This European Standard specifies a method for the determination of the active content and molar mass of sodium dodecyl sulphate used as original titre for the titre determination of standard solutions for surface active agents titration.

NOTE These are used in the mixed indicator two-phase titration (e. g. ISO 2271) and in the potentiometric titration using a surface active agent sensitive electrode (e.g. EN 14480).

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 13267, *Surface active agents – Determination of water content – Karl Fischer method.*

EN ISO 3696, *Water for analytical laboratory use – Specification and test methods (ISO 3696:1987).*

ISO 607, *Surface active agents and detergents – Methods of sample division.*

ISO 894, *Surface active agents – Technical sodium primary alkylsulphates – Methods of analysis.*

ISO 6844, *Surface active agents – Determination of mineral sulfate content – Titrimetric method.*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

3 Principle

SIST EN 14670:2005

The water content, the sodium sulphate content and the extractable matter content by light petroleum of the test sample are determined according to the methods respectively described in EN ISO 3696, ISO 894 and ISO 9844 and the active content is calculated by subtracting the water content, the sodium sulphate content and the content of extractable matter by light petroleum from 100 %. For calculating the average molar mass of the sodium dodecyl sulphate the fatty alcohols C₁₀ to C₁₄ released after acidic hydrolysis are isolated and the C-chain distribution is determined by gas chromatography.

4 Reagents

During the analysis, unless otherwise specified, use only reagents of recognized analytical grade which have been checked in advance as not interfering with the analytical results and water complying with grade 3 as defined in EN ISO 3696 and in particular use.

- for the determination of the water content, the reagents specified in EN 13267;
- for the determination of the sodium sulphate content, the reagents specified in ISO 6844 (or prEN 14880). ;
- for the determination of extractable matter content by light petroleum, the reagents specified in ISO 894.

5 Apparatus

Normal laboratory apparatus and the following:

5.1 Gas chromatograph, suitable for work with a fused silica capillary column and equipped with a flame ionization detector (FID).

5.2 Capillary column, capable of the separation characteristics shown in Figure A.1.

NOTE A 30 m x 0.32 mm ID, fused silica capillary column (film thickness 0,25 µm) with 5 % phenyl-, 95 % methyl polysiloxane stationary phase is advisable.

6 Sampling and preparation of the sample

The laboratory sample shall be prepared and stored in accordance with ISO 607.

7 Procedure

7.1 Determination of water content

Determine the water content in accordance with EN 13267.

NOTE Usually the water content is < 1 % (m/m).

7.2 Determination of the sodium sulphate content

Determine the sodium sulphate content in accordance with ISO 6844 (dithizone method).

NOTE Usually the sodium sulphate content is < 0.1 % (m/m).

7.3 Determination of the extractable matter content by light petroleum

Determine the extractable matter content by light petroleum in accordance with ISO 894.

NOTE 1 Usually the content is < 0,2 % (m/m).

NOTE 2 For the determination of the unsulphated matter, EN 13273 may also be applied if an appropriate calibrant (C₁₂-alcohol) is available.

7.4 Determination of the average molar mass of sodium dodecyl sulfate

Extract the light petroleum soluble matter in accordance with ISO 894 from the neutralized aqueous ethanolic solution of the test sample.

After acid hydrolysis of the alkyl sulphate remaining in the aqueous ethanolic phase, extract the released fatty alcohol with diethyl ether in accordance with ISO 894.

Evaporate the dried diethyl ether extract to a volume of approximately 20 ml. Determine the C-chain distribution of the fatty alcohol using gas chromatography with the given parameters. The peak assignment can be done with a fatty alcohol kit serving as reference. At least the quality of separation shown in Figure A.1 shall be achieved.

EN 14670:2005 (E)

8 Expression of results

8.1 Calculation of the active content

The active content, w , expressed as grams per 100 g, is calculated according to equation (1):

$$w = 100 - w_{\text{H}_2\text{O}} - w_{\text{Na}_2\text{SO}_4} - w_{me} \quad (1)$$

where

$w_{\text{H}_2\text{O}}$ is the water content according to 7.1, in grams per 100 g;

$w_{\text{Na}_2\text{SO}_4}$ is the sodium sulphate content according to 7.2, in grams per 100 g;

w_{me} is the content of matter extractable by light petroleum according to 7.3, in grams per 100 g.

8.2 Calculation of the average molar mass

The average molar mass, M , expressed as grams per mole, is calculated according to equation (2):

$$M = \left[\sum (A_n \times n) \right] \times 12 + \left[2 \sum (A_n \times n) + 1 \right] \times 1 + 119 \quad (2)$$

where

n is the C-number of the fatty alcohol;

A_n is the relative area for the fatty alcohol n.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
<https://standards.iteh.ai/catalog/standards/sist/08614807-6417-4a4c-94e6-fcd1ff6d82f/sist-en-14670-2005>

9 Precision

9.1 General

Despite the sometimes considerable statistical variations during the analysis of minor constituents, the subtraction method offers the most reliable results for the analysis of the active content. As the contents of the minor constituents are generally $< 0,1$ % (m/m) for sodium sulphate and un sulphated matter and < 1 % (m/m) for water, high variation coefficients have only low effect on the final result. The same applies to the high variation coefficient for the C₁₀ and C₁₄ fatty alcohol analysis.

9.2 Repeatability limit

The absolute difference between two independent single test results, obtained using the same method on identical test material in the same laboratory by the same operator using the same equipment within a short interval of time, will not exceed the repeatability limit, r , in more than 5 % of cases.

Precision data are given in Annex B.

9.3 Reproducibility limit

The absolute difference between two independent single test results, obtained using the same method on identical test material in different laboratories by different operators using different equipment, will not exceed the reproducibility limit, R , in more than 5 % of cases.

Precision data are given in Annex B.

10 Test report

The test report shall include the following information:

- a) all information necessary for the complete identification of the sample;
- b) method used (a reference to this European Standard);
- c) test results;
- d) details of any operations not specified in this document or in the European standards to which reference is made, and any operations regarded as optional, as well as any incidents likely to have affected the results.

[SIST EN 14670:2005
https://standards.iteh.ai/catalog/standards/sist/08614807-6417-4a4c-94e6-fd1ff6d82f/sist-en-14670-2005](https://standards.iteh.ai/catalog/standards/sist/08614807-6417-4a4c-94e6-fd1ff6d82f/sist-en-14670-2005)

(standards.iteh.ai)