

# TECHNICAL SPECIFICATION

**Electric vehicles conductive charging system –  
Part 3-5: DC EV supply equipment where protection relies on double or  
reinforced insulation – Pre-defined communication parameters and general  
application objects**

IEC TS 61851-3-5:2023

<https://standards.iteh.ai/catalog/standards/sist/a3c9b79c-fba4-4c32-9061-32db349f7f2b/iec-ts-61851-3-5-2023>



**THIS PUBLICATION IS COPYRIGHT PROTECTED**  
**Copyright © 2023 IEC, Geneva, Switzerland**

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland

Tel.: +41 22 919 02 11  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)

**About the IEC**

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

**About IEC publications**

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

**IEC publications search - [webstore.iec.ch/advsearchform](http://webstore.iec.ch/advsearchform)**

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

**IEC Products & Services Portal - [products.iec.ch](http://products.iec.ch)**

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

**IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)**

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

**Electropedia - [www.electropedia.org](http://www.electropedia.org)**

The world's leading online dictionary on electrotechnology, containing more than 22 300 terminological entries in English and French, with equivalent terms in 19 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

**IEC Customer Service Centre - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)**

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: [sales@iec.ch](mailto:sales@iec.ch).

[IEC TS 61851-3-5:2023](https://standards.iteh.ai/catalog/standards/sist/a3c9b79c-1ba4-4c52-9061-32db3491712b/iec-ts-61851-3-5-2023)

<https://standards.iteh.ai/catalog/standards/sist/a3c9b79c-1ba4-4c52-9061-32db3491712b/iec-ts-61851-3-5-2023>

# TECHNICAL SPECIFICATION

---

**Electric vehicles conductive charging system –  
Part 3-5: DC EV supply equipment where protection relies on double or  
reinforced insulation – Pre-defined communication parameters and general  
application objects**

[IEC TS 61851-3-5:2023](https://standards.iteh.ai/catalog/standards/sist/a3c9b79c-fba4-4c32-9061-32db349f7f2b/iec-ts-61851-3-5-2023)

<https://standards.iteh.ai/catalog/standards/sist/a3c9b79c-fba4-4c32-9061-32db349f7f2b/iec-ts-61851-3-5-2023>

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

---

ICS 43.120

ISBN 978-2-8322-5770-8

**Warning! Make sure that you obtained this publication from an authorized distributor.**

## CONTENTS

FOREWORD.....	12
INTRODUCTION.....	14
1 Scope.....	15
2 Normative references .....	15
3 Terms and definitions .....	15
4 Symbols and abbreviated terms.....	15
5 Pre-defined communication objects .....	16
5.1 General.....	16
5.1.1 Overview .....	16
5.1.2 Object 1000 <sub>h</sub> : Device type.....	16
5.1.3 Object 1001 <sub>h</sub> : Error register.....	17
5.1.4 Object 1003 <sub>h</sub> : Pre-defined error field .....	17
5.1.5 Object 1005 <sub>h</sub> : COB-ID SYNC.....	17
5.1.6 Object 1006 <sub>h</sub> : Communication cycle period .....	17
5.1.7 Object 1007 <sub>h</sub> : Communication window length .....	18
5.1.8 Object 1016 <sub>h</sub> : Heartbeat consumer time .....	18
5.1.9 Object 1017 <sub>h</sub> : Heartbeat producer time .....	18
5.1.10 Object 1018 <sub>h</sub> : Identity.....	18
5.1.11 Object 1029 <sub>h</sub> : Error behaviour .....	18
5.2 PDO communication .....	19
6 General application objects for CANopen devices.....	19
6.1 General.....	19
6.2 Application objects produced by CANopen devices with NMT slave functionality .....	20
6.2.1 General .....	20
6.2.2 Object 6000 <sub>h</sub> : Supported virtual devices.....	20
6.2.3 Object 6002 <sub>h</sub> : Status word.....	23
6.2.4 Object 6003 <sub>h</sub> : Device capability.....	25
6.2.5 Object 6004 <sub>h</sub> : System date and time (optional).....	27
6.2.6 Object 6005 <sub>h</sub> : Device unique part number (optional).....	28
6.2.7 Object 6006 <sub>h</sub> : Device electronic production date (optional).....	28
6.2.8 Object 6007 <sub>h</sub> : Device installation date (optional) .....	29
6.2.9 Object 6008 <sub>h</sub> : Device nominal voltage (optional, mandatory for active devices).....	30
6.2.10 Object 6009 <sub>h</sub> : Device alarm status .....	32
6.2.11 Object 600A <sub>h</sub> : Device alarm capability.....	33
6.2.12 Object 600B <sub>h</sub> : Device warning status (optional) .....	35
6.2.13 Object 600C <sub>h</sub> : Device warning capability (optional) .....	37
6.2.14 Object 600E <sub>h</sub> : Implemented specification versions .....	39
6.2.15 Object 6020 <sub>h</sub> : Device request dynamic voltage limitation.....	41
6.2.16 Object 6022 <sub>h</sub> : Device request dynamic current input limitation.....	42

6.2.17	Object 6023 <sub>h</sub> : Device request dynamic current output limitation .....	44
6.2.18	Object 6024 <sub>h</sub> : Device maximum continuous input current .....	46
6.2.19	Object 6025 <sub>h</sub> : Device maximum continuous output current .....	48
6.2.20	Object 6026 <sub>h</sub> : Device maximum voltage .....	49
6.2.21	Object 6027 <sub>h</sub> : Device minimum voltage .....	51
6.2.22	Object 6039 <sub>h</sub> : Device actual external voltage (optional).....	52
6.2.23	Object 603A <sub>h</sub> : Device peak input current .....	54
6.2.24	Object 603B <sub>h</sub> : Device peak input current time (optional).....	55
6.2.25	Object 603C <sub>h</sub> : Device peak output current (optional) .....	57
6.2.26	Object 603D <sub>h</sub> : Device peak output current time (optional).....	58
6.2.27	Object 603E <sub>h</sub> : Device actual current .....	59
6.2.28	Object 6040 <sub>h</sub> : Device actual voltage .....	61
6.2.29	Object 6042 <sub>h</sub> : Device internal temperature (optional) .....	62
6.2.30	Object 6043 <sub>h</sub> : Device time on (optional) .....	64
6.2.31	Object 6044 <sub>h</sub> : Device time standby (optional) .....	64
6.2.32	Object 6045 <sub>h</sub> : Device switch on counter (optional).....	65
6.2.33	Object 6060 <sub>h</sub> : CANopen device measurement timing (optional) .....	65
6.2.34	Object 6064 <sub>h</sub> : Device maximum AUX continuous input current (optional).....	69
6.2.35	Object 6065 <sub>h</sub> : Device maximum AUX continuous output current (optional) .....	70
6.2.36	Object 6066 <sub>h</sub> : Device maximum AUX voltage (optional).....	72
6.2.37	Object 6067 <sub>h</sub> : Device minimum AUX voltage (optional).....	73
6.2.38	Object 6070 <sub>h</sub> : Device actual AUX current (optional).....	75
6.2.39	Object 6071 <sub>h</sub> : Device actual AUX voltage (optional) .....	77
6.2.40	Object 6072 <sub>h</sub> : Device available output voltage .....	78
6.2.41	Object 6073 <sub>h</sub> : Device available output current .....	79
6.2.42	Object 6074 <sub>h</sub> : Device available input current (optional) .....	81
6.3	Security .....	82
6.3.1	General .....	82
6.3.2	Object 6311 <sub>h</sub> : Locking status.....	83
6.4	Application objects consumed by CANopen devices with NMT slave functionality (mandatory).....	84
6.4.1	General .....	84
6.4.2	Object 6001 <sub>h</sub> : Control word .....	85
6.4.3	Object 6046 <sub>h</sub> : Device set maximum voltage.....	86
6.4.4	Object 6047 <sub>h</sub> : Device set minimum voltage.....	88
6.4.5	Object 604A <sub>h</sub> : Device set maximum continuous input current .....	89
6.4.6	Object 604B <sub>h</sub> : Device set maximum continuous output current .....	90
6.4.7	Object 604C <sub>h</sub> : Device set maximum peak input current .....	91
6.4.8	Object 604D <sub>h</sub> : Device set maximum peak input current time .....	92
6.4.9	Object 604E <sub>h</sub> : Device set maximum peak output current.....	93
6.4.10	Object 604F <sub>h</sub> : Device set maximum peak output current time .....	94

6.5	Application objects consumed by CANopen devices with NMT slave functionality (optional).....	95
6.5.1	General .....	95
6.5.2	Object 600D <sub>h</sub> : Error behaviour at process interface (optional) .....	95
6.5.3	Object 6058 <sub>h</sub> : Device security key (optional) .....	96
6.5.4	Object 6059 <sub>h</sub> : Devices' user name and address (optional).....	97
6.5.5	Object 605A <sub>h</sub> : Device password (optional).....	99
6.5.6	Object 6053 <sub>h</sub> : Prefixes and SI units for analogue values (optional).....	100
7	Application objects relevant for fleet management (optional) .....	103
7.1	General.....	103
7.2	Object 63D5 <sub>h</sub> : Travelled distance .....	103
7.3	Object 63D6 <sub>h</sub> : Travelled distance current trip.....	104
7.4	Object 63D7 <sub>h</sub> : Travelled time.....	105
7.5	Object 63D8 <sub>h</sub> : Travelled time current trip .....	106
7.6	Object 63D9 <sub>h</sub> : Transferred watt hours.....	107
7.7	Object 63DA <sub>h</sub> : Current trip transferred watt hours.....	108
8	Stationary applications (optional).....	110
8.1	General application objects relevant for stationary applications .....	110
8.2	Object 6010 <sub>h</sub> : Ambient temperature .....	110
8.3	Object 6011 <sub>h</sub> : Phase 1 AC Current .....	111
8.4	Object 6012 <sub>h</sub> : Phase 2 AC Current .....	113
8.5	Object 6013 <sub>h</sub> : Phase 3 AC Current .....	114
8.6	Object 6014 <sub>h</sub> : Phase 1 AC voltage.....	115
8.7	Object 6015 <sub>h</sub> : Phase 2 AC voltage.....	117
8.8	Object 6016 <sub>h</sub> : Phase 3 AC voltage.....	118
8.9	Object 6017 <sub>h</sub> : Line 12 AC voltage .....	120
8.10	Object 6018 <sub>h</sub> : Line 23 AC voltage .....	121
8.11	Object 6019 <sub>h</sub> : Line 13 AC voltage .....	123
8.12	Object 601A <sub>h</sub> : Phase 1 AC reactive power .....	124
8.13	Object 601B <sub>h</sub> : Phase 2 AC reactive power .....	126
8.14	Object 601C <sub>h</sub> : Phase 3 AC reactive power.....	127
8.15	Object 601D <sub>h</sub> : Phase 1 AC apparent power .....	129
8.16	Object 601E <sub>h</sub> : Phase 2 AC apparent power .....	130
8.17	Object 601F <sub>h</sub> : Phase 3 AC apparent power.....	132
8.18	Object 6030 <sub>h</sub> : Phase 1 AC real power.....	134
8.19	Object 6031 <sub>h</sub> : Phase 2 AC real power.....	135
8.20	Object 6032 <sub>h</sub> : Phase 3 AC real power.....	137
8.21	Object 6033 <sub>h</sub> : Total AC reactive power .....	138
8.22	Object 6034 <sub>h</sub> : Total AC apparent power.....	140
8.23	Object 6035 <sub>h</sub> : Total AC real power.....	141
8.24	Object 6036 <sub>h</sub> : Phase1 power factor (cos phi) .....	143
8.25	Object 6037 <sub>h</sub> : Phase 2 power factor (cos phi).....	144

8.26	Object 6038 <sub>h</sub> : Phase 3 power factor (cos phi) .....	146
8.27	Object 6050 <sub>h</sub> : AC Frequency .....	147
8.28	Object 6051 <sub>h</sub> : Isolation resistance .....	149
8.29	Object 6052 <sub>h</sub> : Rated power .....	150
Annex A (informative) Measured values .....		152
A.1	General .....	152
A.2	Actual voltage .....	152
Annex B (normative) Process data object (PDO) communication for EMS .....		153
B.1	General .....	153
B.2	Specification of messages .....	153
B.3	Allocation of PDOs to virtual devices .....	153
B.4	Detailed PDO parameters .....	159
B.4.1	General .....	159
B.4.2	TPDO parameters for message number 1 .....	159
B.4.3	TPDO parameters for message number 2 .....	162
B.4.4	TPDO parameters for message number 3 .....	164
B.4.5	TPDO parameters for message number 4 to 9 .....	167
B.4.6	TPDO parameters for message number 10 .....	168
B.4.7	TPDO parameters for message number 12 .....	170
Bibliography .....		173
Figure 1 – Object structure .....		16
Figure 2 – Object structure supported virtual devices .....		20
Figure 3 – Object structure device status .....		23
Figure 4 – Value structure .....		25
Figure 5 – Value structure .....		32
Figure 6 – Value structure .....		33
Figure 7 – Value structure .....		35
Figure 8 – Value structure .....		37
Figure 9 – Value structure .....		39
Figure 10 – Object structure security status .....		83
Figure 11 – Value structure .....		85
Figure 12 – Object structure for prefixes .....		101
Figure A.1 – Voltage measurement at generic active device .....		152
Table 1 – Value definition for the bit field additional information .....		16
Table 2 – Object description .....		17
Table 3 – Entry description .....		17
Table 4 – Default value definition object 1005 <sub>h</sub> .....		17
Table 5 – Value definition .....		18
Table 6 – Object description (optional) .....		18
Table 7 – Entry description .....		19
Table 8 – Value definition for bit fields .....		21
Table 9 – Object description .....		22

Table 10 – Entry description .....	22
Table 11 – Value definition device status .....	23
Table 12 – Object description .....	24
Table 13 – Entry description .....	24
Table 14 – Value definition .....	25
Table 15 – Object description .....	26
Table 16 – Entry description .....	26
Table 17 – Object description .....	27
Table 18 – Entry description .....	27
Table 19 – Object description .....	28
Table 20 – Entry description .....	28
Table 21 – Object description .....	28
Table 22 – Entry description .....	29
Table 23 – Object description .....	29
Table 24 – Entry description .....	30
Table 25 – Object description .....	30
Table 26 – Entry description .....	31
Table 27 – Value definition .....	32
Table 28 – Object description .....	33
Table 29 – Entry description .....	33
Table 30 – Value definition .....	34
Table 31 – Object description .....	35
Table 32 – Entry description .....	35
Table 33 – Value definition .....	36
Table 34 – Object description .....	37
Table 35 – Entry description .....	37
Table 36 – Value definition .....	37
Table 37 – Object description .....	38
Table 38 – Entry description .....	39
Table 39 – Value definition .....	39
Table 40 – Object description .....	40
Table 41 – Entry description .....	40
Table 42 – Value definition .....	41
Table 43 – Object description .....	41
Table 44 – Entry description .....	41
Table 45 – Value definition .....	43
Table 46 – Object description .....	43
Table 47 – Entry description .....	43
Table 48 – Value definition .....	45
Table 49 – Object description .....	45
Table 50 – Entry description .....	45
Table 51 – Object description .....	46
Table 52 – Entry description .....	47



Table 53 – Object description ..... 48

Table 54 – Entry description ..... 48

Table 55 – Object description ..... 49

Table 56 – Entry description ..... 50

Table 57 – Object description ..... 51

Table 58 – Entry description ..... 51

Table 59 – Object description ..... 53

Table 60 – Entry description ..... 53

Table 61 – Object description ..... 54

Table 62 – Entry description ..... 54

Table 63 – Object description ..... 56

Table 64 – Entry description ..... 56

Table 65 – Object description ..... 57

Table 66 – Entry description ..... 57

Table 67 – Object description ..... 58

Table 68 – Entry description ..... 59

Table 69 – Object description ..... 60

Table 70 – Entry description ..... 60

Table 71 – Object description ..... 61

Table 72 – Entry description ..... 61

Table 73 – Object description ..... 63

Table 74 – Entry description ..... 63

Table 75 – Object description ..... 64

Table 76 – Entry description ..... 64

Table 77 – Object description ..... 64

Table 78 – Entry description ..... 64

Table 79 – Object description ..... 65

Table 80 – Entry description ..... 65

Table 81 – Object description ..... 66

Table 82 – Entry description ..... 66

Table 83 – Object description ..... 69

Table 84 – Entry description ..... 69

Table 85 – Object description ..... 70

Table 86 – Entry description ..... 71

Table 87 – Object description ..... 72

Table 88 – Entry description ..... 72

Table 89 – Object description ..... 74

Table 90 – Entry description ..... 74

Table 91 – Object description ..... 75

Table 92 – Entry description ..... 75

Table 93 – Object description ..... 77

Table 94 – Entry description ..... 77

Table 95 – Object description ..... 78

Table 96 – Entry description .....	78
Table 97 – Object description .....	80
Table 98 – Entry description .....	80
Table 99 – Object description .....	81
Table 100 – Entry description .....	81
Table 101 – Value definition security status .....	83
Table 102 – Object description.....	83
Table 103 – Entry description .....	84
Table 104 – Value definition.....	85
Table 105 – Object description.....	85
Table 106 – Entry description .....	86
Table 107 – Object description.....	87
Table 108 – Entry description .....	87
Table 109 – Object description.....	88
Table 110 – Entry description .....	88
Table 111 – Object description.....	89
Table 112 – Entry description .....	89
Table 113 – Object description.....	90
Table 114 – Entry description .....	90
Table 115 – Object description.....	91
Table 116 – Entry description .....	91
Table 117 – Object description.....	92
Table 118 – Entry description .....	92
Table 119 – Object description.....	93
Table 120 – Entry description .....	93
Table 121 – Object description.....	94
Table 122 – Entry description .....	94
Table 123 – Value definition.....	95
Table 124 – Object description.....	95
Table 125 – Entry description .....	96
Table 126 – Object description.....	97
Table 127 – Entry description .....	97
Table 128 – Object description.....	98
Table 129 – Entry description .....	98
Table 130 – Object description.....	99
Table 131 – Entry description .....	99
Table 132 – Additional units.....	101
Table 133 – Allocation of powerlines to sub-indices .....	101
Table 134 – Object description.....	101
Table 135 – Entry description .....	101
Table 136 – Object description.....	103
Table 137 – Entry description .....	104
Table 138 – Object description.....	105

Table 139 – Entry description .....	105
Table 140 – Object description.....	106
Table 141 – Entry description .....	106
Table 142 – Object description.....	107
Table 143 – Entry description .....	107
Table 144 – Object description.....	108
Table 145 – Entry description .....	108
Table 146 – Object description.....	109
Table 147 – Entry description .....	109
Table 148 – Object description.....	110
Table 149 – Entry description .....	110
Table 150 – Object description.....	111
Table 151 – Entry description .....	112
Table 152 – Object description.....	113
Table 153 – Entry description .....	113
Table 154 – Object description.....	114
Table 155 – Entry description .....	114
Table 156 – Object description.....	116
Table 157 – Entry description .....	116
Table 158 – Object description.....	117
Table 159 – Entry description .....	117
Table 160 – Object description.....	118
Table 161 – Entry description .....	119
Table 162 – Object description.....	120
Table 163 – Entry description .....	120
Table 164 – Object description.....	121
Table 165 – Entry description .....	122
Table 166 – Object description.....	123
Table 167 – Entry description .....	123
Table 168 – Object description.....	124
Table 169 – Entry description .....	124
Table 170 – Object description.....	126
Table 171 – Entry description .....	126
Table 172 – Object description.....	127
Table 173 – Entry description .....	128
Table 174 – Object description.....	129
Table 175 – Entry description .....	129
Table 176 – Object description.....	131
Table 177 – Entry description .....	131
Table 178 – Object description.....	132
Table 179 – Entry description .....	132
Table 180 – Object description.....	134
Table 181 – Entry description .....	134

Table 182 – Object description.....	135
Table 183 – Entry description .....	136
Table 184 – Object description.....	137
Table 185 – Entry description .....	137
Table 186 – Object description.....	138
Table 187 – Entry description .....	139
Table 188 – Object description.....	140
Table 189 – Entry description .....	140
Table 190 – Object description.....	141
Table 191 – Entry description .....	142
Table 192 – Object description.....	143
Table 193 – Entry description .....	143
Table 194 – Object description.....	144
Table 195 – Entry description .....	145
Table 196 – Object description.....	146
Table 197 – Entry description .....	146
Table 198 – Object description.....	147
Table 199 – Entry description .....	148
Table 200 – Object description.....	149
Table 201 – Entry description .....	149
Table 202 – Object description.....	150
Table 203 – Entry description .....	151
Table B.1 – PDO mapping entries .....	153
Table B.2 – PDO assignment for active devices .....	154
Table B.3 – PDO assignment for VCU 9 to 16.....	156
Table B.4 – Additional PDO assignment for some active devices .....	156
Table B.5 – PDO assignment for passive devices .....	158
Table B.6 – Object description .....	159
Table B.7 – Entry description .....	159
Table B.8 – Object description .....	161
Table B.9 – Entry description .....	161
Table B.10 – Object description .....	162
Table B.11 – Entry description .....	162
Table B.12 – Object description .....	164
Table B.13 – Entry description .....	164
Table B.14 – TPDO communication parameter.....	165
Table B.15 – Entry description .....	165
Table B.16 – Object description .....	166
Table B.17 – Entry description .....	167
Table B.18 – Object description .....	168
Table B.19 – Entry description .....	168
Table B.20 – Object description .....	169
Table B.21 – Entry description .....	170

Table B.22 – Object description ..... 170  
Table B.23 – Entry description ..... 171  
Table B.24 – Object description ..... 172  
Table B.25 – Entry description ..... 172

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

IEC TS 61851-3-5:2023

<https://standards.iteh.ai/catalog/standards/sist/a3c9b79c-fba4-4c32-9061-32db349f7f2b/iec-ts-61851-3-5-2023>

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**ELECTRIC VEHICLES CONDUCTIVE CHARGING SYSTEM –**

**Part 3-5: DC EV supply equipment where protection relies on double or reinforced insulation – Pre-defined communication parameters and general application objects**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC TS 61851-3-5 has been prepared by s IEC technical committee 69: Electrical power/energy transfer systems for electrically propelled road vehicles and industrial trucks. It is a Technical Specification.

The text of this Technical Specification is based on the following documents:

Draft	Report on voting
69/651/DTS	69/672/RVDTS
	69/672A/RVDTS

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this Technical Specification is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at [www.iec.ch/members\\_experts/refdocs](http://www.iec.ch/members_experts/refdocs). The main document types developed by IEC are described in greater detail at [www.iec.ch/publications](http://www.iec.ch/publications).

The following print types are used:

- requirements: in roman type;
- notes: in small roman type;
- **text formatted in bold and using mixed capital and underline are used as state names and are not to be translated.**

A list of all parts in the IEC 61851 series, published under the general title *Electric vehicles conductive charging system*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under [webstore.iec.ch](http://webstore.iec.ch) in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

[IEC TS 61851-3-5:2023](https://standards.iteh.ai/catalog/standards/sist/a3c9b79c-fba4-4c32-9061-32db349f7f2b/iec-ts-61851-3-5-2023)

<https://standards.iteh.ai/catalog/standards/sist/a3c9b79c-fba4-4c32-9061-32db349f7f2b/iec-ts-61851-3-5-2023>