

SLOVENSKI STANDARD

SIST HD 60269-2:2010

01-november-2010

Nadomešča:

SIST HD 60269-2:2008

Niskonapetostne varovalke - 2. del: Dodatne zahteve za varovalke, ki jih uporabljajo strokovne osebe (uporaba varovalk zlasti v industriji) - Primeri tipov standardiziranih varovalk od A do J (IEC 60269-2:2010, spremenjen)

Low-voltage fuses - Part 2: Supplementary requirements for fuses for use by authorized persons (fuses mainly for industrial application) - Examples of standardized systems of fuses A to J (IEC 60269-2:2010, modified)

Niederspannungssicherungen - Teil 2: Zusätzliche Anforderungen an Sicherungen zum Gebrauch durch Elektrofachkräfte bzw. elektrotechnisch unterwiesene Personen (Sicherungen überwiegend für den industriellen Gebrauch) - Beispiele für genormte Sicherungssysteme A bis J (IEC 60269-2:2010, modifiziert)

Fusibles basse tension - Partie 2: Exigences supplémentaires pour les fusibles destinés à être utilisés par des personnes habilitées (fusibles pour usages essentiellement industriels) - Exemples de systèmes de fusibles normalisés A à J (IEC 60269-2:2010, modifiée)

Ta slovenski standard je istoveten z: HD 60269-2:2010

ICS:

29.120.50	Varovalke in druga medtokovna zaščita	Fuses and other overcurrent protection devices
-----------	---------------------------------------	--

SIST HD 60269-2:2010

en,fr

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST HD 60269-2:2010

<https://standards.iteh.ai/catalog/standards/sist/c3f7e77e-fd11-4792-a631-4d23c9743421/sist-hd-60269-2-2010>

HARMONIZATION DOCUMENT
DOCUMENT D'HARMONISATION
HARMONISIERUNGSDOKUMENT

HD 60269-2

September 2010

ICS 29.120.50

Supersedes HD 60269-2:2007

English version

**Low-voltage fuses -
Part 2: Supplementary requirements for fuses for use by authorized
persons (fuses mainly for industrial application) -
Examples of standardized systems of fuses A to J
(IEC 60269-2:2010, modified)**

Fusibles basse tension -
Partie 2: Exigences supplémentaires pour
les fusibles destinés à être utilisés par
des personnes habilitées (fusibles pour
usages essentiellement industriels) -
Exemples de systèmes de fusibles
normalisés A à J
(CEI 60269-2:2010, modifiée)

Niederspannungssicherungen -
Teil 2: Zusätzliche Anforderungen
an Sicherungen zum Gebrauch durch
Elektrofachkräfte bzw. elektrotechnisch
unterwiesene Personen (Sicherungen
überwiegend für den industriellen
Gebrauch) - Beispiele für genormte
Sicherungssysteme A bis J
(IEC 60269-2:2010, modifiziert)

[SIST HD 60269-2:2010](https://standards.iteh.ai/catalog/standards/sist/c3f7e77e-fd11-4792-a631-4d23c9743421/sist-hd-60269-2-2010)

<https://standards.iteh.ai/catalog/standards/sist/c3f7e77e-fd11-4792-a631-4d23c9743421/sist-hd-60269-2-2010>

This Harmonization Document was approved by CENELEC on 2010-09-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for implementation of this Harmonization Document at national level.

Up-to-date lists and bibliographical references concerning such national implementations may be obtained on application to the Central Secretariat or to any CENELEC member.

This Harmonization Document exists in three official versions (English, French, German).

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Management Centre: Avenue Marnix 17, B - 1000 Brussels

Foreword

The text of document 32B/552/FDIS, future edition 4 of IEC 60269-2, prepared by SC 32B, Low-voltage fuses, of IEC TC 32, Fuses, was submitted to the IEC-CENELEC parallel vote.

A draft amendment, containing common modifications to document 32B/552/FDIS was prepared by Reporting Secretariat CLC/SR 32B, Low-voltage fuses, and was submitted to the formal vote.

The combined texts were approved by CENELEC as HD 60269-2 on 2010-09-01.

This Harmonization Document supersedes HD 60269-2:2007

This document is to be used in conjunction with EN 60269-1:2007.

This Part 2 supplements or modifies the corresponding clauses or subclauses of Part 1.

Where no change is necessary, this Part 2 indicates that the relevant clause or subclause applies.

The following dates were fixed:

- latest date by which the EN has to be implemented
at national level by publication of an identical
national standard or by endorsement (dop) 2011-09-01
- latest date by which the national standards conflicting
with the EN have to be withdrawn (dow) 2013-09-01

Annex ZA has been added by CENELEC.

Endorsement notice

The text of the International Standard IEC 60269-2:2010 was approved by CENELEC as a Harmonization Document with agreed common modifications as given below.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 60060-2	NOTE	Harmonized as EN 60060-2.
IEC 60060-3	NOTE	Harmonized as EN 60060-3.
IEC 60529	NOTE	Harmonized as EN 60529.
ISO 898-1	NOTE	Harmonized as EN ISO 898-1.
ISO 1207:1992	NOTE	Harmonized as EN ISO 1207:1994 (not modified).

COMMON MODIFICATIONS

1 General scope

Replace the note by:

NOTE The following fuse systems are standardized systems in respect to their safety aspects. The National Committees shall select at least one complete fuse system of this standard for their national standards. The time current characteristics "gD" and "gN" are only relevant for the fuse system H.

Fuse system A – Fuses with fuse-links with blade contacts (NH fuse system)

6.2 Marking of fuse-links

Replace the first sentence after the table by the following:

Fuse-links with isolated gripping-lugs shall be marked in a place visible at the front with the graphical symbol of a gripping-lug in a square.

8.5.5.1 Verification of the peak withstand current of a fuse-base

Add at the end of the first sentence:

... or if the minimum withdrawal forces according to 8.11 are exceeded.

Annex ZA (normative)

Normative references to international publications with their corresponding European publications

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60060-1	-	High-voltage test techniques - Part 1: General definitions and test requirements	HD 588.1 S1	-
IEC 60112	-	Method for the determination of the proof and the comparative tracking indices of solid insulating materials	EN 60112	-
IEC 60269-1 + A1	2006 2009	Low-voltage fuses - Part 1: General requirements	EN 60269-1 + A1	2007 2009
IEC 60664-1	-	Insulation coordination for equipment within low-voltage systems - Part 1: Principles, requirements and tests	EN 60664-1	-
IEC 60999	Series	Connecting devices - Electrical copper conductors - Safety requirements for screw- type and screwless-type clamping units	EN 60999	Series
IEC 60999-1	-	Connecting devices - Electrical copper conductors - Safety requirements for screw- type and screwless-type clamping units - Part 1: General requirements and particular requirements for clamping units for conductors from 0,2 mm ² up to 35 mm ² (included)	EN 60999-1	-
IEC 60999-2	-	Connecting devices - Electrical copper conductors - Safety requirements for screw- type and screwless-type clamping units - Part 2: Particular requirements for clamping units for conductors above 35 mm ² up to 300 mm ² (included)	EN 60999-2	-
ISO 6988	-	Metallic and other non-organic coatings - Sulfur dioxide test with general condensation of moisture	EN ISO 6988	-



IEC 60269-2

Edition 4.0 2010-04

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Low-voltage fuses – Part 2: Supplementary requirements for fuses for use by authorized persons (fuses mainly for industrial application) – Examples of standardized systems of fuses A to J

STANDARD PREVIEW
(standards.iteh.ai)
SIST HD 60269-2:2010
<https://standards.iteh.ai/catalog/standards/sist/c3f7e77e-fd11-4792-a631-4d23c9743421/sist-hd-60269-2-2010>

Fusibles basse tension – Partie 2: Exigences supplémentaires pour les fusibles destinés à être utilisés par des personnes habilitées (fusibles pour usages essentiellement industriels) – Exemples de systèmes de fusibles normalisés A à J

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

PRICE CODE
CODE PRIX

XJ

ICS 29.120.50

ISBN 978-2-88910-087-3

CONTENTS

FOREWORD.....	14
INTRODUCTION.....	16
1 General scope.....	17
1.2 Normative references	18
Fuse system A – Fuses with fuse-links with blade contacts (NH fuse system)	19
1 General.....	19
1.1 Scope.....	19
2 Terms and definitions	19
3 Conditions for operation in service.....	19
4 Classification.....	20
5 Characteristics of fuses	20
5.2 Rated voltage	20
5.3.1 Rated current of the fuse-link.....	20
5.3.2 Rated current of the fuse-holder	20
5.5 Rated power dissipation of a fuse-link and rated acceptable power dissipation of a fuse-holder	20
5.6 Limits of time-current characteristics	21
5.6.1 Time-current characteristics, time-current zones and overload curves	21
5.6.2 Conventional times and currents.....	21
5.6.3 Gates	21
5.7.2 Rated breaking capacity	21
6 Marking	22
6.1 Markings of fuse-holders	22
6.2 Markings of fuse-links.....	22
7 Standard conditions for construction.....	22
7.1 Mechanical design.....	23
7.1.2 Connections, including terminals	23
7.1.3 Fuse-contacts.....	23
7.1.6 Construction of fuse-bases	23
7.1.7 Construction of a fuse-link	24
7.2 Insulating properties.....	24
7.7 I^2t characteristics	24
7.8 Overcurrent discrimination of "gG" fuse-links.....	25
7.9 Protection against electric shock	25
8 Tests.....	25
8.1.4 Arrangement of the fuse and dimensions	26
8.1.6 Testing of fuse-holders.....	26
8.2.4 Acceptability of test results.....	27
8.2.5 Resistance to tracking	27
8.3 Verification of temperature rise and power dissipation	27
8.3.1 Arrangement of the fuse	27
8.3.2 Measurement of the temperature rise	28
8.5.8 Acceptability of test results.....	29
8.7.4 Verification of overcurrent discrimination	29

8.9	Verification of resistance to heat	31
8.9.1	Fuse-base	31
8.9.2	Fuse-links with gripping lugs of moulded material or of metal fixed in moulded material	31
8.10	Verification of non-deterioration of contacts and direct terminal clamps	32
8.10.1	Arrangement of the fuse	32
8.10.2	Test method	34
8.10.3	Acceptability of test results	35
8.11	Mechanical and miscellaneous tests	36
Annex AA (informative) Special test for cable overload protection		58
Fuse system B – Fuses with striker fuse-links with blade contacts (NH fuse system)		59
1	General	59
1.1	Scope	59
2	Terms and definitions	59
3	Conditions for operation in service	59
4	Classification	59
5	Characteristics of fuses	59
5.2	Rated voltage	59
5.3.1	Rated current of the fuse-link	59
5.3.2	Rated current of the fuse-holder	60
5.5	Rated power dissipation of a fuse-link and rated acceptable power dissipation of a fuse-holder	60
5.6	Limits of time-current characteristics	60
5.7.2	Rated breaking capacity	60
6	Marking	60
7	Standard conditions for construction	60
7.1	Mechanical design	60
7.1.2	Connections, including terminals	60
7.1.3	Fuse-contacts	60
7.1.7	Construction of a fuse-link	61
7.2	Insulating properties and suitability for insulation	61
7.7	I^2t characteristics	61
7.8	Overcurrent discrimination of "gG" fuse-links	61
7.9	Protection against electric shock	61
8	Tests	61
8.1.6	Testing of fuse-holders	61
8.3	Verification of temperature rise and power dissipation	61
8.7.4	Verification of overcurrent discrimination	62
8.9	Verification of resistance to heat	62
8.9.1	Fuse-base	62
Fuse system C – Fuse-rails (NH fuse system)		71
1	General	71
1.1	Scope	71
2	Terms and definitions	71

3	Conditions for operation in service.....	71
4	Classification.....	71
5	Characteristics of fuses	71
	5.2 Rated voltage	71
	5.3.2 Rated current	71
	5.5.1 Rated acceptable power dissipation.....	71
6	Markings	71
7	Standard conditions for construction.....	72
	7.1 Mechanical design.....	72
	7.1.2 Connections, including terminals	72
	7.2 Insulating properties.....	72
8	Tests.....	72
	8.1.6 Testing of fuse-holders.....	73
	8.3 Verification of temperature rise and power dissipation	73
	8.3.1 Arrangement of the fuse	73
	8.10 Verification of non-deterioration of contacts and direct terminal clamps.....	74
	8.10.1 Arrangement of the fuse	74
Fuse system D – Fuse-bases for busbar mounting (40 mm system) (NH fuse system)		
	1 General	79
	1.1 Scope.....	79
2	Terms and definitions	79
3	Conditions for operation in service.....	79
4	Classification.....	79
5	Characteristics of fuses	79
	5.2 Rated voltage	79
	5.3.2 Rated current	79
	5.5.2 Rated acceptable power dissipation of tandem fuse-bases	80
6	Markings	80
7	Standard conditions for construction.....	80
	7.1 Mechanical design.....	80
	7.1.2 Connections, including terminals	80
	7.1.5 Construction of a fuse-base for busbar mounting	80
	7.2 Insulating properties and suitability for insulation	81
8	Tests.....	81
	8.3 Verification of temperature rise and power dissipation	81
	8.3.1 Arrangement of the fuse	81
	8.9.1 Fuse-base	82
	8.10 Verification of non-deterioration of contacts and direct terminal clamps.....	82
	8.10.1 Arrangement of the fuse	82
	8.10.2 Test method	82
	8.11 Mechanical and miscellaneous tests.....	82
Fuse system E – Fuses with fuse-links for bolted connections (BS bolted fuse system)		
1	General.....	91

1.1	Scope.....	91
2	Terms and definitions	91
3	Conditions for operation in service.....	91
4	Classification.....	91
5	Characteristics of fuses	91
5.3.1	Rated current of the fuse-link.....	91
5.3.2	Rated current of the fuse-holder	91
5.5	Rated power dissipation of a fuse-link and rated acceptable power dissipation of a fuse-holder	91
5.6	Limits of time-current characteristics	92
5.6.1	Time-current characteristics, time-current zones and overload curves	92
5.6.2	Conventional times and currents.....	92
5.6.3	Gates	92
5.7.2	Rated breaking capacity	92
6	Markings	92
6.1	Markings of fuse-holders	92
6.2	Markings of fuse-links.....	92
7	Standard conditions for construction.....	93
7.1	Mechanical design.....	93
7.1.2	Connections including terminals.....	93
7.2	Insulating properties and suitability for insulation	93
7.9	Protection against electric shock.....	93
8	Tests.....	93
8.3	Verification of temperature rise and power dissipation.....	93
8.3.1	Arrangement of the fuse.....	93
8.3.3	Measurement of the power dissipation of the fuse-link.....	93
8.4	Verification of operation	93
8.4.1	Arrangement of the fuse	93
8.5	Verification of breaking capacity.....	93
8.5.1	Arrangement of the fuse	93
8.5.8	Acceptability of test results.....	93
8.9	Verification of resistance to heat	94
8.10	Verification of non-deterioration of contacts.....	94
8.10.1	Arrangement of the fuse	94
8.10.2	Test method	94
8.10.3	Acceptability of the results.....	94
8.11	Mechanical and miscellaneous tests.....	94
Fuse system F – Fuses with fuse-links having cylindrical contact caps (NF cylindrical fuse system)		105
1	General	105
1.1	Scope.....	105
2	Terms and definitions	105
3	Conditions for operation in service.....	105
4	Classification.....	105
5	Characteristics of fuses	105
5.2	Rated voltage.....	105

5.3.1	Rated current of the fuse-link.....	105
5.3.2	Rated current of the fuse-holder	106
5.5	Rated power dissipation of a fuse-link and rated acceptable power dissipation of a fuse-holder	106
5.6	Limits of time-current characteristics	107
5.6.1	Time-current characteristics, time-current zones and overload curves	107
5.6.2	Conventional times and currents.....	107
5.6.3	Gates	107
5.7.2	Rated breaking capacity	107
6	Marking	108
6.1	Markings of fuse-holders	108
6.2	Markings of fuse-links.....	108
7	Standard conditions for construction.....	108
7.1	Mechanical design.....	108
7.1.2	Connections including terminals	108
7.2	Insulating properties and suitability for insulation	109
7.7	I^2t characteristics	109
7.8	Overcurrent discrimination of "gG" fuse-links.....	109
7.9	Protection against electric shock	109
8	Tests	110
8.1.6	Testing of fuse-holders	110
8.3.1	Arrangement of the fuse	110
8.7.4	Verification of overcurrent discrimination	112
8.9	Verification of resistance to heat	113
8.10	Verification of non-deterioration of contacts	113
8.10.1	Arrangement of the fuse	113
8.10.2	Test method	114
8.10.3	Acceptability of test results	114

Fuse system G – Fuses with fuse-links with offset blade contacts (BS clip-in fuse system)	119
1 General	119
1.1 Scope.....	119
2 Terms and definitions	119
3 Conditions for operation in service.....	119
4 Classification.....	119
5 Characteristics of fuses	119
5.2 Rated voltage	119
5.3.1 Rated current of the fuse-link.....	120
5.3.2 Rated current of the fuse-holder	120
5.5 Rated power dissipation of a fuse-link and rated acceptable power dissipation of a fuse-holder	120
5.6.1 Time-current characteristics, time-current zones	120
5.6.2 Conventional times and currents.....	120
5.6.3 Gates	120
5.7.2 Rated breaking capacity	120
6 Markings	121
6.1 Markings of fuse-holders	121

6.2	Markings of fuse-links.....	121
7	Standard conditions for construction.....	121
7.1	Mechanical design.....	121
7.1.2	Connections including terminals	121
7.2	Insulating properties and suitability for insulation	121
7.7	I^2t characteristics	121
7.9	Protection against electric shock	122
8	Tests.....	122
8.3.3	Measurement of the power dissipation of the fuse-link.....	122
8.4.1	Arrangement of the fuse	122
8.5.1	Arrangement of the fuse	122
8.7.4	Verification of overcurrent discrimination	122
8.9	Verification of resistance to heat	123
8.10	Verification of non-deterioration of contacts.....	123
8.10.1	Arrangement of the fuse	123
8.10.2	Test method	123
8.10.3	Acceptability of test results.....	123
8.11	Mechanical and miscellaneous tests.....	123
Fuse system H – Fuses with fuse-links having "gD" and "gN" characteristics (class J, class T, and class L time delay and non time delay fuse types)		129
1	General.....	129
1.1	Scope.....	129
2	Terms and definitions	129
3	Conditions for operation in service.....	129
4	Classification.....	129
5	Characteristics of fuses	129
5.2	Rated voltage	129
5.3.1	Rated current of the fuse-link.....	130
5.3.2	Rated current of the fuse-holder	130
5.5	Rated power dissipation of a fuse-link and rated acceptable power dissipation of a fuse-holder	130
5.6	Limits of the time-current characteristics	130
5.6.1	Time-current characteristics, time-current zones	130
5.6.2	Conventional times and currents.....	130
5.6.3	Gates	130
5.7.2	Rated breaking capacity	131
6	Markings	131
6.1	Markings of fuse-holders	131
6.2	Markings of fuse-links.....	131
7	Standard conditions for construction.....	131
7.1	Mechanical design.....	131
7.2	Insulating properties and suitability for insulation	131
7.5	Breaking Capacity	131
7.6	Cut-off current characteristics.....	131
7.7	I^2t characteristics	132
7.8	Overcurrent discrimination.....	132
7.9	Protection against electric shock	132

8	Tests	133
8.3	Verification of temperature rise and power dissipation	133
8.3.1	Arrangement of the fuse	133
8.4	Verification of operation	133
8.4.1	Arrangement of the fuse	133
8.5.4	Recovery voltage	134
8.6	Verification of cut-off current characteristics	134
8.7	Verification of I^2t characteristics and overcurrent discrimination	134
8.9	Verification of resistance to heat	135
8.10	Verification of non-deterioration of contacts	135
8.10.1	Arrangement of the fuse	135
8.10.2	Test method	135
8.10.3	Acceptability of test results	136
8.11	Mechanical and miscellaneous tests	136
8.11.2	Miscellaneous tests	136
Fuse system I – gU fuse-links with wedge tightening contacts		151
1	General	151
1.1	Scope	151
2	Terms and definitions	151
3	Conditions for operation in service	151
3.9	Discrimination of fuse-links	151
4	Classification	152
5	Characteristics of fuses	152
5.2	Rated voltage	152
5.3.1	Rated current of the fuse-link	152
5.5	Rated power dissipation of a fuse-link	152
5.6.1	Time-current characteristics, time-current zones	152
5.6.2	Conventional times and currents	152
5.6.3	Gates	152
5.7.2	Rated breaking capacity	153
5.8	Cut-off current and I^2t characteristics	153
6	Markings	153
6.1	Markings of fuse-holders	153
6.2	Markings of fuse-links	153
7	Standard conditions for construction	153
7.1	Mechanical design	153
7.2	Insulating properties and suitability for insulation	153
7.5	Breaking capacity	153
7.7	I^2t characteristics	153
7.8	Overcurrent discrimination of the fuse-links	154
8	Tests	154
8.1.1	Kind of tests	154
8.3.1	Arrangement of the fuse	154
8.3.3	Measurement of the power dissipation of the fuse-link	155
8.4.1	Arrangement of the fuse	155
8.5.1	Arrangement of the fuse	155

8.5.2	Characteristics of the test circuit.....	155
8.5.5	Test method	155
8.5.8	Acceptability of test results.....	155
8.7.3	Verification of compliance for fuse-links at 0,01 s	156
8.9	Verification of resistance to heat	156
8.11	Mechanical and miscellaneous tests.....	156
Fuse system J – Fuses with fuse-links having "gD class CC" and "gN class CC" characteristics (Class CC time delay and non-time delay fuse types).....		
1	General	165
1.1	Scope.....	165
2	Terms and definitions	165
3	Conditions for operation in service.....	165
4	Classification.....	165
5	Characteristics of fuses	165
5.2	Rated voltage	165
5.3.1	Rated current of the fuse-link.....	166
5.3.2	Rated current of the fuse-holder	166
5.5	Rated power dissipation of a fuse-link and rated acceptable power dissipation of a fuse-holder	166
5.6	Limits of the time-current characteristics	166
5.6.1	Time-current characteristics, time-current zones	166
5.6.2	Conventional times and currents.....	166
5.6.3	Gates	166
5.7.2	Rated breaking capacity.....	166
6	Markings	167
6.1	Markings of fuse-holders	167
6.2	Markings of fuse-links.....	167
7	Standard conditions for construction.....	167
7.1	Mechanical design.....	167
7.2	Insulating properties and suitability for insulation	167
7.5	Breaking Capacity	167
7.6	Cut-off current characteristics.....	167
7.7	I^2t characteristics	167
7.8	Overcurrent discrimination.....	168
7.9	Protection against electric shock	168
8	Tests	168
8.3	Verification of temperature rise and power dissipation	168
8.3.1	Arrangement of the fuse	168
8.4	Verification of operation	169
8.4.1	Arrangement of the fuse	169
8.5.4	Recovery voltage.....	169
8.6	Verification of cut-off current characteristics	169
8.7	Verification of I^2t characteristics and overcurrent discrimination	170
8.9	Verification of resistance to heat	170
8.10	Verification of non-deterioration of contacts.....	171
8.10.1	Arrangement of the fuse	171
8.10.2	Test method	171